

This document is a preview generated by EVS

Geographic information - Geography Markup Language (GML)

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

| | |
|--|--|
| Käesolev Eesti standard EVS-EN ISO 19136:2009 sisaldb Euroopa standardi EN ISO 19136:2009 ingliskeelset teksti. | This Estonian standard EVS-EN ISO 19136:2009 consists of the English text of the European standard EN ISO 19136:2009. |
| Standard on kinnitatud Eesti Standardikeskuse 31.07.2009 käskkirjaga ja jõustub sellekohase teate avaldamisel EVS Teatajas. | This standard is ratified with the order of Estonian Centre for Standardisation dated 31.07.2009 and is endorsed with the notification published in the official bulletin of the Estonian national standardisation organisation. |
| Euroopa standardimisorganisatsioonide poolt rahvuslikele liikmetele Euroopa standardi teksti kätesaadavaks tegemise kuupäev on 04.03.2009. | Date of Availability of the European standard text 04.03.2009. |
| Standard on kätesaadav Eesti standardiorganisatsionist. | The standard is available from Estonian standardisation organisation. |

ICS 35.240.70

Standardite reproduutseerimis- ja levitamisõigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonilisse süsteemi või edastamine ükskõik millises vormis või millisel teel on keelatud ilma Eesti Standardikeskuse poolt antud kirjaliku loata.

Kui Teil on küsimusi standardite autorikaitse kohta, palun võtke ühendust Eesti Standardikeskusega:
Aru 10 Tallinn 10317 Eesti; www.evs.ee; Telefon: 605 5050; E-post: info@evs.ee

Right to reproduce and distribute Estonian Standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without permission in writing from Estonian Centre for Standardisation.

If you have any questions about standards copyright, please contact Estonian Centre for Standardisation:
Aru str 10 Tallinn 10317 Estonia; www.evs.ee; Phone: +372 605 5050; E-mail: info@evs.ee

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN ISO 19136

March 2009

ICS 35.240.70

English Version

Geographic information - Geography Markup Language (GML)
(ISO 19136:2007)

Information géographique - Langage de balisage en
géographie (GML) (ISO 19136:2007)

This European Standard was approved by CEN on 25 January 2009.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Foreword

The text of ISO 19136:2007 has been prepared by Technical Committee ISO/TC 211 "Geographic information/Geomatics" of the International Organization for Standardization (ISO) and has been taken over as EN ISO 19136:2009 by Technical Committee CEN/TC 287 "Geographic Information" the secretariat of which is held by NEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by September 2009, and conflicting national standards shall be withdrawn at the latest by September 2009.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

Endorsement notice

The text of ISO 19136:2007 has been approved by CEN as a EN ISO 19136:2009 without any modification.

Contents

Page

| | |
|---|-----|
| Foreword | vi |
| Introduction | vii |
| 1 Scope | 1 |
| 2 Conformance | 1 |
| 2.1 Conformance requirements | 1 |
| 2.2 Conformance classes related to GML application schemas | 2 |
| 2.3 Conformance classes related to GML profiles | 2 |
| 2.4 Conformance classes related to GML documents | 4 |
| 2.5 Conformance classes related to software implementations | 4 |
| 3 Normative references | 4 |
| 4 Terms and symbols | 5 |
| 4.1 Terms and definitions | 5 |
| 4.2 Symbols and abbreviated terms | 12 |
| 5 Conventions | 13 |
| 5.1 XML namespaces | 13 |
| 5.2 Versioning | 14 |
| 5.3 Deprecated parts of previous versions of GML | 14 |
| 5.4 UML notation | 14 |
| 5.5 XML Schema | 16 |
| 6 Overview of the GML schema | 16 |
| 6.1 GML schema | 16 |
| 6.2 GML application schemas | 16 |
| 6.3 Relationship between the ISO 19100 series of International Standards, the GML schema and GML application schemas | 17 |
| 6.4 Organization of this International Standard | 18 |
| 6.5 Deprecated and experimental schema components | 19 |
| 7 GML schema — General rules and base schema components | 20 |
| 7.1 GML model and syntax | 20 |
| 7.2 gmlBase schema components | 22 |
| 8 GML schema — Xlinks and basic types | 33 |
| 8.1 Xlinks — Object associations and remote properties | 33 |
| 8.2 Basic types | 34 |
| 9 GML schema — Features | 43 |
| 9.1 General concepts | 43 |
| 9.2 Relationship with ISO 19109 | 43 |
| 9.3 Features | 43 |
| 9.4 Standard feature properties | 44 |
| 9.5 Geometry properties | 46 |
| 9.6 Topology properties | 48 |
| 9.7 Temporal properties | 48 |
| 9.8 Defining application-specific feature types | 49 |
| 9.9 Feature collections | 50 |
| 9.10 Spatial reference system used in a feature or feature collection | 52 |
| 10 GML schema — Geometric primitives | 52 |
| 10.1 General concepts | 52 |
| 10.2 Abstract geometric primitives | 58 |
| 10.3 Geometric primitives (0-dimensional) | 59 |

| | | |
|------|---|-----|
| 10.4 | Geometric primitives (1-dimensional) | 60 |
| 10.5 | Geometric primitives (2-dimensional) | 72 |
| 10.6 | Geometric primitives (3-dimensional) | 81 |
| 11 | GML schema — Geometric complex, geometric composites and geometric aggregates | 83 |
| 11.1 | Overview | 83 |
| 11.2 | Geometric complex and geometric composites | 84 |
| 11.3 | Geometric aggregates | 86 |
| 12 | GML schema — Coordinate reference systems schemas | 91 |
| 12.1 | Overview | 91 |
| 12.2 | Reference systems | 93 |
| 12.3 | Coordinate reference systems | 95 |
| 12.4 | Coordinate systems | 103 |
| 12.5 | Datums | 110 |
| 12.6 | Coordinate operations | 117 |
| 13 | GML schema — Topology | 129 |
| 13.1 | General concepts | 129 |
| 13.2 | Abstract topology | 130 |
| 13.3 | Topological primitives | 130 |
| 13.4 | Topological collections | 135 |
| 13.5 | Topology complex | 137 |
| 14 | GML schema — Temporal information and dynamic features | 139 |
| 14.1 | General concepts | 139 |
| 14.2 | Temporal schema | 140 |
| 14.3 | Temporal topology schema | 148 |
| 14.4 | Temporal reference systems | 151 |
| 14.5 | Representing dynamic features | 158 |
| 15 | GML schema — Definitions and dictionaries | 162 |
| 15.1 | Overview | 162 |
| 15.2 | Dictionary schema | 162 |
| 16 | GML schema — Units, measures and values | 165 |
| 16.1 | Introduction | 165 |
| 16.2 | Units schema | 165 |
| 16.3 | Measures schema | 171 |
| 16.4 | Value objects schema | 172 |
| 17 | GML schema — Directions | 179 |
| 17.1 | Direction schema | 179 |
| 17.2 | direction, DirectionPropertyType | 179 |
| 17.3 | DirectionVectorType | 180 |
| 17.4 | DirectionDescriptionType | 180 |
| 18 | GML schema — Observations | 181 |
| 18.1 | Observations | 181 |
| 18.2 | Observation schema | 182 |
| 19 | GML schema — Coverages | 185 |
| 19.1 | The coverage model and representations | 185 |
| 19.2 | Grids schema | 188 |
| 19.3 | Coverage schema | 191 |
| 20 | Profiles | 205 |
| 20.1 | Profiles of GML and application schemas | 205 |
| 20.2 | Definition of profile | 205 |
| 20.3 | Relation to application schema | 205 |
| 20.4 | Rules for elements and types in a profile | 206 |
| 20.5 | Rules for referencing GML profiles from application schemas | 207 |
| 20.6 | Recommendations for application schemas using GML profiles | 207 |
| 20.7 | Summary of rules for GML profiles | 208 |

| | | |
|-----------------------|---|-----|
| 21 | Rules for GML application schemas | 208 |
| 21.1 | Instances of GML objects | 208 |
| 21.2 | GML application schemas | 209 |
| 21.3 | Schemas defining Features and Feature Collections | 212 |
| 21.4 | Schemas defining spatial geometries | 213 |
| 21.5 | Schemas defining spatial topologies | 214 |
| 21.6 | Schemas defining time | 215 |
| 21.7 | Schemas defining coordinate reference systems | 215 |
| 21.8 | Schemas defining coverages | 216 |
| 21.9 | Schemas defining observations | 218 |
| 21.10 | Schemas defining dictionaries and definitions | 219 |
| 21.11 | Schemas defining values | 220 |
| 21.12 | GML profiles of the GML schema | 220 |
| Annex A (normative) | Abstract test suites for GML application schemas, GML profiles and GML documents | 223 |
| Annex B (normative) | Abstract test suite for software implementations | 238 |
| Annex C (informative) | GML schema | 242 |
| Annex D (normative) | Implemented Profile of the ISO 19100 series of International Standards and Extensions | 244 |
| Annex E (normative) | UML-to-GML application schema encoding rules | 309 |
| Annex F (normative) | GML-to-UML application schema encoding rules | 329 |
| Annex G (informative) | Guidelines for subsetting the GML schema | 339 |
| Annex H (informative) | Default styling | 352 |
| Annex I (informative) | Backwards compatibility with earlier versions of GML | 363 |
| Annex J (informative) | Modularization and dependencies | 380 |
| Bibliography | 382 | |
| Index | 384 | |

Introduction

Geography Markup Language is an XML grammar written in XML Schema for the description of application schemas as well as the transport and storage of geographic information.

The key concepts used by Geography Markup Language (GML) to model the world are drawn from the ISO 19100 series of International Standards and the OpenGIS Abstract Specification.

A feature is an “abstraction of real world phenomena” (ISO 19101); it is a geographic feature if it is associated with a location relative to the Earth. So a digital representation of the real world may be thought of as a set of features. The state of a feature is defined by a set of properties, where each property may be thought of as a {name, type, value} triple.

The number of properties a feature may have, together with their names and types, is determined by its type definition. Geographic features with geometry are those with properties that may be geometry-valued. A feature collection is a collection of features that may itself be regarded as a feature; as a consequence a feature collection has a feature type and thus may have distinct properties of its own, in addition to the features it contains.

Following ISO 19109, the feature types of an application or application domain is usually captured in an application schema. A GML application schema is specified in XML Schema and can be constructed in two different and alternative ways:

- by adhering to the rules specified in ISO 19109 for application schemas in UML, and conforming to both the constraints on such schemas and the rules for mapping them to GML application schemas specified in this International Standard;
- by adhering to the rules for GML application schemas specified in this International Standard for creating a GML application schema directly in XML Schema.

Both ways are supported by this International Standard. To ensure proper use of the conceptual modelling framework of the ISO 19100 series of International Standards, all application schemas are expected to be modelled in accordance with the General Feature Model as specified in ISO 19109. Within the ISO 19100 series, UML is the preferred language by which to model conceptual schemas.

GML specifies XML encodings, conformant with ISO 19118, of several of the conceptual classes defined in the ISO 19100 series of International Standards and the OpenGIS Abstract Specification. These conceptual models include those defined in:

- ISO/TS 19103 — Conceptual schema language (units of measure, basic types);
- ISO 19107 — Spatial schema (geometry and topology objects);
- ISO 19108 — Temporal schema (temporal geometry and topology objects, temporal reference systems);
- ISO 19109 — Rules for application schemas (features);
- ISO 19111 — Spatial referencing by coordinates (coordinate reference systems);
- ISO 19123 — Schema for coverage geometry and functions.

The aim is to provide a standardized encoding (i.e. a standardized implementation in XML) of types specified in the conceptual models specified by the International Standards listed above. If every application schema were encoded independently and the encoding process included the types from, for example, ISO 19108, then,

without unambiguous and completely fixed encoding rules, the XML encodings would be different. Also, since every implementation platform has specific strengths and weaknesses, it is helpful to standardize XML encodings for core geographic information concepts modelled in the ISO 19100 series of International Standards and commonly used in application schemas.

In many cases, the mapping from the conceptual classes is straightforward, while in some cases the mapping is more complex (a detailed description of the mapping is part of this International Standard).

In addition, GML provides XML encodings for additional concepts not yet modelled in the ISO 19100 series of International Standards or the OpenGIS Abstract Specification, for example, dynamic features, simple observations or value objects.

Predefined types of geographic feature in GML include coverages and simple observations.

A coverage is a subtype of feature that has a coverage function with a spatiotemporal domain and a value set range of homogeneous 1- to n -dimensional tuples. A coverage may represent one feature or a collection of features “to model and make visible spatial relationships between, and the spatial distribution of, Earth phenomena” (OGC Abstract Specification Topic 6 [20]) and a coverage “acts as a function to return values from its range for any direct position within its spatiotemporal domain” (ISO 19123).

An observation models the act of observing, often with a camera or some other procedure, a person or some form of instrument (Merriam-Webster Dictionary: “an act of recognizing and noting a fact or occurrence often involving measurement with instruments”). An observation is considered to be a GML feature with a time at which the observation took place, and with a value for the observation.

A reference system provides a scale of measurement for assigning values to a position, time or other descriptive quantity or quality.

A coordinate reference system consists of a set of coordinate system axes that is related to the Earth through a datum that defines the size and shape of the Earth.

A temporal reference system provides standard units for measuring time and describing temporal length or duration.

A reference system dictionary provides definitions of reference systems used in spatial or temporal geometries.

Spatial geometries are the values of spatial feature properties. They indicate the coordinate reference system in which their measurements have been made. The “parent” geometry element of a geometric complex or geometric aggregate makes this indication for its constituent geometries.

Temporal geometries are the values of temporal feature properties. Like their spatial counterparts, temporal geometries indicate the temporal reference system in which their measurements have been made.

Spatial or temporal topologies are used to express the different topological relationships between features.

A units of measure dictionary provides definitions of numerical measures of physical quantities, such as length, temperature and pressure, and of conversions between units.

Geographic information — Geography Markup Language (GML)

1 Scope

The Geography Markup Language (GML) is an XML encoding in compliance with ISO 19118 for the transport and storage of geographic information modelled in accordance with the conceptual modelling framework used in the ISO 19100 series of International Standards and including both the spatial and non-spatial properties of geographic features.

This International Standard defines the XML Schema syntax, mechanisms and conventions that:

- provide an open, vendor-neutral framework for the description of geospatial application schemas for the transport and storage of geographic information in XML;
- allow profiles that support proper subsets of GML framework descriptive capabilities;
- support the description of geospatial application schemas for specialized domains and information communities;
- enable the creation and maintenance of linked geographic application schemas and datasets;
- support the storage and transport of application schemas and datasets;
- increase the ability of organizations to share geographic application schemas and the information they describe.

Implementers may decide to store geographic application schemas and information in GML, or they may decide to convert from some other storage format on demand and use GML only for schema and data transport.

NOTE If an ISO 19109 conformant application schema described in UML is used as the basis for the storage and transportation of geographic information, this International Standard provides normative rules for the mapping of such an application schema to a GML application schema in XML Schema and, as such, to an XML encoding for data with a logical structure in accordance with the ISO 19109 conformant application schema.

2 Conformance

2.1 Conformance requirements

Clauses 7 to 19 of this International Standard specify XML Schema components, i.e. the GML schema, which shall be used in GML application schemas in accordance with Clause 21. Clause 20 specifies rules for the specification of a GML profile that may be defined for use in a GML application schema.

Few applications will require the full range of capabilities described by the GML schema. This clause, therefore, defines a set of conformance classes that will support applications whose requirements range from the minimum necessary to define simple feature types to full use of the GML schema.