
**Natural gas — Designation of the quality of
natural gas for use as a compressed fuel
for vehicles**

*Gaz naturel — Désignation de la qualité de gaz naturel pour usage comme
carburant comprimé pour véhicules*



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO 2000

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 734 10 79
E-mail copyright@iso.ch
Web www.iso.ch

Printed in Switzerland

Contents

Page

Foreword.....	iv
Introduction.....	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Symbols and abbreviations	9
5 Gas composition requirements	10
6 Gas properties	11
7 Driveability	12
8 Test methods	12
9 Sampling	13
Annex A (informative) Propane and butane content	14
Annex B (informative) Wobbe index range	16
Annex C (informative) Engine knock	18
Annex D (informative) Methane number and octane number	19
Annex E (informative) Water content of natural gas	22
Bibliography	23

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

International Standard ISO 15403 was prepared by Technical Committee ISO/TC 193, *Natural gas*.

Annexes A to E of this International Standard are for information only.

Introduction

Natural gas has been used to some extent as a fuel for internal combustion engines in compressor stations, co-generation systems, and vehicles of various types for many years now. However, the prerequisites for growth, i.e. economic viability and fuel availability, were generally not satisfied. Now, with the natural gas industry well established, supplying 20 % of the world's primary energy, and the need for alternative, low-emission fuels, the situation has improved considerably. During the past decade, natural gas vehicles have become a viable option with some one million units now in use around the world. Growth is continuing as many governments actively promote this clean-burning fuel with its environmental benefits. Many fleet operators are converting their vehicles, and vehicle manufacturers are developing and marketing dedicated natural gas equipment.

In the context of this standard, natural gas vehicles (NGVs) utilize compressed natural gas stored "on-board". The pressure of the gas stored in multiple containers is up to a maximum 25 000 kPa. Although the pressure has to be reduced before combustion, compression and storage gives NGVs an adequate range. While NGVs were initially equipped with converted gasoline or diesel engines, high-performance, dedicated natural gas engines are now being extensively developed and produced. Liquefied natural gas (LNG) may also be stored in the fuel tanks of natural gas vehicles. This, however, will be the subject of a separate International Standard.

This International Standard for the quality designation of compressed natural gas is designed to stipulate the international requirements placed on the natural gas used as a motor fuel. Engine and vehicle manufacturers must know these requirements so they can develop high-performance equipment which runs on compressed natural gas.

A technical report giving detailed data on the gas compositions used in ISO 15403 has been drafted and is being circulated as an addendum.

Natural gas — Designation of the quality of natural gas for use as a compressed fuel for vehicles

1 Scope

The aim of this International Standard is to provide manufacturers, vehicle operators, fuelling station operators and others involved in the compressed-natural-gas vehicle industry with information on the fuel quality for natural gas vehicles (NGVs) required to develop and operate compressed-natural-gas vehicle equipment successfully.

Fuel meeting the requirements of this International Standard should:

- a) provide for the safe operation of the vehicle and associated equipment needed for its fuelling and maintenance;
- b) protect the fuel system from the detrimental effects of corrosion, poisoning, and liquid or solid deposition;
- c) provide satisfactory vehicle performance under any and all conditions of climate and driving demands.

Some aspects of this International Standard may also be applicable for the use of natural gas in stationary combustion engines.

2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this International Standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO 6326-1:1989, *Natural gas — Determination of sulfur compounds — Part 1: General introduction.*

ISO 6326-2:—¹⁾, *Natural gas — Determination of sulfur compounds — Part 2: Gas chromatographic method using an electrochemical detector.*

ISO 6326-3:1989, *Natural gas — Determination of sulfur compounds — Part 3: Determination of hydrogen sulfide, mercaptan sulfur and carbonyl sulfide sulfur by potentiometry.*

ISO 6326-4:1994, *Natural gas — Determination of sulfur compounds — Part 4: Gas chromatographic method using a flame photometric detector for the determination of hydrogen sulfide, carbonyl sulfide and sulfur-containing odorants.*

ISO 6326-5:1989, *Natural gas — Determination of sulfur compounds — Part 5: Lingener combustion method.*

ISO 6327:1981, *Gas analysis — Determination of the water dew point of natural gas — Cooled surface condensation hygrometers.*

1) To be published. (Revision of ISO 6326-2:1981)

ISO 6570-1:1983, *Natural gas — Determination of potential hydrocarbon liquid content — Part 1: Principles and general requirements.*

ISO 6570-2:1984, *Natural gas — Determination of potential hydrocarbon liquid content — Part 2: Weighing method.*

ISO 6974 (all parts), *Natural gas — Determination of composition with defined uncertainty by gas chromatography.*

ISO 6976:1995, *Natural gas — Calculation of calorific values, density, relative density and Wobbe index from composition.*

ISO 10101-1:1993, *Natural gas — Determination of water by the Karl Fischer method — Part 1: Introduction.*

ISO 10101-2:1993, *Natural gas — Determination of water by the Karl Fischer method — Part 2: Titration procedure.*

ISO 10101-3:1993, *Natural gas — Determination of water by the Karl Fischer method — Part 3: Coulometric procedure.*

ISO 11541:1997, *Natural gas — Determination of water content at high pressure.*

ISO 13734:1998, *Natural gas — Organic sulfur compounds used as odorants — Requirements and test methods.*

ISO 14532:—²⁾, *Natural gas — Terminology.*

3 Terms and definitions

For the purposes of this International Standard, the following terms and definitions apply. Definitions were taken from ISO 14532 whenever possible.

3.1

natural gas

complex mixture of hydrocarbons, primarily methane, but generally also including ethane, propane and higher hydrocarbons in much smaller amounts and some non-combustible gases, such as nitrogen and carbon dioxide

NOTE 1 Natural gas generally also includes minor amounts of trace constituents.

NOTE 2 Natural gas is produced and processed from the raw gas or liquefied natural gas and, if required, blended to the extent suitable for direct use (for example as gaseous fuel).

NOTE 3 Natural gas remains in the gaseous state under the temperature and pressure conditions normally found in service.

NOTE 4 Natural gas consists predominantly of methane (mole fraction greater than 0,70), and has a superior calorific value normally within the range 30 MJ/m³ to 45 MJ/m³. It contains also ethane (typically up to 0,10 mole fraction), propane, butanes and higher alkanes in steadily decreasing amounts. Nitrogen and carbon dioxide are the principal non-combustible components, each present at levels which typically vary from less than 0,01 mole fraction to 0,20 mole fraction.

Natural gas is processed from the raw gas so as to be suitable for use as industrial, commercial, residential fuel or as a chemical feedstock. The processing is intended to reduce the contents of potentially corrosive components, such as hydrogen sulfide and carbon dioxide, and of other components, such as water and higher hydrocarbons, potentially condensable in the transmission and distribution of the gas. Hydrogen sulfide, organic sulfur compounds and water are then reduced to trace amounts, and high carbon dioxide contents are likely to be reduced to below 0,05 mole fraction.

Natural gas is normally technically free from aerosol, liquid and particulate matter.

2) To be published.