# Plastics - Determination of resistance to environmental stress cracking (ESC) - Part 1: General guidance

Plastics - Determination of resistance to environmental stress cracking (ESC) - Part 1: General guidance



## **EESTI STANDARDI EESSÕNA**

## **NATIONAL FOREWORD**

This Estonian standard EVS-EN ISO 22088-1:2006 consists of the English text of the European standard EN ISO 22088-1:2006.

Käesolev dokument on jõustatud 20.09.2006 ja selle kohta on avaldatud teade Eesti standardiorganisatsiooni ametlikus väljaandes.

This document is endorsed on 20.09.2006 with the notification being published in the official publication of the Estonian national standardisation organisation.

Standard on kättesaadav Eesti standardiorganisatsioonist.

The standard is available from Estonian standardisation organisation.

#### Käsitlusala:

## This part of ISO 22088 provides information and general guidance relevant to the selection of the test method to be used to determine environmental stress cracking (ESC).

## Scope:

This part of ISO 22088 provides information and general guidance relevant to the selection of the test method to be used to determine environmental stress cracking (ESC).

ICS 83.080.01

Võtmesõnad:

## EUROPEAN STANDARD

## **EN ISO 22088-1**

## NORME EUROPÉENNE EUROPÄISCHE NORM

August 2006

ICS 83.080.01

#### **English Version**

Plastics - Determination of resistance to environmental stress cracking (ESC) - Part 1: General guidance (ISO 22088-1:2006)

Plastiques - Détermination de la fissuration sous contrainte dans un environnement donné (ESC) - Partie 1: Lignes directrices générales (ISO 22088-1:2006) Kunststoffe - Bestimmung der Beständigkeit gegen umgebungsbedingte Spannungsrissbildung (ESC) - Teil 1: Allgemeine Anleitung (ISO 22088-1:2006)

This European Standard was approved by CEN on 21 July 2006.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

#### **Foreword**

This document (EN ISO 22088-1:2006) has been prepared by Technical Committee ISO/TC 61 "Plastics" in collaboration with Technical Committee CEN/TC 249 "Plastics", the secretariat of which is held by IBN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by February 2007, and conflicting national standards shall be withdrawn at the latest by February 2007.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

## Endorsement notice

) appre The text of ISO 22088-1:2006 has been approved by CEN as EN ISO 22088-1:2006 without any modifications.

## INTERNATIONAL **STANDARD**

ISO 22088-1

> First edition 2006-08-15

## Plastics — Determination of resistance to environmental stress cracking (ESC) —

## Part 1: General guidance

Plastiques — Détermination de la fissuration sous contrainte dans un environnement donné (ESC) s direc

Partie 1: Lignes directrices générales



#### PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below

#### © ISO 2006

v.ems
v.ems
v.ems
v.ems
v.ems
v.emrelating to it is All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org Published in Switzerland

COL	ntents	Page
	eword	
Intro	oduction	
1	Scope	
2	Normative references	1
3	Terms and definitions	2
4	Principles of the test	
5	Applicability of the test method	3
6	Test specimen preparation	
7	Conditioning and test conditions	
7.1 7.2	Conditioning Test temperature	
7.3	Test medium	
	ex A (informative) Examples of test methods for various p	plastics 5
Bibli	liography	6
	~	
	7	
	.0	<i>b</i>
	liography	
		6
		Y X
		Q.
		<b>6</b> .
		\'/_
		0,

## **Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 22088-1 was prepared by Technical Committee ISO/TC 61, *Plastics*, Subcommittee SC 6, *Ageing, chemical and environmental resistance*.

ISO 22088 consists of the following parts, under the general title *Plastics* — *Determination of resistance to environmental stress cracking (ESC)*:

— Part 1: General guidance

— Part 2: Constant tensile load method (replacement of ISO 6252:1992)

— Part 3: Bent strip method (replacement of ISO 4599:1986)

— Part 4: Ball or pin impression method (replacement of ISO 4600:1992)

— Part 5: Constant tensile deformation method (new test method)

— Part 6: Slow strain rate method (new test method)

## Introduction

When a plastic material is stressed or strained in air below its yield point, stress cracking can occur after a period of time, which may be very long. These stresses may be internal or external, or a combination of both. Simultaneous exposure to a chemical environment and stress or strain may result in a dramatic shortening of the time to failure compared to that in an inert environment. The phenomenon is referred to as environmental stress cracking (ESC) and is exhibited by many materials, including plastics. The permissible long-term stress or strain may be reduced considerably by this phenomenon.

It is generally believed that ESC occurs via the following processes:

- 1) Formation of microvoids in specimens by microscopic stress concentrations after applying stress.
- 2) Formation and subsequent growth of macrovoids caused by the breakdown of intermolecular bonds in intervoids that is produced by the action of a chemical environment, and formation of crazes which are composed of interconnected voids and fibrils.
- 3) Growth of the crazes caused by the break-down of the fibrils due to the applied stress and contact with a chemical environment.
- 4) Finally, a crack starts at the tip of the craze, leading to brittle failure.

The cracks may penetrate completely through the thickness of the material, separating it into two or more pieces, or they may be arrested on reaching regions of lower stress or different material morphology.

The determination of ESC is complex because it is influenced by many parameters, including:

- test specimen dimensions;
- test specimen state (orientation, structure, internal stresses);
- specimen preparation;
- thermal history of specimen;
- stress and strain;
- temperature of test;
- duration of test;
- chemical environment;
- method of application of stress and strain;
- failure criterion.

By keeping all but one parameter constant, the relative influence of the variable parameter on ESC can be assessed. The main objective of ESC measurements is to determine the relative effect of chemical media exposure on plastics (test specimens and articles).

The measurements may also be used to evaluate the influence of the moulding conditions upon the quality of an article when the failure mode corresponds to that obtained in actual service.

It is almost impossible, however, to establish any direct correlation between the results of short-duration ESC measurements on test specimens and the actual service behaviour of articles, because the behaviour of the latter is likely to be more complex than that of test specimens.

© ISO 2006 – All rights reserved

## Plastics — Determination of resistance to environmental stress cracking (ESC) —

## Part 1:

## General guidance

## 1 Scope

- **1.1** This part of ISO 22088 provides information and general guidance relevant to the selection of the test method to be used to determine environmental stress cracking (ESC).
- **1.2** Part 2 describes a method in which a test specimen is subjected to a constant tensile load, while immersed in a stress cracking agent at a specified temperature. The time and/or stress at which the specimen breaks is recorded.
- **1.3** Part 3 describes a method in which strips of plastic are subjected to a fixed flexural strain and exposed to a stress cracking agent for a predetermined period.
- **1.4** Part 4 describes a method in which a hole of specified diameter is drilled in a specimen and an oversized steel ball or pin is inserted into the hole while the test specimen is brought into contact with a stress cracking agent.
- **1.5** Part 5 describes a method in which a constant tensile deformation is applied to a specimen which is immersed in a stress cracking agent at a temperature selected for testing.
- **1.6** Part 6 describes a method in which a slowly increasing strain is applied to a specimen immersed in a stress cracking agent.
- **1.7** These methods are applicable to thermoplastic materials only.
- **1.8** These are essentially ranking tests and are not intended to provide data to be used for design or performance prediction.

#### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 150, Raw, refined and boiled linseed oil for paints and varnishes — Specifications and methods of test

ISO 293, Plastics — Compression moulding of test specimens of thermoplastic materials

ISO 294-1, Plastics — Injection moulding of test specimens of thermoplastic materials — Part 1: General principles, and moulding of multipurpose and bar test specimens

ISO 2818, Plastics — Preparation of test specimens by machining