# Plastid - Vastupidavuse määramine keskkonna pingetest põhjustatud pragunemisele (environmental stress cracking) (ESC) - Kuuli või nõela jälje meetod

Plastics - Determination of resistance to environmental stress cracking (ESC) - Part 4: Ball or pin impression method



# **EESTI STANDARDI EESSÕNA**

# **NATIONAL FOREWORD**

Käesolev Eesti standard EVS-EN ISO 22088-4:2006 sisaldab Euroopa standardi EN ISO 22088-4:2006 ingliskeelset teksti.

This Estonian standard EVS-EN ISO 22088-4:2006 consists of the English text of the European standard EN ISO 22088-4:2006.

Käesolev dokument on jõustatud 20.09.2006 ja selle kohta on avaldatud teade Eesti standardiorganisatsiooni ametlikus väljaandes.

This document is endorsed on 20.09.2006 with the notification being published in the official publication of the Estonian national standardisation organisation.

Standard on kättesaadav Eesti standardiorganisatsioonist.

The standard is available from Estonian standardisation organisation.

# Käsitlusala:

# Käesolev standard määrab kindlaks meetodi plastide vastupidavuse määramiseks keskkonna pingest tekitatud pragunemisele (environmental stress cracking) (ESC) konstantse pingestamise testi abil. Test kehtib viimistletud toodete ja proovikehade kohta, mis on tehtud vormimise ja/või mehaanilise töötlemise teel. Testi võib kasutada erinevate keskkonnamõjudele allutatud plasttoodete ja materjalide ESC-hindamiseks kui ka spetsiifilise keskkonna mõjule allutatud plastide ESC-määramiseks.

# Scope:

This part of ISO 22088 specifies a ball or pin impression method for the determination of the environmental stress cracking (ESC) behaviour of plastics by means of a constant-strain test.

ICS 83.080.01

**Võtmesõnad:** keskkonnatestid, määramine, plastid, pragunemiskindlus, pragunemistestid, testimine, testimisseade

# EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

# **EN ISO 22088-4**

August 2006

ICS 83.080.01

Supersedes EN ISO 4600:1997

# **English Version**

Plastics - Determination of resistance to environmental stress cracking (ESC) - Part 4: Ball or pin impression method (ISO 22088-4:2006)

Plastiques - Détermination de la fissuration sous contrainte dans un environnement donné (ESC) - Partie 4: Méthode par enfoncement de billes ou de goupilles (ISO 22088-4:2006)

Kunststoffe - Bestimmung der Beständigkeit gegen umgebungsbedingte Spannungsrissbildung (ESC) - Teil 4: Kugel- oder Stifteindrückverfahren (ISO 22088-4:2006)

This European Standard was approved by CEN on 21 July 2006.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

# **Foreword**

This document (EN ISO 22088-4:2006) has been prepared by Technical Committee ISO/TC 61 "Plastics" in collaboration with Technical Committee CEN/TC 249 "Plastics", the secretariat of which is held by IBN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by February 2007, and conflicting national standards shall be withdrawn at the latest by February 2007.

This document supersedes EN ISO 4600:1997.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

# **Endorsement notice**

prover. The text of ISO 22088-4:2006 has been approved by CEN as EN ISO 22088-4:2006 without any modifications.

# INTERNATIONAL STANDARD

ISO 22088-4

First edition 2006-08-15

# Plastics — Determination of resistance to environmental stress cracking (ESC) —

Part 4: Ball or pin impression method

Plastiques — Détermination de la fissuration sous contrainte dans un environnement donné (ESC) —

Partie 4: Méthode par enfoncement de billes ou de goupilles



# PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below

### © ISO 2006

verset to comprising Every very relating to it is All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org

Published in Switzerland

# **Contents**

Page

word	iv
Scope	1
Normative references	2
Terms and definitions	2
Principle	4
Apparatus	4
Shape State State Number of test specimens	6 6 7
Conditioning Test temperature Chemical medium	7 7 7
Cleanness Drilling the test specimens Insertion of balls or pins Immersion in the chemical medium Exposure in air Determination of stress cracking	88910
Type A test specimen	10
Precision	10
Test report	11
ography	13
	Scope

# **Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 22088-4 was prepared by Technical Committee ISO/TC 61, *Plastics*, Subcommittee SC 6, *Ageing, chemical and environmental resistance*.

It cancels and replaces ISO 4600:1992, which has been technically revised.

ISO 22088 consists of the following parts, under the general title *Plastics* — *Determination of resistance to environmental stress cracking (ESC)*:

— Part 1: General guidance

— Part 2: Constant tensile load method (replacement of ISO 6252:1992)

— Part 3: Bent strip method (replacement of ISO 4599:1986)

— Part 4: Ball or pin impression method (replacement of ISO 4600:1992)

— Part 5: Constant tensile deformation method (new test method)

— Part 6: Slow strain rate method (new test method)

# Plastics — Determination of resistance to environmental stress cracking (ESC) —

# Part 4:

# Ball or pin impression method

# 1 Scope

- **1.1** This part of ISO 22088 specifies a ball or pin impression method for the determination of the environmental stress cracking (ESC) behaviour of plastics by means of a constant-strain test.
- **1.2** The method is applicable to finished products and to test specimens prepared by moulding and/or machining, and can be used for the assessment of the ESC behaviour of a plastic product or material exposed to different environments, as well as for the determination of the ESC behaviour of different plastics materials exposed to a specific environment.

NOTE Alternative methods for the determination of environmental stress cracking by means of a constant-strain test are specified in ISO 22088-3 and ISO 22088-5. A method for the determination of environmental stress cracking by means of a constant-stress test is specified in ISO 22088-2.

- **1.3** The ball and pin impression methods are both quick and sensitive procedures for assessing the ESC behaviour of plastics. The methods are well suited for amorphous plastics. They are less appropriate for materials displaying a pronounced tendency for creep and/or stress relaxation, i.e. for semi-crystalline materials. If semi-crystalline materials are tested, pins are more appropriate than balls.
- **1.4** The ball impression method is useful for assessing the principal ESC behaviour of the material/chemical combination under consideration. It is less influenced by the near-surface orientation state of the specimens than the pin impression method and the methods in the other parts of this International Standard, where the chemical attacks only the original surface of the material. This, depending on the manner of specimen preparation, may show a considerable degree of orientation.
- 1.5 The pin impression method is useful for testing specimens of small thickness and finished parts.

© ISO 2006 – All rights reserved

## Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 178, Plastics — Determination of flexural properties

ISO 291, Plastics — Standard atmospheres for conditioning and testing

ISO 293, Plastics — Compression moulding of test specimens of thermoplastic materials

ISO 294-1, Plastics — Injection moulding of test specimens of thermoplastic materials — Part 1: General principles, and moulding of multipurpose and bar test specimens

ISO 527-1, Plastics — Determination of tensile properties — Part 1: General principles

ISO 527-2, Plastics — Determination of tensile properties — Part 2: Test conditions for moulding and extrusion plastics

ISO 2557-1, Plastics — Amorphous thermoplastics — Preparation of test specimens with a specified maximum reversion — Part 1: Bars

ISO 2818, Plastics — Preparation of test specimens by machining

ISO 3167, Plastics — Multipurpose test specimens

ISO 3290, Rolling bearings — Balls — Dimensions and tolerances

ISO 4287, Geometrical Product Specifications (GPS) — Surface texture: Profile method — Terms, definitions and surface texture parameters

# Terms and definitions

For the purposes of this document, the following terms and definitions apply.

# 3.1

# oversize

difference between the diameter of an impressed ball or pin  $(d_b)$  and the diameter of the drilled and reamed hole  $(d_h)$  in the test specimen:

$$d_{\mathsf{d}} = d_{\mathsf{b}} - d_{\mathsf{h}} \tag{1}$$

## 3.2

# deformation step

determination made at a defined oversize

# 3.3

## deformation step zero

determination made using test specimens that are drilled and reamed only, i.e. without impressing a ball or pin

# 3.4

# deformation series

number of successive deformation steps beginning with deformation step zero

NOTE Normally, a deformation series consists of seven deformation steps of increasing severity.