

Petroleum and natural gas industries - Compact flanged connections with IX seal ring (ISO 27509:2012)

This document is a preview generated by EVS

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

See Eesti standard EVS-EN ISO 27509:2012 sisaldab Euroopa standardi EN ISO 27509:2012 ingliskeelset teksti.	This Estonian standard EVS-EN ISO 27509:2012 consists of the English text of the European standard EN ISO 27509:2012.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas.	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 19.12.2012.	Date of Availability of the European standard is 19.12.2012.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 23.040.60

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:
Aru 10, 10317 Tallinn, Eesti; www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:
Aru 10, 10317 Tallinn, Estonia; www.evs.ee; phone 605 5050; e-mail info@evs.ee

ICS 23.040.60

English Version

Petroleum and natural gas industries - Compact flanged
connections with IX seal ring (ISO 27509:2012)

Industries du pétrole et du gaz naturel - Raccordements à
brides compactes avec bague d'étanchéité IX (ISO
27509:2012)

Erdöl- und Erdgasindustrie - Kompakte
Flanschverbindungen mit IX Dichtungsring (ISO
27509:2012)

This European Standard was approved by CEN on 18 December 2012.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Foreword

This document (EN ISO 27509:2012) has been prepared by Technical Committee ISO/TC 67 "Materials, equipment and offshore structures for petroleum, petrochemical and natural gas industries" in collaboration with Technical Committee CEN/TC 12 "Materials, equipment and offshore structures for petroleum, petrochemical and natural gas industries" the secretariat of which is held by AFNOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by June 2013, and conflicting national standards shall be withdrawn at the latest by June 2013.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

According to the CEN/CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Endorsement notice

The text of ISO 27509:2012 has been approved by CEN as a EN ISO 27509:2012 without any modification.

Contents

Page

Foreword	v
Introduction.....	vi
1 Scope	1
2 Normative references	1
3 Terms, definitions, symbols and abbreviated terms	2
3.1 Terms and definitions	2
3.2 Symbols	2
3.3 Abbreviated terms	4
4 Design	5
4.1 General	5
4.2 Design principles	5
4.3 Assembly requirements	6
4.4 Standard components	7
4.5 Units of measurements	8
4.6 Rounding	8
4.7 Compliance with piping design codes	8
4.8 Compliance to this International Standard	8
5 Designation	8
5.1 Designation of flanges	8
5.2 Designation of seal rings	9
6 Materials	9
6.1 General	9
6.2 Flange materials	9
6.3 Bolting materials	10
6.4 Seal ring materials	11
7 Strength, pressure/temperature ratings and leak tightness	11
7.1 General	11
7.2 Pressure/temperature ratings	12
7.3 Pressure testing and leak tightness	12
8 Dimensions of flanges	13
8.1 General	13
8.2 Weld neck (WN) dimensions	14
8.3 Blind flange (BL) dimensions	21
8.4 Integral flange (IF) dimensions	24
8.5 Rigid interface (RI) dimensions	31
8.6 Dimensions of paddle blanks (PB) and paddle spacers (PS)	34
8.7 Handle and lifting lugs	37
8.8 Dimensions of orifice spacers (OS)	38
8.9 Dimensions of reducing threaded flanges (RTs)	39
8.10 Auxiliary connections	40
8.11 Flange tolerances	40
8.12 Surface finish	42
9 Marking of flanges	42
9.1 Flanges other than integral flanges	42
9.2 Manufacturer's name or trademark	43
9.3 Nominal size	43
9.4 Pressure class designation	43

9.5	Pipe dimensions	43
9.6	Material designation	43
9.7	Identification of internally threaded flanges	43
9.8	Material traceability	44
9.9	Marking examples.....	44
9.10	Stamping.....	44
10	Dimensions of seal rings	44
11	Inspection and testing of seal rings	48
12	Coating and colour coding	48
13	Marking of seal rings	48
14	Quality management systems	48
15	Bolt dimensions and masses	48
Annex A (normative)	Pressure temperature ratings and shear capacity of seal rings.....	49
Annex B (informative)	Integral flange angle selection	54
Annex C (informative)	Quality management system	64
Annex D (normative)	Bolt dimensions and masses	65
Annex E (informative)	Handling, installation, assembly and repair of flanges.....	71
Annex F (informative)	Mass of flanges.....	84
Annex G (informative)	Metric bolting	95
Annex H (informative)	Additional information on bibliographical references	97
Bibliography		98

Introduction

This International Standard, which is based on NORSOK L-005^[36], has been developed to provide a standard for compact flanged connections (CFCs) that constitutes an alternative to conventional flanges as specified in ASME standards, European Standards and other International Standards, with reduced mass and smaller overall dimensions, as well as increased reliability in leak tightness by means of its inherent design features and make up procedures. CFCs can also provide an alternative to other types of clamp and hub type mechanical connectors.

The use of load carrying sealing elements, traditionally referred to as "gaskets", does not comply with the fundamental requirements of this International Standard.

This International Standard has been developed for use in process piping systems, which are designed according to codes for pressure piping, e.g. ASME B31.3. See 4.7 for more details.

The flange designs have been selected to achieve a minimum safety factor of 2,0 when subjected to a design pressure equal to ASME B16.5 pressure temperature ratings within the temperature limits of this International Standard.

The main body of this International Standard contains all necessary information on how to manufacture and supply flange and seal ring materials, such as

- flange dimensions and material requirements;
- seal ring dimensions and material requirements;
- bolting dimensions and material requirements;
- requirements to tolerances and surface finish;
- requirements to designation and marking of finished products.

Normative annexes A and D cover the following topics:

- structural capacity equations for flange assemblies;
- bolt dimensions and masses.

Informative annexes B, C, E, F and G cover the following topics:

- how to apply the flanges to special geometries of valves and equipment nozzles;
- quality management;
- installation and assembly instructions, and guidelines on how to repair damage and irregularities on sealing surfaces;
- masses of all standard components;
- suitable dimensions of alternative metric bolting.

For the purposes of this International Standard, the following verbal forms apply:

- "shall" indicates a requirement strictly to be followed in order to conform to this International Standard and from which no deviation is permitted, unless accepted by all involved parties;
- "should" indicates that among several possibilities one is recommended as particularly suitable, without mentioning or excluding others, or that a certain course of action is preferred but not necessarily required;
- "may" indicates a course of action permissible within the limits of this International Standard;
- "can" is used for statements of possibility and capability, whether material, physical or casual.

Petroleum and natural gas industries — Compact flanged connections with IX seal ring

1 Scope

This International Standard specifies detailed manufacturing requirements for circular steel and nickel alloy compact flanged connections and associated seal rings, for designated pressures and temperatures in class designations CL 150 (PN 20) to CL 1500 (PN 260) for nominal sizes from DN 15 (NPS ½) to DN 1200 (NPS 48), and for CL 2500 (PN 420) for nominal sizes from DN 15 (NPS ½) to DN 600 (NPS 24).

NOTE NPS is in accordance with ASME B36.10M and ASME B36.19M.

This International Standard is applicable to welding neck flanges, blind flanges, paddle spacers and spacer blinds (paddle blanks), valve/equipment integral flanges, orifice spacers, reducing threaded flanges and rigid interfaces for use in process piping for the petroleum, petrochemical and natural gas industries.

This International Standard is applicable within a temperature range from –196 °C to +250 °C.

This International standard is not applicable for external pressure.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2768-1, *General tolerances — Part 1: Tolerances for linear and angular dimensions without individual tolerance indications*

ISO 4288, *Geometric Product Specifications (GPS) — Surface texture: Profile method — Rules and procedures for the assessment of surface texture*

ISO 5167-1, *Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full — Part 1: General principles and requirements*

ISO 5167-2:2003, *Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full — Part 2: Orifice plates*

ISO 14313, *Petroleum and natural gas industries — Pipeline transportation systems — Pipeline valves*

ISO 80000-1:2009, *Quantities and units — Part 1: General*

ASME B16.5, *Pipe Flanges and Flanged Fittings: NPS 1/2 through NPS 24 Metric/Inch Standard*

ASME B16.34, *Valves — Flanged, Threaded and Welding End*

ASME B1.20.1, *Pipe Threads, General Purpose (Inch)*

ASME B31.3, *Process Piping*

EN 1092-1, *Flanges and their joints — Circular flanges for pipes, valves, fittings and accessories, PN designated — Part 1: Steel flanges*

EN 1779, *Non-destructive testing — Leak testing — Criteria for method and technique selection*

3 Terms, definitions, symbols and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1.1

class

CL

ASME pressure class in accordance with ASME B16.5 and ASME B16.34

3.1.2

compact flanged connection

CFC

non-gasketed bolted static pipe connection including two flanges and where the bolt loads are transferred through metal to metal contact between the flange faces

3.1.3

gasket

barrier to prevent the passage of fluids, but which does transmit all loads between flanges

EXAMPLE As shown in EN 1591-1:2001, Figure 3.

3.1.4

purchaser

individual or organization that buys the pipe connection on behalf of the user and/or operator or for its own use

3.1.5

seal

component providing a barrier to prevent the passage of fluids, transmitting no significant loads between the flanges

3.1.6

supplier

individual or organization that takes the responsibility for the supply of the pipe connection and its conformance with this International Standard

3.2 Symbols

A outside diameter of neck

A_{\max} maximum outer diameter to accommodate standard tools

A_{\min} minimum neck outer diameter listed in Table 7 to Table 12

$Area_{015}$ cross-sectional area of the neck/pipe calculated from t_{015}

$Area_{\text{eqv}}$ cross-sectional area of a special flange neck geometry calculated from t_{eqv}

B bore diameter, where the bore should not exceed the maximum listed bore in this International Standard

B_{\max} maximum listed bore diameter