Acoustics - Measurement of sound absorption in a reverberation room

Acoustics - Measurement of sound absorption in a reverberation room



EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

Käesolev Eesti standard EVS-EN ISO
354:2004 sisaldab Euroopa standardi EN
ISO 354:2003 ingliskeelset teksti.

Käesolev dokument on jõustatud 23.11.2004 ja selle kohta on avaldatud teade Eesti standardiorganisatsiooni ametlikus väljaandes.

Standard on kättesaadav Eesti standardiorganisatsioonist.

This Estonian standard EVS-EN ISO 354:2004 consists of the English text of the European standard EN ISO 354:2003.

This document is endorsed on 23.11.2004 with the notification being published in the official publication of the Estonian national standardisation organisation.

The standard is available from Estonian standardisation organisation.

Käsitlusala:

This International Standard specifies a method of measuring the sound absorption coefficient of acoustical materials used as wall or ceiling treatments, or the equivalent sound absorption area of objects, such as furniture, persons or space absorbers, in a reverberation room. It is not intended to be used for measuring the absorption characteristics of weakly damped resonators.

Scope:

This International Standard specifies a method of measuring the sound absorption coefficient of acoustical materials used as wall or ceiling treatments, or the equivalent sound absorption area of objects, such as furniture, persons or space absorbers, in a reverberation room. It is not intended to be used for measuring the absorption characteristics of weakly damped resonators.

ICS 91.120.20

Võtmesõnad:

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

EN ISO 354

May 2003

ICS 91.120.20

Supersedes EN ISO 354: 1993.

Ref. No. EN ISO 354: 2003 E

English version

Acoustics

Measurement of sound absorption in a reverberation room (ISO 354: 2003)

Acoustique – Mesurage de l'absorption acoustique en salle réverbérante (ISO 354 : 2003)

Akustik – Messung der Schallabsorption in Hallräumen (ISO 354 : 2003)

This European Standard was approved by CEN on 2003-04-23.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Management Centre or to any CEN member.

The European Standards exist in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, the Czech Republic, Denmark, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Luxembourg, Malta, the Netherlands, Norway, Portugal, Slovakia, Spain, Sweden, Switzerland, and the United Kingdom.

CEN

European Committee for Standardization Comité Européen de Normalisation Europäisches Komitee für Normung

Management Centre: rue de Stassart 36, B-1050 Brussels

Page 2 EN ISO 354 : 2003

Foreword

International Standard

ISO 354: 2003 Acoustics - Measurement of sound absorption in a reverberation room,

which was prepared by ISO/TC 43 'Acoustics' of the International Organization for Standardization, has been adopted by Technical Committee CEN/TC 126 'Acoustic properties of building products and of buildings', the Secretariat of which is held by AFNOR, as a European Standard.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, and conflicting national standards withdrawn, by November 2003 at the latest.

In accordance with the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard:

Austria, Belgium, the Czech Republic, Denmark, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Luxembourg, Malta, the Netherlands, Norway, Portugal, Slovakia, Spain, Sweden, Switzerland, and the United Kingdom.

Endorsement notice

The text of the International Standard ISO 354 : 2003 was approved by CEN as a European Standard without any modification.

NOTE: Normative references to international publications are listed in Annex ZA (normative). is a preview senerated by the **Contents** Page

Forew	word	2
Introd	duction	3
1	Scope	4
2	Normative references	4
3	Terms and definitions	4
4	Principle	6
5	Frequency range	6
6 6.1 6.2 6.3	Test arrangementReverberation room and diffusion of sound field	6 7
7 7.1 7.2 7.3 7.4	Measurement of reverberation time	8 9 10
8 8.1 8.2 8.3	Expression of results Method of calculation Precision Presentation of results	12 12 14 15
9	Test report	16
Anne	ex A (normative) Diffusivity of the sound field in the reverberation room	17
	ex B (normative) Test specimen mountings for sound absorption tests	
	ography	

Introduction

When a sound source operates in an enclosed space, the level to which reverberant sound builds up, and the subsequent decay of reverberant sound when the source is stopped, are governed by the sound-absorbing characteristics of the boundary surfaces, the air filling the space, and objects within the space. In general, the fraction of the incident sound power absorbed at a surface depends upon the angle of incidence. In order to relate the reverberation time of an auditorium, office, workshop, etc., to the noise reduction that would be effected by an absorbing treatment, knowledge of the sound-absorbing characteristics of the surfaces, usually in the form of a suitable average over all angles of incidence, is required. Since the distribution of sound waves in typical enclosures includes a wide and largely unpredictable range of angles, a uniform distribution is taken as the basic condition for the purposes of standardization. If, in addition, the sound intensity is independent of the location within the space, the sound distribution is called a diffuse sound field, and the sounds reaching a room surface are said to be at random incidence.

The sound field in a properly designed reverberation room closely approximates a diffuse field. Hence, sound absorption measured in a reverberation room closely approximates the sound absorption that would be measured under the basic conditions assumed for standardization.

The purpose of this International Standard is to promote uniformity in the methods and conditions of measurement of sound absorption in reverberation rooms.

Page 4

EN ISO 354: 2003

1 Scope

This International Standard specifies a method of measuring the sound absorption coefficient of acoustical materials used as wall or ceiling treatments, or the equivalent sound absorption area of objects, such as furniture, persons or space absorbers, in a reverberation room. It is not intended to be used for measuring the absorption characteristics of weakly damped resonators.

The results obtained can be used for comparison purposes and for design calculation with respect to room acoustics and noise control.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 266, Acoustics — Preferred frequencies

ISO 9613-1, Acoustics — Attenuation of sound during propagation outdoors — Part 1: Calculation of the absorption of sound by the atmosphere

IEC 61260, Electroacoustics — Octave-band and fractional-octave-band filters

3 Terms and definitions

For the purpose of this document, the following terms and definitions apply.

3.1

decay curve

graphical representation of the decay of the sound pressure level in a room as a function of time after the sound source has stopped

3.2

reverberation time

T

time, in seconds, that would be required for the sound pressure level to decrease by 60 dB after the sound source has stopped

NOTE 1 The definition of T with a decrease by 60 dB of the sound pressure level can be fulfilled by linear extrapolation of shorter evaluation ranges.

NOTE 2 This definition is based on the assumptions that, in the ideal case, there is a linear relationship between the sound pressure level and time, and that the background noise level is sufficiently low.