Durability of reaction to fire performance - Classes of fire-retardant treated wood products in interior and exterior end use applications



EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

	This Estonian standard EVS-EN 16755:2017 consists of the English text of the European standard EN 16755:2017 and its corrigendum AC:2018.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas.	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
	Date of Availability of the European standard is 11.10.2017, for corrigendum 18.07.2018
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 13.220.40, 13.220.50, 71.100.50

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega: Koduleht www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:

Homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

EUROPEAN STANDARD NORME EUROPÉENNE

EN 16755

EUROPÄISCHE NORM

October 2017

ICS 13.220.40; 13.220.50; 71.100.50

Supersedes CEN/TS 15912:2012

English Version

Durability of reaction to fire performance - Classes of fireretardant treated wood products in interior and exterior end use applications

Durabilité des performances de réaction au feu -Classement des produits à base de bois ignifugés pour utilisation finale en intérieur et en extérieur Dauerhaftigkeit des Verhaltens bei Brandeinwirkung -Klassen der mit Feuerschutzmitteln behandelten Holzprodukte für Anwendungen im Innen- und Außenbereich

This European Standard was approved by CEN on 2 July 2017.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

This document consolidates EN 16755:2017 and the corrigendum EN 16755:2017/AC:2018.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Con	tents	Page
_	· 6	
-	oean foreword	
Intro	ductionduction	4
1	Scope	5
2	Normative references	5
3	Terms and definitions	6
4	Symbols and abbreviations	6
5	Requirements	
5.1	Wood products and non-fire-retardant coating systems	
5.2	Reaction to fire performance	
5.2.1	Initial classification for reaction to fire	
5.2.2	Reaction to fire performance before and after accelerated or natural weathering	
5.2.2	Durability of reaction to fire performance	
5.3.1	General	
5.3.2	DRF Class INT1	_
5.3.3	DRF Class INT2	
5.3.4	DRF Class EXT	
5.3.5	Practise to use DRF classes	
6	Classification report	11
Annos	x A (normative) Hygroscopic properties of fire-retardant treated wood products	
Aime	including those with fire-retardant coatings	12
A.1	GeneralGeneral	
A.2	Field of application	12
A.3	Sampling, sample handling and preparation	
A.3.1	General procedure	
A.3.2	Procedure for end use products	
A.4	Test method	
A.4.1	Principle	
A.4.2	Equipment	
A.4.3	Testing environment	14
Annex	x B (normative) Accelerated weathering of fire-retardant treated wood for fire testing	17
B.1	General	
B.2	Field of application	
B.3	Sampling, sample handling and preparation	
B.4	Test method	
B.4.1	Principle	
B.4.2	Equipment	
B.4.2 B.4.3	Testing environment	
_		19
Annex	x C (informative) Example of classification report — Classification report: Durability	
	classes of reaction to fire performance of fire-retardant wood products in interior	
	and exterior end use applications according to EN 16755:2017	22
Diblia	ography	26
חומום	/gi apiiy	ZO

European foreword

This document (EN 16755:2017) has been prepared by Technical Committee CEN/TC 175 "Round and sawn timber", the secretariat of which is held by AFNOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by April 2018, and conflicting national standards shall be withdrawn at the latest by April 2018.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

AC) This document supersedes CEN/TS 15912:2012. (AC)

This document includes the corrigendum EN 16755:2017/AC:2018 which adds the above superseding note.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, id, nania, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Introduction

Fire-retardant treatments may considerably improve the reaction to fire properties of wood products and these may result in wood products having the highest fire performance characteristics achievable with any combustible product. However, the reaction to fire performance may be reduced by exposure to wet and/or humid conditions [11] and the ability of the treated products to continue to perform even when exposed to these conditions needs to be demonstrated.

Two aspects of the reaction to fire durability of fire-retardant wood products need to be considered. One is the risk for high moisture content and migration of the fire-retardant chemicals within the wood product and salt crystallization on the product surface that may fall off and reduce the improved fire properties. These hygroscopic properties of the treated wood product can be evaluated by exposure to high relative humidity.

The other aspect is the risk for decreased fire performance due to loss of the fire-retardant chemicals by leaching in exterior applications, e.g. facade claddings. Maintained fire performance after weathering needs to be verified.

This standard is based on the Technical Specification CEN/TS 15912, on a Nordtest standard [20] and a of the series on experience from North America [10, 9].

1 Scope

This European Standard describes the characteristics for fire-retardant treated wood products.

NOTE 1 It is based on maintaining performance undiminished throughout the desired service life in the anticipated conditions of use.

The European Standard prescribes the classification requirements for the durability of the reaction to fire performance of fire-retardant treated wood products to be used in interior and exterior end use conditions.

This European Standard applies to wood which has been treated during a production process with fire retardant products applied either by a penetration process or by a superficial process, such as with a film forming or intumescent fire retardant coating. It covers fire-retardant treated products that are coated with an ordinary paint.

Mechanical properties and biological durability of fire-retardant treated wood products are not covered by this European Standard.

NOTE 2 This standard can be used for other manufactured wood products.

This standard covers wood products. It doesn't cover wood-based panels.

NOTE 3 Wood based panels for construction are described in EN 13986.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 927-3, Paints and varnishes — Coating materials and coating systems for exterior wood — Part 3: Natural weathering test

EN 927-6, Paints and varnishes — Coating materials and coating systems for exterior wood — Part 6: Exposure of wood coatings to artificial weathering using fluorescent UV lamps and water

EN 13238, Reaction to fire tests for building products — Conditioning procedures and general rules for selection of substrates

EN 13501-1, Fire classification of construction products and building elements — Part 1: Classification using data from reaction to fire tests

EN 13823, Reaction to fire tests for building products — Building products excluding floorings exposed to the thermal attack by a single burning item

ISO 5660-1, Reaction-to-fire tests — Heat release, smoke production and mass loss rate — Part 1: Heat release rate (cone calorimeter method) and smoke production rate (dynamic measurement)