Bituminous mixtures - Test methods for hot mix asphalt - Part 8: Determination of void characteristics of bituminous specimens

Bituminous mixtures - Test methods for hot mix asphalt - Part 8: Determination of void characteristics of bituminous specimens



EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

Käesolev Eesti standard EVS-EN 12697-
8:2003 sisaldab Euroopa standardi EN
12697-8:2003 ingliskeelset teksti.

Käesolev dokument on jõustatud 15.04.2003 ja selle kohta on avaldatud teade Eesti standardiorganisatsiooni ametlikus väljaandes.

Standard on kättesaadav Eesti standardiorganisatsioonist.

This Estonian standard EVS-EN 12697-8:2003 consists of the English text of the European standard EN 12697-8:2003.

This document is endorsed on 15.04.2003 with the notification being published in the official publication of the Estonian national standardisation organisation.

The standard is available from Estonian standardisation organisation.

Käsitlusala:

This European Standard describes a procedure for calculating two volumetric characteristics of a compacted bituminous specimen: the air voids content (Vm) and the voids content in the mineral aggregate filed with binder (VFB)

Scope:

This European Standard describes a procedure for calculating two volumetric characteristics of a compacted bituminous specimen: the air voids content (Vm) and the voids content in the mineral aggregate filed with binder (VFB)

ICS 93.080.20

Võtmesõnad: constructi, definitions, density of space, determination, determination of content, hot mix asphalts, mathematical calculations, mechanical properties, performance tests, physical properties, road construction, sampling, sampling methods, test specimens, testing

EUROPEAN STANDARD NORME EUROPÉENNE

EUROPÄISCHE NORM

EN 12697-8

March 2003

ICS 93.080.20

English version

Bituminous mixtures - Test methods for hot mix asphalt - Part 8: Determination of void characteristics of bituminous specimens

Mélanges bitumineux - Méthodes d'essai pour enrobés à chaud - Partie 8: Détermination de la teneur en vides des éprouvettes bitumineuses

Asphalt - Prüfverfahren für Heißasphalt - Teil 8: Bestimmung von volumetrischen Charakteristiken von Asphalt-Probekörpern

This European Standard was approved by CEN on 21 November 2002.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Management Centre has the same status as the official versions

CEN members are the national standards bodies of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Luxembourg, Malta, Netherlands, Norway, Portugal, Slovakia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Contents

Eoro	eword	page
1 01 0 1	Scope	
2	Normative references	
- 3	Terms and definitions	
4	Determination of the air voids content $(V_{ m m})$	
5	Determination of the percentage of the voids in the mineral aggregate fille	
Bibli	liography	
	This a province of the second	
2		
_		

Foreword

This document (EN 12697-8:2003) has been prepared by Technical Committee CEN/TC 227 "Road materials", the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by September 2003, and conflicting national standards shall be withdrawn at the latest by August 2005.

This European Standard is one of a series of standards as listed below.

EN 12697-1, Bituminous mixtures - Test methods for hot mix asphalt - Part 1: Soluble binder content

EN 12697-2, Bituminous mixtures – Test methods for hot mix asphalt – Part 2: Determination of particle size distribution

EN 12697-3, Bituminous mixtures – Test methods for hot mix asphalt – Part 3: Binder recovery: Rotary evaporator

EN 12697-4, Bituminous mixtures – Test methods for hot mix asphalt – Part 4: Binder recovery: Fractionating column

EN 12697-5, Bituminous mixtures - Test methods for hot mix asphalt - Part 5: Determination of the maximum density

EN 12697-6, Bituminous mixtures – Test methods for hot mix asphalt – Part 6: Determination of bulk density of bituminous specimen by hydro-static method

EN 12697-7, Bituminous mixtures – Test methods for hot mix asphalt – Part 7: Determination of bulk density of bituminous specimens by gamma rays

EN 12697-8, Bituminous mixtures – Test methods for hot mix asphalt – Part 8: Determination of void characteristics of bituminous mixtures

EN 12697-9, Bituminous mixtures – Test methods for hot mix asphalt – Part 9: Determination of the reference density

EN 12697-10, Bituminous mixtures – Test methods for hot mix asphalt – Part 10: Compactibility

prEN 12697-11, Bituminous mixtures – Test methods for hot mix asphalt – Part 11: Determination of the compatability between aggregate and binder

prEN 12697-12, Bituminous mixtures – Test methods for hot mix asphalt – Part 12: Determination of the water sensitivity of bituminous specimens

EN 12697-13, Bituminous mixtures – Test methods for hot mix asphalt – Part 13: Temperature measurement

EN 12697-14, Bituminous mixtures – Test methods for hot mix asphalt – Part 14: Water content

EN 12697-15, Bituminous mixtures – Test methods for hot mix asphalt – Part 15: Determination of the segregation sensitivity

prEN 12697-16, Bituminous mixtures – Test methods for hot mix asphalt – Part 16: Abrasion by studded tyres

prEN 12697-17, Bituminous mixtures – Test methods for hot mix asphalt – Part 17: Partial loss of porous asphalt specimen

prEN 12697-18, Bituminous mixtures – Test methods for hot mix asphalt – Part 18: Binder drainage from porous asphalt

EN 12697-8:2003 (E)

prEN 12697-19, Bituminous mixtures - Test methods for hot mix asphalt - Part 19: Permeability of specimen

prEN 12697-20, Bituminous mixtures – Test methods for hot mix asphalt – Part 20: Indentation using cube or marshall specimen

prEN 12697-21, Bituminous mixtures – Test methods for hot mix asphalt – Part 21: Indentation using plate specimens

prEN 12697-22, Bituminous mixtures - Test methods for hot mix asphalt - Part 22: Wheel tracking

prEN 12697-23, Bituminous mixtures – Test methods for hot mix asphalt – Part 23: Determination of the indirect tensile strength of bituminous specimens

prEN 12697-24, Bituminous mixtures – Test methods for hot mix asphalt – Part 24: Resistance to fatigue

prEN 12697-25, Bituminous mixtures – Test methods for hot mix asphalt – Part 25: Cyclic compression test

prEN 12697-26, Bituminous mixtures - Test methods for hot mix asphalt - Part 26: Stiffness

EN 12697-27, Bituminous mixtures – Test methods for hot mix asphalt – Part 27: Sampling

EN 12697-28, Bituminous mixtures – Test methods for hot mix asphalt – Part 28: Preparation of samples for determining binder content, water content and grading

EN 12697-29, Bituminous mixtures – Test methods for hot mix asphalt – Part 29: Determination of the dimensions of bituminous specimen

prEN 12697-30, Bituminous mixtures – Test methods for hot mix asphalt – Part 30: Preparation of specimen by impact compactor

prEN 12697-31, Bituminous mixtures – Test methods for hot mix asphalt – Part 31: Specimen preparation, gyratory compactor

EN 12697-32, Bituminous mixtures – Test methods for hot mix asphalt – Part 32: Laboratory compaction of bituminous mixtures by a vibratory compactor

prEN 12697-33, Bituminous mixtures – Test methods for hot mix asphalt – Part 33: Specimen preparation, slab compactor

prEN 12697-34, Bituminous mixtures – Test methods for hot mix asphalt – Part 34: Marshall test

prEN 12697-35, Bituminous mixtures - Test methods for hot mix asphalt - Part 35: Laboratory mixing

EN 12697-36, Bituminous mixtures – Test methods for hot mix asphalt – Part 36: Method for the determination of the thickness of a bituminous pavement

prEN 12697-37, Bituminous mixtures – Test methods for hot mix asphalt – Part 37: Hot sand test for the adhesivity of binder on precoated chippings for HRA

prEN 12697-38, Bituminous mixtures – Test methods for hot mix asphalt – Part 38: Test equipment and calibration

The applicability of this European Standard is described in the product standards for bituminous mixtures. No existing European Standard is superseded.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Luxembourg, Malta, Netherlands, Norway, Portugal, Slovakia, Spain, Sweden, Switzerland and the United Kingdom.

1 Scope

This European Standard describes a procedure for calculating two volumetric characteristics of a compacted bituminous specimen: the air voids content (V_m) and the voids content in the mineral aggregate filed with binder (VFB).

The method is suitable for specimens which are laboratory compacted or specimens from cores cut from the pavement after placement and compacting.

These volumetric characteristics can be used as mix design criteria or as parameters for evaluating the mixture after placing and compacting in the road.

2 Normative references

This European Standard incorporates by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this European Standard only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies (including amendments).

EN 12697-5, Bituminous mixtures – Test methods for hot mix asphalt – Part 5: Determination of the maximum density.

EN 12697-6, Bituminous mixtures – Test methods for hot mix asphalt – Part 6: Determination of bulk density of bituminous specimens by hydro-static method.

3 Terms and definitions

For the purposes of this European Standard, the following terms and definitions apply.

3.1

air void

pocket of air between the bitumen-coated aggregate particles in a compacted bituminous specimen

3.2

air voids content

 (V_{m})

volume of the air voids in a bituminous specimen, expressed as a percentage of the total volume of that specimen

3.3

maximum density

mass per unit volume without air voids of a bituminous material at known test temperature

3.4

bulk density

mass per unit volume, including the air voids, of a specimen at known test temperature

3.5

void in the mineral aggregate

(VMA)

volume of inter-granular void space between the aggregate particles of a compacted bituminous mixture that includes the air voids and the volume of the bituminous binder in the specimen, expressed as a percentage of the total volume of the specimen

NOTE An allowance should be made for the absorbency of binder by the aggregate, which can otherwise lead to an over estimation of the air voids content. The level of absorbency depends on the porosity of the aggregate.