

Third edition
2014-07-15

Corrected version
2014-11-01

**Gas cylinders — Cylinder valves —
Specification and type testing**

*Bouteilles à gaz — Robinets de bouteilles — Spécifications et essais de
type*



Reference number
ISO 10297:2014(E)

© ISO 2014

This document is a preview generated by EBS



COPYRIGHT PROTECTED DOCUMENT

© ISO 2014

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	vii
1 Scope	1
2 Normative references	1
3 Terms, definitions and symbols	2
4 Valve description	6
5 Valve design requirements	10
5.1 General	10
5.2 Materials	11
5.3 Dimensions	11
5.4 Valve connections	12
5.5 Mechanical strength	13
5.6 Valve operating mechanism	13
5.7 Valve operating device	16
5.8 Leakage	16
5.9 Resistance to ignition	16
6 Type testing	17
6.1 General	17
6.2 Documentation	19
6.3 Test samples	19
6.4 Test report	19
6.5 Test temperatures	20
6.6 Test pressures	20
6.7 Test gases	20
6.8 Test schedule	21
6.9 Hydraulic burst pressure test	23
6.10 Flame impingement test	24
6.11 Excessive torque tests	24
6.12 Leak tightness tests	24
6.13 Endurance test	26
6.14 Visual examination	27
7 Marking	27
Annex A (normative) Impact test	29
Annex B (normative) Tests for acetylene valves	31
Annex C (normative) Oxygen pressure surge test	32
Annex D (informative) Example of test schedule	36
Annex E (informative) Example of a vacuum test	37
Annex F (normative) Endurance test machine	38
Bibliography	40

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2. www.iso.org/directives

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received. www.iso.org/patents

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT), see the following URL: [Foreword - Supplementary information](#)

The committee responsible for this document is ISO/TC 58, *Gas cylinders*, Subcommittee SC 2, *Cylinder fittings*.

This third edition cancels and replaces the second edition (ISO 10297:2006), which has been technically revised.

The main technical modifications are:

- a) Scope: inclusion of main valves and valves with integrated pressure regulator (VIPR), exclusion of quick-release valves, non-return valves and ball valves;
- b) Terms, definitions and symbols: introduction of new definitions and adaptation of existing definitions;
- c) Valve description: new clause with figures and general description;
- d) Valve design requirements:
 - 1) General: inclusion of additional requirement of internal leak tightness at -40°C during transport and storage;
 - 2) Materials: deletion of requirements already given in ISO 11114-1 and ISO 11114-2; deletion of ageing sensitivity test for non-metallic materials; addition of requirement on ductility of valve body material; addition of requirement on suitability of lubricants for valve test pressure;
 - 3) Dimensions: deletion of requirement on bore of the valve with regard to flow requirement and adaption of requirements for valves fitted with a valve protection cap according to ISO 11117;
 - 4) Valve connections: addition of requirements for separate valve filling connection;
 - 5) Resistance to mechanical impact: addition of requirement for impact testing valves protected by a valve guard but fixed only to the valve, modification of acceptance criteria;

- 6) Valve operating mechanism: inclusion of allowance to increase the endurance torque for some valve designs and to adjust compressed packed valves during endurance testing; replacement of acetylene flashback test by alternative tests without using acetylene and addition of acetylene decomposition test for main valves; modification of acceptance criteria;
- 7) Valve operating device: addition of requirement on the handwheel diameter required to achieve the minimum closing torque; modification of acceptance criteria for flame impingement test;
- 8) Resistance to ignition: addition of requirement of oxygen pressure surge testing for certain cylinder valves for gas mixtures containing oxygen and other oxidizing gases and of detailed information on acceptance criteria; addition of mandatory reference to oxygen pressure surge test for VIPR specified in ISO 22435 or ISO 10524-3 and for cylinder valves with residual pressure devices specified in ISO 15996;
- e) Production requirements: deletion of all respective requirements but reference to ISO 14246 in scope;
- f) Type testing:
 - 1) General: addition of requirements for repeating tests depending on applied changes for a valve design;
 - 2) Documentation: addition of detailed information on documentation required;
 - 3) Test samples: addition of requirement to have pressure gauges/indicators fitted;
 - 4) Test report: addition of detailed information required;
 - 5) Test pressures: adaption of information on burst test pressure (former hydraulic test pressure);
 - 6) Test gas: addition of requirement for using helium or hydrogen or an inert mixture of these gases for the leak tightness tests for cylinder valves for helium and hydrogen and their mixtures; extension of requirements on gas quality;
 - 7) Test schedule: deletion of ageing as preconditioning and leak tightness test before ageing; addition of internal leak tightness test at $-40\text{ }^{\circ}\text{C}$ after endurance test; adaption of oxygen pressure surge test for cylinder valves with lubricants not rated for valve test pressure; listing of impact test;
 - 8) Hydraulic burst pressure test: addition of testing the valve in closed position;
 - 9) Excessive torque tests: addition of requirement to carry out the test with the valve operating device in place; differentiation between handwheel and key/toggle operated valves; extension of tests with requirement of two additional test samples;
 - 10) Leak tightness tests: reference to informative [Annex E](#) for an example of a vacuum test; unification of the lower test pressure of 0,5 bar for all gases; implementation of internal leak tightness test at $-40\text{ }^{\circ}\text{C}$; addition of information on required position of the valve operating mechanism for external leak tightness test; adaption of requirement for test order for all required test pressures; adaption of requirement for changing and maintaining the different test temperatures; adaption of requirement for minimum closing torque;
 - 11) Endurance test: addition of requirement to carry out the test with the handwheel in place and of description of procedure for increasing the endurance torque for some valve designs;
 - 12) Visual examination: addition of separate sub-clause for visual examination with detailed information on acceptance criteria;
 - 13) Oxygen pressure surge test: information on test installation and test procedure transferred to normative [Annex C](#); addition of detailed information on determination of pressure rise time; addition of divergent installation requirements for testing main valves; addition of detailed information on acceptance criteria;

- 14) Acetylene test: information transferred to normative [Annex B](#);
 - 15) Impact test: addition of information on the valving torque according to ISO 13341 to be used; addition of subsequent hydraulic burst pressure test and internal leak tightness test; modification of test procedure;
 - 16) Marking: addition of requirement for marking cylinder valves oxygen pressure surge tested via different connections and of detailed information on marking of valve inlet, valve outlet and separate valve filling connections;
 - 17) Example of test sequence: information transferred from informative [Annex B](#) to informative [Annex D](#) and adaptation according to new requirements for valve designs and changes and material specifications within a valve design;
 - 18) Addition of informative [Annex E](#), giving an example of a vacuum test;
 - 19) Endurance test equipment and procedure: information transferred from normative [Annex C](#) to normative [Annex F](#).
- g) full editorial rework.

This corrected version of ISO 10297:2014 incorporates the addition of titles to Figures 5 and 6.

Introduction

This International Standard covers the function of a cylinder valve as a closure (defined by the UN Model Regulations). Additional features of cylinder valves (e.g. pressure regulators, residual pressure devices, non-return devices and pressure relief devices) might be covered by other standards and/or regulations.

Cylinder valves complying with this International Standard can be expected to perform satisfactorily under normal service conditions.

This International Standard pays particular attention to:

- a) suitability of materials;
- b) safety (mechanical strength, impact strength, endurance, leak tightness, resistance to ignition, resistance to acetylene flashback);
- c) testing;
- d) marking.

This standard has been written to be in conformity with the UN Model Regulations. When published it will be submitted to the UN Sub Committee of Experts on the Transport of Dangerous Goods with a request that it be included in the UN Model Regulations.

Where there is any conflict between this International Standard and any applicable regulation, the regulation always takes precedence.

Considering the changes described in the Foreword, when a cylinder valve has been approved according to the previous version of this International Standard the body responsible for approving the same cylinder valve to this new edition should consider which tests need to be performed.

In this International Standard the unit bar is used, due to its universal use in the field of technical gases. It should, however, be noted that bar is not an SI unit, and that the corresponding SI unit for pressure is Pa ($1 \text{ bar} = 10^5 \text{ Pa} = 10^5 \text{ N/m}^2$).

Pressure values given in this International Standard are given as gauge pressure (pressure exceeding atmospheric pressure) unless noted otherwise.

Gas cylinders — Cylinder valves — Specification and type testing

1 Scope

This International Standard specifies design, type testing and marking requirements for:

- a) cylinder valves intended to be fitted to refillable transportable gas cylinders;
- b) main valves (excluding ball valves) for cylinder bundles;
- c) cylinder valves or main valves with integrated pressure regulator (VIPR);

which convey compressed, liquefied or dissolved gases.

NOTE 1 Where there is no risk of ambiguity, cylinder valves, main valves and VIPR are addressed with the collective term “valves” within this International Standard.

This International Standard covers the function of a valve as a closure.

This International Standard does not apply to

- valves for cryogenic equipment, portable fire extinguishers and liquefied petroleum gas (LPG), and
- quick-release valves (e.g. for fire-extinguishing, explosion protection and rescue applications), non-return valves or ball valves.

NOTE 2 Requirements for valves for cryogenic vessels are specified in ISO 21011 and at a regional level e.g. in EN 1626. Requirements for LPG valves are specified in ISO 14245 or ISO 15995. Requirements for quick-release valves are specified e.g. in ISO 17871. Requirements for valves for portable fire extinguishers at a regional level are specified e.g. in EN 3 series. Requirements for non-return valves and ball valves might be specified in international/regional standards.

NOTE 3 Requirements for manufacturing tests and examinations of valves covered by this International Standard are given in ISO 14246.

NOTE 4 Additional requirements for VIPR are specified in ISO 22435 for industrial applications or ISO 10524-3 for medical applications. Additional requirements for residual pressure valves with or without a non-return function are specified in ISO 15996. Additional requirements for pressure-relief devices might be specified in international/regional regulations/standards.

NOTE 5 Additional specific requirements for valves for breathing apparatus at a regional level are specified e.g. in EN 144 series. Additional specific requirements for quick-release valves for fixed fire-fighting systems are specified in ISO 16003 and at a regional level e.g. in EN 12094-4.

2 Normative references

The following referenced documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 148-1, *Metallic materials — Charpy pendulum impact test — Part 1: Test method*

ISO 407, *Small medical gas cylinders — Pin-index yoke-type valve connections*

ISO 10286, *Gas cylinders — Terminology*

ISO 10524-3, *Pressure regulators for use with medical gases — Part 3: Pressure regulators integrated with cylinder valves*

ISO 11114-1, *Gas cylinders — Compatibility of cylinder and valve materials with gas contents — Part 1: Metallic materials*

ISO 11114-2, *Gas cylinders — Compatibility of cylinder and valve materials with gas contents — Part 2: Non-metallic materials*

ISO 11117:2008, *Gas cylinders — Valve protection caps and valve guards — Design, construction and tests*

ISO 13341, *Gas cylinders — Fitting of valves to gas cylinders*

ISO 15615:2013, *Gas welding equipment — Acetylene manifold systems for welding, cutting and allied processes — Safety requirements in high-pressure devices*

ISO 15996, *Gas cylinders — Residual pressure valves — General requirements and type testing*

ISO 22435, *Gas cylinders — Cylinder valves with integrated pressure regulators — Specification and type testing*

3 Terms, definitions and symbols

For the purposes of this document, the terms and definitions given in ISO 10286, and the following apply.

3.1
valve operating mechanism
mechanism which closes and opens the valve orifice and which includes the internal and external sealing systems

Note 1 to entry: In ISO 22435 the valve operating mechanism is called shut-off mechanism.

Note 2 to entry: For some VIPR designs the pressure regulating valve can act as the shut-off mechanism.

EXAMPLE A threaded valve spindle which, when rotated, raises and lowers a seal/seal.

3.2
valve design
classification of valves with regard to the *valve operating mechanism* ([3.1](#))

3.3
valve operating device
component which actuates the *valve operating mechanism* ([3.1](#))

EXAMPLE Handwheel, key, knob, toggle, lever or actuator.

3.4
external leak tightness
leak tightness to atmosphere (leakage in and/or leakage out) when the valve is open

Note 1 to entry: See [Figure 1](#).