
**Colloidal systems — Methods for zeta
potential determination —**

**Part 3:
Acoustic methods**

*Systèmes colloïdaux — Méthodes de détermination du potentiel
zêta —*

Partie 3: Méthodes acoustiques



This document is a preview generated by EBS



COPYRIGHT PROTECTED DOCUMENT

© ISO 2014

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms, definitions and symbols	1
3.1 Electric double layer (EDL)	1
3.2 Electrokinetic phenomena	3
3.3 Electroacoustic phenomena	4
4 Symbols	6
5 Principle	7
6 Zeta potential probe design elements	8
7 Determination of the dynamic electrophoretic mobility	8
7.1 Subtracting background electroacoustic signal generated by ions	9
8 Calculation of zeta potential	10
8.1 General	10
8.2 Isolated double layers	10
8.3 Overlapped double layers	13
9 Operational procedures	13
9.1 Requirements	13
9.2 Verification	14
9.3 Sources of measurement error	15
Annex A (informative) Electroacoustics: high frequency electrokinetics	16
Annex B (informative) Verification of electroacoustic theories	17
Bibliography	20

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 24, *Particle characterization including sieving*, Subcommittee SC 4, *Particle characterization*.

ISO 13099 consists of the following parts, under the general title *Colloidal systems — Methods for zeta potential determination*:

- *Part 1: Electroacoustic and electrokinetic phenomena*
- *Part 2: Optical methods*
- *Part 3: Acoustic methods*

Introduction

Zeta potential is a parameter that can be used to predict the long term stability of suspensions and emulsions, and to study surface morphology and surface adsorption of particles and other surfaces in contact with a liquid. Zeta potential is not a directly measurable parameter. It can be determined using appropriate theoretical models from experimentally determined parameters, which depend on electric charge separation at interfaces. “Electrokinetic phenomena” encompass such experimentally observed effects. A group of electrokinetic phenomena at high frequency on MHz scale is referred to as “electroacoustics”.^[1] Each classical electrokinetic phenomenon at DC or low AC conditions has electroacoustic analogue. These electroacoustic phenomena have been widely used to determine electrophoretic mobility of various concentrated particulates without sample dilution. The purpose of this part of ISO 13099 in methods for Zeta potential determination is description of general features of such electroacoustic methods that should be common for all instrumental implementation for measuring electrophoretic mobility using electroacoustics and following calculation of zeta potential of particulates.

Colloidal systems — Methods for zeta potential determination —

Part 3: Acoustic methods

1 Scope

This part of ISO 13099 describes in general electroacoustic effects that can be defined as high frequency electrokinetic phenomena.

Particular attention is given to two methods of measurement of electrophoretic mobility of particles suspended in a liquid at high concentration above 1 % v/v, colloid vibration current (CVI)^[2] and electric sonic amplitude (ESA)^[3] ^[4] respectively.

Estimation of surface charge and determination of zeta potential can be achieved from measured electrophoretic mobility using proper theoretical models, which are described in detail in ISO 13099-1.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 13099-1, *Colloidal systems — Methods for zeta-potential determination — Part 1: Electroacoustic and electrokinetic phenomena*

ISO 13099-2, *Colloidal systems — Methods for zeta-potential determination — Part 2: Optical methods*

3 Terms, definitions and symbols

For the purposes of this document, the following terms and definitions apply.

3.1 Electric double layer (EDL)

The electric double layer (EDL) is a spatial distribution of electric charges that appears on and at the vicinity of the surface of an object when it is placed in contact with a liquid.

3.1.1

Debye-Hückel approximation

model assuming small electric potentials in the electric double layer

3.1.2

Debye length

κ^{-1}

characteristic length of the electric double layer in an electrolyte solution

Note 1 to entry: The Debye length is expressed in nanometres.