INTERNATIONAL STANDARD

First edition 2012-11-01

<text>

Information géographique — Architecture d'identifiants de lieu (IL)



Reference number ISO 19155:2012(E)



(C)

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org

Published in Switzerland

Contents

Page

Fore	word		iv		
Intro	oductio	n	v		
1	Scop	ie			
2	Conf 2.1 2.2 2.3 2.4 2.5	Formance Conformance clause Conformance tests for Semantics Conformance tests for Data Conformance tests for Services Conformance tests for PI encoding	1 1 1 1 1 1 1		
3	Normative references				
4	Tern	ns and definitions			
5	Abbi 5.1 5.2	reviated terms and notation Abbreviated terms UML Notation	4 4 4		
6	PI Re 6.1 6.2 6.3 6.4 6.5	eference Model Background PI Reference Model components PI platform PI interface PI user	5 6 7 8		
7	PI pl 7.1 7.2 7.3	atform components Overall layout of the PI platform Data Services			
8	Inter 8.1 8.2 8.3 8.4 8.5	rfaces for the PI platform Overview Interface for PI matching service Interface for PI reference system service. Structures Exception handling	14 14 14 16 20 27		
Ann	ex A (no	ormative) Abstract test suite			
Ann	ex B (no	ormative) PI encoding using GML			
Ann	ex C (in	formative) PI encoding using 'tag' URI Scheme			
Ann	e x D (in	formative) PI encoding using Well Known Text (WKT)			
Ann	ex E (in	formative) Use case examples			
Bibl	iograpł	ny	41		

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 19155 was prepared by Technical Committee ISO/TC 211, Geographic information/Geomatics.

E. Que		
	2	S

Introduction

The rapid development of information technology has blurred the boundaries between the real and virtual worlds in such a way that they cannot easily be disassociated from each other. Humans can reference places in both worlds and easily differentiate between them. However for computers to clearly differentiate these places, a set of matched linkages between them are required.

In the discipline of geography, space normally refers to the surface of the earth. However, in other disciplines, space can refer to different paradigms. In architecture, space may be the extent of a room or a building. In mathematics, space is defined as a set having structure. In the context of the World Wide Web space is defined by URLs/URIs that identify web pages.

Within this International Standard "space" is considered as a set having structure, in which a position or location identifies an element.

Currently, within the domain of ISO/TC 211, standards exist for precise positioning and locating using either coordinates or geographic identifiers. However, the concept of place is broader than both position and location. A "place" is referred to as a "position" when that place is identified using coordinates. Similarly, a "place" is referred to as a "location" when that place is identified using geographic identifiers. However, existing standards defined by ISO/TC 211 do not provide a mechanism for the representation of a virtual "place" such as a website, or a construct acting as a "common base" which can be used to refer to the other types of identifiers.

Within this International Standard, "place" is defined as an identifiable part of any space. This may include "places" existing not only in the real world but also those in the virtual world. Places are identified using either "position" by coordinates, "location" by geographic identifiers, or "virtual world identifiers" such as a URI.

In this International Standard, the identifier of a place is referred to as a Place Identifier (PI). A single "place" may be identified using several separate Place Identifiers. Clarification of these relationships is shown in Figure 1.



Figure 1 — Relationships among place, position, location and URI

Place descriptions are used for information retrieval. In reality, those identifiers often refer to the same place. Currently these relationships are difficult for machines to correctly distinguish, which impedes the discovery and retrieval of information. The conceptual architecture and reference model defined in this International Standard provides a mechanism for solving these problems.

When implemented, this architecture would enable the access and sharing of place descriptions using the Place Identifier as the standardized method.

Within the reference model, place descriptions are defined using a PI. A PI consists of a reference system (RS), a value, and the valid temporal period of that value.

The internal format and content of the value are determined by each community or domain. The content of the values are not subject to any kind of standardization or unification by this International Standard. The RS is also defined by each community, and should be unique across multiple communities. Subsequently, Place Identifiers are unique within each RS. However, the values of the Place Identifiers may be similar or even identical across multiple communities. This distributed concept ensures that each community would maintain their own Place Identifiers. Well formed Place Identifiers may be shared between communities.

Instead of specifying a framework for a globally unique type of identifier, the key idea of the architecture defined in this International Standard enables the original place descriptions to be easily maintained, without requiring difficult conversions and cross-community harmonization.

An encoding scheme based on Geography Markup Language (GML) (ISO 19136:2007) is normatively defined in this International Standard. In addition, a group of alternate encoding schemes are presented as informative annexes. Depending on the encoding method of choice, globally unique Place Identifiers may be created resulting from the requirements of the encoding method used.

Methods for the conversion of "located features" to Place Identifiers are not covered within the scope of this International Standard. While the direct relationship with the PI Architecture and other Spatial Data Infrastructures (SDIs) is not explained, an implementation of the PI Architecture can be considered part of an SDI. Various constructs, such as registries and databases, may be used to store Place Identifiers. The flexible structure of the Place Identifier will allow for data stored in common GI systems to be easily registered as Place Identifiers, however, the design and implementation of those procedures is out of scope of this International Standard.

Geographic information — Place Identifier (PI) architecture

1 Scope

This International Standard specifies an architecture that defines a reference model with an encoding method for an identifier of a place. The concept of "place" within this International Standard includes "places" not only in the real world but also those in the virtual world. These "places" are identified using either coordinate identifiers, geographic identifiers, or virtual world identifiers such as URI. In this International Standard, an identifier of a place is referred to as a Place Identifier (PI).

The reference model defines a mechanism to match multiple Place Identifiers to the same place. In addition, a data structure and set of service interfaces are also defined in this reference model.

This International Standard is applicable to location based services, emergency management services and other application domains that require a common architecture, across specific domains, for the representation of place descriptions using coordinate, geographic, or virtual world identifiers.

This International Standard is not about producing any kind of specific place description, nor about defining a unique, standardized description of defined places, such as an address coding scheme.

2 Conformance

2.1 Conformance clause

This International Standard specifies four conformance classes. The following conformance clauses should be followed in order to meet the requirements of this International Standard.

2.2 Conformance tests for Semantics

To conform to this International Standard, instances of PI_PlaceIdentifier, PI_ReferenceSystem, PI_MatchingTable, and PI_MatchedPISet shall satisfy the requirements of A.1.

2.3 Conformance tests for Data

To conform to this International Standard, data stored in the PI matching table and the reference system shall satisfy the requirements of A.2.

2.4 Conformance tests for Services

To conform to this International Standard, interfaces between services and users that the PI matching service and the reference system service implement shall satisfy the requirements of A.3.

2.5 Conformance tests for PI encoding

To conform to this International Standard, encoded instances of PI_PlaceIdentifier shall satisfy the requirements of A.4.

3 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/TS 19103:2005, Geographic Information — Conceptual schema language

ISO 19111:2007, Geographic information — Spatial referencing by coordinates

ISO 19112:2003, Geographic information — Spatial referencing by geographic identifiers

ISO 19136:2007, Geographic information — Geography Markup Language

4 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

4.1

client

software component that can invoke an operation from a server (4.16)

[ISO 19128:2005, 4.1]

4.2

coordinate

one of a sequence of *n* numbers designating the position of a point in *n*-dimensional space

[ISO 19111:2007, 4.5]

NOTE In a *coordinate reference system* (4.4), the coordinate numbers are qualified by units.

4.3

coordinate operation

change of *coordinates* (4.2), based on a one-to-one relationship, from one *coordinate reference system* (4.4) to another

[ISO 19111:2007, 4.7]

NOTE Supertype of coordinate transformation and coordinate conversion.

4.4

coordinate reference system

coordinate (4.2) system that is related to an object by a datum

[ISO 19111:2007, 4.8]

NOTE For geodetic and vertical datums, the object will be the Earth.

4.5

gazetteer

directory of instances of a class or classes of features containing some information regarding position

[ISO 19112:2003, 4.2]

NOTE The positional information need not be *coordinates* (4.2), but could be descriptive.

4.6

geographic identifier

spatial reference (4.19) in the form of a label or code that identifies a location

[ISO 19112:2003, 4.3]

EXAMPLE 'Spain' is an example of a country name; 'SW1P 3AD' is an example of a postcode.