# Unbound and hydraulically bound mixtures - Part 41: Test method for the determination of the compressive strength of hydraulically bound mixtures

Unbound and hydraulically bound mixtures - Part 41: Test method for the determination of the compressive strength of hydraulically bound mixtures



#### EESTI STANDARDI EESSÕNA

#### **NATIONAL FOREWORD**

Käesolev Eesti standard EVS-EN 13286-
41:2003 sisaldab Euroopa standardi EN
13286-41:2003 ingliskeelset teksti.

Käesolev dokument on jõustatud 15.04.2003 ja selle kohta on avaldatud teade Eesti standardiorganisatsiooni ametlikus väljaandes.

Standard on kättesaadav Eesti standardiorganisatsioonist.

This Estonian standard EVS-EN 13286-41:2003 consists of the English text of the European standard EN 13286-41:2003.

This document is endorsed on 15.04.2003 with the notification being published in the official publication of the Estonian national standardisation organisation.

The standard is available from Estonian standardisation organisation.

#### Käsitlusala:

This European Standard describes a test method for the determination of the compressive strength of specimens of hydraulically bound mixtures (HBM). This European standard applies to specimens manufactured in the laboratory or prepared from cores

#### Scope:

This European Standard describes a test method for the determination of the compressive strength of specimens of hydraulically bound mixtures (HBM). This European standard applies to specimens manufactured in the laboratory or prepared from cores

ICS 93.080.20

**Võtmesõnad:** density (mass/volume), particu, pavements, pavements (roads), road construction, roads, rocks, sample division, samples, sampling, sampling methods, specification (approval), specifications, specimen preparation, test specimens, testing, testing conditions, unbound

## EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

EN 13286-41

March 2003

ICS 93.080.20

#### **English version**

# Unbound and hydraulically bound mixtures - Part 41: Test method for the determination of the compressive strength of hydraulically bound mixtures

Mélanges traités et mélanges non traités aux liants hydrauliques - Partie 41: Méthode d'essai pour la détermination de la résistance à la compression des mélanges traités aux liants hydrauliques Ungebundene und hydraulisch gebundene Gemische - Teil 41: Prüfverfahren zur Bestimmung der Druckfestigkeit hydraulisch gebundener Gemische

This European Standard was approved by CEN on 29 November 2002.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Luxembourg, Malta, Netherlands, Norway, Portugal, Slovak Republic, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

### Contents

	0	page
Fore		
1		
2	Normative references	 5
3		
4	-	
5	Apparatus	 6
6	Test specimen	 6
7 7.1 7.2 7.3 7.4 7.5 7.6 7.7	Dimensions	6777
9	Test report	8
9.1 9.2	Compulsory information	8
		5
2		

#### **Foreword**

This document (EN 13286-41:2003) has been prepared by Technical Committee CEN/TC 227 "Road materials", the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by September 2003, and conflicting national standards shall be withdrawn at the latest by December 2004.

This European Standard is one of a series of standards as listed below.

EN 13286-1, Unbound and hydraulically bound mixtures - Part 1: Test methods for laboratory reference density and water content – Introduction, general requirements and sampling.

prEN 13286-2, Unbound and hydraulically bound mixtures - Part 2: Test methods for laboratory reference density and water content - Proctor compaction.

EN 13286-3, Unbound and hydraulically bound mixtures - Part 3: Test methods for laboratory reference density and water content - Vibrocompression with controlled parameters.

EN 13286-4, Unbound and hydraulically bound mixtures - Part 4: Test methods for laboratory reference density and water content - Vibrating hammer.

EN 13286-5, Unbound and hydraulically bound mixtures - Part 5: Test methods for laboratory reference density and water content - Vibrating table.

prEN 13286-7, Unbound and hydraulically bound mixtures - Part 7: Cyclic load triaxial test for unbound mixtures.

EN 13286-40, Unbound and hydraulically bound mixtures - Part 40: Test method for the determination of the direct tensile strength of hydraulically bound mixtures.

EN 13286-41, Unbound and hydraulically bound mixtures - Part 41: Test method for the determination of the compressive strength of hydraulically bound mixtures.

EN 13286-42, Unbound and hydraulically bound mixtures - Part 42: Test method for the determination of the indirect tensile strength of hydraulically bound mixtures.

EN 13286-43, Unbound and hydraulically bound mixtures - Part 43: Test method for the determination of the modulus of elasticity of hydraulically bound mixtures.

prEN 13286-44, Unbound and hydraulically bound mixtures - Part 44: Test method for the determination of the alpha coefficient of vitrified blastfurnace slag.

prEN 13286-45, Unbound and hydraulically bound mixtures - Test methods - Part 45: Test method for the determination of the workability period of hydraulically bound mixtures.

EN 13286-46, Unbound and hydraulically bound mixtures - Part 46: Test method for the determination of the moisture condition value.

prEN 13286-47, Unbound and hydraulically bound mixtures - Part 47: Test methods for the determination of California bearing ratio, immediate bearing index and linear swelling.

prEN 13286-48, Unbound and hydraulically bound mixtures - Part 48: Test method for the determination of the degree of pulverisation.

#### EN 13286-41:2003 (E)

prEN 13286-49, Unbound and hydraulically bound mixtures - Part 49: Test method for the determination of the accelerated swelling of soil treated by lime and/or hydraulic binder.

prEN 13286-50, Unbound and hydraulically bound mixtures - Part 50: Method for the manufacture of test specimens of hydraulically bound mixtures using Proctor equipment or vibrating table compaction.

prEN 13286-51, Unbound and hydraulically bound mixtures - Part 51: Method for the manufacture of test specimens of hydraulically bound mixtures using vibrating hammer compaction.

prEN 13286-52, Unbound and hydraulically bound mixtures - Part 52: Method for the manufacture of test specimens of hydraulically bound mixtures using vibrocompression.

prEN 13286-53, Unbound and hydraulically bound mixtures - Part 53: Method for the manufacture of test specimens of hydraulically bound mixtures using axial compression.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Czech Republic, Denmark, Finland, et d, Irt, and and to France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Luxembourg, Malta, Netherlands, Norway, Portugal, Slovak Republic, Spain, Sweden, Switzerland and the United Kingdom.

#### 1 Scope

This European Standard describes a test method for the determination of the compressive strength of specimens of hydraulically bound mixtures. This European Standard applies to specimens manufactured in the laboratory or prepared from cores.

#### 2 Normative references

This European Standard incorporates by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text, and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this European Standard only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies (including amendments).

EN 12390-3:2001, Testing hardened concrete — Part 3: Compressive strength of test specimens.

prEN 13286-50, Unbound and hydraulically bound mixtures — Part 50: Method for the manufacture of test specimens of hydraulically bound mixtures using Proctor equipment or vibrating table compaction.

prEN 13286-51, Unbound and hydraulically bound mixtures — Part 51: Method for the manufacture of test specimens of hydraulically bound mixtures using vibrating hammer compaction.

prEN 13286-52, Unbound and hydraulically bound mixtures — Part 52: Method for the manufacture of test specimens of hydraulically bound mixtures using vibrocompression.

prEN 13286-53, Unbound and hydraulically bound mixtures — Part 53: Method for the manufacture of test specimens of hydraulically bound mixtures using axial compression.

#### 3 Terms and definitions

For the purposes of this European Standard, the following terms and definitions apply.

#### 3.1

#### hydraulically bound mixture

mixture that hardens by hydraulic and/or pozzolanic and/or sulphatic and/or carbonatic reaction, which usually has a workability to suit compaction by rolling and which is generally used in bases, sub-bases and capping layers

#### 3.2

#### compressive strength

stress at failure of a specimen when tested in uniaxial unconfined compression

#### 3.3

#### slenderness ratio

ratio of the length to the diameter of a cylindrical specimen

#### 4 Principle

A specimen is subjected to a compressive force until failure. The maximum load sustained by the specimen is recorded and the compressive strength is calculated.