

Automotive fuels - Paraffinic diesel fuel from synthesis or hydrotreatment - Requirements and test methods

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

See Eesti standard EVS-EN 15940:2016 sisaldab Euroopa standardi EN 15940:2016 ingliskeelset teksti.	This Estonian standard EVS-EN 15940:2016 consists of the English text of the European standard EN 15940:2016.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 29.06.2016.	Date of Availability of the European standard is 29.06.2016.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 75.160.20

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:

Aru 10, 10317 Tallinn, Eesti; koduleht www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:

Aru 10, 10317 Tallinn, Estonia; homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

English Version

Automotive fuels - Paraffinic diesel fuel from synthesis or hydrotreatment - Requirements and test methods

Carburants pour automobiles - Gazoles paraffiniques
de synthèse ou obtenus par hydrotraitement -
Exigences et méthodes d'essais

Kraftstoffe für Kraftfahrzeuge - Paraffinischer
Dieselkraftstoff aus Synthese oder
Hydrierungsverfahren - Anforderungen und
Prüfverfahren

This European Standard was approved by CEN on 15 April 2016.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents	Page
European foreword	4
Introduction	6
1 Scope	7
2 Normative references	7
3 Sampling	9
4 Pump marking	9
5 Requirements and test methods	9
5.1 Dyes and markers	9
5.2 Additives.....	9
5.2.1 General.....	9
5.2.2 Methylcyclopentadienyl Manganese Tricarbonyl (MMT)	9
5.3 Fatty acid methyl ester (FAME).....	10
5.4 Cavitation prevention.....	10
5.5 Seizure protection.....	10
5.6 Generally applicable requirements and related test methods.....	10
5.7 Climate dependent requirements and related test methods	12
5.8 Precision and dispute	13
Annex A (informative) Seizure protection	14
Annex B (normative) Details of interlaboratory test programme	15
Annex C (normative) Details of HPLC procedure	16
C.1 Warning	16
C.2 Scope	16
C.3 Terms and definitions	16
C.4 Principle	17
C.5 Reagents and materials.....	17
C.6 Apparatus.....	18
C.7 Sample handling and storage.....	20
C.8 Apparatus preparation	20
C.9 Calibration	22
C.10 Procedure.....	24
C.11 Calculation	26
C.11.1 Reference time	26
C.11.2 Column resolution	27
C.11.3 Cut times.....	27
C.11.4 Aromatic hydrocarbons type content.....	27
C.11.5 Total aromatic hydrocarbons content.....	27
C.12 Test precision	28
C.12.1 General.....	28
C.12.2 Repeatability, r	28
C.12.3 Reproducibility, R	28
C.13 Test report.....	28
Annex D (normative) Measurements and constants for paraffinic fuel products and components	29
D.1 General.....	29

D.2	Short abstract of density / temperature conversion formulae and constants.....	29
D.3	Measurements and constants for paraffinic diesel fuel products and components	30
D.4	Conclusions	32
	Bibliography	33

This document is a preview generated by EVS

European foreword

This document (EN 15940:2016) has been prepared by Technical Committee CEN/TC 19 “Gaseous and liquid fuels, lubricants and related products of petroleum, synthetic and biological origin”, the secretariat of which is held by NEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by December 2016, and conflicting national standards shall be withdrawn at the latest by December 2016.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes CEN/TS 15940:2012.

Significant other technical changes between this document and CEN/TS 15940:2012 are:

- a) the limits for distillation at 250 °C and 350 °C are included in line with EN 590 and the EU Common Customs tariff for diesel fuel;
- b) EN ISO 3924, also known as simulated distillation, has been incorporated in Table 1 as an additional methodology to determine distillation characteristics;
- c) prEN 16906 (EN equivalent to DIN 51773, *Testing of liquid fuels — Determination of ignition quality (cetane number) of Diesel fuels with the BASF-engine*) has been studied and allowed as an additional methodology to determine cetane number;
- d) in order to allow fitness for purpose product and to align it with EN 590 product that has proven functionality in diesel engines, the arctic climate viscosity limits and the distillation recovery at 180 °C have been introduced in Table 3;
- e) in order to present all relevant requirements within the same fuel specification, the necessary climate dependent properties from EN 590 have been introduced in 5.7; this required reference of some additional test methods in Clause 2;
- f) further clarification on the oxidation stability requirement, as a result of recent changes in EN 15751, has been introduced;
- g) exclusion of special sampling procedures for clean paraffinic fuel as they apply to diesel fuel in general;
- h) to further underline the link with EN 590 that normative reference being stipulated without reference to a particular date of publication;
- i) introduction of an annex of the precision data for test methods where different from normal diesel fuel in following the CEN/TC 19 interlaboratory study [1];
- j) introduction of an annex covering a test procedure for aromatics content determination being developed as part of a second interlaboratory study funded by the EC on three different HPLC techniques;

- k) introduction of an annex on density – temperature corrections being developed as part of a CEN/TC 19 investigation led by Mr. H. Th. Feuerhelm of DIN-FAM.

In this document, all relevant characteristics, requirements and test methods are specified. These specifications are relevant for the driveability of the vehicles and are currently known to prevent harm to the vehicles and their powertrains. Climate dependent requirements of this document may vary according to national adoptions of EN 590 and EN 14214, but should be indicated by a specific National Annex.

Several assessments of test methods for paraffinic diesel fuel have been executed and the results thereof [1] led to conclusions regarding the applicability of each of the test methods as required in Clause 5. The conclusion of these assessments, partially funded by the European Commission, led to the possibility to upgrade the original Technical Specification into a full European Standard. Although it is its main actual use, the product is now no longer limited to captive fleet usage, but the scope defines the need to check the use of the product with the vehicle manufacturer. There are no EU legislative needs to limit the product to captive fleets. Such restriction is not for the specification but for the market to decide upon. Therefore, and in the light of the defined need to check the use of the product with the vehicle manufacturer, all restrictions towards captive fleet from the CEN/TS text have been deleted

This document is based on current knowledge at the time of publishing, but will require revision when the specification for either regular automotive diesel fuel, EN 590, or FAME, EN 14214, has been determined (revised) by CEN/TC 19 or based on further experiences with the use of paraffinic diesel fuel according to this document. Further background can be found in CEN/TR 16389 [2].

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Introduction

This document has been laid down to define a quality specification for diesel fuel on the basis of synthesis gas or of hydrotreated bio-oils or -fats. Its main use is as diesel fuel in dedicated diesel vehicle fleets and engines. Paraffinic diesel fuel does not meet the current diesel fuel specification, EN 590. The main differences between paraffinic diesel fuel and automotive diesel fuel are in the areas of density, sulfur, aromatics and cetane. Its density can be outside the regular diesel specification, and the described class A type fuel has a higher cetane number. Paraffinic diesel fuel is not validated for all vehicles, consult vehicle manufacturer before use.

Paraffinic diesel is a high quality, clean burning fuel with virtually no sulfur and aromatics. Paraffinic diesel fuel can be used in diesel engines (see NOTE 1 under Clause 1 and the last paragraph of Clause 4), also to reduce regulated emissions. In order to have the greatest possible emissions reduction, a specific calibration may be necessary. Paraffinic diesel fuel can also offer a meaningful contribution to the target of increased non-petroleum and/or renewable content in transportation fuel pool.

As some production processes result in a fuel containing *cyclo*-paraffins, as well as *n*-paraffins and *iso*-paraffins, they show different cetane number compared to other paraffinic diesel fuels. Hence, in this document, two classes have been defined, one class showing improved ignition quality compared to regular diesel fuel.

Blending of paraffinic diesel with biodiesel (FAME) is covered in this document. Against the background of the EU Renewable Energy Directive (RED, 2009/28/EC [3]) and also the latest developments regarding European regular diesel specification, there is now a pressing requirement to allow for FAME blend variations of those paraffinic fuels, which are not already classified as being from renewable resources.

As with CEN/TS 15940, this document allows for a paraffinic diesel specification other than the former CWA 15940, to “mirror” the current EN 590 diesel fuel quality specification. That is, allowing a blend variant of paraffinic diesel in the same way that CEN diesel quality specifications allow for refinery diesel up to 7 % (V/V) FAME blend percentage.

Paraffinic diesel may also be used as a blending component for automotive diesel fuel, but this is not in the scope of this document.

The document will be usable on a voluntary basis for engine clearance, fuel acceptance and fuelling station allowance, supporting both local regulations and international trade.

1 Scope

This European Standard describes requirements and test methods for marketed and delivered paraffinic diesel fuel containing a level of up to 7,0 % (V/V) fatty acid methyl ester (FAME). It is applicable to fuel for use in diesel engines and vehicles compatible with paraffinic diesel fuel. It defines two classes of paraffinic diesel fuel: high cetane and normal cetane.

Paraffinic diesel fuel originates from synthesis or hydrotreatment processes.

NOTE 1 For general diesel engine warranty, paraffinic automotive diesel fuel may need a validation step, which for some existing engines may still need to be done (see also the Introduction to this document). The vehicle manufacturer needs to be consulted before use.

NOTE 2 For the purposes of this document, the terms “% (m/m)” and “% (V/V)” are used to represent respectively the mass fraction and the volume fraction.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 116:2015, *Diesel and domestic heating fuels — Determination of cold filter plugging point — Stepwise cooling bath method*

EN 12662:2014, *Liquid petroleum products — Determination of total contamination in middle distillates, diesel fuels and fatty acid methyl esters*

EN 14078:2014, *Liquid petroleum products — Determination of fatty acid methyl ester (FAME) content in middle distillates — Infrared spectrometry method*

EN 14214:2012+A1:2014, *Liquid petroleum products — Fatty acid methyl esters (FAME) for use in diesel engines and heating applications — Requirements and test methods*

EN 15195:2014, *Liquid petroleum products — Determination of ignition delay and derived cetane number (DCN) of middle distillate fuels by combustion in a constant volume chamber*

EN 15751:2014, *Automotive fuels — Fatty acid methyl ester (FAME) fuel and blends with diesel fuel — Determination of oxidation stability by accelerated oxidation method*

EN 16136:2015, *Automotive fuels — Determination of manganese and iron content in unleaded petrol — Inductively coupled plasma optical emission spectrometry (ICP OES) method*

EN 16329:2013, *Diesel and domestic heating fuels — Determination of cold filter plugging point — Linear cooling bath method*

prEN 16906, *Liquid petroleum products — Determination of the ignition quality of diesel fuels — BASF engine method*

EN 23015:1994, *Petroleum products — Determination of cloud point (ISO 3015:1992)*

EN ISO 1042:1999, *Laboratory glassware — One-mark volumetric flasks (ISO 1042:1998)*

EN ISO 2160:1998, *Petroleum products — Corrosiveness to copper — Copper strip test (ISO 2160:1998)*

- EN ISO 2719:2002, *Determination of flash point — Pensky-Martens closed cup method (ISO 2719:2002)*¹⁾
- EN ISO 3104:1996, *Petroleum products — Transparent and opaque liquids — Determination of kinematic viscosity and calculation of dynamic viscosity (ISO 3104:1994)*
- EN ISO 3170:2004, *Petroleum liquids — Manual sampling (ISO 3170:2004)*
- EN ISO 3171:1999, *Petroleum liquids — Automatic pipeline sampling (ISO 3171:1988)*
- EN ISO 3405:2011, *Petroleum products — Determination of distillation characteristics at atmospheric pressure (ISO 3405:2011)*
- EN ISO 3675:1998, *Crude petroleum and liquid petroleum products — Laboratory determination of density - Hydrometer method (ISO 3675:1998)*
- EN ISO 3924:2010, *Petroleum products — Determination of boiling range distribution — Gas chromatography method (ISO 3924:2010)*
- EN ISO 4259:2006, *Petroleum products — Determination and application of precision data in relation to methods of test (ISO 4259:2006)*
- EN ISO 5165:1998, *Petroleum products — Determination of the ignition quality of diesel fuels — Cetane engine method (ISO 5165:1998)*
- EN ISO 6245:2002, *Petroleum products — Determination of ash (ISO 6245:2001)*
- EN ISO 10370:2014, *Petroleum products — Determination of carbon residue — Micro method (ISO 10370:2014)*
- EN ISO 12156-1:2016, *Diesel fuel — Assessment of lubricity using the high-frequency reciprocating rig (HFRR) — Part 1: Test method (ISO 12156-1:2016)*
- EN ISO 12185:1996, *Crude petroleum and petroleum products — Determination of density — Oscillating U-tube method (ISO 12185:1996)*
- EN ISO 12205:1996, *Petroleum products — Determination of the oxidation stability of middle-distillate fuels (ISO 12205:1995)*
- EN ISO 12937:2000, *Petroleum products — Determination of water — Coulometric Karl Fischer titration method (ISO 12937:2000)*
- EN ISO 13759:1996, *Petroleum products — Determination of alkyl nitrate in diesel fuels — Spectrometric method (ISO 13759:1996)*
- EN ISO 20846:2011, *Petroleum products — Determination of sulfur content of automotive fuels — Ultraviolet fluorescence method (ISO 20846:2011)*
- EN ISO 20884:2011, *Petroleum products — Determination of sulfur content of automotive fuels — Wavelength-dispersive X-ray fluorescence spectrometry (ISO 20884:2011)*

1) Under revision.