INTERNATIONAL STANDARD

ISO 18418-2

> First edition 2014-11-15

Gasoline engines — Medium pressure liquid fuel supply connections —

Part 2: Pipe assemblies

enct yenne p. ignes assem. Moteurs à essence — Connections pour des lignes de combustible liquide à moyenne pression —

Partie 2: Lignes assemblées





vroduced or utilized c te internet or an ' or ISO's memb All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org

Published in Switzerland

Contents			Page
Fore	vord		iv
Intro	duction		v
1	Scope		1
2	Normative	references	1
3	Dimensions and tolerances		1
4	Cleanliness	S	3
5	Minimum b	linimum bend radii	
6	6.1 Gene6.2 Type6.3 Pipe	eral end assembly for 60° female cones	3 4
7	Operating p	pressure	5
8	Ovality of bending portion		5
9		torque and sealing performance	
10	Designation	n	6
11		and identification	
@ ICO	2014 All wicks	vacamind	:::

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 22, Road vehicles, Subcommittee SC 7, Injection equipment and filters for use on road vehicles.

ISO 18418 consists of the following parts, under the general title *Gasoline engines — Medium pressure liquid fuel supply connections:*

- Part 1: 60° female cone connectors
- Part 2: Pipe assemblies

Introduction

ait rail a re sim. between th. Some spark ignition (SI) engines use direct injection (DI) fuel systems which supply gasoline under pressure to a rail and to the injectors via pipe assemblies with a 60° female cone connector. Such components are similar to ISO 2974 and ISO 13296 for the diesel injection systems except for the relationship between the outside and inside diameters of the pipes due to the lower pressure range.

This document is a preview general ded by tills

Gasoline engines — Medium pressure liquid fuel supply connections —

Part 2:

Pipe assemblies

1 Scope

This part of ISO 18418 specifies dimensions and requirements for medium-pressure fuel pipe assemblies and assembled pipe sets made of seamless stainless steel tubing to be used with 60° female cone connectors on gasoline (spark-ignition) engines.

NOTE 1 Dimensions of 60° female cone connectors are specified in ISO 18418-1.

NOTE 2 Material properties of stainless steel tubing are specified in ISO 9329-4. The chemical composition of stainless steels can be found in ISO 15510.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 9329-4:1997, Seamless steel tubes for pressure purposes — Technical delivery conditions — Part 4: Austenitic stainless steels

ISO 12345, Diesel engines — Cleanliness assessment of fuel injection equipment

ISO 15510:2014, Stainless steels — Chemical composition

ISO 18418-1:2014, Gasoline engines — Medium pressure liquid fuel supply connections —Part 1: 60° female cone connectors

3 Dimensions and tolerances

The requirement and configuration drawing for a pipe assembly shall include at least the following:

- a) indication of compliance with this part of ISO 18418;
- b) the thread and the hexagon size of the connector nuts according to $\underline{\text{Tables 1}}$ and $\underline{\text{2}}$;
- c) the type of the connection ends as specified in 6.2;
- d) a graphic representation of the centreline of the pipe with the connection ends and each bend intersection labelled as a point, with each point listed in a table with Cartesian coordinates *x*, *y*, and *z* with the orthogonal distance from the axis and the bend radius (the beginning and end points are given as the "S" dimension for the defined configuration);

NOTE The coordinates are used to specify the theoretical exact centreline of the pipe. See the example given in Figure 1.

- e) the developed length of the pipe as an approximated value;
- f) the material and surface finish requirements of the pipe and connector nuts.