Tsiviilkäibes olevad lõhkeained. Detoneernöörid ja süütenöörid. Osa 4: Detoneernööride löögitundlikkuse määramine

Explosives for civil uses - Detonating cords and safety fuses - Part 4: Determination of sensitiveness to impact of detonating cords



EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

Käesolev Eesti standard EVS-EN 13630-
4:2002 sisaldab Euroopa standardi EN
13630-4:2002 ingliskeelset teksti.

This Estonian standard EVS-EN 13630-4:2002 consists of the English text of the European standard EN 13630-4:2002.

Käesolev dokument on jõustatud 18.10.2002 ja selle kohta on avaldatud teade Eesti standardiorganisatsiooni ametlikus väljaandes.

This document is endorsed on 18.10.2002 with the notification being published in the official publication of the Estonian national standardisation organisation.

Standard on kättesaadav Eesti standardiorganisatsioonist.

The standard is available from Estonian standardisation organisation.

Käsitlusala:

This European Standard specifies a method for determining the sensitiveness to impact of flexible, plastic coated detonating cords, and flexible fibrous-overbraided detonating cords for civil uses, for an impact stress up to 10 joules.

Scope:

This European Standard specifies a method for determining the sensitiveness to impact of flexible, plastic coated detonating cords, and flexible fibrous-overbraided detonating cords for civil uses, for an impact stress up to 10 joules.

ICS 71.100.30

Võtmesõnad: determinations of, detonating fuses, drop hammers, explosives, igniters, ignitor, impact appliances, impact testing, inflammable matters, materials testing, mining, priming line, safety, sensitivity, shock resistance, specimen preparation, test equipment, testing

EUROPEAN STANDARD NORME EUROPÉENNE

EUROPÄISCHE NORM

EN 13630-4

September 2002

ICS 71.100.30

English version

Explosives for civil uses - Detonating cords and safety fuses - Part 4: Determination of sensitiveness to impact of detonating cords

Explosifs à usage civil - Cordeaux détonants et mèches de sûreté - Partie 4: Détermination de la sensibilité au choc des cordeaux détonants Explosivstoffe für zivile Zwecke - Sprengschnüre und Sicherheitsanzündschnüre - Teil 4: Bestimmung der Schlagempfindlichkeit von Sprengschnüren

This European Standard was approved by CEN on 11 July 2002.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Malta, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Contents

		page
Forew	word	
1	Scope	
2	Normative references	4
3	Terms and definitions	
4	Apparatus	
5	Test pieces	
6	Procedure	5
7	Test report	5
Anne	ex A (informative) Range of applicability of the test method	6
Anne	ex B (informative) Information on special types of use for detonating cords	7
Anne	ex C (normative) Illustrations of the BAM fall-hammer	8
Anne	ex ZA (informative) Clauses of this European Standard addressing essential requirement provisions of EU Directives	
	provisions of Lo birectives	
		1
		(0)
		0.
2		

Foreword

This document (EN 13630-4:2002) has been prepared by Technical Committee CEN/TC 321 "Explosives for civil uses", the secretariat of which is held by AENOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by March 2003, and conflicting national standards shall be withdrawn at the latest by March 2003.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s).

For relationship with EU Directive(s), see informative annex ZA, which is an integral part of this document.

This European Standard is one of a series of standards on *Explosives for civil uses – Detonating cords and safety fuses*. The other parts of this series are:

prEN 13630-1 Part 1: Requirements.

EN 13630-2 Part 2: Determination of thermal stability of detonating cords and safety fuses.

EN 13630-3 Part 3: Determination of sensitiveness to friction of the core of detonating cords.

prEN 13630-5 Part 5: Determination of resistance to abrasion of detonating cords.

EN 13630-6 Part 6: Determination of resistance to tension of detonating cords.

EN 13630-7 Part 7: Determination of reliability of initiation of detonating cords.

EN 13630-8 Part 8: Determination of resistance to water of detonating cords and safety fuses.

prEN 13630-9 Part 9: Determination of transmission of detonation from detonating cord to detonating cord.

WI 00321088 Part 10: Determination of initiating capability of detonating cords.

EN 13630-11 Part 11: Determination of velocity of detonation of detonating cords.

EN 13630-12 Part 12: Determination of burning duration of safety fuses.

Annexes A and B of this document are informative. Annex C is normative.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Malta, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and the United Kingdom.

1 Scope

This European Standard specifies a method for determining the sensitiveness to impact of flexible, plastics-coated detonating cords and flexible fibrous-overbraided detonating cords for civil uses, when subjected to an impact energy of 10 J.

2 Normative references

This European Standard incorporates by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text, and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this European Standard only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies (including amendments).

prEN 13857-1:2001, Explosives for civil uses — Part 1: Terminology.

EN ISO 4957, Tool steels (ISO 4957:1999).

EN ISO/IEC 17025, General requirements for the competence of testing and calibration laboratories (ISO/IEC 17025:1999).

3 Terms and definitions

For the purposes of this European Standard, the terms and definitions given in prEN 13857-1:2001 and the following apply:

3.1

drop height

distance between the lowest part of the striking head of the drop weight and the uppermost part of the test piece

4 Apparatus

4.1 General

The apparatus is a drop hammer (e.g. BAM fall-hammer), comprising a cast steel block with base, a main anvil and an intermediate anvil, a locating plate, a column, guides, and a drop weight with a release mechanism and a striking head.

4.2 Drop hammer

A steel anvil is screwed onto the steel block and cast base. The steel used for the intermediate anvil and the main anvil is of the same type as for the striking head of the drop weight (see 4.3). The support onto which the column is fixed (made from a seamless drawn steel tube) is bolted to the back of the steel block.

NOTE Figure C.1 shows the arrangement of BAM fall-hammer (the anvil, the steel block and the column)

Figure C.2 shows the arrangement of the lower part of the BAM fall-hammer.

The two guides which are fixed to the column by means of three cross-pieces are fitted with a toothed rack, to limit the rebound of the drop weight, and a moveable graduated scale for adjusting the drop height. The guides shall be vertical.

The drop height shall be (500 ± 5) mm. The drop weight release mechanism is adjustable between the guides and is clamped to them by the operation of a lever mechanism.