
**Ships and marine technology —
Transmitting heading devices (THDs) —**

**Part 3:
GNSS principles**

*Navires et technologie maritime — Dispositifs de transmission de
données de pilotage —*

Partie 3: Principes pour un système global de navigation par satellites



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

This document is a preview generated by EVS

© ISO 2004

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	iv
1 Scope.....	1
2 Normative references	2
3 Terms and definitions.....	2
4 Performance requirements	3
4.1 Functionality.....	3
4.2 Continuous operation.....	3
4.3 Presentation of information	4
4.4 Heading output alignment.....	4
4.5 Compensation for brief GNSS signal interruption	4
4.6 Settling time.....	4
4.7 Heading information	4
4.8 Alarm signal.....	4
5 Accuracy	4
5.1 General.....	4
5.2 Accuracy of transmission data.....	4
5.3 Static error (Settle point error)	4
5.4 Dynamic error.....	5
5.5 Follow-up error.....	5
6 Type tests	5
6.1 General.....	5
6.2 Organization of test conditions	5
6.3 Settling time test	5
6.4 Static error test.....	6
6.5 Dynamic test.....	6
6.6 Follow-up error test	6
6.7 Back-up test.....	7
6.8 Environmental test.....	7
6.9 Electromagnetic compatibility test	7
6.10 Heading information test.....	7
6.11 Malfunction test.....	8
7 Marking and identification	8
Annex A (informative) Equivalent requirements in ISO 22090-3 and IMO Resolution MSC.116(73)	9
Annex B (informative) Equivalent requirements in ISO 22090-3 and IEC 61108-1	10
Bibliography	11

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 22090-3 was prepared by Technical Committee ISO/TC 8, *Ships and marine technology*, Subcommittee SC 6, *Navigation*.

ISO 22090 consists of the following parts, under the general title *Ships and marine technology — Transmitting heading devices (THDs)*:

- *Part 1: Gyro-compasses*
- *Part 2: Geomagnetic principles*
- *Part 3: GNSS principles*

Ships and marine technology — Transmitting heading devices (THDs) —

Part 3: GNSS principles

1 Scope

This part of ISO 22090 specifies general requirements, construction, performance and testing of Transmitting Heading Devices using GNSS principles as required by chapter V, SOLAS 1974 (as amended).

A transmitting heading device (THD) is an electronic device that provides information about the ship's true heading.

In addition to the general requirements contained in IMO Resolution A.694 (17) to which IEC 60945 is associated and the relevant standard for the sensing part used, the THD equipment shall comply with the following minimum requirements.

Where the IMO performance standards that apply to the sensing part do not specify a geographical operating area the THD shall operate

- a) at a maximum rate of turn 20°/s; and
- b) from 70° latitude south to 70° latitude north as a minimum.

The THDs complying with the requirements contained in this part of ISO 22090 can be used for heading information as contained in Chapter V of the SOLAS Convention.

In addition such THDs should meet the dynamic requirements contained in the HSC Code, chapter 13 for the carriage of a suitable device providing heading information.

NOTE 1 Several technologies can be used to detect and transmit heading information. It is illogical to standardize the detection of the heading separately from the transmission of the heading. Therefore, separate parts of this part of ISO 22090 refer to different technologies. The requirements of this part of ISO 22090 only apply to the principle of the GNSS one. Other technologies are covered in other parts of ISO 22090.

NOTE 2 All requirements that are extracted from the recommendation of IMO Resolution MSC. 116 (73) on performance standards for transmitting heading devices are printed in italics.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 694, *Ships and marine technology — Positioning of magnetic compasses in ships*

IEC 60945, *Maritime navigation and radiocommunication equipment and systems — General requirements — Methods of testing and required test results*

IEC 61162 (all parts), *Maritime navigation and radiocommunication equipment and systems — Digital interfaces*

IMO Resolution A.424 (XI), *Performance standards for gyro-compasses*

IMO Resolution A.694 (17), *General requirements for shipborne radio equipment forming part of the global maritime distress and safety system (GMDSS) and for electronic navigational aids*

IMO Resolution A.813 (19), *General requirements for electromagnetic compatibility (EMC) for all electrical and electronic ship's equipment*

IMO Resolution A.821 (19), *Performance standards for gyro-compasses for high-speed craft*

HSC Code, chapter 13

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

heading

any ship's heading to be input to the THD function

NOTE It is defined by the direction of the vertical projection of the fore-and-aft line of the ship onto the horizontal plane. When measured relative to the true north, magnetic north or compass north, it is respectively defined as true heading, magnetic heading or compass heading, and is usually expressed in degrees as a three-figure group, starting from north, in a clockwise direction around the compass card.

3.2

sensing part

sensing function of detecting any heading information, or information of directional source (i.e. GNSS antenna), connected to the transmitting part

3.3

transmitting part

device which receives heading information, or information of directional source, from the sensing part and converts this to the required accurate signal

3.4

true heading

horizontal angle between the vertical plane passing through the true meridian and the vertical plane passing through the craft's fore and aft datum line, measured from true north (000°) clockwise through 360°

3.5

static error

error caused by any reason and which stays unchanged in value during the operation of the system, measured under static conditions

NOTE Static error is formed from the statistical mean (i.e. RMS) of the individual course deviations.