INTERNATIONAL STANDARD

ISO 5660-1

Third edition 2015-03-15

Corrected version 2021-01

Reaction-to-fire tests — Heat release, smoke production and mass loss rate —

Part 1:

Heat release rate (cone calorimeter method) and smoke production rate (dynamic measurement)

Essais de réaction au feu — Débit calorifique, taux de dégagement de fumée et taux de perte de masse —

Partie 1: Débit calorifique (méthode au calorimètre à cône) et taux de dégagement de fumée (mesurage dynamique)



Reference number ISO 5660-1:2015(E)



© ISO 2015

nentation, no part of vical, including provested from All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org

Website: www.iso.org Published in Switzerland

Coi	ntents	S	Page
Fore	word		v
1	Scope	e	1
2	1	native references	
		s and definitions	
3			
4		ools	
5	Princ	ciple	4
6	Appa	ratus	
	6.1	General	
	6.2	Cone-shaped radiant electrical heater	
	6.3	Radiation shield	
	6.4	Irradiance control	
	6.5	Weighing device	
	6.6	Specimen holder	
	6.7	Retainer frame	
	6.8	Exhaust gas system with flow measuring instrumentation	
	6.9	Gas sampling apparatus	
	6.10	Ignition circuit	
	6.11	Ignition timer	
	6.12	Oxygen analyser	
	6.13	Heat flux meters	
	6.14	Calibration burner	
	6.15	Data collection and analysis system	
	6.16	Optional side screens	
	6.17 6.18	Smoke obscuration measuring system	
	6.19	Smoke system thermocouple	0 O
		Optical litters	O
7	Suita	bility of a product for testing	9
	7.1	Surface characteristics	9
	7.2	Asymmetrical products	9
	7.3	Materials of short burning time	
	7.4	Composite specimens	
	7.5	Dimensionally unstable materials	
	7.6	Materials that require testing under compression	10
8		men construction and preparation	10
	8.1	Specimens	
	8.2	Conditioning of specimens	11
	8.3	Preparation	11
		8.3.1 Specimen wrapping	
		8.3.2 Specimen preparation	
		8.3.3 Preparing specimens of materials that require testing under compression	
9	Test e	environment	12
10	Calib	ration	12
	10.1	Preliminary calibrations	
		10.1.1 General	
		10.1.2 Irradiance control system response characteristics	12
		10.1.3 Weighing device response time	
		10.1.4 Weighing device output drift	12
		10.1.5 Oxygen analyser delay and response times	
		10.1.6 Oxygen analyser output noise and drift	
		10.1.7 Effect of side screens	
	10.2	Operating calibrations	14

ISO 5660-1:2015(E)

10	10.2.2 Weighing device accuracy 10.2.3 Oxygen analyser 10.2.4 Heat release rate calibration	
10		1 //.
10	10.2.4 Heat release rate calibration	
10		
10	10.2.5 Heater calibration	
	0.3 Smoke meter calibration	
	10.3.1 Calibration with neutral density filters	
1,	10.3.2 Calibration before test	
10	0.4 Less frequent calibrations	
	10.4.1 Operating heat flux meter calibration	
	10.4.2 Linearity of heat release rate measurements	
	est procedure	
	1.1 General precautions	
	1.2 Initial preparation	
	1.3 Procedure	
12 Ca	alculations	18
	2.1 General	18
	2.2 Calibration constant for oxygen consumption analysis	
	2.3 Heat release rate	18
	2.4 Exhaust duct flow rate	19
	2.5 Mass loss rate	19
	2.6 Smoke obscuration	20
	est report	
Annex A	(informative) Commentary and guidance notes for operators	31
Annex B	(informative) Supplementary calculations — Normalization to the mass loss rafthe specific extinction area of specimen	te
	(informative) Resolution, precision and bias	
	(informative) Mass loss rate and effective heat of combustion	
	(informative) Testing in the vertical orientation	
	(informative) Calibration of the working heat flux meter	
	(informative) Calculation of heat release with additional gas analysis	
	(informative) Calculation of Effective Critical Heat Flux for Ignition	
Bibliogra	aphy	54

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 92, *Fire safety*, Subcommittee SC 1, *Fire initiation and growth*.

This third edition of ISO 5660-1 cancels and replaces ISO 5660-1:2002 (second edition) and ISO 5660-2:2002 (first edition), which have been technically revised and merged.

ISO 5660 consists of the following parts, under the general title *Reaction-to-fire tests* — *Heat release, smoke production and mass loss rate*:

- Part 1: Heat release rate (cone calorimeter method) and smoke production rate (dynamic measurement)
- Part 3: Guidance on measurement [Technical Specification]

The following part is under preparation:

— Part 4: Measurement of heat release for determination of low levels of combustibility.

This corrected version of ISO 5660-1:2015 incorporates the following correction:

Formula (4) has been corrected.

9

This document is a previous general ded by tills

Reaction-to-fire tests — Heat release, smoke production and mass loss rate —

Part 1:

Heat release rate (cone calorimeter method) and smoke production rate (dynamic measurement)

1 Scope

This part of ISO 5660 specifies a method for assessing the heat release rate and dynamic smoke production rate of specimens exposed in the horizontal orientation to controlled levels of irradiance with an external igniter. The heat release rate is determined by measurement of the oxygen consumption derived from the oxygen concentration and the flow rate in the combustion product stream. The time to ignition (sustained flaming) is also measured in this test.

The dynamic smoke production rate is calculated from measurement of the attenuation of a laser light beam by the combustion product stream. Smoke obscuration is recorded for the entire test, regardless of whether the specimen is flaming or not.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 554, Standard atmospheres for conditioning and/or testing — Specifications

ISO 13943, Fire safety — Vocabulary

ISO 14697, Fire tests — Guidance on the choice of substrates for building products

3 Terms and definitions

For the purposes of this international standard, the terms and definitions given in ISO 13943 and the following apply.

3.1

essentially flat surface

surface whose irregularity from a plane does not exceed ± 1 mm

3.2

flashing

existence of flame on or over the surface of the specimen for periods of less than 1 s

3.3

ignition

onset of sustained flaming as defined in 3.10