INTERNATIONAL STANDARD

ISO/IEC 11582

Second edition
2002-07-01

Information technology — Telecommunications and information exchange between systems — Private Integrated Services Network — Generic functional protocol for the support of supplementary services — Inter-exchange signalling procedures and protocol

Technologies de l'information — Télécommunications et échange d'information entre systèmes — Réseau privé à intégration de services — Protocole générique fonctionnel pour le support de compléments de service — Procédures et protocole de signalisation entre commutateurs

Reference number
ISO/IEC 11582:2002(E)

© ISO/IEC 2002

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

This document is a preview generated by EVS

© ISO/IEC 2002

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.ch
Web www.iso.ch

Printed in Switzerland

 © ISO/IEC 2002 – All rights reserved

Contents

Page

Foreword vi

Introduction vii

1 Scope 1

2 Conformance 1

3 Normative references 1

4 Definitions 2

4.1 External definitions 2
4.2 ACSE APDU 2
4.3 Additional Network Feature (ANF) 2
4.4 Adjacent PINX 2
4.5 Application Protocol Data Unit (APDU) 2
4.6 Call, Basic call 2
4.7 Call independent signalling connection 2
4.8 Call independent 3
4.9 Call related 3
4.10 Connection oriented 3
4.11 Connectionless 3
4.12 Coordination Function 3
4.13 Destination PINX 3
4.14 DSE APDU 3
4.15 Dialogue Service Element (DSE) 3
4.16 End PINX 3
4.17 Gateway PINX 3
4.18 Generic Functional Transport Control (GFT-Control) entity 3
4.19 Incoming side 3
4.20 Interpretation APDU 3
4.21 Inter-PINX link 3
4.22 Invocation 3
4.23 Link significance 4
4.24 Mistyped 4
4.25 Network significance 4
4.26 Next PINX 4
4.27 Notification 4
4.28 Originating PINX 4
4.29 Outgoing side 4
4.30 PINX address 4
4.31 Preceding PINX 4
4.32 Private Signalling System No.1 4
4.33 Protocol Control 4
4.34 ROSE APDU 4
4.35 Side 4
4.36 Signalling Carriage Mechanism (SCM) 4
4.37 Source PINX 4
4.38 Subsequent PINX 5
4.39 Supplementary service 5
4.40 Supplementary Services Control (SS-Control) entity 5
4.41 Terminating PINX 5
4.42 Terminal, Terminal Equipment 5
4.43 Transit PINX 5
4.44 Unrecognised 5

This document is a preview generated by EVS

© ISO/IEC 2002 – All rights reserved

5	List of acronyms	**5**
6	General principles	**6**
6.1	Application Association	**6**
6.2	Protocol Model	**6**
6.3	Application of the protocol model to communication between SS-Control entities in non-Adjacent PINXs	**8**
6.4	Services provided by ROSE	**9**
6.5	Services provided by ACSE	**9**
6.6	Services provided by DSE	**9**
6.7	Services provided by GFT-Control	**10**
6.7.1	Connection oriented services	**10**
6.7.2	Connectionless transport services	**11**
6.7.3	Notification services	**11**
6.8	Services provided by Protocol Control to GFT-Control	**11**
6.8.1	Connection oriented transport services	**11**
6.8.2	Connectionless transport service	**12**
6.8.3	Notification services	**12**
6.9	Services required of the Signalling Carriage Mechanism	**12**
7	Protocol Control and GFT-Control Requirements	**12**
7.1	Call related Procedures for the transport of APDUs	**12**
7.1.1	Protocol Control requirements	**12**
7.1.2	GFT-Control requirements	**13**
7.2	Connectionless APDU Transport Mechanism	**20**
7.2.1	Protocol Control requirements	**20**
7.2.2	Control requirements	**20**
7.3	Connection oriented call independent APDU transport mechanism	**21**
7.3.1	Protocol Control requirements	**21**
7.3.2	Dynamic Description (SDL) of Connection oriented Protocol Control procedures	**25**
7.3.3	Generic Functional Transport Control requirements	**31**
7.4	Call related procedures for the transport of Notifications	**34**
7.4.1	Categories of notifications	**34**
7.4.2	Protocol Control requirements	**34**
7.4.3	GFT-Control requirements	**34**
8	Application layer requirements	**35**
8.1	Coordination Function requirements	**35**
8.1.1	Inclusion of an Interpretation APDU at a Source PINX	**35**
8.1.2	Handling of APDUs at a Destination PINX	**35**
8.2	ROSE requirements	**35**
8.3	ACSE requirements	**36**
8.4	DSE requirements	**36**
8.4.1	Actions at the PINX which initiates the dialogue (PINX A)	**36**
8.4.2	Actions at the PINX which terminates the dialogue (PINX B)	**37**
8.4.3	Dialogue Continuation in the Active State	**37**
8.4.4	Dialogue Protocol Timers	**37**
8.4.5	Error procedures relating to dialogue control	**38**
8.4.6	Example of a dialogue	**38**
8.4.7	Dynamic Description (SDL) of Dialogue Identification Protocol Procedures	**38**
8.5	SS-Control requirements	**43**

This document is a preview generated by EVS

 © ISO/IEC 2002 – All rights reserved

9 Manufacturer Specific Information **43**

9.1 Manufacturer specific operations **43**
9.2 Manufacturer specific additions to standardised operations **43**
9.3 Manufacturer specific notifications **44**

10 Message functional definitions and contents **45**

10.1 ALERTING **45**
10.2 CALL PROCEEDING **45**
10.3 CONNECT **46**
10.4 SETUP **46**
10.5 DISCONNECT **46**
10.6 RELEASE **46**
10.7 RELEASE COMPLETE **47**
10.8 FACILITY **47**
10.9 NOTIFY **48**
10.10 PROGRESS **48**

11 General message format and information element coding **48**

11.1 Message Type **48**
11.2 Call reference **49**
11.3 Other information elements **49**

11.3.1 Bearer capability **49**
11.3.2 Channel identification **50**
11.3.3 Facility **50**
11.3.4 Notification indicator **58**

11.4 Encoding of information described using ASN.1 **60**

Annexes

A - Protocol Implementation Conformance Statement (PICS) for ISO/IEC 11582 **61**

B - ASN.1 definitions of generic parameters **70**

C - Application of the functional protocol **75**

D - Remote operations protocol and application association control **82**

E - Formal ROSE Definitions **83**

F - Examples of the use of Manufacturer specific information **84**

G - Problem code definitions **91**

H - Bibliography **92**

I - Object identifiers defined in ISO/IEC 11582 **93**

J - “Recipe” for migration of X.208 / X.209 based QSIG ASN.1 modules to X.680 / X.690 ASN.1 **95**

K - ASN.1 definitions according to ITU-T Recs. X.208 / X.209 **100**

L - Technical changes since third edition of ECMA-165 **112**

This document is a preview generated by EVS

© ISO/IEC 2002 – All rights reserved

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 11582 was prepared by ECMA (as ECMA-165) and was adopted, under a special "fast-track procedure", by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

This second edition cancels and replaces the first edition (ISO/IEC 11582:1995), which has been technically revised.

Annexes A and B form a normative part of this International Standard. Annexes C to L are for information only.

This document is a preview generated by EVS

© ISO/IEC 2002 – All rights reserved

Introduction

This International Standard is one of a series of Standards defining services and signalling protocols applicable to Private Integrated Services Digital Networks (PISNs). The series uses ISDN concepts as developed by ITU-T and conforms to the framework of International Standards on Open Systems Interconnection as defined by ISO/IEC.

This International Standard defines the signalling protocol for use at the Q reference point between two PINXs for the transport of protocol information as part of Supplementary Services and/or Additional Network Features (ANFs) within a PISN. The protocol defined in this International Standard forms part of the PSS1 protocol (informally known as QSIG).

The generic functional procedures provide a flexible and open ended approach to the provision of supplementary service and ANF protocols. These procedures provide:

– generic protocols which may be utilised in the provision of supplementary services and ANFs, both related to existing calls and separate from existing calls where appropriate to the capability required;

– a dialogue identification protocol to enable supplementary service or ANF information flows to be tied together to form a dialogue;

– supplementary service and ANF transparency across a PISN, whereby transit PINXs need have no knowledge of the capability provided to the PISN user or PISN itself unless involved in the provision of that capability; and

– the capability for standardised and manufacturer specific capabilities to coexist in both single and multi-vendor PISNs.

The protocol defined in this International Standard is based upon that described in ITU-T Recommendation Q.932 (1993).

This International Standard is based upon the practical experience of ECMA member companies and the results of their active and continuous participation in the work of ISO/IEC JTC 1, ITU-T, ETSI and other international and national standardization bodies. It represents a pragmatic and widely based consensus.

This document is a preview generated by EVS

© ISO/IEC 2002 – All rights reserved

Information technology — Telecommunications and information exchange between systems — Private Integrated Services Network — Generic functional protocol for the support of supplementary services — Inter-exchange signalling procedures and protocol

1 Scope

This International Standard defines the signalling protocol for the control of Supplementary Services and Additional Network Features (ANFs) at the Q reference point. The protocol is part of Private Signalling System no. 1 (PSS1), known informally as QSIG. The Q reference point exists between Private Integrated services Network eXchanges (PINXs) connected together within a Private Integrated Services Network (PISN) and is defined in ISO/IEC 11579-1. Detailed procedures applicable to individual supplementary services and ANFs are beyond the scope of this International Standard and will be specified by other standards for those services which are standardised and by individual manufacturers for proprietary services using the capabilities defined in this International Standard.

ISO/IEC 11572 defines the Layer 3 protocol for circuit-switched call control at the Q reference point. This International Standard defines additional protocol procedures, to be used in conjunction with those defined in ISO/IEC 11572 for the control of supplementary services and ANFs.

NOTE 1 - Typical examples of the application of these generic functional procedures to some supplementary services are provided in annex C, for explanatory and illustrative purposes only.

NOTE 2 - Specific supplementary services and Additional Network Features may require additional information transfer mechanisms which are service or feature specific and are beyond the scope of this International Standard.

2 Conformance

In order to conform to this International Standard, a PINX shall satisfy the requirements identified in the Protocol Implementation Conformance Statement (PICS) proforma in annex A.

3 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this International Standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO/IEC 11579-1:1994, *Information technology — Telecommunications and information exchange between systems — Private integrated services network — Part 1: Reference configuration for PISN Exchanges (PINX)*

ISO/IEC 11574:2000, *Information technology — Telecommunications and information exchange between systems — Private Integrated Services Network — Circuit-mode 64 kbit/s bearer services — Service description, functional capabilities and information flows*

ISO/IEC 11572:2000, *Information technology — Telecommunications and information exchange between systems — Private Integrated Services Network — Circuit mode bearer services — Inter-exchange signalling procedures and protocol*

ISO/IEC 11571:1998, *Information technology — Telecommunications and information exchange between systems — Private Integrated Services Networks — Addressing*

ISO/IEC 15056:1997, *Information technology — Telecommunications and information exchange between systems — Private Integrated Services Network — Inter-exchange signalling protocol — Transit counter additional network feature*

ISO/IEC 6523-1:1998, *Information technology — Structure for the identification of organizations and organization parts — Part 1: Identification of organization identification schemes*

ISO/IEC 6523-2:1998, *Information technology — Structure for the identification of organizations and organization parts — Part 2: Registration of organization identification schemes*

ITU-T Rec. I.112:1993, *Vocabulary of terms for ISDNs*

ITU-T Rec. I.210:1993, *Principles of telecommunication services supported by an ISDN and the means to describe them*

ITU-T Rec. Q.932:1998, *Digital subscriber signalling system No. 1 — Generic procedures for the control of ISDN supplementary services*

This document is a preview generated by EVS

© ISO/IEC 2002 – All rights reserved