INTERNATIONAL STANDARD

ISO/IEC 22051

First edition 2002-10-01

Information technology — Data interchange on 12,7 mm, 448-track magnetic tape cartridges — SDLT1 format

Technologies de l'information — Échange de données sur cartouche à bande magnétique 12,7 mm, 448 pistes — Format SDLT1



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

This document is a preview denerated by the sylvarians

© ISO/IEC 2002

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.ch Web www.iso.ch

Printed in Switzerland

Contents

1	Scope	1
2	Conformance	1
2.1 2.2 2.3	Magnetic tape cartridges Generating systems Receiving systems	1 1 1
3	Normative references	1
4	Terms and definitions	1
4.1 4.2 4.3 4.4 4.5 4.6 4.7 4.8 4.9 4.10 4.11 4.12 4.13 4.14 4.15 4.16 4.17 4.18 4.19 4.20 4.21 4.22 4.23 4.24 4.25 4.26 4.27 4.28 4.29	back surface Beginning-Of-Tape market (BOT) block byte cartridge Cyclic Redundancy Check (CRC) baracter Error-Detecting Code (EDC) End-Of-Tape marker (EOT) Entity Error-Correcting Code (ECC) Envelope Envelope size flux transition position flux transition spacing logical track magnetic tape Master Standard Reference Tape object page recording density physical track Record Reference Edge Reference Field Secondary Standard Reference Tape Standard Reference Amplitude (SRA) Standard Reference Current Test Recording Current Typical Field Conventions and notations Representation of numbers Dimensions	1 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
5	Conventions and notations	3
5.1 5.2 5.3 5.4	Representation of numbers Dimensions Names Acronyms	3 3 3
6	Environment and safety	4
6.1 6.2 6.3 6.4 6.5 6.6	Cartridge and tape testing environment Cartridge operating environment Cartridge storage environment Safety Flammability Transportation	4 4 4 4 4

© ISO/IEC 2002 – All rights reserved

Section	2 - Requirements for the unrecorded tape	5
7	Mechanical and electrical requirements	5
7.1 7.2 7.3 7.4 7.5 7.6	Material Tape length Tape width Tape thickness Discontinuity Longitudinal curvature	5 5 5 5 5 5
7.6.1 7.6.2	Requirements Procedure	5 5
7.7 7.8 7.9	Out-of-Plane distortions Cupping Roughness of the coating surfaces	5 5 6
7.9.1 7.9.2	Roughness of the back coating surface Roughness of the magnetic coating surface	6
7.10 7.11	Coating adhesion Layer-to-layer adhesion	6
7.11.1 7.11.2	Requirements Procedure	6
7.12	Modulus of elasticity	7
7.12.1 7.12.2	Requirement Procedure	7 7
7.13	Flexural rigidity	8
7.13.1 7.13.2	Requirement Procedure	8
7.14	Tensile yield force	8
7.14.1	Procedure	8
7.15	Electrical resistance	8
7.15.1 7.15.2	Requirement Procedure	8
7.16 7.17 7.18 7.19	Roughness of the back coating afface Roughness of the magnetic coating afface Coating adhesion Layer-to-layer adhesion Requirements Procedure Modulus of elasticity Requirement Procedure Flexural rigidity Requirement Procedure Tensile yield force Procedure Electrical resistance Requirement Procedure Inhibitor tape Light transmittance of the tape and the leader Abrasivity Coefficient of dynamic friction Requirements	9 9 9
7.19.1 7.19.2 7.19.3	Requirements Procedure for the measurement of the friction between the magnetic surface and the back surface Procedure for the measurement of the friction between the magnetic surface or the back surface and calcium titanate ceramic	9 9 10
7.20	Servo	10
7.20.1 7.20.2 7.20.3 7.20.4 7.20.5	Servo Bands Servo Tracks Signal Signal-to Noise Ratio Missing servo mark	10 11 11 11 11
8	Magnetic recording characteristics	12

8.1 8.2 8.3 8.4	Typical Field Signal amplitude Resolution Overwrite	13 13 13 13
8.4.1	Requirement	13
9	Tape quality	13
9.1	Missing pulses	13
9.1.1	Requirement	13
9.2	Missing pulse zone	13
9.2.1	Requirement	13
9.3	Tape durability	13
Section	3 - Mechanical specifications of the tape cartridge	14
10	General	14
10.1 10.2 10.3 10.4 10.5 10.6 10.7 10.8 10.9	Overwrite Requirement Tape quality Missing pulses Requirement Missing pulse zord Requirement Tape durability 3 - Mechanical specifications of the tape cartridge General Bottom side and right side Back side and left side Tape reel Tape leader Front side Operation of the cartridge Tape winding Moment of inertia Material 4 - Requirements for an interchanged tape Tape format Reference Edge Direction of recording Tape layout Data Area Forward Alignment and Directory Area Reverse Alignment Area at EOT Data format Record Data Bytes Pages Page layout MAP entries EDC Data Blocks	14 15 16 17 18 18 19 19
Section	4 - Requirements for an interchanged tape	29
11	Tape format	29
11.1 11.2 11.3	Reference Edge Direction of recording Tape layout	29 29 29
11.3.1 11.3.2 11.3.3	Data Area Forward Alignment and Directory Area Reverse Alignment Area at EOT	29 31 32
12	Data format	33
12.1 12.2 12.3	Record Data Bytes Data Field	33 33 33
12.3.1 12.3.2 12.3.3 12.3.4 12.3.5	Pages Pad Bytes Page layout MAP entries EDC	34 34 34 35
12.4	Data Blocks	35
12.4.1 12.4.2 12.4.3	Control Field 1 (CF1) Control Field 2 (CF2) CRC	36 37 39
13	Method of recording	39
13.1 13.2	Physical recording density Channel bit cell length	40 40

ISO/IEC 22051:2002(E)

13.2.1 13.2.2 13.2.3		40 40 40
13.3 13.4	Read signal amplitude Channel skew	40 40
14	Block Recording Format	41
14.1 14.2	Scrambler Modulation	41 41
14.2.1 14.2.2	Modulation process Modulated Data Group	41 42
14.3 14.4	Precoder Recording Data Block	42 43
14.4.1 14.4.2	Preamble Sync	43 43
15	Types and Use of Blocks	43
15.1 15.2	Types of Blocks Use of blocks	43 43
15.2.1 15.2.2 15.2.3 15.2.4 15.2.5	End of Track Blocks (EOTR) End of Data of Data Blocks (EOD) ECC Blocks	43 44 44 44
16	Format of Entities	44
17	Format of Envelopes	44
18	Error handling	44
Annex	xes Q	
A - M	Measurement of light transmittance	45
B - Pr	rocedure for the measurement of abrasivity	48
C - G	Generation of the Data Block CRCs	50
D - G	Generation of page CRCs	51
E - E0	CCC generation	52
F - Al	Illocation of Physical Tracks to Logical Tracks	55
G - R	Recommendations for transportation	56
H - In	nhibitor tape	57
J - Re	ecommendations on tape durability	58
К - Н	Handling guidelines	59

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the pational bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 22051 was prepared by ECMA (as ECMA-320) and was adopted, under a special "fast-track procedure", by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

Annexes A to F form a normative part of this international Standard. Annexes G to K are for information only.

ation. Of Deckiew Generalized by the S

Inis document is a preview denetated by EUS

Information technology — Data interchange on 12,7 mm, 448-track magnetic tape cartridges — SDLT1 format

Section 1 - General

1 Scope

This International Standard specifies the physical and magnetic characteristics of a 12,7 mm wide, 448-track magnetic tape cartridge, to enable physical interchangeability of such cartridges between drives. It also specifies the quality of the recorded signals, a format - called Super Digital Linear Tape 1 (SDLT 1) - and a recording method, thereby allowing data interchange between drives. Together with a labelling standard, for instance ISO 1001 for Magnetic Tape Labelling, it allows full data interchange by means of such magnetic tape cartridges.

2 Conformance

2.1 Magnetic tape cartridge

A magnetic tape cartridge shall be in conformance with this International Standard if it satisfies all mandatory requirements of this International Standard. The tape requirements shall be satisfied throughout the extent of the tape.

2.2 Generating systems

A system generating a magnetic tape cartridg for interchange shall be in conformance with this International Standard if all the recordings that it makes on a tape according to 2.1 meet the mandatory requirements of this International Standard.

In addition, a claim of conformance shall state

- whether or not one, or more registered algorithms are implemented within the system,
- the registered identification number(s) of the implemented compression algorithm(s).

2.3 Receiving systems

A system receiving a magnetic tape cartridge for interchange shall be in conformance with this International Standard if it is able to handle any recording made on a tape according to 2.1.

In addition, a claim of conformance shall state

- whether or not one, or more de-compression algorithm(s) are intelligented within the system, and are able to be applied to de-compress data prior to making such data available to the host,
- the registered identification number(s) of the implemented compression agorithm(s).

3 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this International Standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currents valid International Standards.

 $ISO\ 1001:1986, \textit{Information processing} - \textit{File structure and labelling of magnetic tapes for information interchange}$

ISO 1302:2002, Geometrical Product Specifications (GPS) — Indication of surface texture in technical product documentation

ISO/IEC 11576:1994, Information technology — Procedure for the registration of algorithms for the lossless compression of data

4 Terms and definitions

For the purpose of this International Standard, the following terms and definitions apply.

4.1 back surface

The surface of the tape opposite the magnetic coating which is used to record data.

4.2 Beginning-Of-Tape marker (BOT)

A hole punched on the centreline of the tape towards the end nearest to the leader.