

Ultraheliga töötavad gaasiarvestid kodumajapidamistes kasutamiseks

Ultrasonic domestic gas meters

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

Käesolev Eesti standard EVS-EN 14236:2007 sisaldab Euroopa standardi EN 14236:2007 ingliskeelset teksti. Käesolev dokument on jõustatud 28.02.2007 ja selle kohta on avaldatud teade Eesti standardiorganisatsiooni ametlikus väljaandes. Standard on kättesaadav Eesti standardiorganisatsioonist.	This Estonian standard EVS-EN 14236:2007 consists of the English text of the European standard EN 14236:2007. This document is endorsed on 28.02.2007 with the notification being published in the official publication of the Estonian national standardisation organisation. The standard is available from Estonian standardisation organisation.
--	---

Käsitlusala: This European Standard specifies requirements and tests for the construction, performance and safety of class 1,0 and class 1,5 battery powered ultrasonic gas meters (hereinafter referred to as meters), having co-axial single pipe, or two pipe connections, used to measure volumes of distributed fuel gases of the second and/or third family, as given in EN 437, at maximum working pressures not exceeding 0,5 bar 1) and maximum actual flow rates of up to 10 m³/h over a minimum ambient temperature range of - 10 °C to +40 °C, and minimum gas temperature span of 40 K, for domestic applications. This European Standard applies to meters where the measuring element and the register(s) are enclosed in the same case.	Scope: This European Standard specifies requirements and tests for the construction, performance and safety of class 1,0 and class 1,5 battery powered ultrasonic gas meters (hereinafter referred to as meters), having co-axial single pipe, or two pipe connections, used to measure volumes of distributed fuel gases of the second and/or third family, as given in EN 437, at maximum working pressures not exceeding 0,5 bar 1) and maximum actual flow rates of up to 10 m³/h over a minimum ambient temperature range of - 10 °C to +40 °C, and minimum gas temperature span of 40 K, for domestic applications. This European Standard applies to meters where the measuring element and the register(s) are enclosed in the same case.
---	---

ICS 91.140.40

Võtmesõnad:

English Version

Ultrasonic domestic gas meters

Compteurs de gaz domestiques à ultrasons

Ultraschall-Haushaltsgaszähler

This European Standard was approved by CEN on 13 December 2006.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Contents

Page

Foreword	7
1 Scope	8
2 Normative references	8
3 Terms, definitions and symbols	10
3.1 Terms and definitions	10
3.2 Symbols	13
4 Normal operating conditions	14
4.1 Flow range	14
4.2 Maximum working pressure	15
4.3 Temperature range	15
4.4 Range of gases	16
4.4.1 Test gases	16
4.5 Orientation	16
5 Metrological performance	16
5.1 General	16
5.2 Mode comparison	17
5.2.1 General	17
5.2.2 Requirements	17
5.2.3 Test	17
5.3 Permissible errors	17
5.3.1 Requirements	17
5.3.2 Test	17
5.4 Gas — air relationship	18
5.4.1 General	18
5.4.2 Requirements	18
5.4.3 Test	19
5.5 Pressure absorption	19
5.5.1 Requirements	19
5.5.2 Test	19
5.6 Metrological stability	20
5.6.1 Requirements	20
5.6.2 Test	20
5.7 Immunity to contaminants in gas stream	20
5.7.1 Requirements	20
5.7.2 Test	20
5.7.3 Specification of contamination dust	22
5.8 Installation effects	22
5.8.1 Requirements	22
5.8.2 Test	22
5.9 Zero flow	22
5.9.1 Requirements	22
5.9.2 Test	22
5.10 Reverse flow	23
5.10.1 Requirements	23
5.10.2 Test	23
5.11 Low flow registration	23
5.11.1 Requirement	23
5.11.2 Test	23
5.12 High flow registration	23

5.12.1	Requirement	23
5.12.2	Test	23
5.13	Pulsed (unsteady) flow	23
5.13.1	General	23
5.13.2	Requirements	24
5.13.3	Test	24
5.14	Temperature sensitivity	25
5.14.1	Requirements	25
5.14.2	Test	25
6	Construction and materials	25
6.1	General	25
6.2	Robustness of meter case	26
6.2.1	General	26
6.2.2	Protection against penetration of dust and water	26
6.2.3	Resistance to internal pressure	26
6.2.4	External leak tightness	26
6.2.5	Heat resistance	27
6.2.6	Connections	27
6.2.7	Resistance to vibration	30
6.2.8	Resistance to impact	32
6.2.9	Resistance to mishandling	34
6.3	Corrosion protection	35
6.3.1	General	35
6.3.2	Protection against external corrosion for material which is not corrosion resistant	35
6.3.3	Protection against external corrosion for corrosion resistant material	37
6.3.4	Protection against internal corrosion for material which is not corrosion resistant	38
6.3.5	Protection against internal corrosion for corrosion resistant material	40
6.4	Casework decorative finish	40
6.4.1	Scratch test	40
6.4.2	Humidity	41
6.5	Ageing of non-metallic casework	41
6.5.1	Requirements	41
6.5.2	Test	41
6.6	Ageing of external surfaces of the meter, including index windows and adhesion of the index window	41
6.6.1	Requirements	41
6.6.2	Test	42
6.7	Protection against solar radiation	42
6.7.1	Requirements	42
6.7.2	Test	42
6.8	Resistance to external humidity	42
6.8.1	Requirements	42
6.8.2	Test	43
6.9	Flame retardance of external surfaces	43
6.9.1	Requirements	43
6.9.2	Test	43
6.10	Resistance to storage temperature range	43
6.10.1	Requirement	43
6.10.2	Test	43
6.11	Resistance to the effects of toluene/iso-octane vapour	44
6.11.1	Requirements	44
6.11.2	Test	44
6.12	Resistance to water vapour	47
6.12.1	Requirements	47
6.12.2	Test	47
6.13	Ageing	48
6.13.1	Requirements	48
6.13.2	Test	49

7	Optional features.....	49
7.1	Pressure measuring point.....	49
7.1.1	Requirements	49
7.1.2	Test.....	49
7.2	Resistance to high ambient temperature	49
7.2.1	Requirements	49
7.2.2	Test.....	50
7.2.3	Meter fitted with a thermal shut-off valve.....	51
7.3	Meters with temperature conversion	51
7.4	Ancillary devices (if fitted)	51
7.4.1	Requirement	51
7.4.2	Test.....	52
7.5	Use in hazardous zones	52
8	Index.....	52
8.1	Recording and storage.....	52
8.1.1	Requirement	52
8.1.2	Test.....	52
8.2	Display.....	52
8.2.1	Requirement	52
8.2.2	Test.....	52
8.3	Segmental display.....	53
8.3.1	Requirements	53
8.3.2	Test.....	53
8.4	Non-volatile memory.....	53
8.4.1	Requirements	53
8.4.2	Test.....	53
8.5	Display reset.....	54
8.5.1	Requirements	54
8.5.2	Test.....	54
9	Marking	54
9.1	All meters.....	54
9.2	Two-pipe meters.....	55
9.2.1	Requirements	55
9.2.2	Test.....	55
9.3	Durability and legibility of marking	55
9.3.1	Requirements	55
9.3.2	Weathering.....	55
9.3.3	Indelibility test	56
9.4	Accompanying information	56
10	Software	57
10.1	Requirements	57
10.2	Test.....	57
11	Communications	57
11.1	General.....	57
11.2	Character transmission	58
11.3	Communications protocol.....	58
11.3.1	General.....	58
11.3.2	Wakeup	58
11.3.3	Sign-off.....	58
11.3.4	Security	58
11.3.5	Time-outs	58
11.4	Data.....	58
11.4.1	General.....	58
11.4.2	Data read-out mode	59
11.5	Test-mode	59
11.5.1	General.....	59
11.5.2	Test-mode commands	59

11.5.3	Response of meter to test commands	59
11.6	Data optical port	61
11.7	Galvanic port (optional)	61
11.8	Diagnostics	61
11.8.1	General	61
11.8.2	Displayed flags	61
12	Battery	62
12.1	General	62
12.2	Voltage interruptions	62
12.2.1	Requirements	62
12.2.2	Test	62
12.3	Minimum operating voltage	63
12.3.1	Requirements	63
12.3.2	Test	63
12.4	Battery life	63
12.4.1	Requirements	63
12.4.2	Test	63
13	Immunity to electromagnetic disturbances	63
13.1	General	63
13.2	Electrostatic discharge	63
13.2.1	Requirements	63
13.2.2	Test	63
13.3	Radio frequency electromagnetic field	64
13.3.1	Requirements	64
13.3.2	Test	64
13.4	Electromagnetic induction (power frequency)	64
13.4.1	Requirements	64
13.4.2	Test	65
13.5	Electromagnetic induction (pulsed field)	65
13.5.1	Requirements	65
13.5.2	Test	65
13.6	Radio interference suppression	65
13.6.1	Requirements	65
13.6.2	Test	65
14	Ultrasonic (acoustic) noise interference	65
14.1	Requirements	65
14.2	Test	66
14.2.1	Test sequence	66
14.2.2	White noise test	66
14.2.3	Scanning frequency test	66
15	Meters supplied for testing	67
Annex A	(informative) Test gases	69
A.1	General	69
A.2	Test gas properties	69
Annex B	(normative) Production requirements for gas meters	70
B.1	Specification	70
B.2	Technical requirements	70
B.3	Certificates of conformity	70
Annex C	(normative) Meters with gas temperature conversion devices	72
C.1	Scope	72
C.2	Metrological performance	72
C.2.1	Errors of indication	72
C.2.2	Error of indication where the temperature of the gas at the meter inlet is significantly different from the ambient temperature of the air surrounding the meter	75
C.2.3	Temperature sensitivity	77

C.2.4	Temperature converted volume	77
Annex ZA	(informative)	78
Bibliography		82

Foreword

This document (EN 14236:2007) has been prepared by Technical Committee CEN/TC 237 "Gas meters", the secretariat of which is held by BSI.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by July 2007, and conflicting national standards shall be withdrawn at the latest by July 2007.

This document supersedes ENV 14236:2002.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive 2004/22/EC.

For relationship with EU Directive 2004/22/EC, see informative Annex ZA, which is an integral part of this document.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

1 Scope

This European Standard specifies requirements and tests for the construction, performance and safety of class 1,0 and class 1,5 battery powered ultrasonic gas meters (hereinafter referred to as meters), having co-axial single pipe, or two pipe connections, used to measure volumes of distributed fuel gases of the second and/or third family, as given in EN 437, at maximum working pressures not exceeding 0,5 bar¹⁾ and maximum actual flow rates of up to 10 m³/h over a minimum ambient temperature range of -10 °C to +40 °C, and minimum gas temperature span of 40 K, for domestic applications. This European Standard applies to meters where the measuring element and the register(s) are enclosed in the same case.

This European Standard applies to meters with and without built-in temperature conversion, that are installed in locations with vibration and shocks of low significance and in

- closed locations (indoor or outdoor with protection as specified by the manufacturer) with condensing or with non-condensing humidity

or, if specified by the manufacturer,

- open locations (outdoor without any covering) with condensing humidity or with non-condensing humidity

and in locations with electromagnetic disturbances.

Unless otherwise stated, all pressures given in this European Standard are gauge pressures.

When more than one meter type is submitted for testing, then each meter type is required to be tested against this European Standard.

Clauses 1 to 15 and Annex C are for design and type testing only.

NOTE See Annex A for production requirements.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 55022, *Information technology equipment — Radio disturbance characteristics — Limits and methods of measurement (CISPR 22:1997, modified)*

EN 60068-2-5, *Environmental testing — Part 2: Tests — Test Sa: Simulated solar radiation at ground level (IEC 60068-2-5:1975)*

EN 60068-2-30, *Environmental testing — Part 2-30: Tests — Test Db: Damp heat, cyclic (12 + 12 h cycle) (IEC 60068-2-30:2005)*

EN 60079-0:2004, *Electrical apparatus for explosive gas atmospheres — Part 0: General requirements (IEC 60079-0:2004, modified)*

¹⁾ 1 bar = 1 000 mbar = 10⁵ Pa.

EN 60079-10, *Electrical apparatus for explosive gas atmospheres — Part 10: Classification of hazardous areas* (IEC 60079-10:1995)

prEN 60079-11, IEC 60079-11, Ed. 5.0: *Explosive atmospheres — Part 11: Equipment protection by intrinsic safety "i"*

EN 60079-15, *Electrical apparatus for explosive gas atmospheres — Part 15: Construction, test and marking of type of protection "n" electrical apparatus* (IEC 60079-15:2005)

EN 60086-1, *Primary batteries — Part 1: General* (IEC 60086-1:2000)

EN 60086-4, *Primary batteries — Part 4: Safety standard for lithium batteries* (IEC 60086-4:2000)

EN 60529, *Degrees of protection provided by enclosures (IP code)* (IEC 60529:1989)

EN 60695-11-5, *Fire hazard testing — Part 11-5: Test flames — Needle-flame test method — Apparatus, confirmatory test arrangement and guidance* (IEC 60695-11-5:2004)

EN 60707, *Flammability of solid non-metallic materials when exposed to flame sources — List of test methods* (IEC 60707:1999)

EN 60730-1:2000, *Automatic electrical controls for household and similar use — Part 1: General requirements* (IEC 60730-1:1999, modified)

EN 61000-4-2, *Electromagnetic compatibility (EMC) — Part 4: Testing and measurement techniques — Section 2: Electrostatic discharge immunity test — Basic EMC publication* (IEC 61000-4-2:1995)

EN 61000-4-3, *Electromagnetic compatibility (EMC) — Part 4-3: Testing and measurement techniques — Radiated, radio frequency, electromagnetic field immunity test —* (IEC 61000-4-3:2006)

EN 61000-4-8, *Electromagnetic compatibility (EMC) — Part 4: Testing and measurement techniques — Section 8: Power frequency magnetic field immunity test — Basic EMC publication* (IEC 61000-4-8:1993)

EN 61000-4-9, *Electromagnetic compatibility (EMC) — Part 4: Testing and measurement techniques — Section 9: Pulse magnetic field immunity test — Basic EMC publication* (IEC 61000-4-9:1993)

EN 61000-6-1, *Electromagnetic compatibility (EMC) — Part 6-1: Generic standards — Immunity for residential, commercial and light-industrial environments*

EN 61000-6-2, *Electromagnetic compatibility (EMC) — Part 6-2: Generic standards — Immunity for industrial environments* (IEC 61006-2-2:2005)

EN 62056-21:2002, *Electricity metering — Data exchange for meter reading, tariff and load control — Part 21: Direct local data exchange* (IEC 62056-21:2002)

EN ISO 2409, *Paints and varnishes — Cross-cut test* (ISO 2409:1992)

EN ISO 2812-1:1994, *Paints and varnishes — Determination of resistance to liquids — Part 1: General methods* (ISO 2812-1:1993)

EN ISO 4628-2:2003, *Paints and varnishes — Evaluation of degradation of coatings — Designation of quantity and size of defects, and of intensity of uniform changes in appearance — Part 2: Assessment of degree of blistering* (ISO 4628-2:2003)

EN ISO 4628-3:2003, *Paints and varnishes — Evaluation of degradation of coatings — Designation of quantity and size of defects, and of intensity of uniform changes in appearance — Part 3: Assessment of degree of rusting* (ISO 4628-3:2003)

EN ISO 4892-3, *Plastics — Methods of exposure to laboratory light sources — Part 3: Fluorescent UV lamps* (ISO 4892-3:2006)

EN ISO 6270-1, *Paints and varnishes — Determination of resistance to humidity — Part 1: Continuous condensation* (ISO 6270-1:1998)

EN ISO 6272-1, *Paints and varnishes — Rapid-deformation (impact resistance) tests — Part 1: Falling-weight test, large-area indenter* (ISO 6272-1:2002)

EN ISO 9001, *Quality management systems — Requirements* (ISO 9001:2000)

EN ISO 9227, *Corrosion tests in artificial atmospheres — Salt spray tests* (ISO 9227:2006)

ISO 834-1, *Fire resistance tests — Elements of building construction — Part 1: General requirements*

ISO 1518, *Paints and varnishes — Scratch test*

ISO 7724-3, *Paints and varnishes — Colorimetry — Part 3: Calculation of colour differences*

ASTM D471, *Standard Test Method for Rubber Property — Effect of Liquids*

ASTM D1003, *Standard Test Method for Haze and Luminous Transmittance of Transparent Plastics*

3 Terms, definitions and symbols

3.1 Terms and definitions

For the purposes of this European Standard, the following terms and definitions apply.

3.1.1

actual flow rate

flow rate at the gas pressure and gas temperature conditions prevailing in the gas distribution line in which the meter is fitted, at the meter inlet

3.1.2

base conditions

fixed conditions to which a volume of gas is converted (i.e. base gas temperature 15 °C, base gas pressure 1 013,25 mbar)

3.1.3

contaminants

gas borne dust, vapour and other substances that could affect the operation of the meter

3.1.4

communications port

galvanic or optical serial data port

3.1.5

display

device (e.g. liquid crystal display) which shows the contents of a memory (e.g. registered volume or flags)