
**Mechanical vibration and shock —
Resilient mounting systems —**

**Part 2:
Technical information to be exchanged
for the application of vibration isolation
associated with railway systems**

Vibrations et chocs mécaniques — Systèmes de montage résilients —

*Partie 2: Informations techniques à échanger pour l'application
d'isolation vibratoire associée aux chemins de fer*



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

This document is a preview generated by EVS



COPYRIGHT PROTECTED DOCUMENT

© ISO 2007

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions.....	2
4 Vibration of railway systems	2
5 Purpose of vibration isolation (why isolate mechanical systems).....	3
6 What is to be isolated	4
6.1 Source isolation	4
6.2 Receiver isolation	4
7 Applicability of vibration isolation (when to isolate structures or mechanical systems).....	4
8 Measurement and evaluation of vibration conditions	5
9 Information for the choice of an isolation mounting system	5
10 Information to be supplied by the railway system authority.....	6
11 Information to be supplied by the receiver producer and user	7
11.1 Buildings.....	7
11.2 Sensitive equipment.....	7
12 Information to be provided by the supplier of the isolation system	8
12.1 Performance of isolation system	8
12.2 Physical data of the isolation system.....	8
12.3 Dynamic behaviour.....	9
12.4 Durability	9
12.5 Environmental data.....	9
12.6 Maintenance data.....	9
13 Guidelines for the validation of isolation performance	10
Bibliography	11

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 2017-2 was prepared by Technical Committee ISO/TC 108, *Mechanical vibration, shock and condition monitoring*.

The first edition, together with ISO 2017-1:2005 cancels and replaces ISO 2017:1982 which has been technically revised.

ISO 2017 consists of the following parts, under the general title *Mechanical vibration and shock — Resilient mounting systems*:

- *Part 1: Technical information to be exchanged for the application of isolation systems*
- *Part 2: Technical information to be exchanged for the application of vibration isolation associated with railway systems*

Introduction

This part of ISO 2017 is limited to consideration of resilient devices.

Some suppliers of shock and vibration isolators (resilient mounts) have experience covering a wide variety of applications. In most instances, they are willing to use their background information for solving the user's isolation problems. However, it is frequently difficult for the supplier to provide this service, because the customer, the user or the producer of vibration source or receiver has not furnished sufficient information regarding the application.

On the other hand, the user is sometimes handicapped in applying isolators properly because sufficient technical information is not furnished by the supplier. Consequently, the user will often conduct his own experimental evaluation of the isolator and may unknowingly duplicate work already carried out by the supplier.

In some cases of vibration source or receiver, the producer provides the isolating system. To do that he needs detailed information from the customer relating to his future application, site and environment.

This part of ISO 2017 is intended to serve as guide for the exchange of technical information regarding the application of isolation elements for vibrations and shocks generated by railway systems, between the customer, supplier of resilient devices and producer of vibration source or receiver as required for their proper application.

For the purposes of this part of ISO 2017, a resilient device is defined as a flexible element or system used between an equipment item and its supporting structure to attenuate the transmission of shock or vibration from the railway systems to the structure.

This document is a preview generated by EVS

Mechanical vibration and shock — Resilient mounting systems —

Part 2: Technical information to be exchanged for the application of vibration isolation associated with railway systems

1 Scope

This part of ISO 2017 establishes requirements to ensure appropriate exchange of information regarding the application of isolation for vibrations and shocks generated by railway systems.

This part of ISO 2017 is applicable to the construction of new railway systems. It may also be applied to previously installed systems when the user wishes to solve a new vibration problem arising from railroad degradation, when new environmental and use planning requirements are put in place, or when new vibration-sensitive land development occurs in proximity to existing railway systems.

It applies to vibration problems encountered in a railway environment but does not address vibration problems within railway cars (carriages) themselves.

This part of ISO 2017 intends to give appropriate responses to questions highlighted by the producer and users (why, what, when and how to isolate mechanical systems).

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2041, *Mechanical vibration, shock and condition monitoring — Vocabulary*

ISO 2631-2, *Mechanical vibration and shock — Evaluation of human exposure to whole-body vibration — Part 2: Vibration in buildings (1 Hz to 80 Hz)*

ISO 4866, *Mechanical vibration and shock — Vibration of buildings — Guidelines for the measurement of vibrations and evaluation of their effects on buildings*

ISO 7626-1, *Vibration and shock — Experimental determination of mechanical mobility — Part 1: Basic definitions and transducers*

ISO 8569, *Mechanical vibration and shock — Measurement and evaluation of shock and vibration effects on sensitive equipment in buildings*

ISO 9688, *Mechanical vibration and shock — Analytical methods of assessing shock resistance of mechanical systems — Information exchange between suppliers and users of analyses*

ISO 10815, *Mechanical vibration — Measurement of vibration generated internally in railway tunnels by the passage of trains*

ISO 10846 (all parts), *Acoustics and vibration — Laboratory measurement of vibro-acoustic transfer properties of resilient elements*

ISO 14837-1, *Mechanical vibration — Ground-borne noise and vibration arising from rail systems — Part 1: General guidance*

ISO 14964, *Mechanical vibration and shock — Vibration of stationary structures — Specific requirements for quality management in measurement and evaluation of vibration*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 2041, ISO 7626-1, ISO 9688, ISO 10846 and ISO 14837-1 and the following apply.

3.1
railway system
all train, track and other elements of railway which generate or transmit vibrations, either in open space or in tunnels

3.2
vibration receiver
all structures or elements of structures responding to vibration energy emitted by an internal or external source

3.3
customer
user or purchaser of a product (building, machine, etc.)

3.4
producer
party constructing or manufacturing the product that needs to be isolated from internal or external vibration and which the customer agrees to purchase

3.5
isolation supplier
party who is responsible for providing and installing an isolation system that will meet the requirements to reduce vibration agreed upon with the customer who agrees to purchase

NOTE 1 In certain cases the producer and the supplier may be the same party.

NOTE 2 Every one of the three main actors can mandate subcontractors to execute the work or to purchase elements. From a legal point of view the three stay responsible in case of failure of the project.

3.6
base isolation
item or support arrangements that secure a structure to its supporting ground or equipment to its supporting structure and provide protection from shock and/or vibration

4 Vibration of railway systems

There are distinct mechanisms that give rise to ground vibration from the passage of trains. They are generally associated with train-track interaction.