
**Intravascular catheters — Sterile and
single-use catheters —**

**Part 6:
Subcutaneous implanted ports**

*Cathéters intravasculaires — Cathéters stériles et non réutilisables —
Partie 6: Chambres à cathéter implantables*



This document is a preview generated by EBS



COPYRIGHT PROTECTED DOCUMENT

© ISO 2015

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Requirements of the implantable subcutaneous implanted port and catheter	3
4.1 General	3
4.2 Biocompatibility	4
4.3 Distance markings	4
4.4 Nominal dimensions of the subcutaneous implanted port	4
4.5 Physical requirements	4
4.5.1 Radio-detectability	4
4.5.2 Surface finish	4
4.5.3 Freedom from leakage	4
4.5.4 Flushing volume	4
4.5.5 Characteristics of the septum	5
4.5.6 Characteristics of the connection or the catheter	5
4.6 Flow rate	5
4.6.1 Subcutaneous implanted ports not indicated for power injection	5
4.6.2 Subcutaneous implanted ports indicated for power injection	5
4.7 Burst pressure of the subcutaneous implanted port and catheter	6
4.7.1 Subcutaneous implanted ports not indicated for power injection	6
4.7.2 Subcutaneous implanted ports indicated for power injection	6
5 Magnetic Resonance Imaging (MRI) compatibility	6
6 Information to be supplied by the manufacturer	6
6.1 Marking on the device	6
6.2 Primary packaging	6
6.3 Labels for traceability	7
6.4 Instruction for use	7
Annex A (normative) Test method for freedom from air leakage	8
Annex B (informative) Determination of flushing volume	10
Annex C (informative) Guidance on further characterization testing: Needle penetration and withdrawal	12
Annex D (normative) Test method for freedom from leakage after multiple punctures	14
Annex E (normative) Peak tensile force	15
Bibliography	16

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#)

The committee responsible for this document is ISO/TC 84, *Devices for administration of medicinal products and intravascular catheters*.

ISO 10555 consists of the following parts, under the general title *Intravascular catheters — Sterile and single-use catheters*:

- *Part 1: General requirements*
- *Part 3: Central venous catheters*
- *Part 4: Balloon dilatation catheters*
- *Part 5: Over-needle peripheral catheters*
- *Part 6: Subcutaneous implanted ports*

The following part has been withdrawn and the content has been included in ISO 10555-1:

- *Part 2: Angiographic catheters*

Intravascular catheters — Sterile and single-use catheters —

Part 6: Subcutaneous implanted ports

1 Scope

This part of ISO 10555 specifies requirements, performance, and user safety issues related to subcutaneous implanted ports and catheters for intravascular long-term use supplied in sterile condition and intended for single use.

This part of ISO 10555 does not specify requirements, performance, and user safety issues related to non-coring needles.

NOTE Subcutaneous implanted ports are known to be used for indications other than intravascular such as intra-peritoneal, intra-theal, intra-pleural, and epidural access.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 10555-1:2013, *Intravascular catheters — Sterile and single-use catheters — Part 1: General requirements*

ISO 10555-3:2013, *Intravascular catheters — Sterile and single-use catheters — Part 3: Central venous catheters*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 10555-1 and the following apply.

3.1 catheter

single- or multiple-lumen tube allowing access to a point within the body at its distal end

3.2 connection

system connecting the catheter to the subcutaneous implanted port

3.3 effective surface area

area available for puncture by the needle

3.4 flushing volume

volume of solution needed to fully replace one solution from the subcutaneous implanted port and catheter with another