
**Cloud Infrastructure Management
Interface (CIMI) Model and RESTful
HTTP-based Protocol — An Interface for
Managing Cloud Infrastructure**

*Model d'interface de management de l'infrastructure du nuage
informatique (CIMI) et protocole RESTful basé HTTP — Une interface
pour le management de l'infrastructure du nuage informatique*



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2015

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

CONTENTS

33			
34	Foreword		7
35	1 Scope		9
36	1.1 Document structure		9
37	1.2 Document versioning scheme		9
38	1.3 Typographical conventions		9
39	2 Normative references		10
40	3 Terms and definitions		11
41	4 HTTP-based protocol		14
42	4.1 Introduction		14
43	4.1.1 Protocol evolution and client expectations		14
44	4.1.2 XML namespaces		14
45	4.1.3 URI space		14
46	4.1.4 Media types		15
47	4.1.5 Request headers		15
48	4.1.6 Request query parameters		15
49	4.2 Protocol operations		21
50	4.2.1 Common CRUD operations		22
51	4.3 OVF support		29
52	5 Model		30
53	5.1 Resource wrappers		30
54	5.2 Extensibility		31
55	5.3 Identifiers		31
56	5.4 Attribute constraints		32
57	5.5 Data types and their serialization		33
58	5.5.1 boolean		33
59	5.5.2 dateTime		33
60	5.5.3 duration		33
61	5.5.4 integer		34
62	5.5.5 string		34
63	5.5.6 ref		34
64	5.5.7 map		35
65	5.5.8 structure		35
66	5.5.9 byte[]		36
67	5.5.10 URI		36
68	5.5.11 Arrays		36
69	5.5.12 Collections		37
70	5.5.13 "Any" type		41
71	5.5.14 Empty attribute values		41
72	5.6 Units		41
73	5.7 Relationship semantics		42
74	5.8 Operations		42
75	5.9 Alternative model formats		43
76	5.10 Resources		43
77	5.10.1 Common attributes		43
78	5.11 Resource metadata		45
79	5.11.1 Serialization of attribute value constraints		49
80	5.11.2 Capabilities		51
81	5.11.3 ResourceMetadataCollection Resource		54
82	5.12 Cloud Entry Point		55
83	5.12.1 Operations		61
84	5.13 System Resources and relationships		61
85	5.13.1 System		62

86	5.13.2	SystemCollection Resource	80
87	5.13.3	SystemTemplate Resource	81
88	5.13.4	SystemTemplateCollection Resource	87
89	5.14	Machine Resources and relationships	88
90	5.14.1	Machine	89
91	5.14.2	MachineCollection	107
92	5.14.3	MachineTemplate	109
93	5.14.4	MachineTemplateCollection Resource	116
94	5.14.5	MachineConfiguration Resource	117
95	5.14.6	MachineConfigurationCollection Resource	119
96	5.14.7	MachineImage Resource	120
97	5.14.8	MachineImageCollection Resource	124
98	5.14.9	Credential Resource	125
99	5.14.10	CredentialCollection Resource	126
100	5.14.11	CredentialTemplate Resource	127
101	5.14.12	CredentialTemplateCollection Resource	128
102	5.15	Volume Resources and relationships	130
103	5.15.1	Volume	131
104	5.15.2	VolumeCollection Resource	135
105	5.15.3	VolumeTemplate Resource	136
106	5.15.4	VolumeTemplateCollection Resource	138
107	5.15.5	VolumeConfiguration Resource	139
108	5.15.6	VolumeConfigurationCollection Resource	141
109	5.15.7	VolumeImage Resource	142
110	5.15.8	VolumeImageCollection Resource	144
111	5.16	Network Resources and relationships	145
112	5.16.1	Network	145
113	5.16.2	NetworkCollection Resource	153
114	5.16.3	NetworkTemplate Resource	154
115	5.16.4	NetworkTemplateCollection Resource	156
116	5.16.5	NetworkConfiguration Resource	157
117	5.16.6	NetworkConfigurationCollection Resource	158
118	5.16.7	NetworkPort	160
119	5.16.8	NetworkPortCollection Resource	164
120	5.16.9	NetworkPortTemplate Resource	165
121	5.16.10	NetworkPortTemplateCollection Resource	168
122	5.16.11	NetworkPortConfiguration Resource	169
123	5.16.12	NetworkPortConfigurationCollection Resource	170
124	5.16.13	Address Resource	171
125	5.16.14	AddressCollection Resource	173
126	5.16.15	AddressTemplate Resource	174
127	5.16.16	AddressTemplateCollection Resource	176
128	5.16.17	ForwardingGroup Resource	177
129	5.16.18	ForwardingGroupCollection Resource	180
130	5.16.19	ForwardingGroupTemplate Resource	181
131	5.16.20	ForwardingGroupTemplateCollection Resource	182
132	5.17	Monitoring Resources and relationships	183
133	5.17.1	Job Resource	184
134	5.17.2	JobCollection Resource	188
135	5.17.3	Meter Resource	189
136	5.17.4	MeterCollection Resource	195
137	5.17.5	MeterTemplate Resource	196
138	5.17.6	MeterTemplateCollection Resource	197
139	5.17.7	MeterConfiguration Resource	198
140	5.17.8	MeterConfigurationCollection Resource	201
141	5.17.9	EventLog Resource	202

142	5.17.10 EventLogCollection Resource	205
143	5.17.11 EventLogTemplate Resource	206
144	5.17.12 EventLogTemplateCollection Resource	207
145	5.17.13 Event Resource	208
146	6 Security considerations	216
147	ANNEX A (normative) OVF support in CIMI	217
148	ANNEX B (informative) XML Schema.....	219
149	ANNEX C (informative) Change log.....	220
150		

151 Figures

152	Figure 1 - Cloud Entry Point.....	56
153	Figure 2 - System Resources.....	62
154	Figure 3 - Machine Resources.....	89
155	Figure 4 - Volume Resources.....	130
156	Figure 5 - Network Resources.....	145
157	Figure 6 - Monitoring Resources.....	184
158		

159 Tables

160	Table 1 – XML namespaces	14
161	Table 2 – Named structure.....	35
162	Table 3 – Converting a relative URI to an absolute URI.....	36
163	Table 4 – Numerical equivalents for attributes.....	42
164	Table 5 – Common attributes.....	43
165	Table 7 – Capability URIs	51
166	Table 8 – CloudEntryPoint attributes	56
167	Table 9 – System attributes	63
168	Table 10 – SystemSystem attributes	67
169	Table 11 – SystemMachine attributes.....	68
170	Table 12 – SystemCredential attributes.....	70
171	Table 13 – SystemVolume attributes	71
172	Table 14 – SystemNetwork attributes	72
173	Table 15 – SystemNetworkPort attributes	74
174	Table 16 – SystemAddress attributes	75
175	Table 17 – SystemForwardingGroup attributes	76
176	Table 18 – SystemTemplate attributes	82
177	Table 19 – Machine attributes.....	89
178	Table 20 – Disk attributes	93
179	Table 21 – MachineVolume attributes	94
180	Table 22 – MachineNetworkInterface attributes	96
181	Table 23 – MachineNetworkInterfaceAddress attributes	98
182	Table 24 – MachineSnapshot attributes	100
183	Table 25 – MachineTemplate attributes.....	109
184	Table 26 – MachineConfiguration attributes	117
185	Table 27 – MachineImage attributes.....	120

ISO/IEC 19831:2015 (E)

186	Table 28 – Credential attributes	125
187	Table 29 – UserName/Password attributes	125
188	Table 30 – Public key attributes	125
189	Table 31 – CredentialTemplate attributes	127
190	Table 32 – Volume attributes	131
191	Table 33 – VolumeVolumeImage attributes	133
192	Table 34 – VolumeTemplate attributes	136
193	Table 35 – VolumeConfiguration attributes	140
194	Table 36 – VolumeImage attributes	142
195	Table 37 – Network attributes	145
196	Table 38 – NetworkTemplate attributes	154
197	Table 39 – NetworkConfiguration attributes	157
198	Table 40 – NetworkPort attributes	160
199	Table 41 – NetworkPortTemplate attributes	165
200	Table 42 – NetworkPortConfiguration attributes	169
201	Table 43 – Address attributes	171
202	Table 44 – AddressTemplate attributes	174
203	Table 45 – ForwardingGroup attributes	178
204	Table 46 – ForwardingGroupNetwork attributes	179
205	Table 47 – ForwardingGroupTemplate attributes	181
206	Table 48 – Job attributes	185
207	Table 49 – Meter attributes	189
208	Table 50 – Sample attributes	192
209	Table 51 – MeterTemplate attributes	196
210	Table 52 – MeterConfiguration attributes	198
211	Table 53 – aspect URIs	200
212	Table 54 – EventLog attributes	202
213	Table 55 – EventLogTemplate attributes	206
214	Table 56 – Event attributes	208
215	Table 57 – type URIs	211
216		
217		

Foreword

The *Cloud Infrastructure Management Interface (CIMI) Model and RESTful HTTP-based Protocol* specification (DSP0263) was prepared by the DMTF Cloud Management Working Group. It defines a logical model for the management of resources within the Infrastructure as a Service domain.

DMTF is a not-for-profit association of industry members dedicated to promoting enterprise and systems management and interoperability.

Acknowledgments

The DMTF acknowledges the following individuals for their contributions to this document:

Editors (past and present):

- Marios Andreou – Red Hat
- Doug Davis – IBM
- Jacques Durand – Fujitsu
- Gilbert Pilz – Oracle

Contributors:

- Ghazanfar Ali – ZTE Corporation
- Marios Andreou – Red Hat
- Keith Bankston – Microsoft Corporation
- Winston Bumpus – VMware Inc.
- Nathan Burkhart – Microsoft Corporation
- Mark Carlson – Oracle
- Steve Carter – Novell
- Junsheng Chu – ZTE Corporation
- Josh Cohen – Microsoft Corporation
- Derek Coleman – Hewlett-Packard Company
- John Crandall – Brocade Communications Systems
- Doug Davis – IBM
- Jim Davis – WBEM Solutions
- Fernando de la Iglesia – Telefónica
- Hiroshi Dempo – NEC Corporation
- Jacques Durand – Fujitsu
- Yigal Edery – Microsoft Corporation
- George Ericson – EMC
- Colleen Evans – Microsoft Corporation
- Norbert Floeren – Ericsson AB
- Robert Freund – Hitachi, Ltd.
- Fermín Galán – Telefónica
- Krishnan Gopalan – Microsoft Corporation
- Kazunori Iwasa – Fujitsu
- Mark Johnson – IBM
- Bhumi Khasnabish – ZTE Corporation
- Dies Köper – Fujitsu
- Vincent Kowalski – BMC Software
- Ruby Krishnaswamy – France Telecom Group
- Lawrence Lamers – VMware Inc.
- Paul Lipton – CA Technologies
- James Livingston – NEC Corporation
- Vince Lubsey – Virtustream Inc.

ISO/IEC 19831:2015 (E)

- 265 • David Lutterkort – Red Hat
- 266 • Fred Maciel – Hitachi, Ltd.
- 267 • Andreas Maier – IBM
- 268 • Ashok Malhotra – Oracle
- 269 • Jeff Mischkinsky – Oracle
- 270 • Jesus Molina – Fujitsu
- 271 • Efraim Moscovich – CA Technologies
- 272 • Bryan Murray – Hewlett-Packard Company
- 273 • Steven Neely – Cisco
- 274 • Ryuichi Ogawa – NEC Corporation
- 275 • John Parchem – Microsoft Corporation
- 276 • Shishir Pardikar – Citrix Systems Inc.
- 277 • Miguel Peñalvo – Telefónica
- 278 • Gilbert Pilz – Oracle
- 279 • Alvaro Polo – Telefónica
- 280 • Enrico Ronco – Telecom Italia
- 281 • Federico Rossini – Telecom Italia
- 282 • Matthew Rutkowski – IBM
- 283 • Tom Rutt – Fujitsu
- 284 • Hemal Shah – Broadcom
- 285 • Nihar Shah – Microsoft Corporation
- 286 • Alan Sill – Texas Tech University
- 287 • Zhexuan Song – Huawei
- 288 • Marvin Waschke – CA Technologies
- 289 • Eric Wells – Hitachi, Ltd.
- 290 • Jeff Wheeler – Huawei
- 291 • Maarten Wiggers – Fujitsu
- 292 • Daniel Wilson – Ericsson AB
- 293 • Steve Winkler – SAP AG
- 294 • Jack Yu – Oracle
- 295 • Aaron Zhang – Huawei
- 296 • HengLiang Zhang – Huawei
- 297

Cloud Infrastructure Management Interface (CIMI) Model and RESTful HTTP-based Protocol

1 Scope

This specification describes the model and protocol for management interactions between a cloud Infrastructure as a Service (IaaS) Provider and the Consumers of an IaaS service. The basic resources of IaaS (machines, storage, and networks) are modeled with the goal of providing Consumer management access to an implementation of IaaS and facilitating portability between cloud implementations that support the specification. This document specifies a Representational State Transfer (REST)-style protocol using HTTP. However, the underlying model is not specific to HTTP, and it is possible to map it to other protocols as well.

CIMI addresses the management of the lifecycle of infrastructure provided by a Provider. CIMI does not extend beyond infrastructure management to the control of the applications and services that the Consumer chooses to run on the infrastructure provided as a service by the Provider. Although CIMI may be to some extent applicable to other cloud service models, such as Platform as a Service ("PaaS") or Storage as a Service ("SaaS"), these uses are outside the design goals of CIMI.

1.1 Document structure

This document defines a model and a RESTful HTTP-based protocol.

The core REST patterns are defined first and, after each resource is defined, any HTTP-specific information for that resource is specified.

1.2 Document versioning scheme

This document adheres to the versioning scheme defined in clause 6.3 of [DSP4004](#).

As the specification changes over time certain features might be deprecated. These are identified in the specification and should not be supported. Each of these deprecated features is clearly denoted in the clause in which they were previously defined.

1.3 Typographical conventions

This specification uses the following conventions:

In the narrative text of the specification:

- The regular or narrative font is Arial.
- Proper CIMI nouns such as Resource names, attribute names, operation names, reserved variable names are in Courier font. (e.g. Machine, volumes, \$expand). The plural form applies to such names to indicate several instances of such Resources (e.g. Machines, Systems).
- Examples text are in small Courier font and over a darker background.
- Quotes are used for any text that needs be distinguished as name or value of a particular concept (e.g. the "value constraints" attribute, the "Resource Name" column, a "false" value). In such cases, the string in quotes is always qualified by the concept it is an instance of.
- Names for CIMI concepts that may be common English words but have a very specific meaning in CIMI, are in narrative font but capitalized, e.g. Provider, Consumer, Resource, Collection.

When used in their common English sense they remain lower-case. However, CIMI modeling concepts that are used in a commonly understood manner remain in lower-case, such as: attribute, operation.

Inside tables describing the Resource data model:

- The narrative font is used for all terms, as the table structure qualifies them sufficiently.
- Where textual descriptions are introduced, the rules for narrative text apply.
- If a name is used as types (i.e., names of embedded structures as well as atomic types such as "integer", "string"), are in *italic*.
- Names that are just placeholders for actual names that may vary with each model instance, are between < > (e.g., <componentTemplate>).

Where the serialization of Resources is described, a pseudo-schema notation is used with the following conventions:

- Values in *italics* indicate data types instead of literal values.
- Characters are appended to items to indicate cardinality:
 - "?" (0 or 1)
 - "*" (0 or more)
 - "+" (1 or more)
- Vertical bars, "|", denote choice. For example, "a|b" means a choice between "a" and "b".
- Parentheses, "(" and ")", are used to indicate the scope of the operators "?", "*", "+" and "|".
- Ellipses (i.e., "...") indicate points of extensibility. Note that the lack of an ellipses does not mean no extensibility point exists, rather it is just not explicitly called out - usually for the sake of brevity.

Operation names Create, Update, Delete, Read are abstract operations that convey the semantics of concrete corresponding operations, such as HTTP methods or CIMI operation URIs.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated or versioned references, only the edition cited (including any corrigenda or DMTF update versions) applies. For references without a date or version, the latest published edition of the referenced document (including any corrigenda or DMTF update versions) applies.

DMTF DSP0223, *Generic Operations 1.0*,
http://www.dmtf.org/standards/published_documents/DSP0223_1.0.pdf

DMTF DSP0243, *Open Virtualization Format Specification 1.1*,
http://www.dmtf.org/sites/default/files/standards/documents/DSP0243_1.1.pdf

DMTF DSP1001, *Management Profile Specification Usage Guide 1.1*,
http://www.dmtf.org/standards/published_documents/DSP1001_1.1.pdf

DMTF DSP4004, *DMTF Release Process 2.4*,
http://www.dmtf.org/sites/default/files/standards/documents/DSP4004_2.4.pdf

IANA HTTP Header Registry, <http://www.iana.org/assignments/message-headers/perm-headers.html>

- 374 IEC 80000-13:2008, International Organization for Standardization, Geneva, Switzerland, *Quantities and*
 375 *units – Part 13: Information science and technology*, April 2008,
 376 http://www.iso.org/iso/catalogue_detail?csnumber=31898
- 377 IETF RFC2616, R. Fielding et al, *Hypertext Transfer Protocol -- HTTP/1.1*,
 378 <http://www.ietf.org/rfc/rfc2616.txt>
- 379 IETF RFC3986, T. Berners-Lee et al, *Uniform Resource Identifiers (URI): Generic Syntax*, August 1998,
 380 <http://www.ietf.org/rfc/rfc3986.txt>
- 381 IETF RFC4627, D. Crockford, *The application/json Media Type for JavaScript Object Notation (JSON)*,
 382 July 2006, <http://www.ietf.org/rfc/rfc4627.txt>
- 383 IETF RFC5246, T. Dierks and E. Rescorla, *The Transport Layer Security (TLS) Protocol Version 1.2*,
 384 <http://www.ietf.org/rfc/rfc5246.txt>
- 385 ISO 8601:2004, International Organization for Standardization, Geneva, Switzerland, *Data elements and*
 386 *interchange formats -- Information interchange -- Representation of dates and times*, March 2008,
 387 http://www.iso.org/iso/catalogue_detail.htm?csnumber=40874
- 388 ISO/IEC 14977:1996, Roger S. Scowen, *Extended BNF — A generic base standard*. Software
 389 Engineering Standards Symposium 1993.
 390 http://www.iso.org/iso/catalogue_detail?csnumber=26153
- 391 ISO/IEC Directives, Part 2, *Rules for the structure and drafting of International Standards*,
 392 <http://isotc.iso.org/livelink/livelink.exe?func=ll&objId=4230456&objAction=browse&sort=subtype>
- 393 NIST Special Publication 800-145, Peter Mell and Timothy Grance, *The NIST Definition of Cloud*
 394 *Computing*, Sept. 2011, <http://csrc.nist.gov/publications/nistpubs/800-145/SP800-145.pdf>
- 395 NIST Special Publication 500-292, Fang Liu, Jin Tong, Jian Mao, Robert Bohn, John Messina, Lee
 396 Badger and Dawn Leaf, *NIST Cloud Computing Reference Architecture*, Sept. 2011,
 397 [http://collaborate.nist.gov/twiki-cloud-](http://collaborate.nist.gov/twiki-cloud-computing/pub/CloudComputing/ReferenceArchitectureTaxonomy/NIST_SP_500-292_-_090611.pdf)
 398 [computing/pub/CloudComputing/ReferenceArchitectureTaxonomy/NIST_SP_500-292_-_090611.pdf](http://collaborate.nist.gov/twiki-cloud-computing/pub/CloudComputing/ReferenceArchitectureTaxonomy/NIST_SP_500-292_-_090611.pdf)
- 399 Representational State Transfer, Roy Fielding, Doctoral dissertation, University of California, *Architectural*
 400 *Styles and the Design of Network-based Software Architectures (Chapter 5)*, 2000,
 401 http://www.ics.uci.edu/~fielding/pubs/dissertation/rest_arch_style.htm
- 402 XMLSchema - Part 1, World Wide Web Consortium (W3C) Recommendation, H. Thompson, et al.,
 403 Editors, *XML Schema Part 1: Structures Second Edition*, 28 October 2004,
 404 <http://www.w3.org/TR/xmlschema-1/>
- 405 XMLSchema - Part 2, World Wide Web Consortium (W3C) Recommendation, P. Biron, A. Malhotra,
 406 Editors, *XML Schema Part 2: Datatypes (Second Edition)*, 28 October 2004,
 407 <http://www.w3.org/TR/xmlschema-2/>

408 3 Terms and definitions

409 In this document, some terms have a specific meaning beyond the normal English meaning. Those terms
 410 are defined in this clause.

411 The terms "shall" ("required"), "shall not," "should" ("recommended"), "should not" ("not recommended"),
 412 "may," "need not" ("not required"), "can" and "cannot" in this document are to be interpreted as described
 413 in [ISO/IEC Directives, Part 2](#), Annex H. The terms in parenthesis are alternatives for the preceding term,
 414 for use in exceptional cases when the preceding term cannot be used for linguistic reasons. Note that
 415 [ISO/IEC Directives, Part 2](#), Annex H specifies additional alternatives. Occurrences of such additional
 416 alternatives shall be interpreted in their normal English meaning.