
**Road vehicles — Pedestrian protection —
Head impact test method**

*Véhicules routiers — Protection des piétons — Méthode d'essai de
choc de la tête du piéton*



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

This document is a preview generated by EVS

© ISO 2006

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

| | |
|--|----|
| Foreword..... | iv |
| Introduction | v |
| 1 Scope | 1 |
| 2 Normative references | 1 |
| 3 Terms and definitions..... | 1 |
| 4 Test equipment | 3 |
| 4.1 Impact test site..... | 3 |
| 4.2 Head form impactor..... | 3 |
| 5 Requirements | 4 |
| 5.1 Head form impactor | 4 |
| 5.2 Impact area | 4 |
| 5.3 Impact angle | 4 |
| 5.4 Head form impactor calibration..... | 5 |
| 5.5 Propulsion of head form impactor | 5 |
| 5.6 Rear face of head impactor..... | 5 |
| 6 Preparation of test vehicle | 5 |
| 6.1 Components | 5 |
| 6.2 Parking brake | 5 |
| 6.3 Time..... | 5 |
| 7 Test conditions | 5 |
| 7.1 Impact angle and impact velocity | 5 |
| 7.2 Impact points..... | 6 |
| 8 Recording of test results | 6 |
| 8.1 Data acquisition | 6 |
| 8.2 Head form impactor data | 6 |
| Annex A (normative) Calibration method for head form impactor..... | 7 |
| Annex B (normative) Velocity and angle | 9 |
| Bibliography | 11 |

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 14513 was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 10, *Impact test procedures*.

Introduction

The intent of this International Standard is to help reduce pedestrian head injuries by providing a standardized test method which will allow different test organizations to use the results from pedestrian impact tests conducted by other organizations. The test method specified applies to adults, but it is anticipated that biomechanical data for children will later be studied in order to determine the potential for child pedestrian protection.

This document is a preview generated by EVS

This document is a preview generated by EVS

Road vehicles — Pedestrian protection — Head impact test method

1 Scope

This International Standard specifies a test method to simulate the head impact of an adult pedestrian to the bonnet top of passenger vehicles or light truck vehicles of up to 3,5 t (GVM), as defined in ISO 3833. The impact device to be used in this test method will be robust for a vehicle impact velocity of up to 11 m/s. The test method specified addresses the reduction of an adult pedestrian head injury risk; it does not test for injuries to other regions of the pedestrian. The evaluation of injury risk to other pedestrian body regions should be determined using other test methods. This test method does not consider downward pitching of the vehicle due to pre-impact braking. This test method and the corresponding HIC measurement utilizes a free flight head form impactor and does not consider the kinematics of the pedestrian body as a whole, nor does it consider the subsequent post-impact kinematics and potential injury risk.

NOTE The test method covers an adult pedestrian head in a simulated impact with a motorized road vehicle. Research suggests vehicle safety improvements in vehicle derived from such pedestrian impact tests may be beneficial also to bicyclists in vehicle front impact.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3784, *Road vehicles — Measurement of impact velocity in collision tests*

ISO 3833, *Road vehicles — Types — Terms and definitions*

ISO 6487, *Road vehicles — Measurement techniques in impact tests — Instrumentation*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

normal ride attitude

the vehicle attitude in driving order positioned on the ground, with the tires inflated to recommended pressures, the front wheels in the straight-ahead position, with maximum capacity of all fluids necessary for operation of the vehicle (with all standard as provided by the vehicle manufacturer), with one adult male 50th percentile dummy or an equivalent mass placed on the driver's seat and with one adult male 50th percentile dummy or an equivalent mass placed on the passenger's seat, and the suspension set in normal running conditions specified by the manufacturer (especially for vehicles with an active suspension or a device for automatic leveling)