

**Eelkoormatavad kõrgtugevad ehituslikud
kinnitusmehhanismid. Osa 7: HR-süsteem.
Koostud peitpeaga poldi ja mutriga**

High-strength structural bolting for preloading -
Part 7: System HR - Countersunk head bolt and
nut assemblies

EESTI STANDARDI EESSÕNA**NATIONAL FOREWORD**

Käesolev Eesti standard EVS-EN 14399-7:2008 sisaldab Euroopa standardi EN 14399-7:2007 ingliskeelset teksti.	This Estonian standard EVS-EN 14399-7:2008 consists of the English text of the European standard EN 14399-7:2007.
Standard on kinnitatud Eesti Standardikeskuse 28.01.2008 käskkirjaga ja jõustub sellekohase teate avaldamisel EVS Teatajas.	This standard is ratified with the order of Estonian Centre for Standardisation dated 28.01.2008 and is endorsed with the notification published in the official bulletin of the Estonian national standardisation organisation.
Euroopa standardimisorganisatsioonide poolt rahvuslikele liikmetele Euroopa standardi teksti kättesaadavaks tegemise kuupäev on 19.12.2007.	Date of Availability of the European standard text 19.12.2007.
Standard on kättesaadav Eesti standardiorganisatsioonist.	The standard is available from Estonian standardisation organisation.

ICS 21.060.01

Võtmesõnad:

Standardite reprodutseerimis- ja levitamiseõigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonilisse süsteemi või edastamine ükskõik millises vormis või millisel teel on keelatud ilma Eesti Standardikeskuse poolt antud kirjaliku loata.

Kui Teil on küsimusi standardite autorikaitse kohta, palun võtke ühendust Eesti Standardikeskusega:
Aru 10 Tallinn 10317 Eesti; www.evs.ee; Telefon: 605 5050; E-post: info@evs.ee

ICS 21.060.01

English Version

High-strength structural bolting assemblies for preloading - Part 7: System HR - Countersunk head bolt and nut assemblies

Boulonnerie de construction métallique à haute résistance
apte à la précontrainte - Partie 7: Système HR - Boulons à
tête fraisée (vis et écrou)

Hochfeste planmäßig vorspannbare
Schraubenverbindungen für den Metallbau - Teil 7: System
HR - Garnituren aus Senkschrauben und Muttern

This European Standard was approved by CEN on 10 November 2007.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Contents

Foreword	3
Introduction	4
1 Scope	5
2 Normative references	5
3 Terms and definitions	6
4 Bolts	6
5 Nuts	12
6 Designation of the countersunk head bolt/nut assembly	16
7 Associated washers	16
8 Functional characteristics of the bolt/nut/washer(s) assembly	17
Bibliography	21
Figures	
Figure 1 — Dimensions of bolts Table 2 — Dimensions of bolts ^a	7
Figure 2 — Example for marking of a bolt	12
Figure 3 — Dimensions of nuts	12
Figure 4 — Example for marking of a nut	16
Figure 5 — Adapter	17
Figure 6 — Test set-up	18
Tables	
Table 1 — Systems of bolt/nut/washer(s) assemblies	4
Table 2 — Dimensions of bolts ^a	8
Table 3 — Specifications for bolts and reference standards	11
Table 4 — Dimensions of nuts ^a	13
Table 5 — Specifications for nuts and reference standards	14
Table 6 — Proof load values of nuts	15
Table 7 — Hardness values of nuts, if specified	15
Table 8 — Characteristics of adapters	17
Table 9 — Values for $\Delta\theta_1$	19
Table 10 — Values for $\Delta\theta_2$	19

Foreword

This document (EN 14399-7:2007) has been prepared by Technical Committee CEN/TC 185 "Fasteners", the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by June 2008, and conflicting national standards shall be withdrawn at the latest by June 2010.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

Introduction

This document for structural bolting reflects the situation in Europe where two technical solutions exist to achieve the necessary ductility of bolt/nut/washer assemblies. These solutions utilize different systems (HR and HV) of bolt/nut/washer assemblies, see Table 1. Both systems are well proved and it is up to the experts responsible for structural bolting whether they use the one or the other system.

It is however important for the performance of the assembly to avoid mixing up the components of both systems. Therefore bolts and nuts for both systems are standardized in one single part of this European Standard each and the marking of the components of the same system is uniform.

Table 1 — Systems of bolt/nut/washer(s) assemblies

	Bolt/nut/washer(s) assembly System HR		Bolt/nut/washer(s) assembly System HV
General requirements	EN 14399-1		
Bolt/nut assemblies	EN 14399-3, EN 14399-7		EN 14399-4, EN 14399-8
Marking	HR		HV
Property classes	8.8/8 or 8.8/10	10.9/10	10.9/10
Washer(s)	EN 14399-5 or EN 14399-6		EN 14399-5 or EN 14399-6
Marking	H		H
Suitability test for preloading	EN 14399-2		EN 14399-2

Preloaded bolted assemblies are very sensitive to differences in manufacture and lubrication. Therefore it is important that the assembly is supplied by one manufacturer who is always responsible for the function of the assembly.

For the same reason it is important that the coating of the assembly is under the control of the manufacturer.

Beside the mechanical properties of the components, the functionality of the assembly requires that the specified pre-load can be achieved if the assembly is tightened with a suitable procedure. For this purpose a test method for the suitability of the components for preloading was created which will demonstrate whether the function of the assembly is fulfilled.

Attention is drawn to the importance of ensuring that the bolts are correctly used if satisfactory results are to be obtained. For recommendations concerning proper application, reference to prEN 1090-2 is made.

1 Scope

This document belongs to the suite of European Standards EN 14399 and is designed to be read in conjunction with EN 14399-1 for:

- general requirements;
- testing for conformity evaluation;
- evaluation of conformity;
- regulatory marking;

for assemblies of high-strength structural countersunk bolts and nuts of system HR suitable for preloaded joints with thread sizes M12 to M36 and bolt property classes 8.8 and 10.9 and EN 14399-2 for suitability testing.

This document gives requirements for:

- dimensions;
- associated washer(s) according to EN 14399-5 or to EN 14399-6;
- performance and suitability tests;

for assemblies with thread sizes M12 to M36 and bolt property classes 8.8 and 10.9.

Countersunk bolt and nut assemblies to this document have been designed to allow preloading of at least $0,7 f_{ub} \times A_s$ ¹⁾ according to EN 1993-1-8 (Eurocode 3) and to obtain ductility predominantly by elongation of the bolt. For this purpose the components have the following characteristics:

- nut height according to style 1 (see EN ISO 4032),
- thread length of the bolt according to ISO 888.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 1993-1-8, *Eurocode 3: Design of steel structures — Part 1-8: Design of joints*

EN 10045-1, *Metallic materials - Charpy impact test - Part 1: Test method*

EN 14399-1:2005, *High-strength structural bolting assemblies for preloading - Part 1: General requirements*

EN 14399-2:2005, *High-strength structural bolting assemblies for preloading - Part 2: Suitability test for preloading*

EN 14399-5, *High-strength structural bolting assemblies for preloading - Part 5: Plain washers*

EN 14399-6, *High-strength structural bolting assemblies for preloading - Part 6: Plain chamfered washers*

1) f_{ub} is the nominal tensile strength (R_m) and A_s is the nominal stress area of the bolt.

EN 20898-2, *Mechanical properties of fasteners - Part 2: Nuts with specified proof load values - Coarse thread (ISO 898-2:1992)*

EN 26157-1, *Fasteners - Surface discontinuities - Part 1: Bolts, screws and studs for general requirements (ISO 6157-1:1988)*

EN ISO 898-1, *Mechanical properties of fasteners made of carbon steel and alloy steel - Part 1: Bolts, screws and studs (ISO 898-1:1999)*

EN ISO 3269, *Fasteners - Acceptance inspection (ISO 3269:2000)*

EN ISO 4032, *Hexagon nuts, style 1 - Product grades A and B (ISO 4032:1999)*

EN ISO 4759-1, *Tolerances for fasteners - Part 1: Bolts, screws, studs and nuts - Product grades A, B and C (ISO 4759-1:2000)*

EN ISO 6157-2, *Fasteners - Surface discontinuities - Part 2: Nuts (ISO 6157-2:1995)*

EN ISO 10684, *Fasteners - Hot dip galvanized coatings (ISO 10684:2004)*

ISO 148-1, *Metallic materials - Charpy pendulum impact test - Part 1: Test method*

ISO 261, *ISO general purpose metric screw threads — General plan*

ISO 888, *Bolts, screws and studs — Nominal lengths, and thread lengths for general purpose bolts*

ISO 965-2, *ISO general purpose metric screw threads - Tolerances - Part 2: Limits of sizes for general purpose external and internal screw threads - Medium quality*

ISO 965-5, *ISO general purpose metric screw threads - Tolerances - Part 5: Limits of sizes for internal screw threads to mate with hot-dip galvanized external screw threads with maximum size of tolerance position h before galvanizing*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in EN 14399-1:2005 and 14399-2:2005 apply.

4 Bolts

4.1 General

The test method for suitability for preloading shall be as specified in EN 14399-2.

4.2 Dimensions of bolts

See Figure 1 and Table 2.