

---

---

**Information technology — 8 mm wide  
magnetic tape cartridge for information  
interchange — Helical scan recording —  
AIT-3 format**

*Technologies de l'information — Cartouche de bande magnétique de  
8 mm de large pour échange d'informations — Enregistrement par  
balayage en spirale — Format AIT-3*

**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

This document is a preview generated by EVS

© ISO/IEC 2003

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

## Contents

<b>Section 1 - General</b>	<b>1</b>
<b>1 Scope</b>	<b>1</b>
<b>2 Conformance</b>	<b>1</b>
2.1 Magnetic tape cartridge	1
2.2 Generating drive	1
2.3 Receiving drive	1
<b>3 Normative references</b>	<b>2</b>
<b>4 Terms and definitions</b>	<b>2</b>
4.1 Absolute Frame Number (AFN)	2
4.2 a.c. erase	2
4.3 Access	2
4.4 algorithm	2
4.5 Area ID	2
4.6 Automatic Track Finding (ATF)	2
4.7 Average Signal Amplitude	2
4.8 azimuth	2
4.9 back surface	2
4.10 byte	2
4.11 cartridge	2
4.12 Channel bit	3
4.13 Codeword	3
4.14 Early Warning Point (EWP)	3
4.15 End of Data (EOD)	3
4.16 Entity	3
4.17 Error Correcting Code (ECC)	3
4.18 flux transition position	3
4.19 flux transition spacing	3
4.20 Frame	3
4.21 Housekeeping Frame	3
4.22 Logical Beginning of Tape (LBOT)	3
4.23 magnetic tape	3
4.24 Master Standard Amplitude Calibration Tape	3
4.25 Master Standard Reference Tape	3
4.26 Partition Boundary	3
4.27 Physical Beginning of Tape (PBOT)	3
4.28 Physical End of Tape (PEOT)	4
4.29 physical recording density	4
4.30 pre-recording condition	4
4.31 processing	4
4.32 processed data	4
4.33 Processed Record	4
4.34 record	4
4.35 Reference Field	4
4.36 Remote Memory In Cartridge (RMIC)	4
4.37 Secondary Standard Amplitude Calibration Tape	4
4.38 Secondary Standard Reference Tape	4

<b>4.39</b>	Separator Mark	<b>4</b>
<b>4.40</b>	Standard Reference Amplitude (SRA)	<b>4</b>
<b>4.41</b>	Standard Reference Current	<b>4</b>
<b>4.42</b>	Tape Reference Edge	<b>4</b>
<b>4.43</b>	Test Recording Current	<b>4</b>
<b>4.44</b>	track	<b>5</b>
<b>4.45</b>	Typical Field	<b>5</b>
<b>4.46</b>	unprocessed data	<b>5</b>
<b>4.47</b>	Unprocessed Record	<b>5</b>
<b>5</b>	<b>Conventions and Notations</b>	<b>5</b>
<b>5.1</b>	Representation of numbers	<b>5</b>
<b>5.2</b>	Names	<b>5</b>
<b>6</b>	<b>Acronyms</b>	<b>5</b>
<b>7</b>	<b>Environment and safety</b>	<b>6</b>
<b>7.1</b>	Test environment	<b>6</b>
<b>7.2</b>	Operating environment	<b>6</b>
<b>7.3</b>	Storage environment	<b>6</b>
<b>7.4</b>	Transportation	<b>6</b>
<b>7.5</b>	Safety	<b>6</b>
<b>7.6</b>	Flammability	<b>6</b>
<b>Section 2 - Requirements for the case</b>		<b>6</b>
<b>8</b>	<b>Dimensional and mechanical characteristics of the case</b>	<b>6</b>
<b>8.1</b>	General	<b>6</b>
<b>8.2</b>	Overall dimension	<b>7</b>
<b>8.3</b>	Holding areas	<b>7</b>
<b>8.4</b>	Cartridge insertion	<b>8</b>
<b>8.5</b>	Window	<b>8</b>
<b>8.6</b>	Loading grips	<b>9</b>
<b>8.7</b>	Label areas	<b>9</b>
<b>8.8</b>	Datum areas and Datum holes	<b>9</b>
<b>8.9</b>	Support areas	<b>10</b>
<b>8.10</b>	Recognition holes	<b>10</b>
<b>8.11</b>	Write-inhibit hole	<b>11</b>
<b>8.12</b>	Pre-positioning surfaces	<b>12</b>
<b>8.13</b>	Cartridge lid	<b>12</b>
<b>8.14</b>	Cartridge reel lock	<b>13</b>
<b>8.15</b>	Reel access holes	<b>14</b>
<b>8.16</b>	Interface between the reels and the drive spindles	<b>14</b>
<b>8.17</b>	Light path	<b>15</b>
<b>8.18</b>	Position of the tape in the case	<b>16</b>
<b>8.19</b>	Tape path zone	<b>16</b>
<b>8.20</b>	Tape access cavity	<b>16</b>
<b>8.21</b>	Tape access cavity clearance	<b>17</b>
<b>8.22</b>	Requirements for the RMIC	<b>17</b>
<b>8.23</b>	Recognition recesses	<b>18</b>
<b>Section 3 - Requirements for the unrecorded tape</b>		<b>38</b>
<b>9</b>	<b>Mechanical, physical and dimensional characteristics of the tape</b>	<b>38</b>
<b>9.1</b>	Materials	<b>38</b>
<b>9.2</b>	Tape length	<b>38</b>

9.2.1	Length of magnetic tape	38
9.2.2	Length of leader and trailer tapes	38
9.2.3	Length of the splicing tapes	38
9.3	Tape width	38
9.3.1	Width of magnetic, leader and trailer tapes	38
9.3.2	Width and position of the splicing tape	38
9.4	Discontinuities	39
9.5	Tape thickness	39
9.5.1	Thickness of the magnetic tape	39
9.5.2	Thickness of the leader and trailer tape	39
9.5.3	Thickness of the splicing tape	39
9.6	Longitudinal curvature	39
9.7	Cupping	39
9.8	Coating adhesion	39
9.9	Layer-to-layer adhesion	40
9.10	Tensile strength	40
9.10.1	Breaking strength	40
9.10.2	Yield strength	40
9.11	Residual elongation	40
9.12	Electrical resistance of the recording surface	40
9.13	Tape winding	41
9.14	Light transmittance of the tape	41
9.15	Recognition stripe	41
10	<b>Magnetic recording characteristics</b>	42
10.1	Typical Field	42
10.2	Signal Amplitude	42
10.3	Resolution	43
10.4	Overwrite	43
10.5	Ease of erasure	43
10.6	Tape quality	43
10.6.1	Missing pulses	43
10.6.2	Missing pulse zone	43
10.7	Signal-to-Noise Ratio (SNR) characteristic	43
<b>Section 4 - Requirements for an interchanged tape</b>		44
11	<b>Format</b>	44
11.1	General	44
11.2	Basic Groups	44
11.2.1	Entity	45
11.2.2	Group Information Table	45
11.2.3	Block Access Table (BAT)	48
11.3	Sub-Groups	50
11.3.1	G1 Sub-Group	50
11.3.2	G2 Sub-Group - Randomizing	51
11.3.3	G3 Sub-Group	52
11.4	Data Block	53
11.4.1	ID information	53
11.4.2	Recording of the ID Information in the Data Block Headers	56
12	<b>Method of recording</b>	61
12.1	Physical recording density	62
12.2	Long-term average bit cell length	62
12.3	Short-term average bit cell length	62
12.4	Rate of change	62

<b>12.5</b>	Bit shift	<b>62</b>
<b>12.6</b>	Read signal amplitude	<b>62</b>
<b>12.7</b>	Maximum recorded levels	<b>62</b>
<b>13</b>	<b>Track geometry</b>	<b>62</b>
<b>13.1</b>	Track configuration	<b>62</b>
<b>13.2</b>	Average track pitch	<b>63</b>
<b>13.3</b>	Variations of the track pitch	<b>63</b>
<b>13.4</b>	Track width	<b>63</b>
<b>13.5</b>	Track angle	<b>63</b>
<b>13.6</b>	Track edge straightness	<b>63</b>
<b>13.7</b>	Track length	<b>63</b>
<b>13.8</b>	Azimuth angles	<b>63</b>
<b>14</b>	<b>Recorded patterns</b>	<b>64</b>
<b>14.1</b>	Recorded Data Block	<b>64</b>
<b>15</b>	<b>Format of tracks</b>	<b>64</b>
<b>15.1</b>	Track structure	<b>64</b>
<b>15.2</b>	Positioning accuracy	<b>64</b>
<b>15.3</b>	Tracking scheme	<b>64</b>
<b>15.4</b>	Generation of Margin Blocks	<b>65</b>
<b>16</b>	<b>Layout of the tape</b>	<b>66</b>
<b>16.1</b>	Device Area	<b>66</b>
<b>16.2</b>	Reference Area	<b>67</b>
<b>16.3</b>	Position Tolerance Band No. 1	<b>67</b>
<b>16.4</b>	System Area	<b>67</b>
<b>16.4.1</b>	System Preamble	<b>67</b>
<b>16.4.2</b>	System Log	<b>67</b>
<b>16.4.3</b>	System Postamble	<b>72</b>
<b>16.4.4</b>	Position Tolerance Band No. 2	<b>72</b>
<b>16.4.5</b>	Vendor Group Preamble	<b>72</b>
<b>16.5</b>	Data Area	<b>72</b>
<b>16.5.1</b>	Vendor Group	<b>72</b>
<b>16.5.2</b>	Recorded Data Group	<b>72</b>
<b>16.5.3</b>	ECC3	<b>73</b>
<b>16.5.4</b>	Multiple Recorded Instances	<b>74</b>
<b>16.5.5</b>	Repeated Frames	<b>74</b>
<b>16.5.6</b>	Appending and overwriting	<b>75</b>
<b>16.6</b>	EOD Area	<b>76</b>
<b>16.7</b>	Optional Device Area	<b>76</b>
<b>16.8</b>	Logical End Of Tape (LEOT)	<b>77</b>
<b>16.9</b>	Logical Beginning of Tape (LBOT)	<b>77</b>
<b>16.10</b>	Early Warning Point - EWP	<b>77</b>
<b>16.11</b>	Empty Partition	<b>77</b>
<b>16.12</b>	Initialization	<b>77</b>
<b>17</b>	<b>Housekeeping Frames</b>	<b>78</b>
<b>17.1</b>	Amble Frames	<b>78</b>
<b>17.2</b>	System Amble Frames	<b>78</b>
<b>18</b>	<b>AIT Remote Memory In Cartridge (AIT RMIC)</b>	<b>78</b>
<b>18.1</b>	General	<b>78</b>
<b>18.2</b>	Content of the AIT RMIC	<b>78</b>
<b>18.2.1</b>	Manufacturer's Information Section	<b>79</b>

18.2.2	Communication Information Section	82
18.2.3	Mechanism Error Log Information Section	82
18.2.4	Memory Management Information Section	83
18.2.5	Volume Information Section	84
18.2.6	Volume Use History Information Section	85
18.3	Memory Heap Management	85
18.3.1	Cell	85
18.3.2	Cell Header	85
18.3.3	Partition Information Cell	87
18.3.4	Physical Tape Directory Information Cell	87
18.3.5	User Volume Information Cell	88
18.3.6	User Partition Information Cell	88
18.3.7	Application Information Cell	89
18.3.8	Date and Time Stamp Information Cell	90
18.3.9	Media Identification Information Cell	91
18.3.10	Tape Alert Information Cell	91
18.4	Electrical interface	92
18.5	Environment	92
18.5.1	Electromagnetic Compatibility	92
18.5.2	Magnetic fields	92
18.5.3	X-rays	92
18.6	Operating Field	92
18.7	Message from AIT RMIC reader-writer to AIT RMIC	92
18.8	Message from AIT RMIC to AIT RMIC reader-writer	93
18.8.1	Load modulation	94
18.9	EDC	95
18.10	AIT RMIC states	95
18.11	Command and Response	96
18.11.1	Attention Command and Response	97
18.11.2	Attention Command and Response Type 1	97
18.11.3	Attention Command and Response Type 2	97
18.11.4	Read Command and Response	98
18.11.5	Write Command and Response	98
18.11.6	Status Command and Response	98
18.11.7	Reset Command and Response	99
18.12	Dialogue	99
18.12.1	Read data from AIT RMIC	99
18.12.2	Write data to AIT RMIC	100
18.12.3	Read and Write with Session ID	101
<b>Annexes</b>		
<b>A (normative) - Measurement of light transmittance</b>		<b>105</b>
<b>B (normative) - Measurement of Signal-to-Noise Ratio</b>		<b>108</b>
<b>C (normative) - Method for determining the nominal and the maximum allowable recorded levels (pre-recording condition)</b>		<b>109</b>
<b>D (normative) - Representation of 16-bit words by 18-Channel bits patterns</b>		<b>110</b>
<b>E (normative) - Measurement of bit shift</b>		<b>111</b>
<b>F (normative) - Method of measuring the straightness of track edges</b>		<b>113</b>
<b>G (normative) - ECC calculation</b>		<b>114</b>
<b>H (informative) - Recommendations for transportation</b>		<b>117</b>
<b>J (informative) - Read-After-Write</b>		<b>118</b>

<b>K (informative) - Basic Group No. 0</b>	<b>119</b>
<b>L (informative) - Chip for the AIT-3 format</b>	<b>120</b>
<b>M (informative) - Generation of EDC bytes for the Error Detecting Code for G2 Sub-Groups</b>	<b>121</b>

This document is a preview generated by EVS



## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

ISO/IEC 23651 was prepared by ECMA (as ECMA-329) and was adopted, under a special “fast-track procedure”, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

This document is a preview generated by EVS

# Information technology — 8 mm wide magnetic tape cartridge for information interchange — Helical scan recording — AIT-3 format

## Section 1 - General

### 1 Scope

This International Standard specifies the physical and magnetic characteristics of an 8 mm wide magnetic tape cartridge containing a memory chip to enable physical interchange of such cartridges between drives. It also specifies the quality of the recorded signals, the recording method and the recorded format - called Advanced Intelligent Tape No. 3 (AIT-3 format) - thereby allowing data interchange between drives by means of such magnetic tape cartridges.

This International Standard specifies two types of cartridge depending on the thickness of the magnetic tape contained in the case.

Information interchange between systems also requires, at a minimum, agreement between the interchange parties upon the interchange code(s) and the specifications of the structure and labelling of the information on the interchanged cartridge.

### 2 Conformance

#### 2.1 Magnetic tape cartridge

A tape cartridge shall be in conformance with this International Standard if it meets all the mandatory requirements specified herein. The tape requirements shall be satisfied throughout the extent of the tape.

#### 2.2 Generating drive

A drive generating a magnetic tape cartridge for interchange shall be in conformance with this International Standard if all recordings on the tape meet the mandatory requirements of this International Standard, and if either one or both methods of appending and overwriting are implemented. In addition, such a drive shall be able to record the System Log in the AIT Remote Memory In Cartridge (AIT RMIC).

A claim of conformance shall state which of the following optional features are implemented and which are not

- the performing of a Read-After-Write check and the recording of any necessary repeated frames;
- the generation of ECC3 Frames.

In addition a claim of conformance shall state

- whether or not one, or more, registered algorithm(s) are implemented within the system and are able to compress data received from the host prior to collecting the data into Basic Groups, and
- the registered identification number(s) of the implemented compression algorithm(s).

#### 2.3 Receiving drive

A drive receiving a magnetic tape cartridge for interchange shall be in conformance with this International Standard if it is able to handle any recording made on the tape according to this International Standard. In particular it shall

- be able to read the System Log recorded in the AIT RMIC;
- be able to recognise repeated frames, and to make available to the host, data and Separator Marks from only one of these frames;
- be able to recognise multiple representations of the same Basic Group, and to make available to the host, data and Separator Marks from only one of these representations;
- be able to recognise an ECC3 frame, and ignore it if the system is not capable of using ECC3 check bytes in a process of error correction;
- be able to recognise processed data within an Entity, identify the algorithm used, and make its registered identification number available to the host;
- be able to make processed data available to the host.

In addition a claim of conformance shall state

- whether or not the system is capable of using ECC3 check bytes in a process of error correction;

- whether or not one or more de-compression algorithm(s) are implemented within the system, and are able to be applied to compressed data prior to making such data available to the host;
- the registered identification number(s) of the compression algorithm(s) for which a complementary de-compression algorithm is implemented.

### 3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 527 (all parts)	<i>Plastics — Determination of tensile properties</i>
ISO 1302:2002	<i>Geometrical Product Specifications (GPS) — Indication of surface texture in technical product documentation</i>
ISO/IEC 11576:1994	<i>Information technology — Procedure for the registration of algorithms for the lossless compression of data</i>

### 4 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

#### 4.1 Absolute Frame Number (AFN)

A sequence number encoded in a Frame.

#### 4.2 a.c. erase

A process of erasure using magnetic fields of decaying intensity.

#### 4.3 Access

A read or write pass over a partition.

#### 4.4 algorithm

A set of rules for transforming the logical representation of data.

#### 4.5 Area ID

An identifier defining the area of the tape and specifying the types of Frame written.

#### 4.6 Automatic Track Finding (ATF)

The method by which tracking is achieved.

#### 4.7 Average Signal Amplitude

The average peak-to-peak value of the output signal from the read head at the fundamental frequency of the specified physical recording density over a minimum of 20,0 mm of track, exclusive of missing pulses.

#### 4.8 azimuth

The angular deviation made by the mean flux transition line with a line normal to the centreline of the recorded track.

#### 4.9 back surface

The surface of the tape opposite to the magnetic coating which is used to record data.

#### 4.10 byte

An ordered set of bits acted upon as a unit.

#### 4.11 cartridge

A case containing magnetic tape stored on twin hubs.