INTERNATIONAL STANDARD

ISO 24335

First edition 2006-03-01

Laminate floor coverings — Determination of impact resistance

Revêtements de sol stratifiés — Détermination de la résistance aux chocs



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below

This document is a preview denetated by this

© ISO 2006

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org

Published in Switzerland

Cor	ntents	Page
Fore	word	i\
1	Scope	1
2	Normative references	1
3	Apparatus)	
4	Test specimens	
4.1	General	6
4.2	Specimens for the small-diameter ball test	
4.3 4.4	Specimens for the large-diameter ball test	6
	Conditioning Procedure	
5 5.1	ProcedureImpact by small-diame@ball	6
5.1 5.2	Impact by large-diameter hall	8
6	Expression of results	C
6.1	Small-diameter ball	
6.2	Large-diameter ball	9
7	Test Report	10
Bibli	ography	11
	Test Report Original Conditions of the Condition of the C	

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in traison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 24335 was prepared by Technical Committee ISO/TC 219, Floor coverings.

SISO/TC 219, Flour -

Laminate floor coverings — Determination of impact resistance

1 Scope

This International standard specifies how to determine the impact resistance of laminate floor covering elements. The test described measures the ability of the surface layer to withstand impact from both small and large objects dropped on the floor covering. The testing is destructive by means of the impact on the surface layer from one small and one larger steel ball simulating different scenarios. The force of the small steel ball and the drop height of the larger steel ball are used to define the ability for a laminate floor covering element to withstand impact.

The precision of the method is not known. When interlaboratory data becomes available, a precision statement will be added in subsequent revisions.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 291, Plastics — Standard atmospheres for conditioning and testing

3 Apparatus

- **3.1 Conditioning chamber**, in accordance with ISO 291, with a standard atmosphere of (23 ± 2) °C and relative humidity (50 ± 5) %.
- **3.2** Polyethylene foam, thickness (2 ± 0.5) mm, density (35 ± 5) kg/m³.
- 3.3 Small-diameter ball apparatus
- **3.3.1 Impact tester**, consisting of an impact bolt with a 5 mm steel ball mounted at one end, which is projected once against the surface under test by the release of a compression spring.

The spring compression force before release can be adjusted continuously from 0 N to 90 N by means of a force-setting barrel (see Figure 1).

The newton-metre $(N \cdot m)$ scale also provided on the tester is only to be used for orientation, as the introduction of a non-linear scale involves relatively great inaccuracies.

The compression spring is 100 mm long when released and has a constant of (1.962 ± 50) N/m. It is compressed by drawing back the impact bolt and is held in the loaded position by a retainer which engages in the bolt. It is released to deliver the impact blow by a release unit that withdraws the retainer.

3.3.2 Force-producing arrangement, (for example, a scale-pan and weights) capable of being suspended from the impact bolt to exert a compressive force on the spring.

© ISO 2006 – All rights reserved