

---

---

**Non-destructive testing — Ultrasonic  
testing — Specification for calibration  
block No. 2**

*Essais non destructifs — Contrôle par ultrasons — Spécifications  
relatives au bloc d'étalonnage n° 2*



**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

This document is a preview generated by EVS

© ISO 2006

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

Page

Foreword.....	iv
Introduction .....	v
1 Scope .....	1
2 Normative references .....	1
3 Terms and definitions.....	1
4 Dimensions.....	1
5 Material .....	1
6 Preparation .....	3
7 Marking .....	3
8 Method of use.....	3
8.1 Setting of the time base .....	3
8.2 Sensitivity setting and probe checking .....	5
9 Certificate .....	7
Annex A (normative) Calibration block characteristics and use .....	8
Bibliography .....	9

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

ISO 7963 was prepared by Technical Committee ISO/TC 44, *Welding and allied processes*, Subcommittee SC 5, *Testing and inspection of welds*.

This second edition cancels and replaces the first edition (ISO 7963:1985), which has been technically revised.

## Introduction

Calibration block No. 2 differs in size and shape from that described in ISO 2400.

Calibration block No. 2 is very much smaller and lighter, and its geometry is much simpler.

Calibration block No. 2 does not offer as much scope as the larger block; in particular it is not meant to check an ultrasonic flaw detector completely.

However, calibration block No. 2 makes it possible, during practical testing, to check simply, from time to time, the setting of the time base and the sensitivity of the ultrasonic equipment. Moreover, it is suited to checking the beam angle and the probe index of miniature angle-beam probes.

NOTE Calibration block No. 1 is currently specified in EN 12223.

Requests for official interpretations of any aspect of this International Standard should be directed to the Secretariat of ISO/TC 44/SC 5 via your national standards body, a complete listing which can be found at [www.iso.org](http://www.iso.org).

This document is a preview generated by EVS

# Non-destructive testing — Ultrasonic testing — Specification for calibration block No. 2

## 1 Scope

This International Standard specifies the dimensions, material, manufacture and methods of use for calibration block No. 2 for calibrating and checking ultrasonic testing equipment.

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 4287, *Geometrical Product Specifications (GPS) — Surface texture: Profile method — Terms, definitions and surface texture parameters*

ISO 5577, *Non-destructive testing — Ultrasonic inspection — Vocabulary*

EN 10025-1, *Hot rolled products of structural steels — Part 1: General technical delivery conditions*

## 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 5577 apply.

## 4 Dimensions

The dimensions of the block are given in Figure 1.

The tolerances are  $\pm 0,1$  mm, except on the length of the engraved scale where it is  $\pm 0,5$  mm.

Average surface roughness values,  $R_a$ , are defined in accordance with ISO 4287.

The thickness of the block can be greater than 12,5 mm (see A.1).

## 5 Material

The calibration block shall be made of steel of grade S355JO in accordance with EN 10025-1 or equivalent.