INTERNATIONAL STANDARD

1SO/IEC 21992

First edition 2003-06-01

Information technology —
Telecommunications and information exchange between systems — Private Integrated Services Network — Mapping functions for the tunnelling of QSIG through IP networks

Technologies de l'information — Télécommunications et échange d'information entre systèmes — Réseau privé à intégration de services — Tracé de fonctions pour le «tunnelling» de QSIG par des réseaux IP



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

This document is a preview denetated by this

© ISO/IEC 2003

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org

Published in Switzerland

Cont	ents	Page
Forewo	ord	iv
Introdu	iction	v
1	Scope	1
2	Conformatice	
2		
3	Normative references	1
4	Terms and demitions	
4.1	External definitions	
4.2	Other definitions	2
5	Introduction Reference configuration Specific scenarios	3
6	Introduction	2
6.1	Reference configuration	ว
6.2	Specific scenarios	4
-	Capabilities at the Q reference point	
7		
8	Capabilities at the C reference point	5
8.1	ICP connection	5
8.2	UDP streams	6
9	Mapping functions	6
9.1	Mapping the D _Q -channel	6
9.2	Mapping functions Mapping a U _Q -channel IPC control functions Procedure for U _Q -channel establishment Procedure for U _Q -channel clearing	6
10	IPC control functions	6
10.1	Procedure for U _Q -channel establishment	6
10.2	Procedure for U _Q -channel clearing	7
Annex	A (informative) Implementation Conformance Statement (ICS) Proforma	8
A .1	Introduction	8
A.2	Instructions for completing the ICS proforma	8
A.2.1	General structure of the ICS proforma	8
A.2.2	Additional information	9
A.2.3	Additional information	9
A.3 A.3.1	Implementation identification	10
A.3.1 A.3.2		10
A.4	General requirements	10
A.5	General requirements U_Q-channel bearer capabilities at the Q reference point D_Q-channel capability at the Q reference point Capabilities at the C reference point	11
A.6	Do-channel capability at the Q reference point	11
A .7	Capabilities at the C reference point	11
A.8	Mapping functions	11
A.9	IPC control functions	
A.10	Support of resource control information	
A.10.1	• • • • • • • • • • • • • • • • • • • •	
	Support of IP address type	
Annex	B (normative) Message syntax for Resource Control Information	
B.1	Introduction	
B.2	Message syntax	
B.2.1	Resource control header	
B.2.2	Protocol indicator	13 13

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in jaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approprial by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 21992 was prepared by ECMA (as ECMA-336) and was adopted, under a special "fast-track procedure", by Joint Technical Committee ISO/IEC TC 1, Information technology, in parallel with its approval by national bodies of ISO and IEC.

Introduction

This International Standard is one of a series of standards defining mapping functions in exchanges of Private Integrated Services Networks required for the utilization of intervening network scenarios. The series uses the ISDN concepts as developed by ITU-T (formerly CCITT) and is also within the framework of standards for open systems interconnection as defined by ISO/IEC.

This International Standard is based upon the practical experience of ECMA member companies and the results of their active and continuous participation in the work of ISO/IEC JTC 1, ITU-T, ETSI and other international and national standardization bodies. It represents a pragmatic and widely based consensus.

da and star. Obochment is a preview denerated by the

Inis document is a preview denetated by EUS

Information technology — Telecommunications and information exchange between systems — Private Integrated Services Network — Mapping functions for the tunnelling of QSIG through IP networks

1 Scope

This International Standard specifies functions for using a packet network that uses the Internet Protocol (IP) as its network layer protocol and UDP and TCP as its transport layer protocols, to interconnect two Private Integrated services Network exchanges (PINXs) forming part of a Private Integrated Services Network (PISN). Interconnection is achieved by carrying the inter-PINX signalling protocol directly over the Transmission Control Protocol (TCP) and inter-PINX user information (e.g., voice) over the Real-time Transport Protocol (RTP), RTP being carried over the User Datagram Protocol (UDP). The inter-PINX signalling protocol is assumed to be QSIG, as specified in SO/IEC 11572, ISO/IEC 11582 and other International Standards.

This International Standard provides for two types of interconnection:

- on-demand, where a separate TCP connection for QSIG is established at the start of each call and cleared down at the end of that call; and
- semi-permanent, where a single TCP connection with an indefinite lifetime carries QSIG on behalf of many single calls.

This International Standard is applicable to PINXs that can be interconnected to form a PISN using QSIG as the inter-PINX signalling protocol.

2 Conformance

In order to conform to this International Standard, a PINX stall satisfy the requirements identified in the Implementation Conformance Statement (ICS) proforma in Annex A

3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 11572:2000, Information technology — Telecommunications and information exchange between systems — Private Integrated Services Network — Circuit mode bearer services — Inter-exchange signalling procedures and protocol

ISO/IEC 11574:2000, Information technology — Telecommunications and information exchange between systems — Private Integrated Services Network — Circuit-mode 64 kbit/s bearer services — Service description, functional capabilities and information flows

ISO/IEC 11579-1:1994, Information technology — Telecommunications and information exchange between systems — Private integrated services network — Part 1: Reference configuration for PISN Exchanges (PINX)

ISO/IEC 11582:2002, Information technology — Telecommunications and information exchange between systems — Private Integrated Services Network — Generic functional protocol for the support of supplementary services — Inter-exchange signalling procedures and protocol