

**TELEVISIOONI-, HELI- JA MULTIMEEDIASIGNAALIDE
KAABELVÕRGUD. OSA 1: SÜSTEEMI PÄRISUUNA-AHELA
NÄITAJAD**

**Cable networks for television signals, sound signals and
interactive services - Part 1: System performance of
forward paths**

EESTI STANDARDI EESSÕNA**NATIONAL FOREWORD**

See Eesti standard EVS-EN 60728-1:2015 sisaldab Euroopa standardi EN 60728-1:2014 ingliskeelset teksti.	This Estonian standard EVS-EN 60728-1:2015 consists of the English text of the European standard EN 60728-1:2014.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas.	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 29.08.2014.	Date of Availability of the European standard is 29.08.2014.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 33.060.40

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:
Aru 10, 10317 Tallinn, Eesti; koduleht www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:

Aru 10, 10317 Tallinn, Estonia; homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

English Version

Cable networks for television signals, sound signals and
interactive services - Part 1: System performance of forward
paths
(IEC 60728-1:2014)

Réseaux de distribution par câbles pour signaux de
télévision, signaux de radiodiffusion sonore et services
interactifs - Partie 1: Caractéristiques des systèmes de voie
directe
(CEI 60728-1:2014)

Kabelnetze für Fernsehsignale, Tonsignale und interaktive
Dienste - Teil 1: Systemanforderungen in Vorwärtsrichtung
(IEC 60728-1:2014)

This European Standard was approved by CENELEC on 2014-06-27. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Foreword

The text of document 100/2269/FDIS, future edition 5 of IEC 60728-1, prepared by Technical Area 5 "Cable networks for television signals, sound signals and interactive services" of IEC/TC 100 "Audio, video and multimedia systems and equipment" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 60728-1:2014.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2015-03-27
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2017-06-27

This document supersedes EN 60728-1:2008.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

For this European Standard the informative Annex K of IEC 60728-1:2014 shall be disregarded and has been replaced by the informative Annex ZB "A-deviations".

Annexes ZA and ZB have been added by CENELEC.

Endorsement notice

The text of the International Standard IEC 60728-1:2014 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 60728 Series	NOTE	Harmonized as EN 60728 Series (not modified).
IEC 61169-2	NOTE	Harmonized as EN 61169-2 (not modified).
IEC 61169-24	NOTE	Harmonized as EN 61169-24 (not modified).
CISPR 16-1 Series	NOTE	Harmonized as EN 55016-1 Series (not modified).
ISO/IEC 13818 Series	NOTE	Harmonized as EN ISO/IEC 13818 Series ¹⁾ (not modified).
ISO/IEC 13818-3	NOTE	Harmonized as EN ISO/IEC 13818-3 ¹⁾ (not modified).

¹⁾ Withdrawn.

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 When an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cenelec.eu

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
		Characteristics of DAB receivers	EN 50248	2001
IEC 60050-705	-	International Electrotechnical Vocabulary (IEV) - Chapter 705: Radio wave propagation	-	-
IEC 60050-712	1992	International Electrotechnical Vocabulary (IEV) - Chapter 712: Antennas	-	-
IEC 60050-725	-	International Electrotechnical Vocabulary (IEV) - Chapter 725: Space radiocommunications	-	-
IEC 60728-1-1	-	Cable networks for television signals, sound signals and interactive services - Part 1-1: RF cabling for two way home networks	EN 60728-1-1	-
IEC 60728-1-2	-	Cable networks for television signals, sound signals and interactive services - Part 1-2: Performance requirements or signals delivered at the system outlet in operation	EN 60728-1-2	-
IEC 60728-2	-	Cable networks for television signals, sound signals and interactive services - Part 2: Electromagnetic compatibility for equipment	EN 50083-2	-
IEC 60728-3	2010	Cable networks for television signals, sound signals and interactive services - Part 3: Active wideband equipment for cable networks	EN 60728-3	2011
IEC 60728-5	-	Cable networks for television signals, sound signals and interactive services - Part 5: Headend equipment	EN 60728-5	-
IEC 60728-10	-	Cable networks for television signals, sound signals and interactive services - Part 10: System performance of return paths	EN 60728-10	-

IEC 60728-11	-	Cable networks for television signals, sound signals and interactive services - Part 11: Safety	EN 60728-11	-
IEC 60728-12	-	Cabled distribution systems for television and sound signals - Part 12: Electromagnetic compatibility of systems	EN 50083-8	-
IEC 60966-2-4	-	Radio frequency and coaxial cable assemblies - Part 2-4: Detail specification for cable assemblies for radio and TV receivers - Frequency range 0 MHz to 3 000 MHz, IEC 61169-2 connectors	EN 60966-2-4	-
IEC 60966-2-5	-	Radio frequency and coaxial cable assemblies - Part 2-5: Detail specification for cable assemblies for radio and TV receivers - Frequency range 0 MHz to 1 000 MHz, IEC 61169-2 connectors	EN 60966-2-5	-
IEC 60966-2-6	-	Radio frequency and coaxial cable assemblies - Part 2-6: Detail specification for cable assemblies for radio and TV receivers - Frequency range 0 MHz to 3 000 MHz, IEC 61169-24 connectors	EN 60966-2-6	-
ISO/IEC 13818-1	2007	Information technology - Generic coding of moving pictures and associated audio information: Systems		-
ISO/IEC 13818-4		Information technology - Generic coding of moving pictures and associated audio information - Part 4: Conformance testing		-
ISO/IEC 14496-1	-	Information technology - Coding of audio-visual objects - Part 1: Systems		-
ITU-R Recommendation BS.412-9	-	Planning standards for terrestrial FM sound-broadcasting at VHF		-
ITU-R Recommendation BT.417-4		Minimum field strengths for which protection may be sought in planning an analogue terrestrial television service		-
ITU-R Recommendation BT.470-7	-	Conventional analogue television systems		-
ITU-R Recommendation BT.500-11	-	Methodology for the subjective assessment-of the quality of television pictures		-
ITU-T Recommendation J.61	-	Transmission performance of television circuits designed for use in international connections		-

ETSI EN 300 421	-	Digital Video Broadcasting (DVB): Framing - structure, channel coding and modulation for 11/12 GHz satellite services	-
ETSI EN 300 429	-	Digital Video Broadcasting (DVB): Framing - structure, channel coding and modulation for cable systems	-
ETSI EN 300 468	-	Digital Video Broadcasting (DVB); - Specification for Service Information (SI) in DVB systems	-
ETSI EN 300 473	-	Digital Video Broadcasting (DVB): Satellite - Master Antenna Television (SMATV) distribution systems	-
ETSI EN 300 744	-	Digital Video Broadcasting (DVB): Framing - structure, channel coding and modulation for digital terrestrial television	-
ETSI EN 302 307/V1.3.1	2013	Digital Video Broadcasting (DVB); Second - generation framing structure, channel coding and modulation systems for Broadcasting, Interactive Services, News Gathering and other broadband satellite applications (DVB-S2)	-
ETSI ETS 300 784	-	Satellite Earth Stations and Systems (SES);Television Receive-Only (TVRO) satellite earth stations operating in the 11/12 GHz frequency bands	-
ETSI TS 101 211	-	Digital Video Broadcasting (DVB); - Guidelines on implementation and usage of Service Information (SI)	-
ETSI TS 102 831 V1.2.1	2012	Digital Video Broadcasting (DVB); - Implementation guidelines for a second generation digital terrestrial television broadcasting system (DVB-T2)	-

Generated by EVS

Annex ZB (informative)

A-deviations

A-deviation: National deviation due to regulations, the alteration of which is for the time being outside the competence of the CENELEC national member.

This European Standard does not fall under any Directive of the EC.

In the relevant CENELEC countries these A-deviations are valid instead of the provisions of the European Standard until they have been removed.

Clause Deviation

3.1.58 Norway

According to Regulations on Electronic Communications Networks and Services (Ecom Regulations) laid down by the Norwegian Ministry of Transport and Communications on 16 February 2004, the following applies:

When installing coaxial cable-based networks, the part of the network to which the end-user is connected shall be placed in a star structure. It is not permitted to insert receiver connections into the connection between the star points.

5.4.1 Netherlands

(Dutch Technical Regulations for CATV networks (Technische Voorschriften voor Centrale Antenne Inrichtingen, 3e uitgave), 21 December 1977, which are valid for CATV networks in accordance with Article 21 of the Dutch Telecommunications law (Stb. 1988, 520))

Replace by/add the following “minimum and maximum carrier levels” regulation as indicated in Table ZB.1.

Table ZB.1 – Carrier signal levels at any system outlet

FM sound mono:	80 dB(μ V) _{max}
----------------	--------------------------------

(measured in accordance with CISPR 16-1 [4] (quasi-peak measurement within 120 kHz bandwidth))

5.6.2 Netherlands

(Dutch Technical Regulations for CATV networks (Technische Voorschriften voor Centrale Antenne Inrichtingen, 3e uitgave), 21 December 1977, which are valid for CATV networks in accordance with Article 21 of the Dutch Telecommunications law (Stb. 1988, 520))

Add the group delay response curve valid for PAL with FM-FM sound (Clause 5.4.1), as shown in Figure ZB.1.




Figure ZB.1 – Mask group delay characteristic for PAL signals with FM-FM sound

5.9.1 Netherlands

(Dutch Technical Regulations for CATV networks (Technische Voorschriften voor Centrale Antenne Inrichtingen, 3e uitgave), 21 December 1977, which are valid for CATV networks in accordance with Article 21 of the Dutch Telecommunications law (Stb. 1988, 520))

Replace by/add the following “single-frequency interference” regulation as indicated in Table ZB.2.

Table ZB.2 – Single-frequency interference

AM-VSB-PAL-signals:	$C/I \geq 60$ dB	(measured in a bandwidth of 300 kHz)
For signals outside used TV channels:	$C/I \geq 40$ dB	

5.10.2 Netherlands

(Dutch Technical Regulations for CATV networks (Technische Voorschriften voor Centrale Antenne Inrichtingen, 3e uitgave), 21 December 1977, which are valid for CATV networks in accordance with Article 21 of the Dutch Telecommunications law (Stb. 1988, 520))

Replace the requirements for “echoes in television channels, PAL-SECAM standards” by the “requirement for echo loss in relation to the time delay of the reflected signal for AM-PAL-TV and FM-radio” (Figure ZB.2).




Figure ZB.2 – Requirement for echo loss in relation to the time delay of the reflected signal

5.12.1 Denmark

(Danish technical regulations for CATV-networks, which are applicable to those networks in accordance with national legislation act. nr; 277 of June 1995, given by the Ministry of Research)

Add the requirement for “decoding margin” being “the decoding margin must be 40 %, when the margin is a minimum of 70 % at the receiving antenna”.

5.14.3 Netherlands

(Dutch Technical Regulations for CATV networks (Technische Voorschriften voor Centrale Antenne Inrichtingen, 3e uitgave), 21 December 1977, which are valid for CATV networks in accordance with Article 21 of the Dutch Telecommunications law (Stb. 1988, 520))

Add the requirement for “adjacent channel spacing” by ≥ 400 kHz.

CONTENTS

FOREWORD.....	10
INTRODUCTION.....	12
1 Scope.....	13
2 Normative references	13
3 Terms, definitions, symbols and abbreviations.....	15
3.1 Terms and definitions.....	15
3.2 Symbols.....	27
3.3 Abbreviations.....	29
4 Methods of measurement at system outlet.....	31
4.1 Performance limits	31
4.2 Mutual isolation between system outlets	33
4.2.1 Overview	33
4.2.2 Equipment required	33
4.2.3 Connection of the equipment	34
4.2.4 Measurement procedure	34
4.2.5 Presentation of the results	35
4.3 Amplitude response within a channel	35
4.3.1 Overview	35
4.3.2 Equipment required.....	35
4.3.3 Connection of the equipment	35
4.3.4 Measurement procedure.....	36
4.3.5 Presentation of the results	37
4.4 Chrominance-luminance gain and delay inequalities	38
4.4.1 Overview	38
4.4.2 Equipment required	39
4.4.3 Connection of the equipment	39
4.4.4 Measurement procedure	39
4.4.5 Presentation of the results	40
4.5 Non-linear distortion.....	41
4.5.1 General	41
4.5.2 Intermodulation.....	41
4.5.3 Composite beat	41
4.5.4 Composite crossmodulation	45
4.5.5 Intermodulation noise	46
4.5.6 Hum modulation of carriers.....	46
4.5.7 Differential gain and phase	51
4.6 Carrier-to-noise ratio.....	56
4.6.1 Overview	56
4.6.2 Equipment required	56
4.6.3 Connection of the equipment	56
4.6.4 Measurement set-up.....	57
4.6.5 Measurement procedure	57
4.6.6 Presentation of the results	58
4.7 Echoes	58
4.7.1 Overview	58
4.7.2 Equipment required	59

4.7.3	Connection of the equipment	59
4.7.4	Measurement procedure	59
4.7.5	Presentation of the results	60
4.8	AM-VSB television, FM radio and FM television signal level	60
4.8.1	General	60
4.8.2	Definitions for NTSC, PAL and SECAM systems	60
4.8.3	Equipment required	60
4.8.4	Measurement procedure	60
4.8.5	Presentation of the results	61
4.9	Data echo rating and data delay inequality	61
4.10	Interference in FM sound radio channels	61
4.11	Methods of measurement for digitally modulated signals	61
4.11.1	Overview	61
4.11.2	Basic assumptions and measurement interfaces	62
4.11.3	Signal level for digitally modulated signals	65
4.11.4	RF signal-to-noise ratio $S_{D,RF}/N$ for digitally modulated signals	66
4.11.5	Bit error ratio (BER)	68
4.11.6	BER versus E_b/N_0 or C/N	69
4.11.7	Noise margin	73
4.11.8	Modulation error ratio (MER)	74
4.11.9	Phase jitter	76
4.11.10	Phase noise of an RF carrier	79
5	Performance requirements at system outlet	82
5.1	General	82
5.2	Impedance	82
5.3	Requirements at the terminal input	82
5.3.1	General	82
5.3.2	Signal level	83
5.3.3	Other parameters	83
5.4	Carrier levels at system outlets	83
5.4.1	Minimum and maximum carrier levels	83
5.4.2	Carrier level differences	85
5.5	Mutual isolation between system outlets	86
5.5.1	Isolation between two subscribers	86
5.5.2	Isolation between individual outlets in one household	86
5.5.3	Isolation between forward and return path	86
5.6	Frequency response within a television channel at any system outlet	87
5.6.1	Amplitude response	87
5.6.2	Group delay	87
5.7	Long-term frequency stability of distributed carrier signals at any system outlet	88
5.8	Random noise	89
5.9	Interference to television channels	91
5.9.1	Single-frequency interference	91
5.9.2	Single-channel intermodulation interference	92
5.9.3	Multiple frequency intermodulation interference	92
5.9.4	Intermodulation noise	92
5.9.5	Cross-modulation	93

5.10	Video baseband requirements.....	93
5.10.1	Differential gain and phase in any television channel.....	93
5.10.2	Echoes.....	93
5.11	Hum modulation of carriers in television channels.....	93
5.12	Requirements for data signal transmission.....	94
5.12.1	Data signals carried in the structure of a television signal.....	94
5.12.2	Data signals other than those carried within the structure of a television signal.....	94
5.13	Digitally modulated signals – Additional performance requirements.....	94
5.13.1	DVB (PSK, QAM, OFDM) performance.....	94
5.13.2	NICAM performance.....	96
5.13.3	DAB performance.....	96
5.14	FM sound radio – Additional performance requirements.....	97
5.14.1	Amplitude response within an FM channel.....	97
5.14.2	Phase response within an FM channel.....	97
5.14.3	Interference within an FM channel.....	97
5.14.4	AM hum modulation on FM sound carriers.....	97
5.14.5	Echoes within an FM channel.....	97
6	Performance requirements at receiving antennas.....	97
6.1	General.....	97
6.2	Method of measurement of field strength.....	98
6.2.1	Overview.....	98
6.2.2	Equipment required.....	98
6.2.3	Connection of the equipment.....	98
6.2.4	Measurement procedure.....	98
6.2.5	Presentation of the results.....	100
6.3	Requirements.....	100
6.3.1	General.....	100
6.3.2	Field strength requirements.....	100
6.3.3	Quality of received signals.....	102
6.3.4	Safety.....	106
6.3.5	Electromagnetic compatibility (EMC).....	107
6.4	Interference reduction.....	107
6.4.1	General.....	107
6.4.2	Active antennas.....	107
7	Performance requirements at home network interfaces of cable networks.....	107
7.1	General.....	107
7.2	Requirements at HNI1 for passive coaxial home networks.....	108
7.2.1	General.....	108
7.2.2	Carrier levels at the HNI1.....	109
7.2.3	Mutual isolation between two HNI1.....	112
7.2.4	Frequency response within any television channel at HNI1.....	112
7.2.5	Long-term frequency stability of distributed carrier signals at HNI1.....	113
7.2.6	Random noise at the HNI1.....	113
7.2.7	Interference to television channels at HNI1.....	113
7.2.8	Return path requirements at HNI1.....	114
7.3	Requirements at HNI2 for active coaxial home networks.....	114
7.3.1	General.....	114

7.3.2	Carrier levels at the HNI2	114
7.3.3	Mutual isolation between two HNI2	117
7.3.4	Frequency response within any television channel at HNI2	117
7.3.5	Long-term frequency stability of distributed carrier signals at HNI2	117
7.3.6	Random noise at HNI2	118
7.3.7	Interference to television channels at the HNI2	121
7.3.8	Return path requirements at HNI2	122
7.4	Requirements at HNI3 and at system outlet or terminal input when the home network is mainly of balanced type	122
7.4.1	Overview	122
7.4.2	Requirements at HNI3	122
7.4.3	Requirements at system output	123
7.4.4	Additional requirements at HNI3 for upstream transmission	123
7.5	Requirements at HNI3 (Case C)	124
7.6	Requirements at HNI3 (Case D)	124
Annex A (informative) Reception of television signals		125
Annex B (normative) Calibration of modulation depth		130
B.1	Equipment required	130
B.2	Connection of the equipment	130
B.3	Calibration procedure	130
Annex C (normative) Equipment required – Additional items		131
C.1	Measuring receiver preamplifier	131
C.2	Measuring receiver input filter	131
Annex D (normative) Preliminary checks on the measuring equipment for carrier-to-noise ratio		132
D.1	Noise	132
D.2	Intermodulation	132
D.3	Overload	132
Annex E (normative) Correction factors		133
E.1	Level correction factor C_m	133
E.2	Bandwidth correction factor C_b	133
Annex F (normative) Calibration of the measuring receiver		134
Annex G (normative) Correction factors for noise		135
G.1	Signal level measurement	135
G.2	Noise level measurement	135
Annex H (normative) Null packet and PRBS definitions		137
H.1	Null packet definition	137
H.2	PRBS definition	138
Annex I (normative) Digital signal level and bandwidth		139
I.1	RF/IF power (carrier)	139
I.2	Bandwidth of a digital signal	139
I.2.1	Occupied bandwidth	139
I.2.2	Noise bandwidth	140
I.2.3	Equivalent signal bandwidth	140
I.3	Examples	141
Annex J (normative) Correction factor for a spectrum analyser		142
Annex K (informative) Differences in some countries		143

K.1	Subclause 3.1.58, Norway	143
K.2	Subclause 5.4.1, Japan, Netherlands	143
	K.2.1 Japan	143
	K.2.2 Netherlands	143
K.3	Subclause 5.4.2, Japan	143
K.4	Subclause 5.5.1, Japan	144
K.5	Subclause 5.6.1, Japan	145
K.6	Subclause 5.6.2, Netherlands	145
K.7	Subclause 5.7, Japan	146
K.8	Subclause 5.8, Japan	146
K.9	Subclause 5.9.1, Japan, Netherlands	147
	K.9.1 Japan	147
	K.9.2 Netherlands	148
K.10	Subclause 5.9.5, Japan	149
K.11	Subclause 5.10.2, Netherlands, Japan	149
	K.11.1 Netherlands	149
	K.11.2 Japan	149
K.12	Subclause 5.11, Japan	150
K.13	Subclause 5.12.1, Denmark	151
K.14	Subclause 5.13.1.5, Japan	151
K.15	Subclause 5.14.3, Netherlands	151
K.16	Clause 7, Japan	151
Bibliography		152
Figure 1 – Arrangement of test equipment for measurement of mutual isolation between system outlets		34
Figure 2 – Arrangement of test equipment for measurement of frequency response within a channel		36
Figure 3 – Interpretation of displays for measurement of frequency response within a channel		37
Figure 4 – Test signal (signal <i>F</i> for 625-line systems) employed for chrominance/luminance gain and delay inequality		38
Figure 5 – Test signal (signal <i>B2</i> for 625-line systems) employed for chrominance/luminance gain and delay inequality		38
Figure 6 – Arrangement of test equipment for measurement of chrominance/luminance gain and delay inequality		39
Figure 7 – Displayed pulses: chrominance low and lagging		40
Figure 8 – Displayed pulses: chrominance high and leading		40
Figure 9 – Connection of test equipment for the measurement of non-linear distortion by composite beat		42
Figure 10 – Weighting curve for 625-line system B, G and D1 (PAL): CW interference with no special (frequency offset) control		44
Figure 11 – Weighting curve for 625-line system I (PAL): CW interference with no special (frequency offset) control		44
Figure 12 – Weighting curve for 625-line systems D and K (PAL): CW interference with no special (frequency offset) control		45
Figure 13 – Weighting curve for 625-line system L (SECAM): CW interference with no special (frequency offset) control		45
Figure 14 – Hum modulation envelope		46

Figure 15 – Calibrated potential divider.....	47
Figure 16 – Stable variable DC source.....	47
Figure 17 – Connection of equipment for measurement of hum modulation (DC method).....	48
Figure 18 – Oscilloscope display.....	49
Figure 19 – Connection of equipment for hum modulation measurement (AC method).....	50
Figure 20 – Signal D2.....	52
Figure 21 – Example of the modified staircase waveform.....	53
Figure 22 – Arrangement of test equipment for measurement of differential gain and phase.....	54
Figure 23 – Arrangement of test equipment for carrier-to-noise ratio measurement.....	56
Figure 24 – Echo rating graticule.....	58
Figure 25 – Arrangement of test equipment for measurement of echo rating.....	59
Figure 26 – PSK modulation (QPSK, BPSK or TC8PSK).....	62
Figure 27 – DVB-S2 modulation (QPSK, 8PSK, 16APSK, 32APSK).....	62
Figure 28 – DVB-C QAM modulation.....	62
Figure 29 – DVB-T OFDM modulation.....	63
Figure 30 – DVB-T2 OFDM modulation.....	63
Figure 31 – Reference receiver for PSK demodulation (QPSK, BPSK or TC8PSK).....	63
Figure 32 – Reference receiver for DVB-S2 demodulation (QPSK, 8PSK, 16APSK, 32APSK).....	64
Figure 33 – Reference receiver for QAM demodulation.....	64
Figure 34 – Reference receiver for DVB-T OFDM demodulation.....	64
Figure 35 – Reference receiver (buffer model) for DVB-T2 OFDM demodulation.....	64
Figure 36 – Test set-up for BER measurement.....	69
Figure 37 – Test set-up for BER measurement versus E_b/N_0 or C/N and noise margin measurement.....	70
Figure 38 – Example of <i>BER</i> measurement versus E_b/N_0	72
Figure 39 – Example of <i>BER</i> measurement versus C/N	72
Figure 40 – Test set-up for modulation error ratio (MER) measurement and phase jitter measurement.....	75
Figure 41 – Example of constellation diagram for a 64 QAM modulation format.....	76
Figure 42 – Example of constellation diagram for a 64 QAM modulation format with arc sections due to phase jitter.....	78
Figure 43 – Test set-up for phase noise measurement.....	79
Figure 44 – Example of mask for phase noise measurements: PSK, APSK and QAM formats.....	81
Figure 45 – Example of mask for phase noise measurements: OFDM format.....	81
Figure 46 – Home network types used to define the requirements at HNI1 (coaxial).....	108
Figure A.1 – Example of a master antenna television system (MATV) for terrestrial reception.....	126
Figure A.2 – Example of the headend of a master antenna television system for satellite (SMATV) reception.....	127
Figure A.3 – Example of a master antenna television system for terrestrial and satellite (SMATV) reception.....	127
Figure A.4 – Example of a cabled distribution system for television and sound signals.....	128