

**INTERNATIONAL  
STANDARD**

**ISO/IEC  
14776-222**

First edition  
2005-02

---

---

**Information technology –  
Small computer system interface (SCSI) –  
Part 222:  
Fibre Channel Protocol for SCSI,  
Second Version (FCP-2)**



Reference number  
ISO/IEC 14776-222:2005(E)

This document is a preview generated by EVS

INTERNATIONAL  
STANDARD

ISO/IEC  
14776-222

First edition  
2005-02

This document is a preview generated by EVS

---

---

Information technology –  
Small computer system interface (SCSI) –  
Part 222:  
Fibre Channel Protocol for SCSI,  
Second Version (FCP-2)

© ISO/IEC 2005

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case postale 56 • CH-1211 Genève 20 • Switzerland

---

---



PRICE CODE XB

*For price, see current catalogue*

## CONTENTS

Foreword .....	11
Introduction .....	12
1 Scope .....	14
2 Normative references.....	14
2.1 International standards.....	14
2.2 International standards under development.....	14
2.3 Other references.....	14
3 Definitions, abbreviations and conventions .....	15
3.1 Definitions.....	15
3.2 Abbreviations.....	20
3.3 Keywords.....	21
3.4 Editorial conventions .....	22
4 General .....	24
4.1 Structure and concepts.....	24
4.2 Device management.....	25
4.3 Precise delivery of SCSI commands.....	27
4.4 Confirmed completion of FCP I/O Operations.....	28
4.5 Retransmission of unsuccessfully transmitted data .....	29
4.6 Task retry identification.....	29
4.7 Discovery of FCP capabilities.....	30
4.8 Task management.....	30
4.9 Clearing effects of task management, FCP, FC-FS, and FC-AL-2 actions.....	31
4.10 I_T nexus loss notification events.....	33
4.11 Transport Reset notification events.....	34
4.12 Port login/logout.....	34
4.13 Process login/logout.....	34
4.14 Link management.....	34
5 Fibre Channel protocol overview .....	35
5.1 FCP addressing and Exchange identification.....	35
5.2 SCSI third-party device identifier for the Fibre Channel protocol.....	35
5.3 Use of World Wide Names .....	35
5.4 FCP Information Units (IUs) .....	36
5.5 Fibre Channel protocol standard formats.....	37
5.6 FC-FS mappings to SCSI-3 functionality.....	38
5.6.1 FC-FS frame header.....	38
5.6.2 Frame header fields.....	38
5.6.2.1 R_CTL .....	38
5.6.2.2 D_ID.....	38
5.6.2.3 CS_CTL.....	38
5.6.2.4 S_ID.....	38
5.6.2.5 TYPE .....	38
5.6.2.6 F_CTL.....	39
5.6.2.7 SEQ_ID.....	39
5.6.2.8 DF_CTL .....	39
5.6.2.9 SEQ_CNT.....	39
5.6.2.10 OX_ID.....	39
5.6.2.11 RX_ID.....	39
5.6.2.12 PARAMETER.....	40

6	FCP basic and extended link service definitions .....	40
6.1	Overview of link service requirements .....	40
6.2	Overview of Process Login/Logout .....	40
6.3	Process Login (PRLI) .....	41
6.3.1	Use of Process Login by the Fibre Channel protocol .....	41
6.3.2	Process_Associator requirements .....	41
6.3.3	New or repeated PRLI .....	41
6.3.4	Process Login request FCP Service Parameter page format .....	42
6.3.5	Process Login accept FCP Service Parameter page format .....	45
6.4	Process Logout (PRLO) .....	46
6.5	Read Exchange Concise (REC) .....	46
7	FC-4 specific name server objects .....	47
7.1	Overview of FC-4 specific objects for the Fibre Channel protocol .....	47
7.2	FC-4 Features object .....	47
7.3	FC-4 Descriptor object .....	47
8	FC-4 Link Service definitions .....	48
8.1	FC-4 Link Services for the Fibre Channel protocol .....	48
8.2	Sequence Retransmission Request (SRR) .....	48
8.3	FCP FC-4 Link Service Reject .....	50
9	FCP Information Unit (IU) formats .....	52
9.1	FCP_CMND IU .....	52
9.1.1	FCP_CMND IU format .....	52
9.1.2	FCP_CMND IU Field descriptions .....	52
9.1.2.1	FCP_LUN .....	52
9.1.2.2	COMMAND REFERENCE NUMBER .....	53
9.1.2.3	TASK ATTRIBUTE .....	53
9.1.2.4	TASK MANAGEMENT FLAGS .....	53
9.1.2.5	ADDITIONAL FCP_CDB LENGTH .....	56
9.1.2.6	RDDATA .....	56
9.1.2.7	WRDATA .....	56
9.1.2.8	FCP_CDB .....	56
9.1.2.9	ADDITIONAL_FCP_CDB .....	56
9.1.2.10	FCP_DL .....	56
9.1.3	Additional mechanisms for performing task management functions - ABORT TASK .....	57
9.2	FCP_XFER_RDY IU .....	57
9.2.1	Overview and format of FCP_XFER_RDY IU .....	57
9.2.2	FCP_DATA_RO .....	57
9.2.3	FCP_BURST_LEN .....	58
9.3	FCP_DATA IU .....	58
9.4	FCP_RSP IU .....	59
9.4.1	Overview and format of FCP_RSP IU .....	59
9.4.2	FCP_CONF_REQ .....	60
9.4.3	FCP_RESID_UNDER .....	60
9.4.4	FCP_RESID_OVER .....	60
9.4.5	FCP_SNS_LEN_VALID .....	61
9.4.6	FCP_RSP_LEN_VALID .....	61
9.4.7	SCSI STATUS CODE .....	61
9.4.8	FCP_RESID .....	61
9.4.9	FCP_SNS_LEN .....	62
9.4.10	FCP_RSP_LEN .....	62
9.4.11	FCP_RSP_INFO .....	62
9.4.12	FCP_SNS_INFO .....	63
9.5	FCP_CONF IU .....	63

10	SCSI mode parameters for the Fibre Channel protocol .....	64
10.1	Overview of mode page codes for the Fibre Channel protocol .....	64
10.2	Disconnect-Reconnect mode page .....	64
10.2.1	Overview and format of Disconnect-Reconnect mode page for FCP .....	64
10.2.2	BUFFER FULL RATIO .....	65
10.2.3	BUFFER EMPTY RATIO .....	66
10.2.4	BUS INACTIVITY LIMIT .....	66
10.2.5	DISCONNECT TIME LIMIT .....	66
10.2.6	CONNECT TIME LIMIT .....	66
10.2.7	MAXIMUM BURST SIZE FIELD .....	66
10.2.8	ENABLE MODIFY DATA POINTERS (EMDP) .....	67
10.2.9	FAA, FAB, FAC .....	67
10.2.10	FIRST BURST SIZE .....	67
10.3	Fibre Channel Logical Unit Control mode page .....	68
10.4	Fibre Channel Port Control mode page .....	68
10.4.1	Overview and format of Fibre Channel Port Control mode page .....	68
10.4.2	DISABLE TARGET ORIGINATED LOOP INITIALIZATION (DTOLI) .....	69
10.4.3	DISABLE TARGET INITIATED PORT ENABLE (DTIPE) .....	69
10.4.4	ALLOW LOGIN WITHOUT LOOP INITIALIZATION (ALWLI) .....	69
10.4.5	REQUIRE HARD ADDRESS (RNA) .....	69
10.4.6	DISABLE LOOP MASTER (DLIM) .....	69
10.4.7	DISABLE DISCOVERY (DDIS) .....	70
10.4.8	PREVENT LOOP PORT BYPASS (PLPB) .....	70
10.4.9	DISABLE TARGET FABRIC DISCOVERY (DTFD) .....	70
10.4.10	RESOURCE RECOVERY TIME-OUT VALUE (RR_TOV) .....	70
11	Timers for FCP operation and recovery .....	72
11.1	Summary of timers for the Fibre Channel protocol .....	72
11.2	Error_Detect Time-out (E_D_TOV) .....	72
11.3	Resource Allocation Time-out (R_A_TOV) .....	73
11.4	Resource Recovery Timer (RR_TOV) .....	73
11.5	Read Exchange Concise Time-out Value (REC_TOV) .....	74
11.6	Upper Level Protocol Time-out (ULP_TOV) .....	74
12	Link error recovery procedure .....	75
12.1	Overview .....	75
12.1.1	Exchange level error recovery .....	75
12.1.2	Sequence level error recovery .....	75
12.2	FCP Error Detection .....	75
12.2.1	Overview of FCP-2 Error Detection .....	75
12.2.2	FCP-2 Error Detection using protocol errors for all classes of service .....	75
12.2.3	Error Detection mechanisms for acknowledged classes of Service .....	76
12.3	Exchange level recovery using recovery abort .....	77
12.3.1	Recovery abort requirements .....	77
12.3.2	Initiator invocation of recovery abort .....	77
12.3.3	Target response to recovery abort .....	77
12.3.4	Additional error recovery by initiator .....	78
12.3.5	Additional error recovery by target .....	78

This document is a preview generated by EVSS

12.4	Sequence level error detection and recovery .....	78
12.4.1	Using information from REC to perform Sequence level recovery.....	78
12.4.1.1	Polling Exchange state with REC.....	78
12.4.1.2	Detection of errors while polling with REC .....	79
12.4.1.3	FCP_CMND IU Recovery using information from REC .....	79
12.4.1.4	FCP_XFER_RDY IU Recovery .....	79
12.4.1.5	FCP_RSP IU Recovery .....	79
12.4.1.6	FCP_DATA IU Recovery – Write .....	81
12.4.1.7	FCP_DATA IU Recovery – Read .....	81
12.4.1.8	FCP_CONF IU Recovery .....	81
12.4.2	Additional error recovery requirements .....	82
12.4.2.1	Error indicated in ACK.....	82
12.4.2.2	Missing ACK.....	82
12.4.2.3	Distinguishing exchange to be aborted.....	82
12.5	Second-level error recovery .....	83
12.5.1	ABTS .....	83
12.5.2	REC .....	83
12.5.3	SRR.....	83
12.6	Responses to FCP type frames before PLOGI or PRLI.....	83

This document is a preview generated by EVS

Annex A (normative) FCP mapping to SAM-2 (Fibre Channel Protocol Service mapping to SCSI Architectural Model (SAM-2)).....	84
A.1 Definition of procedure terms .....	84
A.2 Notation for procedures and functions .....	85
A.3 Application client SCSI command services .....	86
A.4 Send SCSI command service.....	86
A.5 Data Transfer Protocol Services .....	87
A.5.1 Overview of data buffer movement services .....	87
A.5.2 Data-in delivery service .....	87
A.5.3 Data-out delivery service .....	87
A.6 Task management services.....	87
Annex B (informative) FCP examples .....	88
B.1 Examples of the use of FCP Information Units (IUs) .....	88
B.1.1 Overview of examples .....	88
B.1.2 SCSI FCP read operation.....	88
B.1.3 SCSI FCP write operation .....	89
B.1.4 SCSI FCP operation with no data transfer or with check condition.....	89
B.1.5 SCSI FCP read operation with multiple FCP_DATA IUs .....	90
B.1.6 SCSI FCP write operation with FCP_XFR_RDY disabled .....	90
B.1.7 SCSI linked commands .....	91
B.1.8 SCSI WRITE command with confirmed completion.....	91
B.1.9 SCSI FCP task management function .....	92
B.2 FCP write example, frame level .....	93
B.3 FCP read example, frame level.....	95
Annex C (informative) Error detection and recovery action examples.....	97
Annex D (informative) FCP-2 examples of link service usage.....	131
D.1 Formats for recovery link services.....	131
D.2 Abort Sequence (ABTS) Request .....	131
D.2.1 Abort Sequence (ABTS) Request fields.....	131
D.2.2 Basic Accept (BA_ACC) Frame to ABTS.....	132
D.2.3 Basic Reject (BA_RJT) Frame to ABTS.....	132
D.3 Reinstate Recovery Qualifier (RRQ) .....	133
Annex E (informative) Bidirectional operation support.....	134
E.1 Introduction.....	134
E.2 Changes in the FCP device management model.....	134
E.2.1 Support of bidirectional operation.....	134
E.2.2 Relationship between bidirectional and unidirectional operation .....	134
E.3 FCP_CMND IU changes .....	135
E.3.1 FCP_CMND IU payload .....	135
E.3.2 TASK MANAGEMENT FLAGS .....	135
E.3.3 RDDATA and WRDATA .....	136
E.3.4 FCP_DL.....	136
E.3.5 FCP_BIDIRECTIONAL_READ_DL .....	136
E.4 FCP_DATA IU changes.....	136
E.5 FCP_RSP IU changes.....	137
E.5.1 FCP_RSP IU payload.....	137
E.5.2 FCP_BIDI_RSP.....	137
E.5.3 FCP_BIDI_READ_RESID_UNDER .....	137
E.5.4 FCP_BIDI_READ_RESID_OVER.....	138
E.5.5 FCP_RESID .....	138
E.5.6 FCP_BIDIRECTIONAL_READ_RESID.....	138

E.6	Error recovery changes .....	139
E.6.1	Overview .....	139
E.6.2	Sequence level error recovery.....	139
E.6.3	FCP-2 Error Detection using protocol errors for all classes of service.....	139
E.7	FCP Example .....	139
E.7.1	Overview .....	139
E.7.2	SCSI FCP bidirectional command with write before read .....	141
E.7.3	SCSI FCP bidirectional command with read before write .....	141
E.7.4	SCSI FCP bidirectional command, write first, write FCP_XFER_RDY disabled.....	142
E.7.5	SCSI FCP bidirectional command with intermixed writes and reads .....	143
Annex F	(informative) FCP Device Discovery Procedure .....	144
F.1	FCP Device Discovery Procedure .....	144
F.1.1	Initiator discovery of Fabric-attached targets .....	144
F.1.2	Initiator discovery of loop-attached targets.....	144
F.2	Fabric and Device Authentication.....	145
F.3	Logical unit authentication .....	145
Bibliography	.....	146

This document is a preview generated by EVS

Table 1 – SCSI and Fibre Channel protocol functions .....	25
Table 2 – Discovery of FCP–2 capabilities .....	30
Table 3 – Task management functions, SAM–2 to FCP .....	31
Table 4 – Clearing effects of link related functions .....	32
Table 5 – Clearing effects of initiator actions .....	33
Table 6 – FCP third–party device id format .....	35
Table 7 – FCP Information Units (IUs) sent to targets .....	36
Table 8 – FCP Information Units (IUs) sent to initiators .....	37
Table 9 – FCP frame header .....	38
Table 10 – FCP Service Parameter page, PRLI request .....	42
Table 11 – FCP Service Parameter page, PRLI accept .....	45
Table 12 – FCP definition of FC–4 Feature bits .....	47
Table 13 – FCP FC–4 Link Service Requests and Responses for FCP–2 .....	48
Table 14 – SRR Payload .....	49
Table 15 – SRR Accept Payload .....	49
Table 16 – FCP FC–4 Link Service Reject (FCP_RJT) Payload .....	50
Table 17 – FCP FC–4 Link Service Reject reason codes .....	50
Table 18 – FCP FC–4 Link Service Reject reason code explanation .....	51
Table 19 – FCP_CMND IU Payload .....	52
Table 20 – TASK ATTRIBUTE field values .....	53
Table 21 – task management Flags .....	54
Table 22 – FCP_XFER_RDY IU payload .....	57
Table 23 – FCP_RSP IU Payload .....	60
Table 24 – FCP_RSP_INFO field format .....	62
Table 25 – RSP_CODE definitions .....	63
Table 26 – Mode page codes for FCP .....	64
Table 27 – Disconnect–reconnect page (02h) .....	65
Table 28 – Fibre Channel Logical Unit Control page (18h) .....	68
Table 29 – Fibre Channel Port Control page (19h) .....	69
Table 30 – Values for RR_TOV UNITS .....	71
Table 31 – Timer summary .....	72
Table 32 – Initiator REC_TOV Usage .....	74
Table 33 – Target REC_TOV usage .....	74
Table A.1 – FCP procedure terms mapped to terms from SAM–2 standard .....	84
Table A.2 – Procedure Terms .....	85
Table A.3 – Processing of send SCSI command service procedure .....	86
Table A.4 – Processing of data–in delivery service procedure .....	87
Table A.5 – Processing of data–out delivery service procedure .....	87
Table B.1 – FCP read operation, example .....	88
Table B.2 – FCP write operation, example .....	89
Table B.3 – FCP operation without data transfer, example .....	89
Table B.4 – FCP read operation, example .....	90
Table B.5 – FCP write operation with FCP_XFER_RDY disabled, example .....	90
Table B.6 – FCP linked commands, example .....	91
Table B.7 – FCP write command with confirmed completion .....	91
Table B.8 – FCP task management function, example .....	93
Table C.1 – Diagram Drawing conventions .....	97
Table D.1 – ABTS Frame .....	131
Table D.2 – BA_ACC Frame to ABTS .....	132
Table D.3 – BA_RJT Frame to ABTS .....	132
Table D.4 – Reinstate Recovery Qualifier .....	133
Table E.1 – FCP_CMND payload for a bidirectional command .....	135
Table E.2 – FCP_RSP IU Payload .....	137
Table E.3 – FCP bidirectional command with write before read, example .....	140
Table E.4 – FCP bidirectional command with read before write, example .....	141
Table E.5 – FCP bidirectional command, write FCP_XFER_RDY disabled, example .....	142
Table E.6 – FCP bidirectional command with intermixed writes and reads, example .....	143

Figure B.1 – Example of class 2 FCP write I/O operation.....	93
Figure B.2 – Example of class 2 FCP_DATA write .....	94
Figure B.3 – Example of class 2 FCP read I/O operation .....	95
Figure B.4 – Example of class 2 FCP_DATA read .....	96
Figure C.1 – Lengthy FCP_CMND or Lost ACK .....	98
Figure C.2 – FCP_CMND Lost, Unacknowledged Classes .....	99
Figure C.3 – FCP_CMND Lost, Acknowledged Classes .....	100
Figure C.4 – FCP_CMND Acknowledgement Lost, Acknowledged Classes.....	101
Figure C.5 – FCP_XFER_RDY Lost, Unacknowledged Classes.....	102
Figure C.6 – FCP_XFER_RDY Lost, Acknowledged Classes.....	103
Figure C.7 – FCP_XFER_RDY Received, ACK Lost, Acknowledged Classes .....	104
Figure C.8 – FCP_RSP Lost, FCP_CONF not requested, Unacknowledged Classes.....	105
Figure C.9 – FCP_RSP Lost, FCP_CONF not requested, Acknowledged Classes .....	106
Figure C.10 – FCP_RSP Lost Read Command, no FCP_CONF, Acknowledged Classes.....	107
Figure C.11 – FCP_RSP Received, ACK Lost, Acknowledged Classes, Example 1 .....	108
Figure C.12 – FCP_RSP Received, ACK Lost, Acknowledged Classes, Example 2.....	109
Figure C.13 – Lost Write Data, Last Frame of Sequence, Unacknowledged Classes .....	110
Figure C.14 – Lost Write Data, Last Frame of Sequence, Acknowledged Classes.....	111
Figure C.15 – Lost Write Data, Not Last Frame of Sequence, Unacknowledged Classes.....	112
Figure C.16 – Lost Write Data, Not Last Frame of Sequence, Acknowledged Classes.....	113
Figure C.17 – Lost Read Data, Last Frame of Sequence, Unacknowledged Classes .....	114
Figure C.18 – Lost Read Data, Last Frame of Sequence, Acknowledged Classes .....	115
Figure C.19 – Lost Read Data, Not Last Frame of Sequence, Unacknowledged Classes .....	116
Figure C.20 – Lost Read Data, Not Last Frame of Sequence, Acknowledged Classes.....	117
Figure C.21 – ACK Lost on Read (Acknowledged Classes).....	118
Figure C.22 – ACK Lost on Write (Acknowledged Classes).....	119
Figure C.23 – FCP_CONF Lost, Unacknowledged Classes.....	120
Figure C.24 – FCP_CONF Lost, Acknowledged Classes.....	121
Figure C.25 – ACK lost on FCP_CONF, Acknowledged Classes.....	122
Figure C.26 – REC or REC Response Lost, Unacknowledged Classes .....	123
Figure C.27 – REC Lost, Acknowledged Classes.....	124
Figure C.28 – REC Response Lost, Acknowledged Classes .....	125
Figure C.29 – Two RECs Lost, Unacknowledged Classes, Abort the original Exchange .....	126
Figure C.30 – SRR Lost, Unacknowledged Classes, Abort original Exchange .....	127
Figure C.31 – SRR Response Lost, Unacknowledged Classes.....	128
Figure C.32 – SRR Lost, Acknowledged Classes.....	129
Figure C.33 – SRR Response Lost, Acknowledged Classes .....	130

This document is a preview generated by EVS

**INFORMATION TECHNOLOGY –  
SMALL COMPUTER SYSTEM INTERFACE –  
PART 222: Fibre Channel Protocol for SCSI,  
Second Version (FCP-2)**

**FOREWORD**

- 1) ISO (International Organization for Standardization) and IEC (International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.
- 2) In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.
- 3) All users should ensure that they have the latest edition of this publication.
- 4) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC or ISO National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication or use of, or reliance upon this ISO/IEC publication or any other IEC or ISO publications.
- 5) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 6) Attention is drawn to the possibility that some of the elements of this ISO/IEC Publication may be the subject of patent rights. ISO/IEC shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 14776-222 was prepared by subcommittee 25: Inter-connection of information technology equipment, of ISO/IEC joint technical committee 1: Information technology.

## INTRODUCTION

This International Standard defines a Fibre Channel mapping layer (FC-4) that uses the services defined by NCITS Project 1311D, Fibre Channel Framing and Signaling Interface (FC-FS) to transmit SCSI command, data and status information between a SCSI initiator and a SCSI target. The use of this standard enables the transmission of standard SCSI command formats, the transmission of standard SCSI data and parameter strings, and the receipt of SCSI status and sense information across the Fibre Channel using only the standard Fibre Channel frame and sequence formats. The Fibre Channel protocol operates with Fibre Channel Classes of Service 1, 2 and 3 and operates across Fibre Channel fabrics and arbitrated loops.

The Small Computer System Interface (SCSI) command set is widely used and applicable to a wide variety of device types. The transmission of SCSI command set information across Fibre Channel links allows the large body of SCSI application and driver software to be successfully used in the high performance Fibre Channel environment.

This standard describes the protocol for transmitting SCSI commands, data, and status using Fibre Channel FC-FS Exchanges and Information Units. Fibre Channel is a high speed serial architecture that allows either optical or electrical connections at data rates from 265 Mbits up to 4 Gbits per second. The topologies supported by Fibre Channel include point-to-point, fabric switched and arbitrated loop. All Fibre Channel connections use the same standard frame format and standard hierarchy of transmission units to transmit the Information Units that carry SCSI information.

This standard is divided into 12 clauses and comprises 6 Annexes:

Clause	Subject
1	Scope
2	Normative references
3	Definitions, abbreviations and conventions
4	Overview of the protocol for transmitting SCSI information over Fibre Channel
5	Information Units used to transfer SCSI commands, data and status across a Fibre Channel connection
6	Basic Link Services and Extended Link Services used by the protocol for transmitting SCSI information over Fibre Channel
7	FC-GS-3 Name Server objects defined for FCP-2
8	FCP FC-4 Link Service definitions for the protocol for transmitting SCSI information over Fibre Channel
9	Details of the Information Unit formats
10	SCSI management features for Fibre Channel, including the SCSI mode pages used by the protocol for transmitting SCSI information over Fibre Channel
11	Timers used for FCP-2 error recovery algorithms
12	Error recovery algorithms for FCP-2
Annex A	Relationship between the services defined by SAM-2 and the corresponding functions defined by this standard
Annex B	Examples of the protocol for transmitting SCSI information over Fibre Channel
Annex C	Examples of the FCP-2 error recovery mechanisms
Annex D	Techniques for discovering SCSI device capabilities over Fibre Channel
Annex E	Examples of the content of ELs used during FCP-2 recovery operations
Annex F	Mechanism to support bidirectional SCSI data transfer using SCSI commands

Fibre channel Protocol-2 (FCP-2) is part of the SCSI family of standards developed by T10 to facilitate the use of the SCSI command sets for many different types of devices across many different types of physical interconnects. The architectural model for the family of standards is ISO/IEC 14776-412, Information technology – SCSI Architecture Model-2 (SAM-2).

This document is a preview generated by EVS

**INFORMATION TECHNOLOGY –  
SMALL COMPUTER SYSTEM INTERFACE –  
PART 222: Fibre Channel Protocol for SCSI,  
Second Version (FCP-2)**

## 1 Scope

This part of ISO/IEC 14776 defines a second version of the SCSI Fibre Channel Protocol (FCP). This part of ISO/IEC 14776 is a mapping protocol for applying the SCSI command set to Fibre Channel. It defines how the Fibre Channel services and the defined Information Units (IUs) are used to perform the services defined by the SCSI-3 Architecture Model – 2 (SAM-2). This second version includes additions and clarifications to the first version, removes information that is now contained in other standards, and describes additional error recovery capabilities for the Fibre Channel protocol.

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

### 2.1 International standards

ISO/IEC 14165-122, Information technology – Fibre Channel – Part 122: Arbitrated loop-2 (FC-AL-2)<sup>1</sup>

ISO/IEC 14776-412, Information technology – Small Computer System Interface (SCSI) – Part 412: Architecture Model-2 (SAM-2)<sup>1</sup>

ISO/IEC 14776-452, Information technology – Small Computer System Interface (SCSI) – Part 452: Primary commands-2 (SPC-2)<sup>1</sup>

### 2.2 International Standards under development

ISO/IEC 14776-221, Information technology – Small Computer System Interface (SCSI) – Part 221: Protocol for SCSI (FCP)

ISO/IEC 14776-312, Information technology – Small Computer System Interface (SCSI) – Part 312: Primary commands-2 (SPC-2)

### 2.3 Other references

NOTE Copies of NCITS Technical Reports are available for purchase from Global Engineering Documents. For further information, contact Global Engineering Documents at ++1 800-854-7179 (telephone) or ++1 303-792-2181 (telephone) or by mail at 15 Inverness Way East, Englewood, CO 80122-5704, USA.

NCITS TR-19:1998, Fibre Channel Private Loop, SCSI Direct Attach (FC-PLDA) (Technical Report)

NCITS TR-20:1998, Fibre Channel Fabric Loop Attachment (FC-FLA) (Technical Report)

NCITS TR-24:1999, Fibre Channel – Tape Technical Report (FC-TAPE)

---

<sup>1</sup> To be published.