## TECHNICAL SPECIFICATION

First edition 2007-03-15

### Geosynthetics — Procedure for simulating damage under interlockingconcrete-block pavement by the roller compactor method

Géosynthétiques — Mode opératoire pour simuler l'endommagement sous un revêtement en pavés béton autobloquants par la méthode du compacteur à rouleau



Reference number ISO/TS 19708:2007(E)

#### PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below

The service of the se

© ISO 2007

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org Published in Switzerland

#### Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

In other circumstances, particularly when there is an urgent market requirement for such documents, a technical committee may decide to oblish other types of normative document:

- an ISO Publicly Available Specification (ISO/PAS) represents an agreement between technical experts in an ISO working group and is accepted for publication if it is approved by more than 50 % of the members of the parent committee casting a vote
- an ISO Technical Specification (ISO/TS) expresents an agreement between the members of a technical committee and is accepted for publication if the approved by 2/3 of the members of the committee casting a vote.

An ISO/PAS or ISO/TS is reviewed after three years in order to decide whether it will be confirmed for a further three years, revised to become an International Standard, or withdrawn. If the ISO/PAS or ISO/TS is confirmed, it is reviewed again after a further three years at which time it must either be transformed into an International Standard or be withdrawn.

Attention is drawn to the possibility that some of the elements on this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

DY FLYS

ISO/TS 19708 was prepared by Technical Committee ISO/TC 221, Cocynthetics.

this document is a preview denerated by EUS

# Geosynthetics — Procedure for simulating damage under interlocking-concrete-block pavement by the roller compactor method

#### 1 Scope

This Technical Specification specifies a test method for the determination, using a roller compactor for bituminous mixtures, of the damage to a geosynthetic used as a separator in interlocking-concrete-block pavements. The geosynthetic is placed between a cushion-sand course and a base coarse material. The roller compactor simulates highway traffic load and pedestrian load. After the roller compactor test, the cushion sand retained is determined.

This Technical Specification can be used for selecting a geosynthetic.

#### 2 Normative references

The following referenced documents are indepensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 554, Standard atmospheres for conditioning and ortesting — Specifications

ISO 9862, Geosynthetics — Sampling and preparation of test specimens

ISO 3310-1, Test sieves — Technical requirements and testing — Part 1: Test sieves of metal wire cloth

ISO 7619-1, Rubber, vulcanized or thermoplastic — Determination of indentation hardness — Part 1: Durometer method (Shore hardness)

ISO 7619-2, Rubber, vulcanized or thermoplastic — Determination of indentation hardness — Part 2: IRHD pocket meter method

EN 1097-2, Tests for mechanical and physical properties of aggregates — Part 2: Methods for the determination of resistance to fragmentation

EN 12697-33, Bituminous mixtures — Test methods for hot mix asphalt — Part 33, Specimen prepared by roller compactor

#### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply:

#### 3.1

#### line pressure

pressure defined as the value of total loading force over a part of roller width contacting the surface of an interlocking-concrete-block pavement area