

**Allmaa kaevandamise masinad.
Ohutusnõuded liikuvatele eest
väljatõmbamismasinadele,
sahklaaduritele ja saahksüsteemidele**

Underground mining machines - Mobile extracting machines at the face - Safety requirements for shearer loaders and plough systems

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

<p>Käesolev Eesti standard EVS-EN 1552:2003 sisaldab Euroopa standardi EN 1552:2003 ingliskeelset teksti.</p> <p>Käesolev dokument on jõustatud 16.05.2003 ja selle kohta on avaldatud teade Eesti standardiorganisatsiooni ametlikus väljaandes.</p> <p>Standard on kättesaadav Eesti standardiorganisatsioonist.</p>	<p>This Estonian standard EVS-EN 1552:2003 consists of the English text of the European standard EN 1552:2003.</p> <p>This document is endorsed on 16.05.2003 with the notification being published in the official publication of the Estonian national standardisation organisation.</p> <p>The standard is available from Estonian standardisation organisation.</p>
------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

<p>Käsitlusala:</p> <p>This European Standard specifies safety requirements which shall be met to minimize the hazards listed in clause 4 that may occur during the assembly, use, maintenance, repair, decommissioning, disassembly and disposal of shearer loaders and plough systems when operated in accordance with the manufacturer's requirements in underground mining</p>	<p>Scope:</p> <p>This European Standard specifies safety requirements which shall be met to minimize the hazards listed in clause 4 that may occur during the assembly, use, maintenance, repair, decommissioning, disassembly and disposal of shearer loaders and plough systems when operated in accordance with the manufacturer's requirements in underground mining</p>
-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

ICS 73.100.30

Võtmesõnad:

ICS 73.100.30

English version

Underground mining machines - Mobile extracting machines at the face - Safety requirements for shearer loaders and plough systems

Machines d'exploitation de mines et carrières souterraines -
Machines mobiles d'abattage de front de taille - Exigences
de sécurité imposées aux haveuses à tambour(s) et aux
robots

Bergbaumaschinen unter Tage - Mobile Abbaumaschinen im
Streb - Sicherheitsanforderungen für Walzenlader und
Hobelanlagen

This European Standard was approved by CEN on 14 February 2003.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Luxembourg, Malta, Netherlands, Norway, Portugal, Slovakia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Contents

	page
Foreword	3
Introduction	4
1 Scope	4
2 Normative references	4
3 Terms and definitions	5
4 List of significant hazards	6
5 Safety requirements/protective measures	8
5.1 General	8
5.2 Stability	8
5.3 Control devices	10
5.4 Starting	10
5.5 Start-up warning devices	10
5.6 Stopping	10
5.6.1 Stopping in normal operation	10
5.6.2 Stopping at the end of the working range	10
5.6.3 Stopping in an emergency	11
5.7 Measures to prevent inadvertent movements	11
5.8 Hydraulic equipment	11
5.9 Pipes and hoses	12
5.10 Fire protection	12
5.11 Other hazard points	12
5.12 Load attachment points	12
5.13 Maintenance and repair	13
6 Verification of the safety requirements	13
7 User information	14
7.1 Warning notices	14
7.2 Accompanying documents	14
7.2.1 General	14
7.2.2 Information on transportation, handling and storage	14
7.2.3 Information on assembly and commissioning	14
7.2.4 Information on the machine	14
7.2.5 Information on use	15
7.2.6 Information on maintenance and repairs	15
7.2.7 Information on decommissioning, dismantling and disposal	16
7.2.8 Information for emergencies	16
7.3 Marking	16
Annex ZA (informative) Relationship of this European Standard with EU Directives	17
Bibliography	18

Foreword

This document (EN 1552:2003) has been prepared by Technical Committee CEN/TC 196, "Machines for underground mines - Safety", the secretariat of which is held by BSI.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by October 2003, and conflicting national standards shall be withdrawn at the latest by October 2003.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s).

For relationship with EC Directive(s), see informative annex ZA, which is an integral part of this document.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Luxembourg, Malta, Netherlands, Norway, Portugal, Slovakia, Spain, Sweden, Switzerland and the United Kingdom.

Introduction

This European Standard is a type C standard as stated in EN 1070.

The machinery and the extend to which hazards, hazardous situations and events are covered are indicated in the scope of this document

When provisions of this type C standard are different from those which are stated in type A or B standards, the provisions of this type C standard take precedence over the provisions of the other standards, for machines that have been designed and built according to the provisions of this type C standard.

1 Scope

1.1 This European Standard specifies safety requirements which shall be met to minimize the hazards listed in clause 4 that may occur during the assembly, use, maintenance, repair, decommissioning, disassembly and disposal of shearer loaders and plough systems when operated in accordance with the manufacturer's requirements in underground mining.

The machines work with tools for cutting minerals such as coal, ore, salt and surrounding rock, at a fixed or variable height and are guided on armoured face conveyors or their attachments. Shearer loaders have built-in haulage systems. They may be directly operated by one or more drivers or be remotely or program controlled. Plough systems are remotely controlled. Wireless remote control systems of shearer loaders are used in the immediate environment of the machines.

1.2 This European Standard does not cover any hazards resulting from the electrical equipment associated with the machine. It does not contain any requirements relating to dust suppression or firedamp hazards. Hazards due to noise are also excluded from this standard, but a separate standard is in preparation where hazards due to noise will be addressed.

NOTE Only a small amount of the noise emitted at the point of use of shearer loaders and plough systems is generated by the machines themselves. The noise level is affected more by the breaking mineral and the conveyors. Dust is generated not only by the mode of operation of the machines, but also by the material to be extracted, the environment, the roof support and the conveyor. For example, equipping the machine with a water spray may not completely eliminate the hazard on its own.

It does not cover face conveyors, spill plates and auxiliary devices such as lasers etc.

It is intended for manufacturers producing and marketing complete machines, and for manufacturers assembling machines or parts of machines from different origins or assembling machines for their own use. These are called "manufacturers" in this European Standard.

1.3 This document is not applicable to machines that are manufactured before the date of publication of this European Standard by CEN.

2 Normative references

This European Standard incorporates by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this European Standard only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies (including amendments).

EN 292-1:1991, *Safety of machinery – Basic concepts, general principles for design - Part 1: Basic terminology, methodology*

EN 292-2:1991, *Safety of machinery – Basic concepts, general principles for design – Part 2: Technical principles and specifications*

EN 457:1992, *Safety of machinery – Auditory danger signals – General requirements, design and testing (ISO 7731:1986, modified)*

EN 563, *Safety of machinery – Temperatures of touchable surfaces – Ergonomics data to establish temperature limit values for hot surfaces*

EN 853, *Rubber hoses and hose assemblies – Wire braid reinforced hydraulic type – Specification*

EN 857, *Rubber hoses and hose assemblies – Wire braid reinforced compact type for hydraulic applications – Specification*

EN 894-1, *Safety of machinery – Ergonomics requirements for the design of displays and control actuators – Part 1: General principles for human interactions with displays and control actuators*

EN 953, *Safety of machinery – General requirements for the design and construction of fixed and movable guards*

EN 954-1:1996, *Safety of machinery – Safety related parts of control systems – Part 1: General principles for design*

EN 982:1996, *Safety of machinery – Safety requirements for fluid power systems and components – Hydraulics*

EN 1050:1996, *Safety of machinery - Principles for risk assessment*

EN 1070, *Safety of machinery – Terminology*

EN 61310-1, *Safety of machinery – Indications, marking and actuation – Part 1: Requirements for visual, auditory and tactile signals (IEC 61310-1:1995)*

3 Terms and definitions

For the purposes of this European Standard, the following terms and definitions apply.

3.1

remote control console

plough systems are generally controlled from a fixed remote control console. It is situated either on the surface or underground and is usually out of the line of sight of the plough system.

3.2

load attachment point

means of attachment for devices to enable them to carry a load, e.g. a threaded hole for a transport ring.

3.3

transport units

parts or subassemblies which, for transportation reasons, are not fitted to the complete machine until the point of use.

3.4

starting

energizing the machine drive or first of the drives without necessarily causing the machine to move. For example, a shearer loader is started up when the hydraulic pump drive is switched on but externally the machine has clearly not yet moved.