
**Sampling procedures for inspection by
attributes —**

Part 5:

**System of sequential sampling plans
indexed by acceptance quality limit (AQL)
for lot-by-lot inspection**

Règles d'échantillonnage pour les contrôles par attributs —

*Partie 5: Système de plans d'échantillonnage progressif pour le contrôle
lot par lot, indexés d'après la limite d'acceptation de qualité (LAQ)*



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

This document is a preview generated by EVS

© ISO 2005

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	iv
Introduction	v
1 Scope	1
2 Normative references	2
3 Terms and definitions.....	2
4 Symbols and abbreviated terms	9
5 Expression of nonconformity.....	10
6 Acceptance quality limit (AQL).....	10
7 Submission of product for sampling	11
8 Acceptance and non-acceptance.....	11
9 Drawing of samples	12
10 Normal, tightened and reduced inspection.....	12
11 Sampling plans	14
12 Determination of acceptability	21
13 Further information.....	21
14 Tables.....	22
Annex A (normative) Sampling plans for normal inspection	23
Annex B (normative) Sampling plans for tightened inspection	27
Annex C (normative) Sampling plans for reduced inspection	31
Annex D (informative) Average sample numbers for sequential sampling plans	35
Bibliography	43

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 2859-5 was prepared by Technical Committee ISO/TC 69, *Applications of statistical methods*, Subcommittee SC 5, *Acceptance sampling*.

This first edition cancels and replaces Annex A of ISO 8422:1991, which has been technically revised to greatly improve its compatibility with the sampling systems in ISO 2859-1.

ISO 2859 consists of the following parts, under the general title *Sampling procedures for inspection by attributes*:

- *Part 1: Sampling schemes indexed by acceptance quality limit (AQL) for lot-by-lot inspection*
- *Part 2: Sampling plans indexed by limiting quality (LQ) for isolated lot inspection*
- *Part 3: Skip-lot sampling procedures*
- *Part 4: Procedures for assessment of declared quality levels*
- *Part 5: System of sequential sampling plans indexed by acceptance quality limit (AQL) for lot-by-lot inspection*
- *Part 10: Overview of the ISO 2859 attribute sampling systems*

Introduction

In contemporary production processes quality is often expected to reach such high levels that the number of nonconforming items is reported in parts per million (10^{-6}). Under such circumstances, popular acceptance sampling plans, such as those presented in ISO 2859-1, require prohibitively large sample sizes. To overcome this problem, users apply acceptance sampling plans with higher probabilities of wrong decisions or, in extreme situations, abandon the use of acceptance sampling procedures altogether. However, in many situations there is still a need to accept products of high quality using standardized statistical methods. In such cases, there is a need to apply statistical procedures that require the smallest possible sample sizes. Sequential sampling plans are the only statistical procedures that satisfy that need as, among all possible sampling plans having similar statistical properties, the sequential sampling plan has the smallest average sample number. Therefore there is a strong need to present sequential sampling plans which are statistically equivalent to the commonly used acceptance sampling plans from ISO 2859-1, but which require significantly smaller average sample numbers.

The principal advantage of sequential sampling plans is the reduction in the average sample number. The average sample number is the weighted average of all the sample sizes that may occur under a sampling plan for a given lot or process quality level. Like double and multiple sampling plans, the use of sequential sampling plans leads to a smaller average sample number than single sampling plans having the equivalent operating characteristics. However, the average savings are even greater when using a sequential sampling plan than when a double or multiple sampling plan is used. For lots of very good quality, the maximum savings for sequential sampling plans may reach 85 % as compared to 37 % for double sampling plans and 75 % for multiple sampling plans. On the other hand, when using a double, multiple or sequential sampling plan, the actual number of items inspected for a particular lot may exceed the sample size of the corresponding single sampling plan n_0 . For double and multiple sampling plans, there is an upper limit of $1,25 n_0$ to the actual number of items to be inspected. For classical sequential sampling plans there is no such limit, and the actual number of inspected items may considerably exceed the corresponding single sample size, n_0 , or even the lot size, N . For the sequential sampling plans in this part of ISO 2859, a curtailment rule has been introduced involving an upper limit of $1,5 n_0$ on the actual number of items to be inspected.

Other factors that should be taken into account include the following.

a) Simplicity

The rules of a sequential sampling plan are more easily misunderstood by inspectors than the simple rules for a single sampling plan.

b) Variability in the amount of inspection

As the actual number of items inspected for a particular lot is not known in advance, the use of sequential sampling plans brings about various organisational difficulties. For example, scheduling of inspection operations may be difficult.

c) Ease of drawing sample items

If drawing sample items is expensive at different times, the reduction in the average sample number by sequential sampling plans may be cancelled out by the increased sampling cost.

d) Duration of test

If the test of a single item is of long duration and a number of items can be tested simultaneously, sequential sampling plans are much more time-consuming than the corresponding single sampling plans.

e) Variability of quality within the lot

If the lot consists of two or more sublots from different sources and if there is likely to be any substantial difference between the qualities of the sublots, drawing of a representative sample under a sequential sampling plan is far more awkward than under the corresponding single sampling plan.

The advantages and disadvantages of double and multiple sampling plans always lie between those of single and sequential sampling plans. The balance between the advantage of a smaller average sample number and the above disadvantages leads to the conclusion that sequential sampling plans are suitable only when inspection of individual items is costly in comparison with inspection overheads.

The choice between the use of a single, double, multiple, or sequential sampling plan shall be made before the inspection of a lot is started. During the inspection of a lot, it is not permitted to switch from one type of plan to another, because the operating characteristics of the plan may be drastically changed if the actual inspection results influence the choice of acceptability criteria.

Although use of sequential sampling plans is on average much more economical than the use of corresponding single sampling plans, during inspection of a particular lot, acceptance or non-acceptance may occur at a very late stage due to the cumulative count of nonconforming items (or nonconformities) remaining between the acceptance number and the rejection number for a long time. When using the graphical method, this corresponds to the random progress of the step curve remaining in the indecision zone. Such a situation is most likely to occur when the lot or process quality level (in terms of percent nonconforming or in nonconformities per 100 items) is close to $(100/g)$, where g is the parameter giving the slope of the acceptance and rejection lines.

To improve upon this situation the sample size curtailment value is set before the inspection of a lot begins. If the cumulative sample size reaches the curtailment value n_t without determination of lot acceptability, inspection terminates and the acceptance or non-acceptance of the lot is then determined using the curtailment values of the acceptance and rejection numbers.

For sequential sampling plans in common use, curtailment usually represents a deviation from their intended usage, leading to a distortion of their operating characteristics. In this part of ISO 2859; however, the operating characteristics of the sequential sampling plans have been determined with curtailment taken into account, so curtailment is an integral component of the provided plans.

Sampling procedures for inspection by attributes —

Part 5:

System of sequential sampling plans indexed by acceptance quality limit (AQL) for lot-by-lot inspection

1 Scope

This part of ISO 2859 specifies sequential sampling schemes that supplement the ISO 2859-1 acceptance sampling system for inspection by attributes.

The ISO 2859-1 acceptance sampling system is indexed in terms of the acceptance quality limit (AQL). Its purpose is to induce a supplier, through the economic and psychological pressure of lot non-acceptance, to maintain a process average at least as good as the specified acceptance quality limit, while at the same time providing an upper limit for the risk to the consumer of accepting the occasional poor lot.

The sampling schemes defined in this part of ISO 2859 are applicable, but not limited, to the inspection of:

- end items,
- components and raw materials,
- operations,
- materials in process,
- supplies in storage,
- maintenance operations,
- data or records, and
- administrative procedures.

These schemes are designed to be applied to a continuing series of lots, that is, a series long enough to permit the switching rules in 10.3 to be applied. These switching rules provide

- a) enhanced protection to the consumer (by means of tightened sampling inspection criteria or discontinuation of sampling inspection) should deterioration in quality occur,
- b) an incentive, at the discretion of the responsible authority, to reduce inspection costs (by means of reduced sampling inspection criteria) should consistently good quality be demonstrated over time.

The individual sampling plans are not designed to be used outside of the schemes in which they are presented. Where lots are produced in isolation or in a series too short for this part of ISO 2859 to apply, the user is advised to consult ISO 2859-2 for appropriate sampling plans.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2859-1:1999, *Sampling procedures for inspection by attributes — Part 1: Sampling schemes indexed by acceptance quality limit (AQL) for lot-by-lot inspection*

ISO 3534-2:—¹⁾, *Statistics — Vocabulary and symbols — Part 2: Applied statistics*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1 inspection

conformity evaluation by observation and judgement accompanied as appropriate by measurement, testing or gauging

[ISO 3534-2]

3.2 original inspection

inspection of a lot, or other amount, not previously inspected

NOTE This is in contrast, for example, to inspection of a lot which has previously been designated as not acceptable and which is submitted again for inspection after having been further sorted, reprocessed, etc.

[ISO 3534-2]

3.3 inspection by attributes

inspection by noting the presence, or absence, of the characteristic(s) in each of the items in the group of consideration, and counting how many items do, or do not, possess the characteristic(s), or how many such events occur in the item, group or opportunity space

NOTE When inspection is performed by simply noting whether the item is nonconforming or not, the inspection is termed inspection for nonconforming items. When inspection is performed by noting whether the number of nonconformities on each unit, the inspection is termed inspection for number of nonconformities

[ISO 3534-2]

3.4 item

anything that can be described and considered separately

EXAMPLES A discrete physical item; a defined amount of bulk material, a service, activity, person and or some combination thereof.

[ISO 3534-2]

3.5 nonconformity

non-fulfilment of a requirement

[ISO 3534-2]

1) To be published. (Revision of ISO 3534-2:1993)