EESTI STANDARD

Corrosion tests in artificial atmospheres - Salt spray tests (ISO 9227:2017)



EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

3.	
See Eesti standard EVS-EN ISO 9227:2017 sisaldab Euroopa standardi EN ISO 9227:2017 ingliskeelset teksti.	This Estonian standard EVS-EN ISO 9227:2017 consists of the English text of the European standard EN ISO 9227:2017.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 05.04.2017.	Date of Availability of the European standard is 05.04.2017.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile <u>standardiosakond@evs.ee</u>.

ICS 77.060

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega: Koduleht <u>www.evs.ee</u>; telefon 605 5050; e-post <u>info@evs.ee</u>

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:

Homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

EUROPEAN STANDARD NORME EUROPÉENNE **EUROPÄISCHE NORM**

EN ISO 9227

April 2017

ICS 77.060

Supersedes EN ISO 9227:2012

English Version

Corrosion tests in artificial atmospheres - Salt spray tests (ISO 9227:2017)

Essais de corrosion en atmosphères artificielles -Essais aux brouillards salins (ISO 9227:2017)

Korrosionsprüfungen in künstlichen Atmosphären -Salzsprühnebelprüfungen (ISO 9227:2017)

This European Standard was approved by CEN on 28 February 2017.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

European foreword

This document (EN ISO 9227:2017) has been prepared by Technical Committee ISO/TC 156"Corrosion of metals and alloys" in collaboration with Technical Committee CEN/TC 262 "Metallic and other inorganic coatings, including for corrosion protection and corrosion testing of metals and alloys" the secretariat of which is held by BSI.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by October 2017, and conflicting national standards shall be withdrawn at the latest by October 2017.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN ISO 9227:2012.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Endorsement notice

The text of ISO 9227:2017 has been approved by CEN as EN ISO 9227:2017 without any modification.

Contents

Page

Forew	ord		v
Intro	luction	l	vi
1	Scope		
2	Norm	ative references	
3	Terms and definitions		
4		ple	
5		olutions	
	5.1 5.2	Preparation of the sodium chloride solution pH adjustment	
	5.2	5.2.1 pH of the salt solution	
		5.2.2 Neutral salt spray (NSS) test	
		5.2.3 Acetic acid salt spray (AASS) test	
		5.2.4 Copper-accelerated acetic acid salt spray (CASS) test	
	5.3	Filtration	4
6	Annai	ratus	1
	6.1	Component protection	
	6.2	Spray cabinet	4
	6.3	Heater and temperature control	4
	6.4		
	6.5	Spraying device Collecting devices	5
	6.6	Re-use	5
7	Mothe	ad for avaluating cabinot corresivity	6
/	7 1	o d for evaluating cabinet corrosivity General	0
	7.2	Reference specimens	6
	7.3	Arrangement of the reference specimens	
	7.4	Determination of mass loss (mass per area)	
	7.5	Satisfactory performance of cabinet	
8	Test s	pecimens	7
9	Arran	gement of the test specimens	Q
		iting conditions	
10			
11	Durat	ion of tests	9
12	Treat	ment of test specimens after test	9
	12.1	General	9
	12.2	Non-organic coated test specimens: metallic and/or inorganic coated	9
	12.3.	Organic coated test specimens	9
		12.3.1 Scribed organic coated test specimens	9
		12.3.2 Organic coated but not scribed test specimens	10
13	Evalu	ation of results	
14	Test r	eport	
Anney		ormative) Example schematic diagram of one possible design of spray cabinet	
1 111102		neans for optional treating fog exhaust and drain	
Annes		ormative) Complementary method for evaluating cabinet corrosivity using	
	zinc r	eference specimens	14
Annex		mative) Preparation of specimens with organic coatings for testing	
	-	rmative) Required supplementary information for testing test specimens with	
		ic coatings	17

Bibliography 18

z

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 156, Corrosion of metals and alloys.

This fourth edition cancels and replaces the third edition (ISO 9227:2012), which has been technically revised. The main technical changes are as follows:

- new definitions for reference material, reference specimen, test specimen and substitute specimen have been implemented;
- checking of the test apparatus during test operation has been made possible;
- <u>Clause 4</u> has been added, with some of its text moved from the scope;
- <u>Clause 7</u> has been summarized.

Introduction

There is seldom a direct relation between resistance to the action of salt spray and resistance to corrosion in other media, because several factors influencing the progress of corrosion, such as the formation of protective films, vary greatly with the conditions encountered. Therefore, the test results should not be regarded as a direct guide to the corrosion resistance of the tested metallic materials in all environments where these materials might be used. Also, the performance of different materials during the test should not be taken as a direct guide to the corrosion resistance of these materials in service.

Nevertheless, the method described gives a means of checking that the comparative quality of a metallic material, with or without corrosion protection, is maintained.

Different metallic substrates (metals) cannot be tested in direct comparison in accordance to their corrosion resistances in salt spray tests. Comparative testing is only applicable for the same kind of substrate.

Salt spray tests are generally suitable as corrosion protection tests for rapid analysis for discontinuities, pores and damage in organic and inorganic coatings. In addition, for quality control purposes, comparison can be made between specimens coated with the same coating. As comparative tests, however, salt spray tests are only suitable if the coatings are sufficiently similar in nature.

It is often not possible to use results gained from salt spray testing as a comparative guide to the long-term behaviour of different coating systems, since the corrosion stress during these tests differs significantly from the corrosion stresses encountered in practice.

s ince red in p.

Corrosion tests in artificial atmospheres — Salt spray tests

1 Scope

This document specifies the apparatus, the reagents and the procedure to be used in conducting the neutral salt spray (NSS), acetic acid salt spray (AASS) and copper-accelerated acetic acid salt spray (CASS) tests for assessment of the corrosion resistance of metallic materials, with or without permanent or temporary corrosion protection.

It also describes the method employed to evaluate the corrosivity of the test cabinet environment.

It does not specify the dimensions or types of test specimens, the exposure period to be used for a particular product, or the interpretation of results. Such details are provided in the appropriate product specifications.

The salt spray tests are particularly useful for detecting discontinuities, such as pores and other defects, in certain metallic, organic, anodic oxide and conversion coatings.

The neutral salt spray (NSS) test particularly applies to

- metals and their alloys,
- metallic coatings (anodic and cathodic),
- conversion coatings,
- anodic oxide coatings, and
- organic coatings on metallic materials.

The acetic acid salt spray (AASS) test is especially useful for testing decorative coatings of copper + nickel + chromium, or nickel + chromium. It has also been found suitable for testing anodic and organic coatings on aluminium.

The copper-accelerated acetic acid salt spray (CASS) test is useful for testing decorative coatings of copper + nickel + chromium, or nickel + chromium. It has also been found suitable for testing anodic and organic coatings on aluminium.

The salt spray methods are all suitable for checking that the quality of a metallic material, with or without corrosion protection, is maintained. They are not intended to be used for comparative testing as a means of ranking different materials relative to each other with respect to corrosion resistance or as means of predicting long-term corrosion resistance of the tested material.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1514, Paints and varnishes — Standard panels for testing

ISO 2808, Paints and varnishes — Determination of film thickness

ISO 3574, Cold-reduced carbon steel sheet of commercial and drawing qualities

ISO 4623-2:2016, Paints and varnishes — Determination of resistance to filiform corrosion — Part 2: Aluminium substrates

ISO 4628-1, Paints and varnishes — Evaluation of degradation of coatings — Designation of quantity and size of defects, and of intensity of uniform changes in appearance — Part 1: General introduction and designation system

ISO 4628-2, Paints and varnishes — Evaluation of degradation of coatings — Designation of quantity and size of defects, and of intensity of uniform changes in appearance — Part 2: Assessment of degree of blistering

ISO 4628-3, Paints and varnishes — Evaluation of degradation of coatings — Designation of quantity and size of defects, and of intensity of uniform changes in appearance — Part 3: Assessment of degree of rusting

ISO 4628-4, Paints and varnishes — Evaluation of degradation of coatings — Designation of quantity and size of defects, and of intensity of uniform changes in appearance — Part 4: Assessment of degree of cracking

ISO 4628-5, Paints and varnishes — Evaluation of degradation of coatings — Designation of quantity and size of defects, and of intensity of uniform changes in appearance — Part 5: Assessment of degree of flaking

ISO 4628-8, Paints and varnishes — Evaluation of degradation of coatings — Designation of quantity and size of defects, and of intensity of uniform changes in appearance — Part 8: Assessment of degree of delamination and corrosion around a scribe or other artificial defect

ISO 8044, Corrosion of metals and alloys – Basic terms and definitions

ISO 8407, Corrosion of metals and alloys — Removal of corrosion products from corrosion test specimens

ISO 8993, Anodizing of aluminium and its alloys – Rating system for the evaluation of pitting corrosion – Chart method

ISO 10289, Methods for corrosion testing of metallic and other inorganic coatings on metallic substrates — Rating of test specimens and manufactured articles subjected to corrosion tests

ISO 17872, Paints and varnishes — Guidelines for the introduction of scribe marks through coatings on metallic panels for corrosion testing

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 8044 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— IEC Electropedia: available at http://www.electropedia.org/

ISO Online browsing platform: available at http://www.iso.org/obp

3.1

reference material

material with known test performance

3.2

reference specimen

portion of the *reference material* (3.1) that is to be exposed with the intention to check the reproducibility and repeatability of the test results for the test cabinet in use

3.3

test specimen

specific portion of the samples upon which the testing is to be performed

3.4

substitute specimen

specimen made of inert materials (such as plastic or glass) used for the substitute of a *test specimen* (3.3)