

MÖÖBEL. KODUSED LASTEVOODID JA LASTE
KLAPPVOODID. OSA 2: KATSEMEETODID

Furniture - Children's cots and folding cots for domestic
use - Part 2: Test methods

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

See Eesti standard EVS-EN 716-2:2017 sisaldab Euroopa standardi EN 716-2:2017 ingliskeelset teksti.	This Estonian standard EVS-EN 716-2:2017 consists of the English text of the European standard EN 716-2:2017.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 07.06.2017.	Date of Availability of the European standard is 07.06.2017.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 97.140, 97.190

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:

Koduleht www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:

Homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

English Version

Furniture - Children's cots and folding cots for domestic use - Part 2: Test methods

Möbel - Kinderbetten und Reisekinderbetten für den Wohnbereich - Teil 2: Prüfverfahren

This European Standard was approved by CEN on 21 February 2016.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

Page

European foreword.....	4
1 Scope.....	5
2 Normative references.....	5
3 General test conditions.....	5
3.1 Preliminary preparation.....	5
3.2 Test equipment.....	5
3.3 Application of forces.....	6
3.4 Tolerances.....	6
3.5 Test sequence.....	6
3.6 Prevention of movement during test.....	6
4 Test apparatus.....	6
4.1 Measuring probes.....	6
4.2 Bottom impactor.....	7
4.3 Test mattress.....	8
4.4 Side impactor.....	8
4.5 Loading pad.....	9
4.6 Stops.....	9
4.7 Floor surface.....	9
4.8 Test chain and mass.....	9
4.9 Small parts cylinder.....	9
4.10 Test mass.....	10
4.11 Bite tester.....	10
4.12 Retaining block.....	11
4.13 Foothold template.....	11
4.14 Head probes.....	12
4.14.1 Small head probe.....	12
4.14.2 Large head probe.....	12
4.15 Template for V-shaped openings.....	13
4.16 Test dummy.....	14
5 Test procedures.....	14
5.1 Assembly and inspection.....	14
5.2 Stability - test.....	14
5.3 Footholds.....	15
5.3.1 Determination of a foothold.....	15
5.3.2 Tests for footholds.....	16
5.3.3 Measurement of distance between footholds and/or top of cot sides and ends.....	19
5.4 Measurements.....	20
5.4.1 Holes, gaps and openings inside the cot.....	20
5.4.2 Holes, gaps and openings on the outside of the cot.....	21
5.5 Small parts.....	23
5.5.1 General.....	23
5.5.2 Torque test.....	23
5.5.3 Tension test.....	24
5.6 Bite test.....	24
5.7 Tests for cot base and mattress base.....	24

5.7.1	Folding test of the mattress base and cot base	24
5.7.2	Strength of cot base and mattress base (impact test)	25
5.8	Strength of sides and ends.....	26
5.8.1	Static load test of slats (bending test)	26
5.8.2	Strength of sides or side slats (impact test)	26
5.8.3	Strength of corners (impact test).....	27
5.8.4	Strength of mesh and flexible sides and ends (static load test).....	28
5.9	Strength of frame and fastenings.....	28
5.9.1	Vertical static load test	28
5.9.2	Durability test.....	29
5.10	Snag points	30
5.11	Locking systems	30
5.11.1	Durability.....	30
5.11.2	Strength.....	30
5.12	Stability test.....	30
6	Test report	31
Annex A (informative) A-deviations.....		32
Bibliography		33

European foreword

This document (EN 716-2:2017) has been prepared by Technical Committee CEN/TC 207 “Furniture”, the secretariat of which is held by UNI.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by December 2017, and conflicting national standards shall be withdrawn at the latest by December 2017.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 716-2:2008+A1:2013.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association.

Compared to EN 716-2:2008+A1:2013, the following modifications have been made:

- introduction of the elements of the amendment;
- modification of the wrong references to clauses;
- clarification of 4.3, “Test mattress”;
- modification of 5.7.1, “Folding test of the mattress base and cot base”.

EN 716, *Furniture — Children's cots and folding cots for domestic use*, is composed with the following parts:

- *Part 1: Safety requirements*;
- *Part 2: Test methods*.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

1 Scope

This European Standard specifies test methods for assessing the safety of children's cots and folding cots for domestic use.

It applies to children's cots and folding cots with an internal length greater than 900 mm but not more than 1 400 mm.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN ISO 2439:2008, *Flexible cellular polymeric materials — Determination of hardness (indentation technique)* (ISO 2439:2008)

ISO 7619-2, *Rubber, vulcanized or thermoplastic — Determination of indentation hardness — Part 2: IRHD pocket meter method*

3 General test conditions

3.1 Preliminary preparation

The tests are designed to be applied to a cot that is fully assembled and ready for use.

The test unit shall be stored in indoor ambient conditions for at least one week immediately prior to testing. Any deviation from this procedure shall be stated in the test report.

Before testing, any fabrics intended to be removable shall be cleaned or washed twice in accordance with the manufacturer's instructions. If no instructions are supplied, the manner of washing/cleaning shall be stated in the test report.

The tests shall be carried out under indoor ambient conditions, but if during a test the atmospheric temperature is outside the range 15 °C to 25 °C, the maximum and/or minimum temperature shall be recorded in the test report.

The cot shall be tested as delivered. If the cot is a knock down type, it shall be assembled according to the manufacturer's instructions supplied with the cot. If the cot can be assembled, combined or adjusted in different ways, the most adverse combination shall be used for each test.

Knock-down fittings shall be tightened before testing. Further re-tightening shall not take place unless this is specifically required by the manufacturer.

In the case of designs not catered for in the test procedures, the tests shall be carried out as far as possible as described, and a list made of the deviations from the test procedures.

3.2 Test equipment

Unless otherwise specified, the tests may be applied by any suitable device because results are dependent only upon correctly applied forces and loads and not upon the apparatus.

The equipment shall not inhibit the deformation of the cot during testing. It shall be able to move so that it can follow the deformation of the cot during testing, so that the loads are always applied at the specified point and in the specified direction.

All loading pads shall be capable of pivoting in relation to the direction of the applied force. The pivot point shall be as close as practically possible to the load surface.