
**Cinematography — Image area produced
by 65 mm/5 perforation motion-picture
camera aperture and maximum
projectable image area on 70 mm/5
perforation motion-picture prints —
Positions and dimensions**

*Cinématographie — Champ d'image enregistré par la fenêtre des
caméras 65 mm/5 perforations et champ maximal d'image projetable sur
copies d'exploitation 70 mm/5 perforations — Positions et dimensions*



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

This document is a preview generated by EVS

© ISO 2004

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 2467 was prepared by Technical Committee ISO/TC 36, *Cinematography*.

This third edition cancels and replaces the second edition (ISO 2467:1980), of which it constitutes a minor revision.

This document is a preview generated by EVS

Cinematography — Image area produced by 65 mm/5 perforation motion-picture camera aperture and maximum projectable image area on 70 mm/5 perforation motion-picture prints — Positions and dimensions

1 Scope

This International Standard specifies, for 65 mm/5 perforation motion-picture cameras and projectors, the dimensions of the image area produced by the camera on the film and the maximum projectable image area as well as the image positions relative to the reference edge of the film, and the perforations used to position the film in the camera.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3023, *Cinematography — 65 mm and 70 mm unexposed motion-picture film — Cutting and perforating dimensions*

3 Dimensions and characteristics

3.1 The dimensions shall be as shown in Figures 1 and 2 and given in Tables 1 and 2 and apply to measurements of the image as formed on, or projected from, a recently exposed and processed film.

3.2 The angle between the horizontal edges of the camera aperture image and the reference edge of the film shall be $90^\circ \pm 30'$.

3.3 The angle of the vertical edges of the camera aperture image shall be $0^\circ \pm 30'$ to the reference edge of the film.

NOTE 1 It is the intent of this International Standard to provide a camera image such that the exposed area will be larger than the maximum projectable image area. Observance of the dimensions given meets this objective without causing double exposure of the area between the frames.

NOTE 2 It is recognized that, in many cases, the actual film image area that is projected may be smaller than the projectable maximum. It is intended that the actual projected image area be the largest appropriately shaped figure that can be inscribed within the specified dimensions.

Since dimension B is the minimum width for available projection, it is necessary that, for release prints by contact printing or any other system, the plus tolerance should be used in the printing system.

NOTE 3 Image steadiness could be improved if the reference edge is the guided edge as well.