
**Petroleum and natural gas industries —
Drilling fluid materials — Specifications
and tests**

*Industries du pétrole et du gaz naturel — Produits pour fluides de
forage — Spécifications et essais*



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO 2006

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	vi
Introduction.....	vii
1 Scope	1
2 Normative references	1
3 Terms, definitions, symbols and abbreviations	1
3.1 Terms and definitions	1
3.2 Symbols and abbreviations	2
4 Requirements	4
4.1 Quality control instructions	4
4.2 Use of test calibration materials in checking testing procedures	4
4.3 Records retention	4
5 Calibration	4
5.1 Coverage	4
5.2 Equipment requiring calibration	5
5.3 Calibration intervals	9
6 Packaged material	11
6.1 Description	11
6.2 Apparatus — Pallets	11
6.3 Apparatus — Bags	11
6.4 Marking — Pallets	11
6.5 Marking — Bags	12
6.6 Pallet covers	12
6.7 Package weight	12
6.8 Storage	12
6.9 Recycling	12
7 Barite	13
7.1 Principle	13
7.2 Reagents and apparatus — Density by Le Chatelier flask	13
7.3 Procedure — Density by Le Chatelier flask	14
7.4 Calculation — Density by Le Chatelier flask	15
7.5 Reagents and apparatus — Water-soluble alkaline earths as calcium	15
7.6 Procedure — Water-soluble alkaline earth metals as calcium	16
7.7 Calculation — Water-soluble alkaline earths as calcium	16
7.8 Reagents and materials — Residue of diameter greater than 75 µm	16
7.9 Procedure — Residue of diameter greater than 75 µm	17
7.10 Calculation — Residue of diameter greater than 75 µm	17
7.11 Reagents and apparatus — Particles less than 6 µm in equivalent spherical diameter by sedimentation method	18
7.12 Procedure — Particles less than 6 µm in equivalent spherical diameter by sedimentation method	18
7.13 Calculation — Particles less than 6 µm in equivalent spherical diameter by sedimentation method	19
8 Haematite (hematite)	22
8.1 Principle	22
8.2 Reagent and apparatus — Density by Le Chatelier flask	23
8.3 Procedure — Density by Le Chatelier flask	23
8.4 Calculation — Density by Le Chatelier flask	24
8.5 Reagents and apparatus — Water-soluble alkaline earth metals as calcium	24

8.6	Procedure — Water-soluble alkaline earth metals as calcium	25
8.7	Calculation — Water-soluble alkaline earth metals as calcium	25
8.8	Reagents and apparatus — Residues greater than 75 µm and 45 µm.....	26
8.9	Procedure — Residues of diameter greater than 75 µm and 45 µm	26
8.10	Calculation — Residues of diameter greater than 75 µm and 45 µm.....	27
8.11	Reagents and apparatus — Particles less than 6 µm in equivalent spherical diameter by sedimentation method.....	27
8.12	Procedure — Particles less than 6 µm in equivalent spherical diameter by sedimentation method	28
8.13	Calculation — Particles less than 6 µm in equivalent spherical diameter by sedimentation method	28
9	Bentonite.....	31
9.1	Principle	31
9.2	Reagents and apparatus — Suspension properties	31
9.3	Procedure — Rheology of suspension.....	31
9.4	Calculation — Rheology of suspension	32
9.5	Procedure — Filtrate volume of suspension.....	32
9.6	Calculation — Filtrate volume of suspension	33
9.7	Reagents and apparatus — Residue of diameter greater than 75 µm.....	33
9.8	Procedure — Residue of diameter greater than 75 µm	33
9.9	Calculation — Residue of diameter greater than 75 µm	34
10	Non-treated bentonite	34
10.1	Principle	34
10.2	Reagents and apparatus — Suspension properties	34
10.3	Procedure — Rheology of suspension.....	35
10.4	Calculation — Rheology of suspension	35
10.5	Procedure — Dispersed plastic viscosity of suspension.....	36
10.6	Procedure — Dispersed filtrate volume of suspension	36
10.7	Calculation — Dispersed filtrate volume of suspension	36
11	OCMA grade bentonite	36
11.1	Principle	36
11.2	Reagents and apparatus — Suspension properties	37
11.3	Procedure — Rheology of suspension.....	37
11.4	Calculation — Rheology of suspension	38
11.5	Procedure — Filtrate volume of suspension.....	38
11.6	Calculation — Filtrate volume of suspension	38
11.7	Reagents and apparatus — Residue of diameter greater than 75 µm.....	39
11.8	Procedure — Residue of diameter greater than 75 µm	39
11.9	Calculation — Residue of diameter greater than 75 µm	39
12	Attapulgate.....	40
12.1	Principle	40
12.2	Reagents and apparatus — Suspension properties	40
12.3	Procedure — 600 r/min dial reading of suspension	41
12.4	Reagent and apparatus — Residue of diameter greater than 75 µm.....	41
12.5	Procedure — Residue of diameter greater than 75 µm	41
12.6	Calculation — Residue of diameter greater than 75 µm	42
12.7	Reagent and apparatus — Moisture.....	42
12.8	Procedure — Moisture.....	42
12.9	Calculation — Moisture	42
13	Sepiolite	43
13.1	Principle	43
13.2	Reagents and apparatus — Suspension properties	43
13.3	Procedure — 600 r/min dial reading of suspension	44
13.4	Reagents and apparatus — Residue of diameter greater than 75 µm.....	44
13.5	Procedure — Residue of diameter greater than 75 µm	44
13.6	Calculation — Residue of diameter greater than 75 µm	45
13.7	Reagents and apparatus — Moisture.....	45

13.8	Procedure — Moisture.....	45
13.9	Calculation — Moisture.....	45
14	Technical grade low-viscosity CMC (CMC-LVT).....	46
14.1	Principle.....	46
14.2	Reagents and apparatus — Determination of starch and starch derivatives.....	46
14.3	Procedure — Determination of starch and starch derivatives.....	47
14.4	Interpretation — Determination of starch and starch derivatives.....	47
14.5	Reagents and apparatus — Solution properties of water-soluble polymers.....	48
14.6	Procedure — Viscometer reading in deionized water.....	48
14.7	Procedure — Filtrate volume of solution.....	49
14.8	Calculation — Filtrate volume of solution.....	50
15	Technical grade high-viscosity CMC (CMC-HVT).....	50
15.1	Principle.....	50
15.2	Reagents and apparatus — Determination of starch and starch derivatives.....	50
15.3	Procedure — Determination of starch and starch derivatives.....	51
15.4	Interpretation — Determination of starch and starch derivatives.....	52
15.5	Reagents and apparatus — Solution properties of water-soluble polymers.....	52
15.6	Procedure — Viscometer reading in deionized water.....	53
15.7	Procedure — Viscometer reading in 40 g/l salt water.....	53
15.8	Procedure — Viscometer reading in saturated salt water.....	54
15.9	Procedure — Filtrate volume of solution.....	54
15.10	Calculation — Filtrate volume of solution.....	55
16	Starch.....	55
16.1	Principle.....	55
16.2	Reagents and apparatus — Suspension properties.....	56
16.3	Procedure — Viscometer reading in 40 g/l salt water.....	56
16.4	Procedure — Filtrate volume of 40 g/l salt solution.....	57
16.5	Calculation — Filtrate volume of 40 g/l salt solution.....	57
16.6	Procedure — Viscometer reading in saturated salt solution.....	57
16.7	Procedure — Filtrate volume of saturated salt solution.....	58
16.8	Calculation — Filtrate volume of saturated salt solution.....	58
16.9	Reagents and apparatus — Residue greater than 2 000 µm.....	59
16.10	Procedure — Residue greater than 2 000 µm.....	59
Annex A (informative) Mineral impurities in barite.....		60
Annex B (informative) Test precision.....		61
Annex C (informative) Examples of calculations.....		66
Bibliography.....		74

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 13500 was prepared by Technical Committee ISO/TC 67, *Materials, equipment and offshore structures for petroleum, petrochemical and natural gas industries*, Subcommittee SC 3, *Drilling and completion fluids, and well cements*.

This second edition cancels and replaces the first edition (ISO 13500:1998), which has been technically revised.

Introduction

This International Standard covers materials which are in common usage in petroleum and natural gas drilling fluids. These materials are used in bulk quantities, can be purchased from multiple sources, and are available as commodity products. No single-source or limited-source products are included, nor are speciality products.

International Standards are published to facilitate communication between purchasers and manufacturers, to provide interchangeability between similar equipment and materials purchased from different manufacturers and/or at different times, and to provide an adequate level of safety when the equipment or materials are utilised in the manner and for the purposes intended. This International Standard provides minimum requirements and is not intended to inhibit anyone from purchasing or producing materials to other standards.

This International Standard is substantially based on API Spec 13A, 16th Edition, December 1, 2003. The purpose of this International Standard is to provide product specifications for barite, haematite, bentonite, nontreated bentonite, Oil Companies Materials Association (OCMA) grade bentonite, attapulgite, sepiolite, technical-grade low viscosity carboxymethylcellulose (CMC-LVT), technical-grade high viscosity carboxymethylcellulose (CMC-HVT), and starch.

The intent of the document was to incorporate all International Standards for drilling fluid materials into an ISO-formatted document. A survey of the industry found that only the American Petroleum Institute (API) issued testing procedures and specification standards for these materials.

Reference to OCMA materials has been included in API work, as the OCMA and subsequent holding committees were declared defunct, and all specifications were submitted to API in 1983.

Annex A (informative) lists the mineral impurities in barite, Annex B (informative) provides the test precision and Annex C (informative) details examples of calculations.

Petroleum and natural gas industries — Drilling fluid materials — Specifications and tests

1 Scope

This International Standard covers physical properties and test procedures for materials manufactured for use in oil- and gas-well drilling fluids. The materials covered are barite, haematite, bentonite, nontreated bentonite, OCMA grade bentonite, attapulgite, sepiolite, technical grade low-viscosity carboxymethylcellulose (CMC-LVT), technical grade high-viscosity carboxymethylcellulose (CMC-HVT), and starch. This International Standard is intended for the use of manufacturers of named products.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 6780, *Flat pallets for intercontinental materials handling — Principal dimensions and tolerances*

ISO 10414-1, *Petroleum and natural gas industries — Field testing of drilling fluids — Part 1: Water-based fluids*

ASTM D422, *Standard Test Method for Particle-Size Analysis of Soils*

ASTM E11, *Standard Specification for Wire Cloth and Sieves for Testing Purposes*

ASTM E161, *Standard Specification for Precision Electroformed Sieves*

ASTM E77, *Standard Test Method for Inspection and Verification of Thermometers*

ASTM E177, *Standard Practice for Use of the Terms Precision and Bias in ASTM Test Methods*

NIST (NBS) Monograph 150, *Liquid-in-glass thermometry*

3 Terms, definitions, symbols and abbreviations

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1.1

ACS reagent grade

chemicals which meet purity standards as specified by the American Chemical Society (ACS)

3.1.2

flash side

side containing residue (“flash”) from stamping, or the side with concave indentation