# INTERNATIONAL STANDARD



First edition 2007-08-01

# Plastics piping systems — Polyethylene (PE) pipes and fittings for water supply —

Part 1: General

Systèmes de canalisations en plastique — Tubes et raccords en polyéthylène (PE) destinés à l'alimentation en eau —

Partie 1: Généralités



Reference number ISO 4427-1:2007(E)

#### PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below

This document is a preview denerated by Fig.



# **COPYRIGHT PROTECTED DOCUMENT**

#### © ISO 2007

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org Published in Switzerland

# Contents

| Forewo                                      | rd  | iv         |
|---|---|------------|
| Introdu                                     | ction   |            |
| 1   | Scope   |            |
| 2   | Normative references  | . 1        |
| 3<br>3.1<br>3.2<br>3.3                      | Terms, definitions, symbols and abbreviated terms<br>Terms and definitions<br>Symbols<br>Abbreviated terms  | 3          |
| 4<br>4.1<br>4.2<br>4.3<br>4.4<br>4.5<br>4.6 | Abbreviated terms<br>Material<br>Compound<br>Colour<br>Use of reprocessable and recyclable material<br>Physical characteristics of the compound<br>Fusion compatibility<br>Classification and designation | . /<br>. 7 |
| 5   | Effect on water quality of pipes intended for conveyance of water for human consumption   | 10         |
| Annex                                       | consumption   A (informative)   Pressure reduction coefficients   | 11         |
| A   | P (informative) Projector on to read an effective   | 40         |
| Bibliog                                     | raphy   | 14         |
|   | raphy   |            |

# Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in Maison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 4427-1 was prepared by Technical Committee ISO/TC 138, *Plastics pipes, fittings and valves for the transport of fluids*, Subcommittee SC 2, *Plastics pipes and fittings for water supplies*.

This first edition, together with ISO 4427-2, cancels and replaces ISO 4427:1996, of which it constitutes a technical revision.

ISO 4427 consists of the following parts, under the general title *Plastics piping systems* — *Polyethylene (PE)* pipes and fittings for water supply:

- Part 1: General
- Part 2: Pipes
- Part 3: Fittings
- Part 5: Fitness for purpose of the system



# Introduction

ISO 4427, the system standard, specifies the requirements for a piping system and its components when made from polyethylene (PE). The piping system is intended to be used for water supply intended for human consumption, including the conveyance of raw water prior to treatment and that of water for general purposes.

In respect of potential adverse effects on the quality of water intended for human consumption caused by the products covered by JSO 4427:

- ISO 4427 provides no information as to whether the products may be used without restriction; a)
- existing national regulations concerning the use and/or the characteristics of these products are in force. b)
- spent of conformity can be found in Bibliographical references [9] and [10]. NOTE Guidance for asses

sce

this document is a preview denerated by EUS

5:00

# Plastics piping systems — Polyethylene (PE) pipes and fittings for water supply —

# Part 1: General

# 1 Scope

This part of ISO 4427 specifies the general aspects of polyethylene (PE) piping systems (mains and service pipes) intended for the conveyance of water for human consumption, including raw water prior to treatment and water for general purposes.

It also specifies the test parameters for the test methods to which it refers.

In conjunction with the other parts of ISO 4427, it is applicable to PE pipes, fittings, their joints and to mechanical joints with components of other naterials, intended to be used under the following conditions:

a) a maximum operating pressure (MOP) up to and including 25 bar<sup>1</sup>;

b) an operating temperature of 20 °C as the reference temperature.

NOTE 1 For applications operating at constant temperatures greater than 20 °C and up to 40 °C, see Annex A.

NOTE 2 ISO 4427 covers a range of maximum operating persures and gives requirements concerning colours and additives. It is the responsibility of the purchaser or specifier to make the appropriate selections from these aspects, taking into account their particular requirements and any relevant national guidance or regulations and installation practices or codes.

# 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3:1973, Preferred numbers — Series of preferred numbers

ISO 472, Plastics — Vocabulary



ISO 1043-1, Plastics — Symbols and abbreviated terms — Part 1: Basic polymers and their special characteristics

ISO 1133:2005, Plastics — Determination of the melt mass-flow rate (MFR) and the melt volume-flow rate (MVR) of thermoplastics

<sup>1) 1</sup> bar = 0,1 MPa =  $10^5$  Pa; 1 MPa = 1 N/mm<sup>2</sup>.

#### ISO 4427-1:2007(E)

ISO 1167-1, Thermoplastics pipes, fittings and assemblies for the conveyance of fluids — Determination of the resistance to internal pressure — Part 1: General method

ISO 1167-2, Thermoplastics pipes, fittings and assemblies for the conveyance of fluids — Determination of the resistance to internal pressure — Part 2: Preparation of pipe test pieces

ISO 1183-2, *Plastics — Methods for determining the density of non-cellular plastics — Part 2: Density gradient column method* 

ISO 4065:1996, Thermoplastics pipes — Universal wall thickness table

ISO 4427-2:2007, Plastics biping systems — Polyethylene (PE) pipes and fittings for water supply — Part 2: Pipes

ISO 4427-3:2007, Plastics piping systems — Polyethylene (PE) pipes and fittings for water supply — Part 3: Fittings

ISO 4427-5:2007, Plastics piping systems — Polyethylene (PE) pipes and fittings for water supply — Part 5: Fitness for purpose of the system

ISO 6259-1:1997, Thermoplastics pipes Opetermination of tensile properties — Part 1: General test method

ISO 6259-3:1997, Thermoplastics pipes — Determination of tensile properties — Part 3: Polyolefin pipes

ISO 6964:1986, Polyolefin pipes and fittings – Determination of carbon black content by calcination and pyrolysis – Test method and basic specification

ISO 9080, Plastics piping and ducting systems — Determination of the long-term hydrostatic strength of thermoplastics materials in pipe form by extrapolation

ISO 11357-6:2002, Plastics — Differential scanning caloringry (DSC) — Part 6: Determination of oxidation induction time

ISO 11414, Plastics pipes and fittings — Preparation of polyeth the (PE) pipe/pipe or pipe/fitting test piece assemblies by butt fusion

ISO 12162, Thermoplastics materials for pipes and fittings for pressure applications — Classification and designation — Overall service (design) coefficient

ISO 13479:1997, Polyolefin pipes for the conveyance of fluids — Determation of resistance to crack propagation — Test method for slow crack growth on notched pipes (notch test **C** 

ISO 13761:1996, Plastics pipes and fittings — Pressure reduction factors for polyethylene pipeline systems for use at temperatures above 20 °C

ISO 13953:2001, Polyethylene (PE) pipes and fittings — Determination of the tensile strength and failure mode of test pieces from a butt-fused joint

ISO 13954, Plastics pipes and fittings — Peel decohesion test for polyethylene (PE) electrofusion assemblies of nominal outside diameter greater than or equal to 90 mm

ISO 16871, Plastics piping and ducting systems — Plastics pipes and fittings — Method for exposure to direct (natural) weathering

ISO 18553, Method for the assessment of the degree of pigment or carbon black dispersion in polyolefin pipes, fittings and compounds

EN 12099, Plastics piping systems — Polyethylene piping materials and components — Determination of volatile content

ISO 15512, Plastics - Determination of water content

Guidelines for drinking water quality, Volume 1: Recommendations, WHO, Geneva, 1984

EC Council Directive 98/83/EC of 3 November 1998 on the quality of water intended for human consumption, *Official Journal of the European Communities* 

# 3 Terms, definitions, symbols and abbreviated terms

# 3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 3, ISO 472 and ISO 1043-1, and the following, apply.

# 3.1.1 Geometrical characteristics

# 3.1.1.1

nominal size

DN

numerical designation of the size of component, other than a component designated by a thread size, which is a convenient round number approximately equal to the manufacturing dimension in millimetres (mm)

#### 3.1.1.2

nominal size

DN/OD nominal size, related to the outside diameter

#### 3.1.1.3

# nominal outside diameter

d<sub>n</sub> specified outside diameter, in millimetres, assigned to a nominal size DN/OD

S

#### 3.1.1.4

#### outside diameter at any point

 $d_{e}$ 

value of the measurement of the outside diameter through its cross section at any point of the pipe rounded to the next greater 0,1 mm

#### 3.1.1.5

#### mean outside diameter

 $d_{em}$ 

value of the measurement of the outer circumference of the pipe or spigot end of a fitting in any cross-section divided by  $\pi$  (= 3,142), rounded to the next greater 0,1 mm

#### 3.1.1.6

#### minimum mean outside diameter

d<sub>em min</sub>

minimum value of the outside diameter as specified for a given nominal size

#### 3.1.1.7

#### maximum mean outside diameter

d<sub>em max</sub>

maximum value of the outside diameter as specified for a given nominal size