INTERNATIONAL STANDARD

ISO 11140-3

Second edition 2007-03-15

Sterilization of health care products — Chemical indicators —

Part 3:

Class 2 indicator systems for use in the Bowie and Dick-type steam penetration test

Stérilisation des produits de santé — Indicateurs chimiques —

Partie 3: Systèmes d'indicateurs de Classe 2 pour utilisation lors de l'essai de Bowie et Dick de pénétration de la vapeur



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below

This document is a preview denetated by this

© ISO 2007

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org

Published in Switzerland

Contents Page	
Forewo	ordiv
Introdu	ıctionv
1	Scope1
2	Normative references
3	Terms and definitions
4	General requirements
5	Indicator system format
6	Performance requirements
7	Packaging and labelling3
8	Quality assurance
	A (normative) Determination of strength after steam sterilization 5
Annex	B (normative) Estimation of visual difference between colour of the substrate and the changed (or unchanged) indicator system by determination of relative reflectance density 6
Annex	C (normative) Determination of indicator colour change on exposure to dry saturated steam
Annex	D (normative) Determination of indicator colour change on exposure to dry heat 11
Annex	E (normative) Accelerated ageing of test samples
	F (normative) Determination of transfer of indicator to standard test pack on processing 13
Annex	G (normative) Determination of shelf life of the oduct
	H (normative) Steam exposure apparatus
Annex	I (normative) Determination of sensitivity of the indicator to the presence of air
Annex	J (normative) Air injection system
Annex	I (normative) Determination of sensitivity of the indicator to the presence of air
Bibliog	raphy21

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in Maison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 11140-3 was prepared by Technical Committee ISO/TC 198, Sterilization of health care products.

This second edition cancels and replaces the first edition (ISO 11140-3:2000) which has been technically revised.

ISO 11140 consists of the following parts, under the peral title Sterilization of health care products—

Chemical indicators:

- Part 1: General requirements
- Part 3: Class 2 indicator systems for use in the Bowie and Di€ type steam penetration test
- Part 4: Class 2 indicators as an alternative to the Bowie and Dick-type test for detection of steam penetration
- Part 5: Class 2 indicators for Bowie and Dick-type air removal tests

Introduction

The Bowie and Dick test is a performance test for steam sterilizers for wrapped goods and porous loads. As such it is performed during the demonstration of conformance of steam sterilizers to EN 285 and as a routine test of performance in ISO 17665-1. The test method is described in EN 285.

A failure of the Boylie and Dick test is symptomatic of a number of potential problems with the sterilizer that could compromise the uniform sterilization of a load to be processed. This failure is not conclusive proof that the fault in the sterilizer is due to air retention, air leakage or non-condensable gases and it can be necessary to investigate other causes of failure.

The Bowie and Dick test was conceived as a test for successful air removal from high-vacuum porous-load sterilizers used in the sterilization of health care products ^[1]. A successful Bowie and Dick test indicates rapid and even penetration of steam into the test pack. The presence of air within the pack, due to an inefficient air removal stage, an air leak during this stage or non-condensable gases in the steam supply, is a circumstance which can lead to failure of the [63]. The result of the test may also be affected by other factors which inhibit steam penetration. The test does not necessarily demonstrate either achievement of the required temperature or maintenance of that temperature for the required time to achieve sterilization.

A test pack for the Bowie and Dick test sonsists of two components:

- a) a small standardized test load;
- b) a chemical indicator to detect the presence of team.

The Bowie and Dick test as originally described [1] utilized huckaback towels as the material for the test load. The test as described in EN 285 uses cotton sheets for this purpose.

Because a range of different tests in different countries has historically been termed the Bowie and Dick test, the term "Bowie and Dick-type test" is used in this part of 15 of 1140.

© ISO 2007 – All rights reserved

Inis document is a preview denetated by EUS

Sterilization of health care products — Chemical indicators —

Part 3:

Class 2 indicator systems for use in the Bowie and Dick-type steam penatration test

1 Scope

This part of ISO 11140 specifies the requirements for chemical indicators to be used in the steam penetration test for steam sterilizers for wrapped goods, e.g. instruments and porous materials. The indicator for this purpose is a Class 2 indicator as described in ISO 11140-1.

Indicators complying with this part of ISO 11140 are intended for use in combination with the standard test pack as described in EN 285. This part of ISO 11140 does not consider the performance of the standard test pack, but does specify the performance of the indicator systems.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 5-1, Photography — Density measurements — Part Germs, symbols and notations

ISO 5-3, Photography — Density measurements — Part 3: Spectral conditions

ISO 5-4:1995, Photography — Density measurements — Part 4: Geometric conditions for reflection density

ISO 187:1990, Paper, board and pulps — Standard atmosphere for conditioning and testing and procedure for monitoring the atmosphere and conditioning of samples

ISO 2248, Packaging — Complete, filled transport packages — Vertical impact test by dropping

ISO 5457, Technical product documentation — Sizes and layout of drawing sheets

ISO 5636-3, Paper and board — Determination of air permeance (medium range) 🔫 🆓 rt 3: Bendtsen method

ISO 11140-1:2005, Sterilization of health care products — Chemical indicators — Part 1: General requirements

ISO/CIE 10526:1999, CIE standard illuminants for colorimetry

EN 285:2006, Sterilization — Steam sterilizers — Large sterilizers