

This document is a preview generated by EVS

Packaging - Test method to determine the porosity of the internal coating of flexible aluminium tubes - Part 2: Copper sulphate test

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

See Eesti standard EVS-EN 15384-2:2017 sisaldb Euroopa standardi EN 15384-2:2017 ingliskeelset teksti.	This Estonian standard EVS-EN 15384-2:2017 consists of the English text of the European standard EN 15384-2:2017.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 25.01.2017.	Date of Availability of the European standard is 25.01.2017.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 55.120

Standardite reproduutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:
Koduleht www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:

Homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN 15384-2

January 2017

ICS 55.120

Supersedes EN 15384:2007

English Version

Packaging - Test method to determine the porosity of the
internal coating of flexible aluminium tubes - Part 2:
Copper sulphate test

Emballage - Méthode d'essai pour déterminer la
porosité du revêtement intérieur des tubes souples en
aluminium - Partie 2 : Essai au sulfate de cuivre

Packmittel - Prüfverfahren zur Bestimmung der
Porosität der Innenbeschichtung von Aluminiumtuben
- Teil 2: Kupfersulfatverfahren

This European Standard was approved by CEN on 14 November 2016.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

	Page
EUROPEAN FOREWORD	3
1 SCOPE	4
2 PRINCIPLE	4
3 APPARATUS	4
FIGURE 1 — TEST DEVICE	5
4 PROCEDURE.....	5
TABLE 1 — TEST CONDITIONS FOR THE COPPER SULPHATE METHOD	6
5 TOLERANCES.....	7
TABLE 2 — TOLERANCES FOR THE COPPER SULPHATE METHOD	7
6 TEST REPORT	7
BIBLIOGRAPHY	8

European foreword

This document (EN 15384-2:2017) has been prepared by Technical Committee CEN/TC 261 "Packaging", the secretariat of which is held by AFNOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by July 2017, and conflicting national standards shall be withdrawn at the latest by July 2017.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 15384:2007.

According to the CEN-CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

1 Scope

This European Standard is applicable for internally coated cylindrical aluminium tubes, mainly used for the packing of pharmaceutical, cosmetic, hygiene, food or other household products.

The internal coating is used as a barrier and should avoid any contact between aluminium and the product. This standard defines the copper sulphate method to detect the electrolyte conductivity as one criterion for the quality of the internal coating.

The electrolyte conductivity of the internal coating is only one criterion for evaluation of the quality of an internal coating. It does not give any information on the quantity or size of any pores or uncoated areas, nor any hint on possible reactions between the aluminium tube and the product. The electrolyte conductivity should never be used as the sole criterion for quality evaluation of the internal coating, but always with other parameters e.g. film thickness, acetone and/or ammonia resistance and of course results of enhanced stability studies.

2 Principle

The electrolyte conductivity of internally coated aluminium tubes is tested by an enamel conductometer. The aluminium tubes are filled with an electrolyte solution up to a fixed level at its open end. One electrode is connected to the tube nozzle, the second electrode is dipped into the solution. A defined voltage is applied for a fixed time. The induced current is a measure for the quality (pores and/or film thickness) of the internal coating.

3 Apparatus

3.1 Enamel conductometer

3.2 Moveable electrode

3.3 Electrolyte

NOTE A schematic diagram of the test equipment is given in Figure 1.