

Imperfections in thermoplastics welded joints - Quality levels

This document is a preview generated by EVS

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

See Eesti standard EVS-EN 16296:2012 sisaldab Euroopa standardi EN 16296:2012 ingliskeelset teksti.	This Estonian standard EVS-EN 16296:2012 consists of the English text of the European standard EN 16296:2012.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas.	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 31.10.2012.	Date of Availability of the European standard is 31.10.2012.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 25.160.40

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:
Aru 10, 10317 Tallinn, Eesti; www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:
Aru 10, 10317 Tallinn, Estonia; www.evs.ee; phone 605 5050; e-mail info@evs.ee

ICS 25.160.40

English Version

Imperfections in thermoplastics welded joints - Quality levels

Défauts dans les assemblages soudés en
thermoplastiques - Niveaux de qualité

Unregelmäßigkeiten an Schweißverbindungen von
thermoplastischen Kunststoffen - Qualitätsstufen

This European Standard was approved by CEN on 22 September 2012.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents	Page
Foreword	3
Introduction	4
1 Scope	5
2 Normative reference	6
3 Terms and definitions	6
4 Quality levels	6
4.1 Classification	6
4.2 Choice of quality level	7
5 Requirements for welded joints	7
Bibliography	18

Foreword

This document (EN 16296:2012) has been prepared by Technical Committee CEN/TC 249 "Plastics", the secretariat of which is held by NBN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by April 2013, and conflicting national standards shall be withdrawn at the latest by April 2013.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

According to the CEN/CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Introduction

This European Standard should be used as a reference in drafting of application codes and/or other application standards. It contains a simplified selection of imperfections based on the designations given in EN 14728, *Imperfections in thermoplastic welds — Classification*.

Some imperfections according to EN 14728 have been used directly and some have been grouped together. The basic numerical referencing system from EN 14728 has been used.

The purpose of this standard is to define quality levels based on typical imperfections, which might occur in normal fabrication. It may be used within a quality system for the production of factory welded joints. It provides three sets of dimensional values from which a selection can be made for a particular application. The quality level necessary in each case should be defined by the application standard or the fabricator in conjunction with the user and/or other parties concerned. The level should be prescribed before the start of production, preferably at the enquiry or order stage.

The quality levels given in this standard are intended to provide basic reference data and are not specifically related to any particular application. They refer to the types of welded joints in a fabrication and not to the complete product or component itself. It is possible, therefore, that different quality levels are applied to individual welded joints in the same product or component.

The choice of quality level for any application should take account of design considerations, subsequent processing, mode of stressing (e.g. static, dynamic), service conditions (e.g. pressure, temperature, environment) and consequences of failure. Economic factors are also important and should include not only the cost of welding but also of inspection, test and repair.

Although this European Standard includes types of imperfections relevant to the processes given in Clause 1, only those which are applicable to the process and application in question need to be considered.

Imperfections are quoted in terms of their actual dimensions. However their detection and evaluation may require the use of one or more methods of non-destructive testing. It should be noted that the detection and sizing of imperfections is dependent on the inspection methods and the extent of testing specified in the application standard or contract.

The need for detection is not the subject of this standard.

This European Standard is directly applicable to visual examination of welds or test specimens. It does not include details of recommended methods of detection and sizing. The indication provided by non-destructive testing should not be used directly for the evaluation of quality levels. Therefore, it needs to be supplemented by requirements for examinations, inspection and testing.

1 Scope

This European Standard provides quality levels for imperfections in thermoplastics welded joints. It applies to material thickness above 2,0 mm.

Three quality levels are given in order to permit application for a wide range of welded fabrication. They are designated by symbols B, C and D, where B is the most stringent. The quality levels refer to production quality and not to the fitness-for-purpose (see 3.2) of the manufactured product.

This European Standard applies to the following thermoplastic materials:

Table 1

Abbreviation	Material description
ABS	Acrylonitrile-butadiene-styrene plastic
ECTFE	Ethylene-chlorotrifluoroethylene copolymer
FEP	Fluorinated ethylene propylene
PB	Polybutylene
PE	Polyethylene
PFA	Perfluoroalkoxy
PP-B	Polypropylene block copolymer
PP-H	Polypropylene homopolymer
PP-R	Polypropylene random copolymer
PVC-C	Chlorinated polyvinyl chloride
PVC-U	Unplasticised polyvinyl chloride (rigid PVC)
PVDF	Polyvinylidene fluoride

and to the following welding processes:

- Heated tool welding;
- Electrofusion welding;
- Hot gas welding using filler rod only;
- Extrusion welding;

— Solvent welding of pipes.

2 Normative reference

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 14728, *Imperfections in thermoplastic welds — Classification*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply

3.1

quality level

description of the qualities of a weld on the basis of type and size of selected imperfections

3.2

fitness-for-purpose

ability of a product, process or service to serve a defined purpose under specific conditions

4 Quality levels

4.1 Classification

Three quality levels are defined as B, C and D in order to permit application for a wide range of welded fabrications (see Table 2).

Table 2 — Quality levels for weld imperfections

Symbol	Requirement
B	Stringent
C	Intermediate
D	Moderate

The purpose of this standard is to define quality levels based on typical imperfections, which might occur in normal fabrications and are classified in EN 14728. It may be used within a quality system for the production of factory welded joints. It provides three sets of dimensional values from which a selection can be made for a particular application. The quality level necessary in each case should be defined by the application standard or the fabricator in conjunction with the user and/or other parties concerned. The level should be prescribed before the start of production, preferably at the enquiry or order stage.

For specific applications, additional requirements not covered by this standard may need to be prescribed. These additional requirements shall be defined as quality level A.