

This document is a preview generated by EVS

## EESTI STANDARDI EESSÕNA

## NATIONAL FOREWORD

See Eesti standard EVS-EN 16306:2013 sisaldab Euroopa standardi EN 16306:2013 ingliskeelset teksti.	This Estonian standard EVS-EN 16306:2013 consists of the English text of the European standard EN 16306:2013.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas.	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kätesaadavaks 13.02.2013.	Date of Availability of the European standard is 13.02.2013.
Standard on kätesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile [standardiosakond@evs.ee](mailto:standardiosakond@evs.ee).

ICS 73.020, 91.100.15

### Standardite reproduutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:  
Aru 10, 10317 Tallinn, Eesti; [www.evs.ee](http://www.evs.ee); telefon 605 5050; e-post [info@evs.ee](mailto:info@evs.ee)

### The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:  
Aru 10, 10317 Tallinn, Estonia; [www.evs.ee](http://www.evs.ee); phone 605 5050; e-mail [info@evs.ee](mailto:info@evs.ee)

EUROPEAN STANDARD

EN 16306

NORME EUROPÉENNE

EUROPÄISCHE NORM

February 2013

ICS 73.020; 91.100.15

English Version

## Natural stone test methods - Determination of resistance of marble to thermal and moisture cycles

Méthodes d'essai pour pierres naturelles - Détermination de la résistance du marbre aux cycles thermiques et d'humidité

Prüfverfahren für Naturstein - Bestimmungen der Beständigkeit von Marmor bei zyklischer Belastung mit Wärme und Feuchtigkeit

This European Standard was approved by CEN on 7 December 2012.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

	Page
<b>Foreword</b> .....	<b>3</b>
1 <b>Scope</b> .....	4
2 <b>Normative references</b> .....	4
3 <b>Terms and definitions</b> .....	4
4 <b>Principle</b> .....	4
5 <b>Symbols</b> .....	5
6 <b>Apparatus</b> .....	5
7 <b>Preparation of specimens</b> .....	9
7.1 <b>Sampling</b> .....	9
7.2 <b>Test specimens</b> .....	9
7.3 <b>Reference marks on the specimens</b> .....	10
7.4 <b>Drying the specimen</b> .....	10
8 <b>Test procedure</b> .....	10
8.1 <b>Control measurements before cycling</b> .....	10
8.2 <b>Procedure for bow measurement</b> .....	10
8.3 <b>Readings, exposure and duration of test</b> .....	10
8.4 <b>Measurements after exposure</b> .....	10
9 <b>Calculation of results</b> .....	11
9.1 <b>Bowing magnitude</b> .....	11
9.2 <b>Flexural strength</b> .....	11
10 <b>Precision</b> .....	12
11 <b>Test report</b> .....	12
<b>Annex A (informative) Guidance on limit values</b> .....	<b>13</b>
A.1 <b>General</b> .....	13
A.2 <b>Flexural strength</b> .....	13
<b>Annex B (informative) Non-destructive testing</b> .....	<b>14</b>
B.1 <b>General</b> .....	14
B.2 <b>Ultrasonic velocity</b> .....	14
B.3 <b>Modulus of elasticity</b> .....	15
<b>Annex C (informative) Enhanced petrographic analysis</b> .....	<b>16</b>
C.1 <b>General</b> .....	16
<b>Bibliography</b> .....	<b>18</b>

## Foreword

This document (EN 16306:2013) has been prepared by Technical Committee CEN/TC 246 "Natural stones", the secretariat of which is held by UNI.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by August 2013, and conflicting national standards shall be withdrawn at the latest by August 2013.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

According to the CEN/CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

## 1 Scope

This European Standard specifies a laboratory method for determining the resistance to thermal and moisture cycling of marble intended for cladding of building facades.

For scientific definition of marble, reference is made to EN 12670:2001, Terminology: 2.1.243 a.

NOTE Bowing and rapid strength loss is known to occur in some marbles when used as exterior claddings.

## 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 12372, *Natural stone test methods – Determination of flexural strength under concentrated load*

EN 12670:2001, *Natural stone – Terminology*

EN 13161, *Natural stone test methods – Determination of flexural strength under constant moment*

EN 14146, *Natural stone test methods – Determination of the dynamic modulus of elasticity (by measuring the fundamental resonance frequency)*

EN 14579, *Natural stone test methods – Determination of sound speed propagation*

EN ISO 4892-1:2000, *Plastics - Methods of exposure to laboratory light sources - Part 1: General guidance (ISO 4892-1:1999)*

## 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

### 3.1

#### **bowing**

change in shape from flat and planar to a curved or dished shape in a convex or concave direction

Note 1 to entry: Other terms commonly used for the same phenomenon are dishing and warping. Convex bowing is quantified by positive values, concave bowing by negative values.

### 3.2

#### **convex**

centre part of the specimen is bowing upwards, away from the moist substratum

### 3.3

#### **concave**

centre part of the specimen is bowing downwards, against the moist substratum

## 4 Principle

Bowing is measured on test samples exposed to moisture from beneath and heating from above. The temperature interval is from 20°C to 80°C, one cycle completed each 24 h. The 80 °C is measured on a black reference, placed on the surface of one specimen to control the climate of the chamber/bath.