Plastics piping systems for non-pressure underground drainage and sewerage - Structured-wall piping systems of unplasticized poly(vinyl chloride) (PVC-U), polypropylene (PP) and polyethylene (PE) - Part 1:General requirements and performance characteristics



EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

	This Estonian standard EVS-EN 13476-1:2018 consists of the English text of the European standard EN 13476-1:2018.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas.	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 04.04.2018.	Date of Availability of the European standard is 04.04.2018.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile <u>standardiosakond@evs.ee</u>.

ICS 23.040.01, 93.030

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega: Koduleht <u>www.evs.ee</u>; telefon 605 5050; e-post <u>info@evs.ee</u>

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:

Homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

EUROPEAN STANDARD

EN 13476-1

NORME EUROPÉENNE

EUROPÄISCHE NORM

April 2018

ICS 23.040.01; 93.030

Supersedes EN 13476-1:2007

English Version

Plastics piping systems for non-pressure underground drainage and sewerage - Structured-wall piping systems of unplasticized poly(vinyl chloride) (PVC-U), polypropylene (PP) and polyethylene (PE) - Part 1:General requirements and performance characteristics

Systèmes de canalisations en plastique pour les branchements et les collecteurs d'assainissements sans pression enterrés - Systèmes de canalisations à parois structurées en poly(chlorure de vinyle) non plastifié (PVC-U), polypropylène (PP) et polyéthylène (PE) -Partie 1: Exigences générales et caractéristiques de performance Kunststoff-Rohrleitungssysteme für erdverlegte drucklose Abwasserkanäle und -leitungen -Rohrleitungssysteme mit profilierter Wandung aus weichmacherfreiem Polyvinylchlorid (PVC-U), Polypropylen (PP) und Polyethylen (PE) - Teil 1: Allgemeine Anforderungen und Leistungsmerkmale

This European Standard was approved by CEN on 8 February 2018.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Cont	tents	Page
Furon	oean foreword	4
-	duction	
11111 OU 1	Scope	
ı		
2	Normative references	
3 3.1	Terms and definitions	
3.1 3.2	Terms and definitionsSymbols and abbreviations	
4	Material	
+ 4.1	General	11 11
4.2	Utilization of non-virgin material	
4.3	Sealing ring retaining components	
4.4	Sealing rings	
4.5	Fused or welded joints	
4.6	Adhesives for PVC-U	
5	Designation of wall construction	
6	Appearance and colour	
6.1	Appearance	
6.2	Colour	12
7	Geometrical characteristics	
8	Types of fittings	12
8.1	General	
8.2	Design length of fittings	
9	System performance related test methods and characteristics	
10	Marking, general	
10.1	Presentation	
10.2	Marking process	
10.3	Size	
Annex	x A (informative) Characteristics of PVC-U, PP and PE pipes and fittings	
4.1	General	18
A.2	Material characteristics	18
A.3	Chemical resistance	18
A.4	Abrasion resistance	
A.5	Hydraulic roughness	19
Annex	x B (informative) Structural design	
	x C (informative) Designation of pipes and corresponding fittings	
	x D (informative) Guidance in cleaning plastics pipes	
D.1	Introduction	
		

D.2	Cleaning and unblocking	22
D.3	Conclusions from independent jetting tests	23
D.4	Supplementary cleaning techniques	23
D.5	Recommended practice principles for jetting	24
Biblio	ography	26

European foreword

This document (EN 13476-1:2018) has been prepared by Technical Committee CEN/TC 155 "Plastics piping systems", the secretariat of which is held by NEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by October 2018, and conflicting national standards shall be withdrawn at the latest by October 2018.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN not be held responsible for identifying any or all such patent rights.

This document supersedes EN 13476-1:2007.

The main changes with respect to the previous edition are listed below:

- a) updating of references in Clause 2, Table 2 and Bibliography;
- b) deletion of Note 3 (Scope);
- c) definition fabricated fitting changed (3.1.1.3);
- d) clarification requirements sealing ring (4.4);
- e) extension of nominal sizes range (Table 1, Table 2);
- f) substitute "DURABILITY" Table 2;
- g) new reference for hydraulic roughness (A.5);
- h) text updated and new reference (Annex B);
- i) adhesives PVC-U added (4.6);
- j) saddle branches deleted (8.1);
- k) updated with new CEN template (entire document).

This standard is a part of a System Standard for plastics piping systems of particular materials for specified applications. There are a number of such System Standards.

System Standards are based on the results of the work being undertaken in ISO/TC 138 "Plastics pipes, fittings and valves for the transport of fluids", which is a Technical Committee of the International Organization for Standardization (ISO).

They are supported by separate standards on test methods to which references are made throughout the System Standard.

The System Standards are consistent with general standards on functional requirements and on recommended practice for installation.

EN 13476 consists of the following parts under the general title "Plastics piping systems for non-pressure underground drainage and sewerage — Structured-wall piping systems of unplasticized poly(vinyl chloride) (PVC-U), polypropylene (PP) and polyethylene (PE)":

- Part 1: General requirements and performance characteristics (this standard);
- Part 2: Specifications for pipes and fittings with smooth internal and external surface and the system,
 Type A;
- Part 3: Specifications for pipes and fittings with smooth internal and profiled external surface and the system, Type B:
- Part 4: Assessment of conformity.

National standards specifically for pipes and fittings for the transport of surface water are not considered to be conflicting with this standard and may thus be allowed to coexist.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, ant omans. France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Introduction

Due to the variety in materials, pipe constructions, application areas and classes, several combinations are possible.

n. each count a rodes. The purchaser or specifier may select between these possibilities by designating the pipe and fitting he or she prefers to use for each case, as described in Annex C "Designation of pipes and corresponding fittings", taking into account any particular requirements and relevant national regulations and installation practices or codes.

1 Scope

This European Standard, together with EN 13476-2 and EN 13476-3, specifies the definitions and general requirements for pipes, fittings and the system based on unplasticized poly(vinyl chloride) (PVC-U), polypropylene (PP) and polyethylene (PE) structured-wall piping systems that are to be used for non-pressure underground drainage and sewerage systems.

This standard is applicable to:

- a) structured-wall pipes and fittings, which are to be used buried in the ground outside a building structure only; reflected by the marking of products by "U";
- b) structured-wall pipes and fittings, which are to be used buried in ground both outside (application area code "U") and within a building structure (application area code "D"); reflected in the marking of products by "UD".

In conjunction with EN 13476-2 and EN 13476-3, it is applicable to structured-wall pipes and fittings with or without an integral socket with elastomeric ring seal joints, as well as welded and fused joints.

This part specifies general aspects and gives guidance concerning a national selection of requirement levels and classes where part 2 and part 3 of this standard provide options.

EN 13476-2 and EN 13476-3 specify material characteristics, dimensions and tolerances, test methods, test parameters and requirements for pipes with smooth internal and external surfaces, Type A, and pipes with smooth internal and profiled external surfaces, Type B.

This standard, together with EN 13476-2 and EN 13476-3, covers a range of pipe and fitting sizes, materials, pipe constructions, stiffness classes and tolerance classes and offers recommendations concerning colours.

NOTE 1 It is the responsibility of the purchaser or specifier to make the appropriate selections from these aspects, taking into account their particular requirements and any relevant national regulations and installation practices or codes.

NOTE 2 Pipes, fittings and other components conforming to any plastic product standards referred to in Clause 2 can be used with pipes and fittings conforming to this standard, when they conform to the requirements for joint dimensions given in part 2 and part 3 of this standard and to the performance requirements given in Clause 9.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 681-1, Elastomeric seals — Materials requirements for pipe joint seals used in water and drainage applications — Part 1: Vulcanized rubber

EN 681-2, Elastomeric Seals — Materials requirements for pipe joint seals used in water and drainage applications — Part 2: Thermoplastic elastomers

EN 681-4, Elastomeric seals — Materials requirements for pipe joint seals used in water and drainage applications — Part 4: Cast polyurethane sealing elements

EN 13476-2:2018, Plastics piping systems for non-pressure underground drainage and sewerage — Structured-wall piping systems of unplasticized poly(vinyl chloride) (PVC-U), polypropylene (PP) and

polyethylene (PE) — Part 2: Specifications for pipes and fittings with smooth internal and external surface and the system, Type A

EN 13476-3.2018, Plastics piping systems for non-pressure underground drainage and sewerage — Structured-wall piping systems of unplasticized poly(vinyl chloride) (PVC-U), polypropylene (PP) and polyethylene (PE) — Part 3: Specifications for pipes and fittings with smooth internal and profiled external surface and the system, Type B

EN ISO 472, Plastics — Vocabulary (ISO 472)

EN ISO 1043-1, Plastics — Symbols and abbreviated terms — Part 1: Basic polymers and their special characteristics (ISO 1043-1)

EN ISO 9969, Thermoplastics pipes — Determination of ring stiffness (ISO 9969)

EN ISO 13967, Thermoplastics fittings — Determination of ring stiffness (ISO 13967)

ISO 11922-1, Thermoplastics pipes for the conveyance of fluids — Dimensions and tolerances — Part 1: Metric series

3 Terms and definitions

For the purposes of this document, the terms and definitions given in EN ISO 472, EN ISO 1043-1, ISO 11922-1 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

3.1 Terms and definitions

3.1.1 General definitions

3.1.1.1

application area code

code used to mark pipes and fittings to indicate the permitted application area(s) for which they are intended

Example 1: U: code for the area more than 1 m from the building to which the buried piping system is connected

Example 2: D: code for the area under and within 1 m from the building where the pipes and fittings are buried underground and are connected to the soil and waste discharge system of the building

Note 1 to entry: In the "D" application area, the existence of hot water discharge in addition to external forces from the surroundings is usual.