TECHNICAL SPECIFICATION SPÉCIFICATION TECHNIQUE TECHNISCHE SPEZIFIKATION

CEN ISO/TS 25377

October 2007

ICS 17.120.20

English Version

Hydrometric uncertainty guidance (HUG) (ISO/TS 25377:2007)

Lignes directrices relatives à l'incertitude en hydrométrie (ISO/TS 25377:2007)

Leitfaden zu Messunsicherheiten in der Hydrometrie (HUG) (ISO/TS 25377:2007)

This Technical Specification (CEN/TS) was approved by CEN on 2 August 2007 for provisional application.

The period of validity of this CEN/TS is limited initially to three years. After two years the members of CEN will be requested to submit their comments, particularly on the question whether the CEN/TS can be converted into a European Standard.

CEN members are required to announce the existence of this CEN/TS in the same way as for an EN and to make the CEN/TS available promptly at national level in an appropriate form. It is permissible to keep conflicting national standards in force (in parallel to the CEN/TS) until the final decision about the possible conversion of the CEN/TS into an EN is reached.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom. it -V I Q Z C



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Ref. No. CEN ISO/TS 25377:2007: E

Foreword

This document (CEN ISO/TS 25377:2007) has been prepared by Technical Committee CEN/TC 318 "Hydrometry", the secretariat of which is held by BSI, in collaboration with Technical Committee ISO/TC 113 "Hydrometric determinations".

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to announce this European Standard: Austria, Belgium, Bulgaria, Cyprus, Czech Fr. a, Net. e United. Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

Contents

-		
Forewo	Dra	IV
Introdu	iction	V
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols and abbreviations	2
5	ISO/IEC Guide 98 (GUM) — Basic definitions and rules	4
5.1	General	4
5.2 5.3	Random and systematic effects	4 4
5.4	Uncertainty models — Probability distributions	5
5.5	Combining uncertainties — The law of propagation	5
5.6	Expressing results	6
6 6 1	Open channel flow — Velocity area methods	6
6.2	Mean velocity \overline{V}	0
6.3	Velocity-area determination	7 8
6.4	Stationary determination of velocity.	9
6.5	Moving determination of velocity	10
6.6	Velocity-area uncertainties	11
6.7	Integration uncertainties $\begin{bmatrix} u & (F_y), u & (F_z) \end{bmatrix}$	15
6.8	Perimeter flow uncertainties, $u(Q_p)$	16
7	Open channel flow — Critical depth methods	16
7.1	General	16
7.3	Iterative calculation	17
7.4	Evaluating uncertainty	18
8	Dilution methods	18
8.1	General	18
8.2	Continuous feed	19
8.3	i ransient mass	20
9	Hydrometric instrumentation	21
9.2	Validity of uncertainty statements	21
9.3	Manufacturer's performance specifications	22
9.4	Performance guide for hydrometric equipment for use in technical standard examples	23
10	Guide for the drafting of uncertainty clauses in hydrometric standards	24
10.1	General	24
	Δ (informative) Introduction to hydrometric uncertainty	24 26
	R (informative) An introduction to Monto Carlo Simulation (MCS)	20 12
Annex	C (informative) Berformance guide for hydrometric equipment for use in technical	43
Annex	standard examples	48
Biblioa	iraphy	51
	·····	

Introduction

The management of a natural environment requires knowledge, by measurement, of what is happening. Only then can effective action be taken and the effectiveness of the action assessed. Much depends on the quality of the knowledge itself.

The quality of measurable knowledge is stated in terms of measurement uncertainty. The internationally agreed method for assessing measurement quality is the *Guide to the estimation of uncertainty in measurement* (GUM). Without this uniformity of measurement standards, equitable sharing of the environment is not possible and international obligations to care for the environment would be weakened.

The essential purpose of the GUM is that a statement of the quality of a measurement result will be presented with all measurements described in technical standards. Without this, no two measurements can be compared or standards set. Whereas the GUM is a reference document serving the universal requirements of metrology, the *Hydrometric uncertainty guidance (HUG)* document is specific to hydrometry, i.e. to the measurement of the components of the hydrological cycle. It borrows from the GUM the methods that are the most applicable to hydrometry and applies them to techniques and equipment used in hydrometry.

In the past, error analysis has provided an indication of measurement quality, but such statements cannot properly convey the quality of the result because it presupposes a knowledge of a true, error-free, value against which the measured result can be compared. The true value can never be known. Uncertainty therefore remains. For this reason, the GUM uses the concept of uncertainty and uses it for all stages and components of the measurement process. This ensures consistency.

The GUM defines standard uncertainty of a result as being equivalent to a standard deviation. This can be the standard deviation of a set of measured values or of probable values. This is broadly similar to the approach used in error analysis that preceded the uncertainty technique. However, the GUM provides additional methods of estimating uncertainty based on probability models. The two approaches are equivalent but uncertainty requires only a knowledge or estimate of the dispersion of measurement about its mean value, and not the existence of a true value. It is assumed that a careful evaluation of the components of measurement uncertainty brings the mean value close to a probable true value, at least well within its margin of uncertainty.

In more general terms, uncertainty is a parameter that characterizes the dispersion of measurable values that can be attributed to their mean value.

By treating standard deviations and probability models as if they approximated to Gaussian (or normal) distributions, the GUM provides a formal methodology for combining components of uncertainty in measurement systems where several input variables combine to determine the result.

Within this formal framework, the GUM can be consistently applied to a range of applications and, thereby, be used to make meaningful comparisons of results.

The HUG seeks to promote an understanding of the nature of measurement uncertainty and its significance in estimating the 'quality' of a measurement or a determination in hydrometry.

Hydrometry is principally concerned with the determination of flow in rivers and man-made channels. This includes

- environmental hydrometry, i.e. the determination of the flow of natural waters (largely concerned with hydrometric networks, water supply and flood protection),
- industrial hydrometry, i.e. the determination of flows within industrial plants and discharges into the natural environment (largely concerned with environment protection and also irrigation).

Both are the subject of international treaties and undertakings. For this reason, measured data needs to conform to the GUM to assure that results can be compared.

Hydrometry is also concerned with the determination of rainfall, the movement/diffusion of groundwater and the transport by water flow of sediments and solids. This version of the HUG is concerned with flow determination only.

The results from hydrometry are used by other disciplines to regulate and manage the environment. If knowledge is required of biomass, sedimentary material, toxins, etc., the concentration of these components is determined and their uncertainty estimated. The uncertainty of mass-load can then be determined from the uncertainty of flow determination. The components of this calculation are made compatible through compliance with the GUM.

For practitioners of hydrometry and for engineers, the GUM is not a simple document to refer to. The document has been drafted to provide a legal framework for professional metrologists with a working knowledge of statistical methods and their mathematical representation. A helpful document, NIST Technical Note 1297 ^[12], is an abbreviated version of the GUM written to be more accessible to engineers and to specialists in fields other than metrology.

The HUG, although simplifying the concepts, in no way conflicts with the principles and methods of the GUM. Accordingly, the HUG interprets the GUM to apply its requirements to hydrometry in a practical way, and, hopefully, in a way accessible to engineers and those responsible for managing the environment.

In addition, the HUG introduces and develops Monte Carlo Simulation, a complementary technique, which has benefits for hydrometry, insomuch as complex measurement systems can be represented realistically.

The HUG summarizes basic hydrometric methods defined in various technical standards. The HUG develops uncertainty estimation formulae from the GUM for these basic methods. The basic hydrometric methods described in the HUG may not be identical to those recited in the published technical standards. In such cases, the methods described in these standards are to be taken as authoritative. However, clauses in technical standards that concern uncertainty should be adapted to be in accordance with the HUG.

NOTE There is no unified definition of space coordinates within the hydrometric standards. The textbook conventional axes are adopted in this document when describing open channel flow: the x axis being horizontal and positive in the mean flow direction, the y axis being orthogonal to the x axis in the horizontal plane and the z axis being vertical positive.

Hydrometric uncertainty guidance (HUG)

1 Scope

This Technical Specification provides an understanding of the nature of measurement uncertainty and its significance in estimating the 'quality' of a measurement or a determination in hydrometry.

It is applicable to flow measurements in natural and man-made channels. Rainfall measurements are not covered.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 772, Hydrometric determinations — Vocabulary and symbols

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 772 and the following apply.

NOTE For a complete appreciation of the scope of definitions used in measurement uncertainty, the reader is referred to the GUM ^[10] or to NIST Technical Note 1297 ^[12].

3.1

standard uncertainty

uncertainty of the result of a measurement expressed as a standard deviation

3.2

type A evaluation of uncertainty

method of evaluation uncertainty by the statistical analysis of a series of observations

3.3

type B evaluation of uncertainty

method of evaluation uncertainty by means other than the statistical analysis of a series of observations

3.4

combined standard uncertainty

standard uncertainty of the result of a measurement when that result is obtained from the values of a number of other quantities, equal to the positive square root of a sum of terms, the terms being the variances or covariances of these other quantities weighted according to how the measurement result varies with changes in these quantities

3.5

expanded uncertainty

quantity defining an interval about the result of a measurement that may be expected to encompass a large fraction of the values that could be attributed to the measurand