
Wheelchairs —

Part 19:
**Wheeled mobility devices for use as
seats in motor vehicles**

Fauteuils roulants —

*Partie 19: Dispositifs de mobilité montés sur roues et destinés à être
utilisés comme sièges dans des véhicules à moteur*



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

This document is a preview generated by EVS



COPYRIGHT PROTECTED DOCUMENT

© ISO 2008

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	iv
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions.....	2
4 Design requirements	6
4.1 Wheelchair securement	6
4.2 Occupant restraints.....	6
4.2.1 Wheelchair-anchored pelvic-belt restraint.....	6
4.2.2 Wheelchair-anchored shoulder-belt restraint.....	8
4.2.3 Accommodation of vehicle-anchored occupant belt restraints	9
5 Performance requirements.....	10
5.1 Wheelchair-anchored belt restraints	10
5.2 Frontal impact	11
5.2.1 During the test.....	11
5.2.2 After the test.....	12
5.3 Accessibility of securement points intended for use with four-point strap-type tiedowns with hook-type end-fittings.....	13
5.4 Accommodation of vehicle-anchored belt restraints.....	13
6 Identification, labelling, user instructions, warning, and disclosure requirements	13
6.1 Identification and labelling	13
6.2 Presale literature.....	14
6.3 User and maintenance instructions.....	14
7 Documentation of compliance	17
7.1 General.....	17
7.2 Frontal impact test.....	17
7.3 Design, labelling, and literature requirements	18
Annex A (normative) Method for frontal impact test.....	19
Annex B (normative) Geometric specifications for securement points on wheelchairs intended for attachment of four-point strap-type tiedowns	27
Annex C (normative) Method for testing accessibility of wheelchair securement points intended for attachment of four-point strap-type tiedowns	29
Annex D (normative) Methods for rating wheelchair accommodation of vehicle-anchored belt restraints.....	32
Annex E (informative) Guidelines for surrogate tiedown devices	37
Annex F (normative) Specifications for wheelchair universal docking interface geometry (UDIG).....	38
Bibliography	43

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 7176-19 was prepared by Technical Committee ISO/TC 173, *Assistive products for persons with disability*, Subcommittee SC 1, *Wheelchairs*.

This second edition cancels and replaces the first edition (ISO 7176-19:2001), most clauses of which have been technically revised.

ISO 7176 consists of the following parts, under the general title *Wheelchairs*:

- *Part 1: Determination of static stability*
- *Part 2: Determination of dynamic stability of electric wheelchairs*
- *Part 3: Determination of effectiveness of brakes*
- *Part 4: Energy consumption of electric wheelchairs and scooters for determination of theoretical distance range*
- *Part 5: Determination of dimensions, mass and manoeuvring space*
- *Part 6: Determination of maximum speed, acceleration and deceleration of electric wheelchairs*
- *Part 7: Measurement of seating and wheel dimensions*
- *Part 8: Requirements and test methods for static, impact and fatigue strengths*
- *Part 9: Climatic tests for electric wheelchairs*
- *Part 10: Determination of obstacle-climbing ability of electrically powered wheelchairs*
- *Part 11: Test dummies*
- *Part 13: Determination of coefficient of friction of test surfaces*
- *Part 14: Power and control systems for electrically powered wheelchairs and scooters — Requirements and test methods*

- *Part 15: Requirements for information disclosure, documentation and labelling*
- *Part 16: Resistance to ignition of upholstered parts — Requirements and test methods*
- *Part 19: Wheeled mobility devices for use as seats in motor vehicles*
- *Part 21: Requirements and test methods for electromagnetic compatibility of electrically powered wheelchairs and scooters, and battery chargers*
- *Part 22: Set-up procedures*
- *Part 23: Requirements and test methods for attendant-operated stair-climbing devices*
- *Part 24: Requirements and test methods for user-operated stair-climbing devices*
- *Part 25: Requirements and test methods for batteries and their chargers for electrically powered wheelchairs and motorized scooters*
- *Part 26: Vocabulary*

A technical report, ISO/TR 13570-1, is also available, giving a simplified explanation of these parts of ISO 7176.

Introduction

Transportation safety research has shown that the vehicle seat is an important part of the occupant-restraint system and therefore plays a key role in reducing the risk of serious injuries to vehicle occupants in many types of vehicle crashes. In particular, the seat needs to allow and facilitate the proper positioning of belt restraints on the skeletal regions of the occupant, not add to occupant loads during impact loading, and provide effective support for the occupant so that the belt restraint will remain in place over skeletal regions throughout a crash. People with physical disabilities must often remain in their wheelchairs whilst travelling in motor vehicles as drivers or passengers. Since many wheelchairs were not designed for this purpose, wheelchair-seated occupants are often at higher risk of injury in crashes than are people seated in seats provided by the vehicle manufacturer.

ISO 10542-1 provides design, performance, labelling, and the manufacturer's literature requirements, and specifies associated test methods, for wheelchair tiedown and occupant-restraint systems (WTORS). This part of ISO 7176 addresses the seating part of wheelchair-user occupant-protection systems by establishing design, performance, labelling, and the manufacturer's literature requirements, as well as associated test methods, for wheelchairs that may be used as seats in motor vehicles.

Whilst wheelchairs may be secured by various types of tiedown and securement systems that were available throughout the world at the time this part of ISO 7176 was developed, effective wheelchair securement in the real world requires compatibility of the wheelchair tiedown system available in the vehicle and the method of securement provided on the wheelchair. At the time that this part of ISO 7176 was developed, the four-point strap-type tiedown was considered to be the most effective, common, and universally adaptable system for securing a wide range of wheelchair types and sizes. For these reasons, this part of ISO 7176 requires that wheelchairs intended for use as seats in motor vehicles provide for securement using a four-point strap-type tiedown system by providing at least four designated securement points, with two in front and two in the back. However, this part of ISO 7176 also provides for evaluating wheelchairs that are also designed for securement by other methods, such as docking-type securement systems.

To evaluate the crashworthiness performance of a wheelchair, Annex A specifies procedures for dynamically testing a wheelchair loaded with an appropriate-size crash-test dummy using a 48 km/h crash pulse with the wheelchair secured facing forward on the impact sled. This test is based on well-documented motor vehicle crash and injury statistics, which show that more than 50 % of all serious injuries to occupants of motor vehicles occur in frontal crashes, and that more than 95 % of frontal crashes result in a longitudinal change in vehicle speed of less than 48 km/h. Dynamic performance for forward-facing wheelchairs in rear and side impacts might be addressed in future International Standards.

This part of ISO 7176 has also been developed with the recognition that the use of a pelvic-belt restraint alone does not provide the wheelchair occupant with the same level of crash protection in a frontal impact as the use of both pelvic-belt and shoulder-belt restraints. Therefore, the provisions and test methods of this part of ISO 7176 are based on the use of both pelvic- and shoulder-belt-type restraints.

Although the four-point strap-type tiedown system was considered to be the most common and universal method for effectively securing a wide range of wheelchairs at the time this part of ISO 7176 was developed, it is a method of wheelchair securement that requires the involvement of a second person and cannot be implemented by the wheelchair occupant. Accordingly, it is desirable to progress toward a securement method that can be implemented independently by the wheelchair-seated passenger who may travel in different public transportation and private vehicles. As a step toward this goal, this part of ISO 7176 includes a normative annex (Annex F) that establishes universal docking interface geometry (UDIG) for securement points on wheelchairs when it is intended for the wheelchair to be secured by docking-type securement devices in public transportation and/or multiple private vehicles.

Finally, this part of ISO 7176 can be viewed in the totality of daily wheelchair use and the range of standards to which all wheelchairs are expected to comply. Wheelchairs are designed primarily to serve as effective mobility devices and, in that respect, they must first conform to the applicable requirements set forth in other

parts of the ISO 7176 series. Transportation is only one of many daily activities that introduce unique circumstances and requirements that wheelchairs and wheelchair occupants may experience. Wheelchair products that comply with this part of ISO 7176 will have additional features that provide increased levels of occupant security and safety whilst their occupants are riding in motor vehicles. However, a wheelchair's failure to comply with this part of ISO 7176 cannot be used to limit access to, and availability of, motor vehicle transportation for wheelchair users.

This document is a preview generated by EVS

This document is a preview generated by EVS

Wheelchairs —

Part 19:

Wheeled mobility devices for use as seats in motor vehicles

1 Scope

This part of ISO 7176 applies to all manual and powered wheelchairs, including scooters, which, in addition to their primary function as wheeled mobility devices, are also likely to be used as forward-facing seats in motor vehicles by children and adults with a body mass equal to or greater than 22 kg. This part of ISO 7176 specifies wheelchair design requirements, performance requirements and associated test methods, and requirements for wheelchair labelling, presale literature, user instructions and user warnings. It applies to complete wheelchairs, including a base frame and seating system, as well as to wheelchairs equipped with add-on adaptive components designed to facilitate compliance with one or more of the requirements.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3795, *Road vehicles, and tractors and machinery for agriculture and forestry — Determination of burning behaviour of interior materials*

ISO 6487, *Road vehicles — Measurement techniques in impact tests — Instrumentation*

ISO 7176-5, *Wheelchairs — Part 5: Determination of dimensions, mass and manoeuvring space*

ISO 7176-15:1996, *Wheelchairs — Part 15: Requirements for information disclosure, documentation and labelling*

ISO 7176-22:2000, *Wheelchairs — Part 22: Set-up procedures*

ISO 7176-26:2007, *Wheelchairs — Part 26: Vocabulary*

ISO 10542-1, *Technical systems and aids for disabled or handicapped persons — Wheelchair tiedown and occupant-restraint systems — Part 1: Requirements and test methods for all systems*

ISO 10542-2, *Technical systems and aids for disabled or handicapped persons — Wheelchair tiedown and occupant-restraint systems — Part 2: Four-point strap-type tiedown systems*

FMVSS 209:2004, Standard No. 209, *Seat belt assemblies*. Federal Motor Vehicle Safety Standards, 49 CFR 571.209, 1 October, 2004

ECE Regulation 16, *Uniform provisions concerning the approval of safety belts and restraint systems for adult occupants of power-driven vehicles*, Revision 3, Amendment 2, 16 August 1993