INTERNATIONAL STANDARD

ISO 4586-3

First edition 2015-11-01

High-pressure decorative laminates (HPL, HPDL) — Sheets based on thermosetting resins (Usually called Laminates) —

Part 3:

Classification and specifications for laminates less than 2 mm thick and intended for bonding to supporting substrates

Stratifiés décoratifs haute pression (HPL, HPDL) — Plaques à base de résines thermodurcissables (communément appelées stratifiés) —

Partie 3: Classification et spécifications des stratifiés d'épaisseur moins de 2 mm d'épaisseur et destiné pour le collage de support





© ISO 2015, Published in Switzerland

voduced or utilized c te internet or an 'nr ISO's memb All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Ch. de Blandonnet 8 • CP 401 CH-1214 Vernier, Geneva, Switzerland Tel. +41 22 749 01 11 Fax +41 22 749 09 47 copyright@iso.org www.iso.org

Contents			Page
For	eword		iv
1	Scop	e	1
2	Norn	native references	1
3	50	ns and definitions	
4		rial types	
5	Requirements		
	5.1	General	
	5.2	Numerical classification system	
	5.3 5.4	Alphabetical classification systemNomenclature	
_	_		
6	Requ 6.1	irements Compliance	
	6.2	Inspection requirements	
		6.2.1 General	
		6.2.2 Colour and pattern 6.2.3 Surface finish	
		6.2.4 Reverse side	
		6.2.5 Visual inspection	
	6.3	Dimensional tolerance requirements	
	6.4	Test requirements 6.4.1 General requirements	
		6.4.2 Additional requirements for Type P laminates	
		6.4.3 Notes on requirements for reaction to fire (see <u>Annex B</u>)	
Ann	ex A (in	formative) Addendum to Table 5 relating to Test Method 29: Scratch Resistance	10
Ann	ex B (in	formative) Addendum to 6.4.3, relating to fire performance	11
		formative) Addendum relating to electrostatic properties	
		ıy	

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2. www.iso.org/directives

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received. www.iso.org/patents

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT), see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 61, *Plastics*, Subcommittee SC 11, *Products*.

This first edition of ISO 4586-3:2015 cancels and replaces (ISO 4586-1:2004), which has been technically revised.

ISO 4586 consists of the following parts, under the general title *Plastics* — *High-Pressure Decorative Laminates (HPL, HPDL)* — *Sheets based on Thermosetting Resins (Usually called Laminates):*

- Part 1: Introduction and general Information
- Part 2: Determination of properties
- Part 3: Classification and specifications for laminates less than 2 mm thick intended for bonding to supporting substrates
- Part 4: Classification and specifications for compact laminates of thickness 2 mm and greater
- Part 5: Classification and specifications for flooring grade laminates less than 2 mm thick intended for bonding to supporting substrates
- Part 6: Classification and specifications for exterior-grade compact laminates of thickness 2 mm and areater
- Part 7: Classification and specifications for design laminates
- Part 8: Classification and specifications for alternative core laminates

High-pressure decorative laminates (HPL, HPDL) — Sheets based on thermosetting resins (Usually called Laminates) —

Part 3:

Classification and specifications for laminates less than 2 mm thick and intended for bonding to supporting substrates

1 Scope

This part of ISO 4586 applies to laminates less than 2 mm thick normally intended for bonding to supporting substrates to produce HPL composite panels and establishes a classification system for high-pressure decorative laminates according to their performance and main recommended fields of application, including materials with special characteristics, for example formability or defined reaction to fire. This part of ISO 4586 also specifies requirements for the properties of the various types of laminates covered by this classification system.

High-pressure decorative laminates are characterized by their qualities, durability and functional performance. HPL sheets are available in a wide variety of colours, patterns and surface finishes; they are resistant to wear, scratching, impact, moisture, heat and staining; and possess good hygienic and anti-static properties, being easy to clean and maintain.

ISO 4586-2 specifies the methods of test relevant to this part of ISO 4586. ISO 4586-4 through ISO 4586-8 are reserved for special types of HPL materials.

In an effort to harmonize ISO 4586 with other High-Pressure Decorative Laminate standards, multiple methods may be published that demonstrate similar properties. In these instances, the same test method title is given and is annotated as either "Method A" or "Method B". This is the case in the following tests: Edge Squareness - 8/9, Dry Heat - 17/18 Dimensional Stability at Elevated Temperatures - 19/20, Dimensional Stability at Ambient Temperature - 21/22, Staining - 30/31, Lightfastness - 32/33, Cigarette Burns - 36/37, Formability - 38/39, and Blistering - 40/41. In these instances, either method may be utilized in testing. Compliance to both methods is not required. While these tests are similar they are by no means identical and results of one method do not necessarily correspond to the results of the accompanying test. In these situations, consult the documentation in specific clauses of ISO 4586 for performance requirements. Each specific method has performance requirements particular to that method for individual grades of high-pressure decorative laminate.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 4586-2, High-pressure decorative laminates (HPL, HPDL) — Sheets based on thermosetting resins (Usually called Laminates) — Part 2: Determination of properties

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.