
**Information technology —
Telecommunications and information
exchange between systems — Using
CSTA for SIP phone user agents
(uaCSTA)**

*Technologies de l'information — Télécommunications et échange
d'information entre systèmes — Utilisation de CSTA pour agents
d'utilisateurs de téléphone de SIP (uaCSTA)*

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

This document is a preview generated by EVS

© ISO/IEC 2005

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	vii
Introduction.....	viii
1 Scope.....	1
2 Purpose.....	1
3 Normative references.....	2
4 Terminology.....	2
4.1 General terms.....	2
4.2 SIP/CSTA Terminology Mappings.....	3
5 Example Environments for uaCSTA.....	3
5.1 Controlling and Observing a SIP Phone.....	3
5.2 Controlling and Observing a SIP Phone by Augmenting B2BUA Functionality.....	4
5.3 Controlling a PBX Phone.....	4
6 Example User Agent Configurations.....	5
6.1 Single Line Phone UA.....	5
6.2 Multi Line Phone UA.....	6
6.3 Bridged Appearance Phone and other Advanced UA Configurations.....	6
7 SIP Transport Mechanism for CSTA Messages.....	7
7.1 Establishing a CSTA Application Session.....	7
7.2 Transporting CSTA Service Requests and Responses.....	8
7.3 Starting a Monitor and Transporting CSTA Events.....	9
8 uaCSTA Profiles.....	9
8.1 Minimal uaCSTA Call Control Profile.....	10
8.1.1 Services.....	10
8.1.2 Events.....	10
8.2 Basic uaCSTA Call Control Profile.....	10
8.2.1 Services.....	10
8.2.2 Events.....	11
8.3 Advanced uaCSTA Call Control Profile.....	11
8.3.1 Services.....	11
8.3.2 Events.....	12
8.4 Conferencing uaCSTA Call Control Feature Profile.....	12
8.4.1 Services.....	12
8.4.2 Events.....	13
8.5 Basic uaCSTA Device Feature Profile.....	13
8.5.1 Services.....	13
8.5.2 Events.....	13
8.6 Speaker uaCSTA Device Feature Profile.....	13
8.6.1 Services.....	13
8.6.2 Events.....	13
9 CSTA Calls and Connections.....	13
9.1 CSTA Connection State Model.....	14
9.2 Connection State Transitions for CSTA Calls.....	14
9.2.1 Incoming Call.....	14
9.2.2 Outgoing Call.....	15
10 Call Control.....	15
10.1 Alternate Call.....	15
10.1.1 Service Request.....	16

10.1.2	Positive Service Response	16
10.1.3	Negative Service Response	16
10.2	Answer Call	17
10.2.1	Service Request	17
10.2.2	Positive Service Response	18
10.2.3	Negative Service Response	18
10.3	Clear Connection	19
10.3.1	Service Request	19
10.3.2	Positive Service Response	19
10.3.3	Negative Service Response	19
10.4	Consultation Call	20
10.4.1	Service Request	20
10.4.2	Positive Service Response	21
10.4.3	Negative Service Response	21
10.5	Deflect Call	22
10.5.1	Service Request	22
10.5.2	Positive Service Response	22
10.5.3	Negative Service Response	23
10.6	Generate Digits	23
10.6.1	Service Request	24
10.6.2	Positive Service Response	24
10.6.3	Negative Service Response	24
10.7	Hold Call	25
10.7.1	Service Request	25
10.7.2	Positive Service Response	25
10.7.3	Negative Service Response	26
10.8	Make Call	26
10.8.1	Service Request	26
10.8.2	Positive Service Response	27
10.8.3	Negative Service Response	27
10.9	Reconnect Call	28
10.9.1	Service Request	28
10.9.2	Positive Service Response	29
10.9.3	Negative Service Response	29
10.10	Retrieve Call	30
10.10.1	Service Request	30
10.10.2	Positive Service Response	30
10.10.3	Negative Service Response	30
10.11	Single Step Transfer Call	31
10.11.1	Service Request	31
10.11.2	Positive Service Response	32
10.11.3	Negative Service Response	32
10.12	Transfer Call	33
10.12.1	Service Request	33
10.12.2	Positive Service Response	34
10.12.3	Negative Service Response	34
11	Physical Phone Features	35
11.1	Get Message Waiting Indicator	35
11.1.1	Service Request	36
11.1.2	Service Response	36
11.2	Set Message Waiting Indicator	36
11.2.1	Service Request	36
11.2.2	Service Response	37
11.3	Get Speaker Mute	37
11.3.1	Service Request	37
11.3.2	Service Response	37
11.4	Set Speaker Mute	38
11.4.1	Service Request	38
11.4.2	Service Response	38

11.5	Get Speaker Volume	39
11.5.1	Service Request	39
11.5.2	Service Response	39
11.6	Set Speaker Volume	40
11.6.1	Service Request	40
11.6.2	Service Response	40
12	Logical Phone Features	41
12.1	Get Do Not Disturb	41
12.1.1	Service Request	41
12.1.2	Service Response	41
12.2	Set Do Not Disturb	41
12.2.1	Service Request	42
12.2.2	Service Response	42
12.3	Get Forwarding	42
12.3.1	Service Request	42
12.3.2	Service Response	42
12.4	Set Forwarding	43
12.4.1	Service Request	43
12.4.2	Service Response	44
13	Monitoring Services and Events	44
13.1	Monitor Start	44
13.1.1	Service Request	44
13.1.2	Positive Service Response	45
13.1.3	Negative Service Response	45
13.2	Monitor Stop	46
13.2.1	Service Request	46
13.2.2	Positive Service Response	47
13.2.3	Negative Service Response	47
13.3	Events	47
14	Snapshot Services	48
14.1	Snapshot Device	48
14.1.1	Service Request	48
14.1.2	Positive Service Response	48
14.1.3	Negative Service Response	51
15	Discovery and System Status Services	51
15.1	Get CSTA Features	51
15.1.1	Service Request	52
15.1.2	Service Response	52
15.1.3	Negative Service Response	53
15.2	Request System Status	53
15.2.1	Service Request	53
15.2.2	Service Response	53
15.2.3	Negative Service Response	54
15.3	System Status	54
15.3.1	Service Request	54
15.3.2	Positive Service Response	55
15.3.3	Negative Service Response	55
16	ECMA-323 Illustrative Examples	55
16.1	Controlling a SIP UA	55
16.1.1	Creating an Application Session, Establishing a Monitor for a SIP Phone	56
16.1.2	Creating a Call from a SIP UA, Clearing a Call at a SIP UA	58
16.1.3	Answering and Clearing an Incoming Call at a UA	63
16.1.4	Answering an Incoming Call at a UA (no CSTA monitor or CSTA events)	65
16.1.5	Examples of Exception Conditions at a SIP UA	67
16.2	Controlling a PBX Phone	68
16.2.1	Creating an Application Session, Establishing a Monitor for a PBX Phone	69
16.2.2	Creating a Call from a PBX Phone, Clearing a Call at a PBX Phone	71

16.2.3 Answering and Clearing an Incoming Call at a PBX Phone 75

16.2.4 Examples of Exception Conditions at a PBX Phone 78

Annex A (informative) Example use of SIP and TEL URIs..... 80

This document is a preview generated by EVS

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

In exceptional circumstances, the joint technical committee may propose the publication of a Technical Report of one of the following types:

- type 1, when the required support cannot be obtained for the publication of an International Standard, despite repeated efforts;
- type 2, when the subject is still under technical development or where for any other reason there is the future but not immediate possibility of an agreement on an International Standard;
- type 3, when the joint technical committee has collected data of a different kind from that which is normally published as an International Standard ("state of the art", for example).

Technical Reports of types 1 and 2 are subject to review within three years of publication, to decide whether they can be transformed into International Standards. Technical Reports of type 3 do not necessarily have to be reviewed until the data they provide are considered to be no longer valid or useful.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC TR 22767, which is a Technical Report of type [3], was prepared by Ecma International (as ECMA TR/87) and was adopted, under a special "fast-track procedure" by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 6, *Telecommunications and information exchange between systems*, in parallel with its approval by national bodies of ISO and IEC.

Introduction

This Technical Report illustrates how CSTA can be used over a SIP session to control and observe SIP user agents (uaCSTA).

This Technical Report is part of a suite of Ecma CSTA Phase III Standards and Technical Reports.

All of the Standards and Technical Reports in this suite are based upon the practical experience of Ecma member companies and each one represents a pragmatic and widely based consensus.

This document is a preview generated by EVS

Information technology — Telecommunications and information exchange between systems — Using CSTA for SIP phone user agents (uaCSTA)

1 Scope

The Session Initiation Protocol (SIP) is a control (signalling) protocol for creating, modifying, and terminating sessions with one or more participants. These sessions include Internet telephone calls, multimedia distribution, and multimedia conferences.

CSTA standardizes a very powerful and flexible set of application services to observe and control voice and non-voice media calls as well as control and observe non-call related features.

This Technical Report describes how CSTA can be used to provide a subset of CSTA call control functionality, called 1st party call control, for SIP user agents. The term uaCSTA (for user agent CSTA) refers to transporting ECMA-323 (CSTA XML) messages over a SIP session.

uaCSTA leverages SIP mechanisms to provide a highly featured, robust, and extensible set of features to support applications in the Enterprise environment.

uaCSTA can be implemented by several different types of SIP user agents:

- directly by a SIP user agent on a SIP phone
- uaCSTA can also be implemented by a SIP B2BUA to augment 3PCC functionality
- by a proxy server that is front-ending a PBX.

2 Purpose

- Describe the relevant portions of the CSTA Standards – The two primary CSTA Standards, Services for Computer Supported Telecommunications Applications (ECMA-269) and the XML Protocol for CSTA (ECMA-323), are relatively large standards (combined over 1100 pages). Due to their size it is sometimes difficult for SIP developers without prior knowledge of CSTA standards to quickly find the relevant parts of the CSTA standards needed to implement basic features. This TR shows the relevant CSTA concepts and how they can be used to implement a CSTA-based application protocol without having to read all of the CSTA Standards.
- Terminology – Although many of the concepts are similar, different terms are used in SIP and CSTA to describe the same concepts. Since CSTA is designed to be protocol independent, it is helpful to show how the abstract terminology of CSTA is mapped to SIP specific terminology.
- Extensibility - A SIP phone that is being developed to support a specific application may initially need to only support a small subset of the features standardized in CSTA. As the types and complexity of applications using these devices increase, it is expected that these devices will need to support additional, more advanced, features standardized by CSTA, similar to features supported by other types of phones in Enterprise environments. This TR shows how basic features can be extended to support a rich standards-based feature set for applications.

- Interoperability - In order to encourage interoperability of applications and phones supporting this application protocol, additional CSTA Profiles, which include minimal sets of CSTA functionality, are described. These profiles can be extended by implementations to provide a more complete set of call and devices features commonly used by Enterprise applications.

3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

This TR provides informative examples of how to use CSTA concepts as an application protocol for SIP user agents. The following Ecma Standards should be used as the definitive references for CSTA.

ECMA-269, *Services for Computer Supported Telecommunications Applications (CSTA) Phase III, 6th edition, June 2004 (International Standard ISO/IEC 18051)*

ECMA-323, *XML Protocol for Computer Supported Telecommunications Applications (CSTA) Phase III, 3rd edition, June 2004 (International Standard ISO/IEC 18056)*

The following IETF references provide information on the SIP features referenced in this TR:

RFC 3261, *SIP: Session Initiation Protocol*, Rosenberg, J. et al, IETF, June 2002

4 Terminology

4.1 General terms

The following table summarizes some of the commonly used terminologies used in this Technical Report.

application	Refers to all components that control and observe uaCSTA instances that may be present in an application/computing domain such as an application residing on any type of computing device (desktop PC, mobile computing device, CTI middleware, SIP B2BUA, SIP UA, etc.).
uaCSTA	<u>user agent CSTA</u> – This refers the mechanism to transport CSTA messages over a SIP session, and the type of call control, called 1 st party call control, that allows an application to control and observe only the device or devices it is directly involved with. A desktop application controlling its associated phone, for example.
uaCSTA device	Refers to a SIP UA, such as a SIP or PBX phone, that supports the CSTA features over SIP as described in this TR.
phone	A SIP UA that supports calls. It is also a PBX device that supports calls. Examples of the types of phones that can be supported by this application protocol are described in clause 6.
B2BUA	A back-to-back-user-agent is a type of user agent that acts both as a user agent server (receives requests) and acts as a user agent client (generates requests). B2BUA is used to implement SIP third party call control (3PCC) features. uaCSTA could be used to augment the existing B2BUA functionality for enhanced call control.