TECHNICAL SPECIFICATION SPÉCIFICATION TECHNIQUE

TECHNISCHE SPEZIFIKATION

CEN/TS 13307-2

December 2009

ICS 79.080

English Version

Laminated and finger jointed timber blanks and semi-finished profiles for non-structural uses - Part 2: Production control

Ebauches et profilés semi-finis en bois lamellé-collés et assemblés par enture multiples pour usages non structurels - Partie 2: Contrôle de production

Holzkanteln und Halbfertigprofile für nicht tragende Anwendungen - Teil 2: Produktionskontrolle

This Technical Specification (CEN/TS) was approved by CEN on 1 September 2009 for provisional application.

The period of validity of this CEN/TS is limited initially to three years. After two years the members of CEN will be requested to submit their comments, particularly on the question whether the CEN/TS can be converted into a European Standard.

CEN members are required to announce the existence of this CEN/TS in the same way as for an EN and to make the CEN/TS available promptly at national level in an appropriate form. It is permissible to keep conflicting national standards in force (in parallel to the CEN/TS) until the final decision about the possible conversion of the CEN/TS into an EN is reached.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Foreword	4
Introduction	
1 Scope	
Normative references	
3 Terms and definitions	
4 Material requirements	
5 Manufacturing	
Sampling and testing	
7 Testing requirements	10
Air conditioning chamber requirements	1′
Climate classification	1 ²
Air temperature and Relative Humidity conditions	11 11 12
Sampling conditioning B.1 Sequences B.2 Pre-conditioning B.3 Conditioning sequences B.3.1 Service Class 1 B.3.2 Service Class 2 B.3.3 Service Class 3	
Lamella glue line assessment 9.1 Moisture resistance 9.1.1 Conditioning requirements 9.1.2 Delamination 9.2 Shear assessment 9.3 Chisel/wedge assessment (FPC only) 9.4 Penetration test (FPC only) 9.5 Calculation of results	
10 Finger joint assessment	14 15 15

11	Requirements	
11.1	General	
11.2	Laminate glue line	
11.2.1 11.2.2	Moisture resistance Chisel test.	
11.2.2	Penetration test	
11.3	Finger joints	
11.3.1	Bending	
11.3.2	Bending (Service Class 3)	
11.4	Water tightness	
11.5	Penetration test (Coloured Water test)	17
12	Records	18
	A (informative) Classification of adhesives	
	B (informative) Manufacturing recommendations	
B.1	Premises	
B.2	Storage	
B.2.1	Timber	20
B.2.2	Adhesive	20
B.2.3	Finished products	
B.3	Equipment	
B.4	Tolerance	
B.5	Moisture content	
	C (informative) Calculation of results for laminated profiles	22
C.1	Calculation of de-lamination quality of the glue line	
C.2	Calculation of the shear strength of the glue line	22
Annex	D (informative) Calculation of results for finger joints	
D.1	Calculation of finger joints strength under bending	
D.2	Calculation of strength radio under bending for moisture resistance	25
	7	
	Calculation of strength radio under bending for moisture resistance	

Foreword

This document (CEN/TS 13307-2:2009) has been prepared by Technical Committee CEN/TC 175 "Round and sawn timber", the secretariat of which is held by AFNOR.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to announce this Technical Specification: Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, in tis a provious denotation of the parties of the Sweden, Switzerland and the United Kingdom.

Introduction

The production requirements and control described in this Technical Specification are designed so as to obtain a reliable and durable bond between the lamellae, in order that the bonds in the glued laminated blanks Junean is a previous generated of the will maintain their integrity throughout their intended service life. Such blanks are not intended to be used as load-bearing members.

1 Scope

This Technical Specification specifies the method of control and tests for glue bond performance of lamination and finger jointing processes employed in the production of timber blanks and semi-finished profiles (products) for joinery applications.

The methods of control are set out to ensure the durability of the glue line according to the service class.

The specific requirements for dimensions, stability and moisture content are given in EN 13307-1.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 204, Classification of thermoplastic wood adhesives for non-structural applications

EN 301, Adhesives, phenolic and aminoplastic, for load-bearing timber structures — Classification and performance requirements

EN 392, Glued laminated timber — Shear test of glue lines

EN 408, Timber structures — Structural timber and glued laminated timber — Determination of some physical and mechanical properties

EN 12765, Classification of thermosetting wood adhesives for non-structural applications

EN 13183-1, Moisture content of a piece of sawn timber — Part 1: Determination by oven dry method

EN 13183-2, Moisture content of a piece of sawn timber — Part 2: Estimation by electrical resistance method

EN 13183-3, Moisture content of a piece of sawn timber — Part 3: Estimation by capacitance method

EN 13307-1, Timber blanks and semi-finished profiles for non-structural uses — Part 1: Requirements

EN 13354, Solid wood panels (SWP) — Bonding quality — Test method

EN 14220, Timber and wood-based materials in external windows, external door leaves and external doorframes — Requirements and specifications

EN 14221, Timber and wood-based materials in internal windows, internal door leaves and internal doorframes — Requirements and specifications

EN 14257, Adhesives — Wood adhesives — Determination of tensile strength of lap joints at elevated temperature (WATT '91)

EN 14298, Sawn timber — Assessment of drying quality

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

adhesive failure

failure of the glue bond, where an adhesive film, free of wood particles, may be detected on the opposing sheared wood surfaces