INTERNATIONAL STANDARD

ISO 10251

Second edition
2006-05-01

Copper, lead, zinc and nickel concentrates — Determination of mass loss of bulk material on drying

Concentrés de cuivre, de plomb, de zinc et de nickel — Détermination de la perte de masse au séchage du matériau en vrac

Reference number
ISO 10251:2006(E)

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 10251 was prepared by Technical Committee ISO/TC 183, *Copper, lead, zinc and nickel ores and concentrates*.

This second edition cancels and replaces the first edition (ISO 10251:1997), which has been technically revised.

Introduction

Reference to the percentage mass loss as moisture content is appropriate because, although oxidation, decomposition or sublimation of elemental sulfur may contribute, most of the mass loss on drying is due to loss of moisture.

When oxidation, decomposition or sublimation of elemental sulfur has been shown to occur or volatile organic flotation reagents such as kerosene are present, the chemical analysis test sample should be prepared from the dried moisture test portions. Under these circumstances, the sampling scheme established in accordance with ISO 12743 must ensure that moisture samples and test portions are sufficiently representative for subsequent chemical analysis. Where oxidation is a problem, an inert atmosphere may also be used during the drying stage. Annex A provides a procedure by which it can be determined whether or not a concentrate is susceptible to oxidation, decomposition or sublimation.

Copper, lead, zinc and nickel concentrates — Determination of mass loss of bulk material on drying

WARNING — This International Standard may involve hazardous materials, operations and equipment. This International Standard does not purport to address all of the safety issues associated with its use. It is the responsibility of the user to establish appropriate health and safety practices and determine the applicability of regulatory limitations prior to use.

1 Scope

This International Standard specifies methods for the determination of moisture content of a lot of copper, lead, zinc or nickel concentrate, defined as the percentage mass loss of the moisture test portion under the conditions of drying specified in this document.

In order to obtain an unbiased estimate of the metal content of the lot, it is important that the same drying conditions are used for the determination of bulk and hygroscopic moisture or for preparing a predried test portion.

This International Standard is not applicable to drying samples used for determination of volatile elements such as mercury and sulfur. Such samples are allowed to dry at ambient temperature, and a hygroscopic moisture determination is carried out according to ISO 9599 at the time of chemical analysis.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 12743, *Copper, lead, zinc and nickel concentrates — Sampling procedures for determination of metal and moisture content*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1
representative sample
quantity of concentrate representing a larger mass of concentrate with both precision and bias within acceptable limits

3.2
lot
quantity of concentrate to be sampled

3.3
lot sample
quantity of concentrate that is representative of the lot